

MGA Entertainment (HK) Ltd.

Application
For
Certification
(FCC ID: LU9600715)

Transmitter

Sample Description : Shop & Learn Market

Model: 600715

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [4-5-2005]

0713835 AC/at June 30, 2007

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- · This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: General Description

EXHIBIT 2: System Test Configuration

EXHIBIT 3: Emission Results

EXHIBIT 4: Equipment Photographs

EXHIBIT 5: Product Labelling

EXHIBIT 6: Technical Specifications

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Miscellaneous Information

MEASUREMENT/TECHNICAL REPORT

MGA Entertainment (HK) Ltd. - MODEL: 600715 FCC ID: LU9600715

June 30, 2007

| This report concerns (check one:) | Original Grant X | Class II Cha | nge | | | | | |
|---|-------------------------------------|--|----------------------|--|--|--|--|--|
| Equipment Type: Low Power Transmitter | | | | | | | | |
| Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No_X_ | | | | | | | | |
| | If yes, defer | until: | data | | | | | |
| Company Name agrees to notify the Commission by: date date | | | | | | | | |
| of the intended date of announcer issued on that date. | ment of the product | so that the gra | int can be | | | | | |
| Transition Rules Request per 15.37 | ? Yes | No_2 | X | | | | | |
| If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [4-5-2005 Edition] provision. | | | | | | | | |
| Report prepared by: | Inter 2/F. 576, HON Pho | n Kar Ming, Ant tek Testing Ser Garment Cente Castle Peak Ro NG KONG ne: 852-2173-85 852-2742-91 | vices er, oad, | | | | | |

Table of Contents

| 1.0 | General Description | 2 |
|------------|--|----|
| | 1.1 Product Description | |
| | 1.2 Related Submittal(s) Grants | |
| | 1.3 Test Methodology | |
| | 1.4 Test Facility | |
| | | |
| 2.0 | System Test Configuration | 5 |
| | 2.1 Justification | |
| | 2.2 EUT Exercising Software | |
| | 2.3 Special Accessories | |
| | 2.4 Equipment Modification | |
| | 2.5 Support Equipment List and Description | 6 |
| | | |
| 3.0 | Emission Results | |
| | 3.1 Field Strength Calculation | |
| | 3.1 Field Strength Calculation (cont'd) | |
| | 3.2 Radiated Emission Configuration Photograph | |
| | 3.3 Radiated Emission Data | |
| | 3.4 Frequency Tolerance | 15 |
| | | |
| 4.0 | Equipment Photographs | 17 |
| | | |
| 5.0 | Product Labelling | 19 |
| ~ ~ | Table 1 On a 10 and and | O4 |
| 6.0 | <u>Technical Specifications</u> | 21 |
| 7.0 | Instruction Manual | വ |
| 7.0 | IIIST UCTION Manual | 23 |
| 8 0 | Miscellaneous Information | 25 |
| 0.0 | 8.1 Measured Bandwidth | |
| | 8.2 Emission Test Procedures | _ |
| | 8.2 Emission Test Procedures (Cont'd) | |
| | | |

List of attached file

| Exhibit type File Description | | filename | |
|-------------------------------|----------------------------|---------------------|--|
| Test Report | Test Report | report.pdf | |
| Operation Description | Technical Description | descri.pdf | |
| Test Setup Photo | Radiated Emission | radiated photos.doc | |
| Test Report | Bandwidth Plot | bw.pdf | |
| External Photo | External Photo | external photos.doc | |
| Internal Photo | Internal Photo | internal photos.doc | |
| Block Diagram | Block Diagram | block.pdf | |
| Schematics | Circuit Diagram | circuit.pdf | |
| ID Label/Location | Label Artwork and Location | label.pdf | |
| User Manual | User Manual | manual.pdf | |

EXHIBIT 1

GENERAL DESCRIPTION

1.0 **General Description**

1.1 Product Description

The equipment under test (EUT) is a transmitter for an inductive toy cash register (RFID toy reader) operating at 13.56 MHz which is controlled by a crystal. The EUT is powered by 3 AA batteries. This toy consists of a toy cash register (RFID tag reader) and ten toy food items (passive type powered tags). The EUT has an ON/OFF switch, a cash register keypad, a 3-Way mode switch and a RFID tag sensor on the flatbed scanner. Set the 3-Way mode switch to desired game mode. In each game mode, the EUT will give instructions to the player and ask the player to scan the food items over scanner.

The brief circuit description is saved with filename: descri.pdf

1.2 Related Submittal(s) Grants

The receiver for this transmitter is exempted form the Part 15 technical rules per 15.101(b).

1.3 Test Methodology

The radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

EXHIBIT 2 SYSTEM TEST CONFIGURATION

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered by 3 new AA batteries during test.

For maximizing emission below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on the turntable and rotate through 360°, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The unit can transmit continuously, when it is switched on.

2.2 EUT Exercising Software

There was no special software to exercise the device.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by MGA Entertainment (HK) Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services.

2.5 Support Equipment List and Description

Ten corresponding passive-type tags, model: 600715

All the items listed under section 2.0 of this report are

Confirmed by:

Chan Kar Ming, Anthony Assistant Manager Intertek Testing Services Agent for MGA Entertainment (HK) Ltd.

Signature

June 30, 2007 Date

EXHIBIT 3

EMISSION RESULTS

3.0 **Emission Results**

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of $62.0~dB_{\mu}V$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is $32~dB_{\mu}V/m$. This value in $dB_{\mu}V/m$ was converted to its corresponding level in $\mu V/m$.

 $RA = 62.0 dB\mu V$

AF = 7.4 dB

CF = 1.6 dB

AG = 29.0 dB

PD = 0 dB

AV = -10 dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(32 dB μ V/m)/20] = 39.8 μ V/m

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission

81.384 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.doc

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 9.2 dB

TEST PERSONNEL:

| | 1 | | | |
|-----|-------|---|-------|--|
| / | 11/14 | M | 51911 | |
| 1/6 | Wille | 1 | r cum | |
| W/ | | 0 | | |
| | | | | |

Signature

Gary M. K. Li, Compliance Engineer
Typed/Printed Name

June 30, 2007

Date

Applicant: MGA Entertainment (HK) Ltd. Date of Test: June 16, 2007

Model: 600715 Mode: TX Sample: 1/1

Table 1

Radiated Emissions

| Polarization | Frequency | Reading | Antenna | Pre- | Net | Distance | Calculated | Limit | Margin |
|--------------|-----------|---------|---------|------|----------|----------|------------|----------|--------|
| | (MHz) | (dBµV) | Factor | Amp | at 3m | Factor | at 30m | at 30m | (dB) |
| | | | (dB) | Gain | (dBµV/m) | (-dB) | (dBµV/m) | (dBµV/m) | |
| | | | | (dB) | | | | | |
| V | 13.564 | 43.3 | 10.8 | 0.0 | 54.1 | 40.0 | 14.1 | 84.0 | -69.9 |
| V | 27.128 | 20.2 | 9.5 | 0.0 | 29.7 | 40.0 | -10.3 | 29.5 | -39.8 |

Table 2

Radiated Emissions

| Polarization | Frequency | Reading | Antenna | Pre- | Net | Limit | Margin |
|--------------|-----------|---------|---------|------|----------|----------|--------|
| | (MHz) | (dBµV) | Factor | Amp | at 3m | at 3m | (dB) |
| | | | (dB) | Gain | (dBµV/m) | (dBµV/m) | |
| | | | | (dB) | | | |
| V | 40.692 | 35.9 | 10 | 16 | 29.9 | 40.0 | -10.1 |
| V | 54.256 | 35.1 | 11 | 16 | 30.1 | 40.0 | -9.9 |
| V | 67.820 | 37.7 | 8 | 16 | 29.7 | 40.0 | -10.3 |
| V | 81.384 | 39.8 | 7 | 16 | 30.8 | 40.0 | -9.2 |
| V | 94.948 | 34.6 | 11 | 16 | 29.6 | 43.5 | -13.9 |
| V | 108.512 | 32.8 | 13 | 16 | 29.8 | 43.5 | -13.7 |
| V | 122.076 | 32.1 | 14 | 16 | 30.1 | 43.5 | -13.4 |
| V | 135.640 | 33.1 | 14 | 16 | 31.1 | 43.5 | -12.4 |
| V | 149.204 | 32.2 | 14 | 16 | 30.2 | 43.5 | -13.3 |

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3 meter distance were measured at 0.3 meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3 meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Loop antenna is used for emissions below 30 MHz.
- 5. Worst case emissions were measured.

*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and peak detector data with average factor for frequencies over 1000 MHz.

Test Engineer: Gary M. K. Li

Applicant: MGA Entertainment (HK) Ltd. Date of Test: June 16, 2007

Model: 600715 Mode: Sound Sample: 1/1

Table 2

Radiated Emissions

| | Frequency | Reading | Pre- | Antenna | Net | Limit | Margin |
|--------------|-----------|---------|------|---------|----------|----------|--------|
| Polarization | | | Amp | Factor | at 3m | at 3m | |
| | (MHz) | (dBµV) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 36.349 | 34.7 | 16 | 10 | 28.7 | 40 | -11.3 |
| V | 42.171 | 35.3 | 16 | 10 | 29.3 | 40 | -10.7 |
| V | 48.129 | 34.1 | 16 | 11 | 29.1 | 40 | -10.9 |
| V | 54.749 | 34.0 | 16 | 11 | 29.0 | 40 | -11.0 |
| V | 60.317 | 34.8 | 16 | 10 | 28.8 | 40 | -11.2 |
| V | 66.489 | 35.7 | 16 | 9 | 28.7 | 40 | -11.3 |

Notes: Negative signs (-) in the margin column signify levels below the limit.

Test Engineer: Gary M. K. Li

3.4 Frequency Tolerance

FCC Part 15 Section 15.225(e)

Data Table Frequency tolerance of Transmitter (Temperature Variation : -20°C to +50°C)

| Operating frequer | псу | 13.563826 MHz | | |
|-------------------|----------------------|---------------|-----------|-------|
| Test Voltage | Temperature Measured | | Frequency | Limit |
| (V) | (°C) | frequency | shift | (%) |
| | | (MHz) | (%) | |
| 4.5 | +50 | 13.563978 | +0.00112 | ±0.01 |
| | +40 | 13.563937 | +0.00082 | ±0.01 |
| | +30 | 13.563878 | +0.00038 | ±0.01 |
| | +20 | 13.563826 | 0 | ±0.01 |
| | +10 | 13.563788 | -0.00028 | ±0.01 |
| | 0 | 13.563779 | -0.00035 | ±0.01 |
| | -10 | 13.563757 | -0.00051 | ±0.01 |
| | -20 | 13.563742 | -0.00062 | ±0.01 |

We found that the EUT met the requirement of FCC Part 15 Section 15.225(e).

Test Engineer: Gary M. K. Li

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc and internal photos.doc

EXHIBIT 5

PRODUCT LABELLING

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf

EXHIBIT 6

TECHNICAL SPECIFICATIONS

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematics are saved with filename: block.pdf and circuit.pdf

EXHIBIT 7

INSTRUCTION MANUAL

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

EXHIBIT 8

MISCELLANEOUS INFORMATION

8.0 <u>Miscellaneous Information</u>

This miscellaneous information includes details of the measured bandwidth and the test procedure.

8.1 Measured Bandwidth

The plot saved in bw.pdf which shows the fundamental emission is confined in the specified band. The emission of the fundamental is 14.1 dB μ V/m at 30m. It mees the requirement of Section 15.225(b), (c), & (d).

Figure 8.1 Bandwidth

8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

When determining the test result, the Measurement Uncertainty of the test has been considered.