

TEST REPORT

Report No.: 20050867HKG-001

MGA Entertainment (HK) Ltd.

Application For Certification
(Original Grant)

FCC ID: LU9655388

Transceiver

Prepared and Checked by:

Approved by:

Signed On File
Lee For Yiu, Florey
Assistant Engineer

Wong Kwok Yeung, Kenneth
Senior Lead Engineer
Date: July 29, 2020

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

TEST REPORT

GENERAL INFORMATION

Grantee:	MGA Entertainment (HK) Ltd.
Grantee Address:	Suite 301, 3/F., Chinachem Golden Plaza, No.77 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Contact Person:	Julian Chung
Tel:	(852) 27329200
Fax:	(852) 27329242
e-mail:	julian.chung@mgae.com
Manufacturer:	MGA Entertainment (HK) Limited
Manufacturer Address:	Suite 301, 3/F., Chinachem Golden Plaza, No.77 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Brand Name:	Soundtrack Kick Scooter
Model:	655388
Additional Model:	655388ALT, 655388E5C
Type of EUT:	Transceiver
Description of EUT:	Soundtrack Kick Scooter
Serial Number:	N/A
FCC ID:	LU9655388
Date of Sample Submitted:	May 19, 2020
Date of Test:	May 19, 2020 to July 21, 2020
Report No.:	20050867HKG-001
Report Date:	July 29, 2020
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%
Conclusion:	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 Certification.

TEST REPORT

SUMMARY OF TEST RESULT

Test Specification	Reference	Results
Transmitter Power Line Conducted Emissions	15.207	Pass
Radiated Emission Radiated Emission on the Bandedge	15.249, 15.209	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards:
FCC Part 15, October 1, 2019 Edition

- Note:
1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.
 2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

TEST REPORT

TABLE OF CONTENTS

1.0	GENERAL DESCRIPTION	5
1.1	Product Description	5
1.2	Related Submittal(s) Grants	5
1.3	Test Methodology.....	5
1.4	Test Facility	5
2.0	SYSTEM TEST CONFIGURATION.....	6
2.1	Justification	6
2.2	EUT Exercising Software.....	6
2.3	Special Accessories	6
2.4	Measurement Uncertainty.....	6
2.5	Support Equipment List and Description.....	6
3.0	EMISSION RESULTS.....	7
3.1	Field Strength Calculation	7
3.2	Radiated Emission Configuration Photograph.....	8
3.3	Radiated Emission Data	8
3.4	Conducted Emission Configuration Photograph	8
3.5	Conducted Emission Data	8
4.0	EQUIPMENT PHOTOGRAPHS	17
5.0	PRODUCT LABELLING.....	17
6.0	TECHNICAL SPECIFICATIONS	17
7.0	INSTRUCTION MANUAL.....	17
8.0	MISCELLANEOUS INFORMATION	18
8.1	Radiated Emission on the Bandedge.....	18
8.2	Emissions Test Procedures.....	23
9.0	EQUIPMENT LIST.....	27

TEST REPORT

1.0 GENERAL DESCRIPTION

1.1 Product Description

The Equipment Under Test (EUT), is a portable 2.4GHz Bluetooth 5.0 Speaker (Speaker Unit) for a RC Speaker. This sample is Bluetooth 5.0 without supporting 2Mbps data rate. The sample supplied operated on 40 channels, normally at 2402 - 2480MHz. The channels are separated with 2MHz spacing.

Another mode for the Equipment Under Test (EUT) is Bluetooth BDR/EDR. The sample supplied operated on 79 channels, normally at 2402 - 2480MHz. The channels are separated with 1MHz spacing.

The EUT is powered by 1 x 3.7V Rechargeable battery. After switching on the EUT, the speaker will be playing music based on the switches pressed in smartphone controller app.

The Models: 655388ALT and 655388E5C are the same as the Model: 655388 in hardware aspect as declared by client. The difference in model number serves as marketing strategy as declared by client. The models are different in model number and packaging only as declared by client.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC.

TEST REPORT

2.0 SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by DC 3.7V (1 x 3.7V Rechargeable Battery).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.5 Support Equipment List and Description

1. HP EliteBook Notebook
(Provided by Intertek)
2. 1 x USB cable with length of 0.53 meter long
(Provided by Applicant)

TEST REPORT

3.0 EMISSION RESULTS

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m

RR = RA - AG - AV in dB μ V

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V/m}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V/m}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$LF = 9.0 \text{ dB}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

TEST REPORT

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 7320 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 5.4 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.1905 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 14.88 dB

TEST REPORT

RADIATED EMISSIONS

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth BDR/EDR)

Table 1
Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	86.3	33	29.4	82.7	94.0	-11.3
H	4804.000	40.7	33	34.9	42.6	54.0	-11.4
V	7206.000	40.2	33	37.9	45.1	54.0	-8.9
V	9608.000	31.6	33	40.4	39.0	54.0	-15.0
H	12010.000	26.1	33	40.5	33.6	54.0	-20.4
V	14412.000	29.7	33	40.0	36.7	54.0	-17.3
H	16814.000	29.4	33	37.6	34.0	54.0	-20.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	97.7	33	29.4	94.1	114.0	-19.9
H	4804.000	53.2	33	34.9	55.1	74.0	-18.9
V	7206.000	54.3	33	37.9	59.2	74.0	-14.8
V	9608.000	41.9	33	40.4	49.3	74.0	-24.7
H	12010.000	39.5	33	40.5	47.0	74.0	-27.0
V	14412.000	43.1	33	40.0	50.1	74.0	-23.9
H	16814.000	42.4	33	37.6	47.0	74.0	-27.0

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth BDR/EDR)

Table 2
Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	85.9	33	29.4	82.3	94.0	-11.7
H	4880.000	41.6	33	34.9	43.5	54.0	-10.5
V	7320.000	43.7	33	37.9	48.6	54.0	-5.4
V	9760.000	27.9	33	40.4	35.3	54.0	-18.7
V	12200.000	28.8	33	40.5	36.3	54.0	-17.7
H	14640.000	30.7	33	38.4	36.1	54.0	-17.9
V	17080.000	34.6	33	37.6	39.2	54.0	-14.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	97.5	33	29.4	93.9	114.0	-20.1
H	4880.000	54.3	33	34.9	56.2	74.0	-17.8
V	7320.000	57.6	33	37.9	62.5	74.0	-11.5
V	9760.000	42.4	33	40.4	49.8	74.0	-24.2
V	12200.000	42.3	33	40.5	49.8	74.0	-24.2
H	14640.000	44.1	33	38.4	49.5	74.0	-24.5
V	17080.000	48.2	33	37.6	52.8	74.0	-21.2

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth BDR/EDR)

Table 3
Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	86.0	33	29.4	82.4	94.0	-11.6
V	4960.000	43.9	33	34.9	45.8	54.0	-8.2
V	7440.000	42.0	33	37.9	46.9	54.0	-7.1
V	9920.000	31.9	33	40.4	39.3	54.0	-14.7
V	12400.000	26.3	33	40.5	33.8	54.0	-20.2
H	14880.000	30.6	33	38.4	36.0	54.0	-18.0
H	17360.000	37.3	33	37.6	41.9	54.0	-12.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	97.4	33	29.4	93.8	114.0	-20.2
V	4960.000	57.5	33	34.9	59.4	74.0	-14.6
V	7440.000	56.1	33	37.9	61.0	74.0	-13.0
V	9920.000	42.9	33	40.4	50.3	74.0	-23.7
V	12400.000	39.7	33	40.5	47.2	74.0	-26.8
H	14880.000	43.9	33	38.4	49.3	74.0	-24.7
H	17360.000	50.7	33	37.6	55.3	74.0	-18.7

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth 5.0)

Table 4
Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	81.6	33	29.4	78.0	94.0	-16.0
H	4804.000	35.7	33	34.9	37.6	54.0	-16.4
V	7206.000	39.9	33	37.9	44.8	54.0	-9.2
V	9608.000	28.3	33	40.4	35.7	54.0	-18.3
V	12010.000	28.3	33	40.5	35.8	54.0	-18.2
H	14412.000	29.9	33	40.0	36.9	54.0	-17.1
H	16814.000	30.3	33	37.6	34.9	54.0	-19.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	99.7	33	29.4	96.1	114.0	-17.9
H	4804.000	54.5	33	34.9	56.4	74.0	-17.6
V	7206.000	61.0	33	37.9	65.9	74.0	-8.1
V	9608.000	47.1	33	40.4	54.5	74.0	-19.5
V	12010.000	44.6	33	40.5	52.1	74.0	-21.9
H	14412.000	43.2	33	40.0	50.2	74.0	-23.8
H	16814.000	43.7	33	37.6	48.3	74.0	-25.7

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth 5.0)

Table 5
Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	80.6	33	29.4	77.0	94.0	-17.0
H	4880.000	38.0	33	34.9	39.9	54.0	-14.1
V	7320.000	42.5	33	37.9	47.4	54.0	-6.6
V	9760.000	29.4	33	40.4	36.8	54.0	-17.2
V	12200.000	29.6	33	40.5	37.1	54.0	-16.9
V	14640.000	31.3	33	38.4	36.7	54.0	-17.3
V	17080.000	35.2	33	37.6	39.8	54.0	-14.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	98.6	33	29.4	95.0	114.0	-19.0
H	4880.000	57.2	33	34.9	59.1	74.0	-14.9
V	7320.000	63.6	33	37.9	68.5	74.0	-5.5
V	9760.000	48.6	33	40.4	56.0	74.0	-18.0
V	12200.000	47.5	33	40.5	55.0	74.0	-19.0
V	14640.000	45.5	33	38.4	50.9	74.0	-23.1
V	17080.000	49.9	33	37.6	54.5	74.0	-19.5

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Transmitting (Bluetooth 5.0)

Table 6
Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	80.5	33	29.4	76.9	94.0	-17.1
V	4960.000	39.5	33	34.9	41.4	54.0	-12.6
V	7440.000	40.6	33	37.9	45.5	54.0	-8.5
V	9920.000	28.4	33	40.4	35.8	54.0	-18.2
V	12400.000	30.9	33	40.5	38.4	54.0	-15.6
V	14880.000	31.0	33	38.4	36.4	54.0	-17.6
V	17360.000	37.8	33	37.6	42.4	54.0	-11.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	98.9	33	29.4	95.3	114.0	-18.7
V	4960.000	58.7	33	34.9	60.6	74.0	-13.4
V	7440.000	60.6	33	37.9	65.5	74.0	-8.5
V	9920.000	46.9	33	40.4	54.3	74.0	-19.7
V	12400.000	49.9	33	40.5	57.4	74.0	-16.6
V	14880.000	45.9	33	38.4	51.3	74.0	-22.7
V	17360.000	52.8	33	37.6	57.4	74.0	-16.6

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Charging with BT

Table 7
Pursuant to FCC Part 15 Section 15.249 Requirement

Polarization	Frequency (MHz)	Reading (dBmV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	35.116	34.9	16	10.0	28.9	40.0	-11.1
V	80.941	40.2	16	6.0	30.2	40.0	-9.8
V	151.750	32.4	16	15.0	31.4	43.5	-12.1
H	281.547	26.0	16	22.0	32.0	46.0	-14.0
H	561.494	20.9	16	28.0	32.9	46.0	-13.1
H	770.422	18.4	16	31.0	33.4	46.0	-12.6

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. Average detector is applied according to ANSI C63.10.
 3. All measurements were made at 3 meters.
 4. Negative sign in the column shows value below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.


TEST REPORT

CONDUCTED EMISSION

Model: 655388

Date of Test: July 21, 2020

Worst-Case Operating Mode: Charging with BT



EDIT PEAK LIST (Final Measurement Results)

Trace1: CF15MQP
Trace2: CF15MAV
Trace3: ---

TRACE	FREQUENCY	LEVEL dBµV	DELTA	LIMIT dB
1 Quasi Peak	150 kHz	50.08	N	-15.91
2 CISPR Average	190.5 kHz	39.13	N	-14.88
1 Quasi Peak	235.5 kHz	40.81	N	-21.44
2 CISPR Average	249 kHz	35.10	N	-16.68
1 Quasi Peak	402 kHz	31.85	N	-25.95
2 CISPR Average	492 kHz	27.46	L1	-18.67
1 Quasi Peak	501 kHz	35.86	L1	-20.13

Note: Measurement Uncertainty is ±4.2dB at a level of confidence of 95%.

TEST REPORT

4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 PRODUCT LABELLING

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

TEST REPORT

8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth.



8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

TEST REPORT

PEAK MEASUREMENT (Bluetooth BDR/EDR)



TEST REPORT

PEAK MEASUREMENT (Bluetooth BDR/EDR)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=94.1 dB μ V/m – 38.8 dB

=55.3 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=82.7 dB μ V/m – 38.8 dB

=43.9 dB μ V/m

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=93.8 dB μ V/m – 42.4 dB

=51.4 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot



=82.4 dB μ V/m – 42.4 dB

=40.0 dB μ V/m

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) but exceeded 54 dB μ V/m (Average Limit).

TEST REPORT

PEAK MEASUREMENT (Bluetooth 5.0)



Date: 20.JUL.2020 15:25:32

TEST REPORT

PEAK MEASUREMENT (Bluetooth 5.0 BLE)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=96.1 \text{ dB}\mu\text{V/m} - 37.8 \text{ dB}$$

$$=58.3 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=78.0 \text{ dB}\mu\text{V/m} - 37.8 \text{ dB}$$

$$=40.2 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=95.3 \text{ dB}\mu\text{V/m} - 44.5 \text{ dB}$$

$$=50.8 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=76.9 \text{ dB}\mu\text{V/m} - 44.5 \text{ dB}$$

$$=32.4 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) but exceeded 54 dB μ V/m (Average Limit).

TEST REPORT

8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

TEST REPORT

8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


TEST REPORT

8.2.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


TEST REPORT

8.2.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

8.2.3 Conducted Emission Test Setup



TEST REPORT

9.0 EQUIPMENT LIST

1) Radiated Emissions Test

Equipment	Test Receiver	Biconical Antenna	Spectrum Analyzer
Registration No.	EW-3156	EW-0571	EW-2253
Manufacturer	ROHDESCHWARZ	EMCO	ROHDESCHWARZ
Model No.	ESR26	3104C	FSP40
Calibration Date	August 01, 2019	July 23, 2019	November 18, 2019
Calibration Due Date	August 01, 2020	January 23, 2021	November 18, 2020

Equipment	Log Periodic Antenna	RF Pre-amplifier 3 pcs (9kHz to 40GHz)	14m Double Shield RF Cable
Registration No.	EW-1042	EW-3006	EW-2505
Manufacturer	EMCO	SCHWARZBECK	RADIALL
Model No.	3148	BBV 9718	Nm-RG142-
Calibration Date	November 23, 2018	November 25, 2019	November 14, 2019
Calibration Due Date	November 23, 2020	November 25, 2020	November 14, 2020

Equipment	Double Ridged Guide Antenna	Horn Antenna (14GHz – 40GHz)	RF Cable 14m
Registration No.	EW-0194	EW-1679	EW-2505
Manufacturer	EMCO	SCHWARZBECK	GREATBILLION
Model No.	3115	BBHA9170	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	March 26, 2020	October 01, 2019	November 14, 2019
Calibration Due Date	March 26, 2021	October 01, 2020	November 14, 2020

2) Conducted Emissions Test

Equipment	Test Receiver	Artificial Mains Network
Registration No.	EW-3156	EW-2874
Manufacturer	ROHDESCHWARZ	ROHDESCHWARZ
Model No.	ESR26	ENV-216
Calibration Date	August 01, 2019	July 05, 2019
Calibration Due Date	August 01, 2020	October 05, 2020

3) Bandwidth Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2253
Manufacturer	ROHDESCHWARZ
Model No.	FSP40
Calibration Date	November 18, 2019
Calibration Due Date	November 18, 2020

END OF TEST REPORT