



1601 North A.W. Grimes Blvd., Suite B
Round Rock, TX 78665
e-mail: info@ptitest.com
(512) 244-3371 Fax: (512) 244-1846

November 7, 2014

David Cameron
Hetric International
3905 NW 36th St.
Oklahoma City, OK 73112
USA

David:

Thank you for allowing Professional Testing (EMI), Inc. an opportunity to perform testing for Hetric International. Enclosed is the Wireless Certification Report for the RX-MFS-ESCAN-HS1. This report can be used to demonstrate compliance with requirements for wireless devices in North America.

If you have any questions, please contact me.

Sincerely,

Jeffrey A. Lenk
President

Attachment

Project 16271-15

**Hetronic International
Model RX-MFS-ESCAN-HS1**

Wireless Certification Report

Prepared for:

Hetronic International
3905 NW 36th St.
Oklahoma City, OK 73112
USA

By

Professional Testing (EMI), Inc.
1601 North A.W. Grimes Blvd., Suite B
Round Rock, Texas 78665

November 7, 2014

Reviewed by



Larry Finn
Chief Technical Officer

Written by



Eric Lifsey
Test Engineer

Revision History

Revision Number	Description	Date
00	Draft for review.	November 7, 2014
01	Revised per comments of Dave Cameron & Larry Finn.	November 7, 2014

Table of Contents

Revision History..... 3

Compliance Certificate..... 6

1.0 Introduction..... 7

 1.1 Scope..... 7

 1.2 EUT Description 7

 1.3 EUT Operation..... 7

 1.4 Modifications to Equipment..... 7

 1.5 Test Site 7

 1.6 Applicable Documents and Clauses..... 8

2.0 Fundamental Power 9

 2.1 Test Procedure 9

 2.2 Test Criteria 9

 2.3 Test Results..... 9

 2.3.1 Low Channel 10

 2.3.2 Middle Channel 11

 2.3.3 High Channel..... 12

3.0 Power Spectral Density..... 13

 3.1 Test Procedure 13

 3.2 Test Criteria 13

 3.3 Test Results..... 13

 3.3.1 Low Channel PSD 14

 3.3.2 Middle Channel PSD..... 15

 3.3.3 High Channel PSD 16

4.0 Transmitter Duty Cycle..... 17

 4.1 Test Procedure 17

 4.2 Test Criteria 17

 4.3 Test Results..... 17

 4.3.1 Transmit On Time 18

 4.3.2 Transmit Interval Time..... 19

5.0 Occupied Bandwidth..... 20

 5.1 Test Procedure 20

 5.2 Test Criteria 20

 5.3 Test Results..... 20

 5.3.1 Bandwidth Plots, 6 dB..... 21

 5.3.2 Bandwidth Plots, 20 dB..... 24

6.0 Band Edge..... 27

 6.1 Test Procedure 27

 6.2 Test Criteria 27

 6.3 Test Results..... 27

 6.3.1 Low Channel Band Edge..... 28

 6.3.2 High Channel Band Edge 29

7.0 Radiated Spurious Emissions, Receive Mode..... 30

 7.1 Test Procedure 30

 7.2 Test Criteria 30

 7.3 Test Results..... 30

8.0 Radiated Spurious Emissions, Transmit Mode 36

 8.1 Test Procedure 36

 8.2 Test Criteria 36

 8.3 Test Results..... 36

9.0 Setup Photographs 51

 9.1 Receive Mode Spurious 51

 9.2 Transmit Mode Spurious, 30 MHz to 25 GHz 52

 9.3 Conducted Port Setup, Power, PSD, Timing and Bandwidth 53

10.0 Antenna Construction Requirements 54

 10.1 Procedure..... 54

 10.2 Criteria 54

 10.3 Results..... 54

11.0 Equipment..... 55

 11.1 Spurious Radiated Emissions 30 MHz to 18 GHz 55

11.2 Timing and Bandwidth Measurements..... 56
12.0 Measurement Bandwidths, Radiated Emissions, Spurious 57
Appendix: Policy, Rationale, and Evaluation of EMC Measurement Uncertainty 58
End of Report 60

NOTICE: (1) This Report must not be used to claim product endorsement, by NVLAP, NIST, the FCC or any other Agency. This report also does not warrant certification by NVLAP or NIST. (2) This report shall not be reproduced except in full, without the written approval of Professional Testing (EMI), Inc. (3) The significance of this report is dependent on the representative character of the test sample submitted for evaluation and the results apply only in reference to the sample tested. The manufacturer must continuously implement the changes shown herein to attain and maintain the required degree of compliance.



Compliance Certificate

Applicant	Device & Test Identification
David Cameron Hetronic International 3905 NW 36th St. Oklahoma City, OK 73112 USA Certificate Date: November 7, 2014	FCC ID: LW9-RXMFSESCANHS1 Industry Canada ID: 2119B-RXMFSCANHS1 Model(s): RX-MFS-ESCAN-HS1 Part Number(s): N/A Laboratory Project ID: 16271-15

The device named above was tested utilizing the following documents and found to be in compliance with the required criteria:

Standard	Reference	Detail
FCC 47 CFR Part 15 C	15.247	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
FCC 47 CFR Part 15 C	15.209	Radiated emission limits; general requirements.
FCC 47 CFR Part 15 C	15.205	Restricted Bands of Operation
KDB 558074 D01	DR01	DTS Measurement Guidance v03r02
KDB 412172	D01	Guidelines for Determining the ERP and EIRP of an RF Transmitting System
OET Bulletin 65*	Edition 97-01, and Supplement C, Ed. 01-01	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
RSS-210	Issue 8	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment
RSS-Gen	Issue 3	General Requirements and Information for the Certification of Radio Apparatus
RSS-102	Issue 4	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

*MPE is reported separately from this document.

I, Eric Lifsey, for Professional Testing (EMI), Inc., being familiar with the above rules and test procedures have reviewed the test setup, measured data, and this report. I believe them to be true and accurate.

Eric Lifsey
EMC Engineer

This report has been reviewed and accepted by the Applicant. The undersigned is responsible for ensuring that this device will continue to comply with the rules listed above.

Representative of Applicant

1.0 Introduction

1.1 Scope

This report describes the extent to which the equipment under test (EUT) conformed to the intentional radiator requirements of the United States and Canada.

Professional Testing (EMI), Inc., (PTI) follows the guidelines of National Institute of Standards and Technology (NIST) for all uncertainty calculations, estimates, and expressions thereof for electromagnetic compatibility testing. The procedures of ANSI C63.4: 2009 were used for making all radiated enclosure and mains emission measurements.

1.2 EUT Description

The device (EUT) as tested is identified in the table that follows.

Table 1.2.1: Equipment Under Test

Manufacturer	Model	Serial #	Description
Hetronic International	RX-MFS-ESCAN-HS1	None	Wirelessly controlled transmitter/receiver for 2400-2483.5 MHz.

This device is a remote wireless transmitter/receiver for actuating relays on industrial vehicles/machines such as cranes. It is normally mounted to a surface of the host machine and is not hand held. It is controlled by wireless means from a companion portable wireless control device that is operated by a person.

The EUT measures approximately 6 x 12 x 17 cm and is shaped as a simple box with an external antenna. The EUT is powered by a 6 to 36 Volt DC source on the host machine.

1.3 EUT Operation

The EUT was exercised in a manner consistent with normal operations.

The EUT internal software operated the transmitter in a continuous modulated transmit mode, receive mode, or operated in communication with the remote wireless control device as needed for measurement.

1.4 Modifications to Equipment

Programmatic power setting for the highest channel of 2480 MHz was reduced to meet the limits of band edge and spurious above 1 GHz. The final setting was 0x7.

1.5 Test Site

Measurements were made at the PTI semi-anechoic facility designated Site 45 (FCC 459644, IC 3036B-1) in Austin, Texas. The site is registered with the FCC under Section 2.948 and Industry Canada per RSS-GEN, and is subsequently confirmed by laboratory accreditation (NVLAP). The test site is located at 11400 Burnet Road, Austin, Texas 78758, while the main office is located at 1601 North A.W. Grimes Boulevard, Suite B, Round Rock, Texas, 78665.

1.6 Applicable Documents and Clauses

Table 1.6.1: Applicable Documents	
Document	Title
47 CFR	Part 15 – Radio Frequency Devices Subpart C -Intentional Radiators
RSS-210 Issue 3	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment
RSS-Gen Issue 3	General Requirements and Information for the Certification of Radio Apparatus
ANSI C63.4 2009	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment

Table 1.6.2: Applicable Clauses		
Parameter	FCC Part 15 Rule Paragraphs	IC RSS References
Transmitter Characteristics	15.247	RSS 210 A1.1, RSS-Gen
Spurious Radiated Power	15.247, 15.209, 15.205	RSS 210 A1.1
Antenna Requirement	15.203	RSS-Gen

2.0 Fundamental Power

2.1 Test Procedure

Bandwidth is first determined to select correct entire bandwidth for power measurement and the fundamental power is measured.

2.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date
15.247(a)(3) // RSS-210 Issue 8, A2.9	Fundamental Power Conducted Limit: 1 Watt	2014-10-03

2.3 Test Results

Bandwidth was found to be 1343.8 kHz in 6 dB, so 3 MHz resolution bandwidth was employed for peak power measurement. Power was measured conducted direct to spectrum analyzer with no attenuation or cable loss. Power was measured with peak detection.


Table 2.3.1 Fundamental Conducted Power, Peak		
Conducted Limit 1 Watt (30 dBm)		
Frequency (MHz)	Measured Peak Power (dBm)	Measured Peak Power Restated Linear Terms (mW)
2405	7.87	6.12
2440	7.72	5.92
2480	2.01	1.59

Measured in 3 MHz RBW, 10 MHz VBW.

Power is reduced on the high channel to reduce band edge emissions (setting reference 0xB).


The EUT was found to be in compliance with the applicable criteria. Plotted measurements follow.

2.3.1 Low Channel




Peak Power, Low Channel

2.3.2 Middle Channel



Peak Power, Middle Channel

2.3.3 High Channel



Peak Power, High Channel

3.0 Power Spectral Density

3.1 Test Procedure

The EUT is placed in maximum signal orientation in operation on the test site turntable positioned for maximum signal. The spectrum analyzer is then adjusted to measure the power spectral density in the prescribed resolution bandwidth with an extended sweep time.

3.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date
15.247e // RSS-210 Issue 8, A2.9	Power Spectral Density, Conducted Limit: 8 dBm / 3 kHz	2014-10-03

3.3 Test Results

**Power Spectral Density
Conducted Limit 8 dBm in 3 kHz**


Frequency MHz	Corrected Measured Peak PSD (dBm)
2405	-7.55
2440	-7.63
2480	-13.52

Sweep time 500 seconds.


The EUT was found to be in compliance with the applicable criteria.

Plotted measurements appear below.

3.3.2 Middle Channel PSD



3.3.3 High Channel PSD



4.0 Transmitter Duty Cycle

4.1 Test Procedure

EUT is placed into normal transmit operation to observe and record transmitter time domain performance.

4.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date
15.35(c) // RSS-Gen Issue 8, 4.5	Averaging of Pulsed Transmissions	2014-09-15

Measurement is based on intervals not to exceed 100 msec. Maximum transmitter on time is divided by the lesser of 100 msec or the actual measured minimum transmitter interval time. The result is converted to dB and applied as needed to peak measurements of transmitter artifacts to determine average power. For permissible exposure the calculation is based on power and no limit applies to the result. This is not a pass/fail measurement.


4.3 Test Results

Table 4.3.1 Duty Cycle Results				
Measured On Time (msec)	Measured Time Interval (msec)	Duty Cycle Factor Calculation	Result (dB)	Duty Cycle Factor Allowed (dB)
0.96275	13.28	$= 20 * \text{Log}_{10} (0.96275 \text{ msec} / 13.28 \text{ msec})$	-23.13	-20


Table 4.3.2 Exposure Source Duty Cycle Results				
Measured On Time (msec)	Measured Time Interval (msec)	Exposure Duty Cycle Factor Calculation	Result (dB)	Duty Cycle Factor Allowed (dB)
0.96275	13.28	$= 10 * \text{Log}_{10} (0.96275 \text{ msec} / 13.28 \text{ msec})$	-11.56	-11.56

Plotted measurements appear below.

4.3.1 Transmit On Time



4.3.2 Transmit Interval Time



5.0 Occupied Bandwidth

5.1 Test Procedure

Bandwidth is measured by conducted means.

5.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date(s)
14.247(a)(2), 2.1049, KDB 558074 D01 // RSS-Gen Issue 3, 4.6	Bandwidth, 6 dB, 20 dB	2014-10-03

5.3 Test Results


Table 5.3.1 Bandwidth 6 dB, Minimum 500 kHz			
Low Channel Measured BW (kHz)	Mid Channel Measured BW (kHz)	High Channel Measured BW (kHz)	Minimum BW (kHz)
1343.8	1344.4	1566.9	1343.8

Table 5.3.2 Bandwidth 20 dB, Measure and Report			
Low Channel Measured BW (kHz)	Mid Channel Measured BW (kHz)	High Channel Measured BW (kHz)	Reported Maximum BW (kHz)
2536.3	2536.3	2536.3	2536.3


EUT was found to be in compliance with applicable requirements.

Plotted measurements appear on the following pages.


5.3.1 Bandwidth Plots, 6 dB



6 dB, Low Channel




6 dB, Middle Channel




6 dB, High Channel


5.3.2 Bandwidth Plots, 20 dB



20 dB, Low Channel



20 dB, Middle Channel



20 dB, High Channel

6.0 Band Edge

6.1 Test Procedure

EUT is placed into normal transmit operation on the nearest band edge channel. The spectrum analyzer is centered on the band edge frequency with span sufficient to include the peak of the adjacent fundamental signal. Measurement includes at least two standard bandwidths from the respective band edge. If required, the band-edge marker-delta method of C63.4 is utilized.

6.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date(s)
15.247, 15.205 // RSS-Gen Issue 3, 4.9	Unwanted Emissions Adjacent to Authorized Band, Conducted	2014-10-03

6.3 Test Results


Measurements included more than 2 standard bandwidths (standard bandwidth 100 kHz) from the band edges to provide a clear view of the declining emission levels. Peak detection with max-hold is employed. The general emission (FCC 15.209) limits for peak and average detection are shown.

The average duty cycle factor is -20 dB so the average emission would be 20 dB below the peak detected levels in every case.

Peak detection of emissions at low band-edge was below the -20 dBc criteria and below the general emission peak limits. At high band-edge peak limit margin was -2.6 dB and consequently average would have the same margin to the average limit.


The EUT satisfied the criteria. Plotted results appear on the following pages.

6.3.1 Low Channel Band Edge



Band Edge Emission, Peak Detection, Satisfies -20 dBc and 15.209 Criteria

6.3.2 High Channel Band Edge




Band Edge Emission, Peak Detection, Satisfies -20 dBc and 15.209 Criteria

7.0 Radiated Spurious Emissions, Receive Mode

7.1 Test Procedure

The EUT was placed on a non-conductive table 0.8 meters above the ground plane. The EUT was centered on a rotating turntable. Measurements below 1 GHz were taken at a test distance of 10 meters from the measurement antenna. Above 1 GHz the measurement distance was 3 meters.

Spurious emissions below 1 GHz were measured with quasi-peak detection with a resolution bandwidth of 120 kHz. Above 1 GHz peak measurements were taken and average measured where appropriate. A diagram showing the test setup appears below.



7.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date(s)
15.247, 15.209 // RSS-Gen Issue 3, 4.9, 4.10	Field Strength of Radiated Spurious/Harmonic Emissions	2014-08-27

7.3 Test Results

The EUT was tuned to the middle channel and external antenna was attached. The EUT was oriented as if mounted on a vertical surface with the antenna on top such that it was polarized vertically.

The EUT satisfied the criteria. Recorded data is presented below.


Table 7.3.1: Radiated Spurious Emissions, Receive Mode, Below 1 GHz, Vertical Polarity

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators, Radiated Emissions Limits		
Section:	15.109		
Test Date(s):	8/27/2014	EUT Serial #:	None
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Bob Redoutey
Purchase Order #:	Not Listed	Supervisor:	Rob McCollough
Equip. Under Test:	RX-MFS-ESCAN-HS-1 Receiver	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Vertical	Frequency Range:	30MHz to 1GHz
EUT Mode of Operation:		Receive	

Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
31.7347	10	297	3.74	Quasi-peak	24.1	12.153	29.5	-17.3	Pass
52.977	10	174	1.4	Quasi-peak	23.5	2.938	29.5	-26.6	Pass
56.9022	10	351	1.45	Quasi-peak	23.6	2.644	29.5	-26.9	Pass
128.028	10	116	2.74	Quasi-peak	23.3	2.224	33.1	-30.9	Pass
129.699	10	356	2.54	Quasi-peak	23.5	2.481	33.1	-30.6	Pass
253.392	10	22	1.46	Quasi-peak	22.2	8.711	35.6	-26.9	Pass
621.871	10	39	3.23	Quasi-peak	22	16.412	35.6	-19.2	Pass
916.52	10	288	4.05	Quasi-peak	21.3	21.148	35.6	-14.5	Pass




≤ 1GHz Vertical Antenna Polarity Measured Emissions

Table 7.3.2: Radiated Spurious Emissions, Receive Mode, Below 1 GHz, Horizontal Polarity

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators, Radiated Emissions Limits		
Section:	15.109		
Test Date(s):	8/27/2014	EUT Serial #:	None
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Bob Redoutey
Purchase Order #:	Not Listed	Supervisor:	Rob McCollough
Equip. Under Test:	RX-MFS-ESCAN-HS-1 Receiver	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12	VDC	EUT Power Frequency:	-	N/A				
Antenna Orientation:	Horizontal		Frequency Range:	30MHz to 1GHz					
EUT Mode of Operation:			Receive						
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
31.0865	10	321	3.45	Quasi-peak	24.2	12.59	29.5	-16.9	Pass
50.5305	10	335	1.67	Quasi-peak	23.2	2.925	29.5	-26.6	Pass
90.1008	10	281	1.31	Quasi-peak	23.1	2.063	33.1	-31.0	Pass
170.8	10	29	3.76	Quasi-peak	22.8	4.763	33.1	-28.3	Pass
251.796	10	165	1.3	Quasi-peak	22.2	8.71	35.6	-26.9	Pass
479.091	10	182	1.06	Quasi-peak	22.3	13.871	35.6	-21.7	Pass
616.217	10	122	1.19	Quasi-peak	22.1	16.359	35.6	-19.2	Pass
924.64	10	201	2.3	Quasi-peak	21.2	21.098	35.6	-14.5	Pass



≤ 1GHz Horizontal Antenna Polarity Measured Emissions

Table 7.3.3: Radiated Spurious Emissions, Receive Mode, Above 1 GHz, Vertical Polarity

Professional Testing, EMI, Inc.									
Test Method:		ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).							
In accordance with:		FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators, Radiated Emissions Limits							
Section:		15.109							
Test Date(s):		8/27/2014			EUT Serial #:		None		
Customer:		Hetronic			EUT Part #:		None		
Project Number:		16271-15			Test Technician:		Bob Redoutey		
Purchase Order #:		Not Listed			Supervisor:		Rob McCollough		
Equip. Under Test:		RX-MFS-ESCAN-HS-1 Receiver			Witness' Name:		None		
Radiated Emissions Test Results Data Sheet							Page: 1 of 1		
EUT Line Voltage:		12 VDC		EUT Power Frequency:		- N/A			
Antenna Orientation:		Vertical			Frequency Range:		Above 1GHz		
EUT Mode of Operation:					Receive				
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
1347.16	3	88	1	Average	35.4	22.825	54.0	-31.1	Pass
1971.55	3	302	1	Average	38.1	27.957	54.0	-26.0	Pass
2398.81	3	314	1	Average	34.8	25.851	54.0	-28.1	Pass
2792.56	3	228	1	Average	35	27.415	54.0	-26.5	Pass
3608.63	3	202	1	Average	34.8	27.554	54.0	-26.4	Pass
6649.75	3	348	1	Average	30.4	32.443	54.0	-21.5	Pass
8680.45	3	237	1	Average	27.3	35.718	54.0	-18.2	Pass
11593.2	3	101	1	Average	27.4	38.275	54.0	-15.7	Pass
16764.4	3	260	1	Average	27.6	43.733	54.0	-10.2	Pass

Professional Testing, EMI, Inc
 Radiated Emissions, 3m Distance
 1-18GHz Vertical Polarity Measured Emissions

Operator: Bob Redoutey
 16271_2014 Rad Emissions_ClassB_071514.tif
 11:29:03 AM, Wednesday, August 27, 2014

EUT Mode: Receive
 EUT Power: 12VDC

EUT: RX-MFS-ESCAN-HS-1 Receiver
 Project Number: 16271-15
 Client: Hetronic

> 1GHz Vertical Antenna Polarity Measured Emissions

Table 7.3.4: Radiated Spurious Emissions, Receive Mode, Above 1 GHz, Vertical Polarity

Professional Testing, EMI, Inc.									
Test Method:		ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).							
In accordance with:		FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators, Radiated Emissions Limits							
Section:		15.109							
Test Date(s):		8/27/2014			EUT Serial #:		None		
Customer:		Hetronic			EUT Part #:		None		
Project Number:		16271-15			Test Technician:		Bob Redoutey		
Purchase Order #:		Not Listed			Supervisor:		Rob McCollough		
Equip. Under Test:		RX-MFS-ESCAN-HS-1 Receiver			Witness' Name:		None		
Radiated Emissions Test Results Data Sheet							Page: 1 of 1		
EUT Line Voltage:		12 VDC		EUT Power Frequency:		- N/A			
Antenna Orientation:		Horizontal			Frequency Range:		Above 1GHz		
EUT Mode of Operation:					Receive				
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
1390.27	3	321	1	Average	36.1	23.495	54.0	-30.5	Pass
1989.11	3	219	1	Average	35	24.874	54.0	-29.1	Pass
2403.38	3	33	1	Average	34.8	25.892	54.0	-28.1	Pass
4202.9	3	309	1	Average	34.1	28.521	54.0	-25.4	Pass
6108.29	3	65	1	Average	31.3	31.556	54.0	-22.4	Pass
8682.24	3	312	1	Average	27.3	35.714	54.0	-18.2	Pass
10736.1	3	182	1	Average	27.2	37.172	54.0	-16.8	Pass
11589.3	3	94	1	Average	27.3	38.242	54.0	-15.7	Pass
16923.5	3	240	1	Average	27.4	43.678	54.0	-10.3	Pass

Professional Testing, EMI, Inc
 Radiated Emissions, 3m Distance
 1-18GHz Horizontal Polarity Measured Emissions

Operator: Bob Redoutey
 16271_2014 Rad Emissions_ClassB_071514.til
 11:29:03 AM, Wednesday, August 27, 2014

EUT Mode: Receive
 EUT Power: 12VDC

EUT: RX-MFS-ESCAN-HS-1 Receiver
 Project Number: 16271-15
 Client: Hetronic


> 1GHz Horizontal Antenna Polarity Measured Emissions

8.0 Radiated Spurious Emissions, Transmit Mode

8.1 Test Procedure

The EUT was placed on a non-conductive table 0.8 meters above the ground plane. The EUT was centered on a rotating turntable. Measurements below 1 GHz were taken at a test distance of 10 meters from the measurement antenna. Above 1 GHz the measurement distance was 3 meters.

Spurious emissions below 1 GHz were measured with quasi-peak detection with a resolution bandwidth of 120 kHz. Above 1 GHz peak measurements were taken and average measured where appropriate. A diagram showing the test setup appears below.



8.2 Test Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date(s)
15.247, 15.209 // RSS-Gen Issue 3, 4.9, 4.10	Field Strength of Radiated Spurious/Harmonic Emissions	2014-09-11 to 2014-10-02

8.3 Test Results

Below 1 GHz measurements were taken in transmit mode on the middle channel. Above 1 GHz measurements were taken on the three standard channels of the band.

The EUT external antenna was attached. The EUT was oriented as if mounted on a vertical surface with the antenna on top such that it was polarized vertically.

Peak measurements were taken above 1 GHz. The applicable duty cycle factor for averaging transmitter spurious to compare to average limit above 1 GHz is -20 dB. General emission peak and average limits lines are provided on the relevant plots.


Table 8.3.1: TX Mode, Below 1 GHz, Vertical Polarity, Mid. Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/11/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet

Page: 1 of 1

EUT Line Voltage:	12	VDC	EUT Power Frequency:	-	N/A				
Antenna Orientation:	Vertical		Frequency Range:	30MHz to 1GHz					
EUT Mode of Operation:			Transmit Mid Chan						
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
52.2059	10	15	1.54	Quasi-peak	23.9	3.421	29.5	-26.1	Pass
52.7798	10	220	1.54	Quasi-peak	24.3	3.738	29.5	-25.8	Pass
53.1388	10	17	3.82	Quasi-peak	24	3.385	29.5	-26.1	Pass
935.79	10	242	3.97	Quasi-peak	21.2	21.205	35.6	-14.4	Pass




≤ 1GHz Vertical Antenna Polarity Measured Emissions

Table 8.3.2: TX Mode, Below 1 GHz, Horizontal Polarity, Mid. Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/11/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12	VDC	EUT Power Frequency:	-	N/A				
Antenna Orientation:	Horizontal		Frequency Range:	30MHz to 1GHz					
EUT Mode of Operation:			Transmit Mid Chan						
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
938.628	10	72	3.64	Quasi-peak	21	21.11	35.6	-14.5	Pass
990.793	10	21	1.73	Quasi-peak	21.1	22.163	43.5	-21.3	Pass



≤ 1GHz Horizontal Antenna Polarity Measured Emissions

Table 8.3.3: TX Mode, Above 1 GHz, Vertical Polarity, Low Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/28/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None
Radiated Emissions Test Results Data Sheet			Page: 1 of 1
EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Vertical	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Low Chan	
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Vertical Polarity Measured Emissions</p> </div> <div style="width: 35%; border: 1px solid black; padding: 5px;"> <ul style="list-style-type: none"> — Average Limit Level ▽ Corrected Average Reading — Peak Limit Level — Corrected Peak Reading </div> </div> <p style="font-size: small;">Operator: Eric Lifsey 16271'RE2'Run02'Tx'MHzGHz'Ch1.tif 03:27:37 PM, Sunday, September 28, 2014</p> <p style="font-size: small; text-align: center;">Frequency</p> <p style="font-size: small; text-align: right;">EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p>			
> 1GHz Vertical Antenna Polarity Measured Emissions			

Table 8.3.4: TX Mode, Above 1 GHz, Horizontal Polarity, Low Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/28/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None
Radiated Emissions Test Results Data Sheet			Page: 1 of 1
EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Low Chan	
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Horizontal Polarity Measured Emissions</p> </div> <div style="width: 35%; border: 1px solid black; padding: 5px;"> <p>— Average Limit Level △ Corrected Average Reading — Peak Limit Level — Corrected Peak Reading</p> <p style="text-align: right;">PROFESSIONAL TESTING, INC.</p> </div> </div> <p>Operator: Eric Lifsey 16271'RE2'Run02'Tx'MHzGHz'Ch1.ttl 03:27:34 PM, Sunday, September 28, 2014</p> <p style="text-align: center;">Frequency</p> <p>EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p> <p style="text-align: center;">EUT Mode: Transmit Ch 1 EUT Power: 12 VDC Sample 2</p>			
> 1GHz Horizontal Antenna Polarity Measured Emissions			

Table 8.3.5: TX Mode, Above 1 GHz, Vertical Polarity, Middle Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/28/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None
Radiated Emissions Test Results Data Sheet			Page: 1 of 1
EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Vertical	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Mid Chan	
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Vertical Polarity Measured Emissions</p> </div> <div style="width: 35%; border: 1px solid black; padding: 5px;"> <ul style="list-style-type: none"> — Average Limit Level ▽ Corrected Average Reading — Peak Limit Level — Corrected Peak Reading </div> </div> <p style="font-size: small;">Operator: Eric Lifsey 16271'RE2'Run01'Tx'MHzGHz'Ch8.ttl 02:22:12 PM, Sunday, September 28, 2014</p> <p style="font-size: small; text-align: center;">EUT Mode: Transmit Ch 8 EUT Power: 12 VDC Sample 2</p> <p style="font-size: small; text-align: right;">EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p>			
> 1GHz Vertical Antenna Polarity Measured Emissions			

Table 8.3.6: TX Mode, Above 1 GHz, Horizontal Polarity, Middle Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	9/28/2014	EUT Serial #:	Sample 2
Customer:	\	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None
Radiated Emissions Test Results Data Sheet			Page: 1 of 1
EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Mid Chan	
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Horizontal Polarity Measured Emissions</p> </div> <div style="width: 35%; text-align: right;"> <p>Operator: Eric Lifsey 16271'RE2'Run01Tx'MHzGHz'Ch8.tif 02:22:08 PM, Sunday, September 28, 2014</p> </div> <div style="width: 35%; text-align: right;"> <p>EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p> </div> </div>			
> 1GHz Horizontal Antenna Polarity Measured Emissions			

Table 8.3.7: TX Mode, Above 1 GHz, Vertical Polarity, High Channel



Professional Testing, EMI, Inc.									
Test Method:		ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).							
In accordance with:		FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits							
Section:		15.209							
Test Date(s):		10/2/2014			EUT Serial #:		Sample 2		
Customer:		Hetronic			EUT Part #:		None		
Project Number:		16271-15			Test Technician:		Eric Lifsey		
Purchase Order #:		Not Listed			Supervisor:		Lisa Arndt		
Equip. Under Test:		RX-MFS-ESCAN-HS-1			Witness' Name:		None		
Radiated Emissions Test Results Data Sheet							Page: 1 of 1		
EUT Line Voltage:		12 VDC		EUT Power Frequency:		- N/A			
Antenna Orientation:		Vertical			Frequency Range:		Above 1GHz		
EUT Mode of Operation:					Transmit High Chan				
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
9919	3	0	1	Peak	72.97	72.97	74.0	-1.0	Pass
<div style="display: flex; justify-content: space-between;"> <div> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Vertical Polarity Measured Emissions</p> </div> <div style="border: 1px solid black; padding: 2px;"> <p>— Average Limit Level ▽ Corrected Average Reading — Peak Limit Level — Corrected Peak Reading</p> </div> <div style="text-align: right;">  </div> </div>  <p>Operator: Erik Lifsey 16271'RE2'Run04'Tx'MHzGHz'Ch16'0x7.tif 03:30:25 PM, Thursday, October 02, 2014</p> <p>EUT Mode: Transmit Ch 16 EUT Power: 12 VDC Sample 2, Power 0x7</p> <p>EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p>									
> 1GHz Vertical Antenna Polarity Measured Emissions									

Table 8.3.8: TX Mode, Above 1 GHz, Horizontal Polarity, High Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None
Radiated Emissions Test Results Data Sheet			Page: 1 of 1
EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit High Chan	
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Professional Testing, EMI, Inc Radiated Emissions, 3m Distance 1-18GHz Horizontal Polarity Measured Emissions</p> </div> <div style="width: 35%;"> <p>Operator: Eric Lifsey 16271'RE2'Run04Tx'MHzGHz'Ch16'0x7.tif 03:30:23 PM, Thursday, October 02, 2014</p> </div> </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div style="width: 30%;"> <p>EUT Mode: Transmit Ch 16 EUT Power: 12 VDC Sample 2, Power 0x7</p> </div> <div style="width: 35%;"> <p>EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p> </div> </div>			
> 1GHz Horizontal Antenna Polarity Measured Emissions			

8.3.9 TX Mode, 18 GHz to 25 GHz, Vertical, Low Channel


Professional Testing, EMI, Inc.									
Test Method:		ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).							
In accordance with:		FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits							
Section:		15.209							
Test Date(s):		10/2/2014			EUT Serial #:		Sample 2		
Customer:		Hetronic			EUT Part #:		None		
Project Number:		16271-15			Test Technician:		Eric Lifsey		
Purchase Order #:		Not Listed			Supervisor:		Lisa Arndt		
Equip. Under Test:		RX-MFS-ESCAN-HS-1			Witness' Name:		None		
Radiated Emissions Test Results Data Sheet								Page: 1 of 1	
EUT Line Voltage:		12 VDC		EUT Power Frequency:		- N/A			
Antenna Orientation:		Vertical			Frequency Range:		Above 1GHz		
EUT Mode of Operation:					Transmit Low Chan				
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results
<p>Professional Testing, EMI, Inc Radiated Emissions, Measured at 1m and Scaled to 3m Distance 18-26.5 GHz Vertical Polarity Measured Emissions</p> <p>Operator: Eric Lifsey 16271 RE2 Run 05 Tx MHzGHzGHz2 Ch1 0x7.tiff EUT Mode: Transmit Ch 1 04:38:46 PM, Thursday, October 02, 2014 EUT Power: 12 VDC Sample 2, Power 0x7</p> <p>EUT: RX-MFS-ESCAN-HS-1 Project Number: 16271-15 Client: Hetronic</p>									
> 1GHz Vertical Antenna Polarity Measured Emissions									

8.3.10 TX Mode, 18 GHz to 25 GHz, Horizontal, Low Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Low Chan	



> 1GHz Horizontal Antenna Polarity Measured Emissions


8.3.11 TX Mode, 18 GHz to 25 GHz, Vertical, Middle Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12	VDC	EUT Power Frequency:	-	N/A
Antenna Orientation:	Vertical		Frequency Range:	Above 1GHz	

EUT Mode of Operation:					Transmit Middle Chan				
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results




> 1GHz Vertical Antenna Polarity Measured Emissions

8.3.12 TX Mode, 18 GHz to 25 GHz, Horizontal, Middle Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit Middle Chan	



> 1GHz Horizontal Antenna Polarity Measured Emissions


8.3.13 TX Mode, 18 GHz to 25 GHz, Vertical, High Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Arndt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1

EUT Line Voltage:	12	VDC	EUT Power Frequency:	-	N/A				
Antenna Orientation:	Vertical		Frequency Range:	Above 1GHz					
EUT Mode of Operation:			Transmit High Chan						
Frequency Measured (MHz)	Test Distance (Meters)	EUT Direction (Degrees)	Antenna Height (Meters)	Detector Function	Recorded Amplitude (dBµV)	Corrected Level (dBµV/m)	Limit Level (dBµV/m)	Margin (dB)	Test Results

Professional Testing, EMI, Inc
 Radiated Emissions, Measured at 1m and Scaled to 3m Distance
 18-26.5 GHz Vertical Polarity Measured Emissions



Operator: Eric Lifsey
 16271 RE2 Run07 Tx MHzGHzGHz2 Ch16 0x7
 05:01:37 PM, Thursday, October 02, 2014
 EUT Mode: Transmit Ch 16
 EUT Power: 12 VDC
 Sample 2, Power 0x7
 EUT: RX-MFS-ESCAN-HS-1
 Project Number: 16271-15
 Client: Hetronic


> 1GHz Vertical Antenna Polarity Measured Emissions

8.3.14 TX Mode, 18 GHz to 25 GHz, Horizontal, High Channel

Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, see §15.38).		
In accordance with:	FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators, Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Test Results Data Sheet Page: 1 of 1



EUT Line Voltage:	12 VDC	EUT Power Frequency:	- N/A
Antenna Orientation:	Horizontal	Frequency Range:	Above 1GHz
EUT Mode of Operation:		Transmit High Chan	



> 1GHz Horizontal Antenna Polarity Measured Emissions

9.0 Setup Photographs

9.1 Receive Mode Spurious


Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators,		
In accordance with:	Radiated Emissions Limits		
Section:	15.109		
Test Date(s):	8/27/2014	EUT Serial #:	None
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Bob Redoutey
Purchase Order #:	Not Listed	Supervisor:	Rob McCollough
Equip. Under Test:	RX-MFS-ESCAN-HS-1 Receiver	Witness' Name:	None
Radiated Emissions Photographs			Page: 1 of 1
			
Front		Back	

9.2 Transmit Mode Spurious, 30 MHz to 25 GHz


Professional Testing, EMI, Inc.			
Test Method:	ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, FCC Part 15.209 - Code of Federal Regulations Part 47, Subpart C - Intentional Radiators,		
In accordance with:	Radiated Emissions Limits		
Section:	15.209		
Test Date(s):	10/2/2014	EUT Serial #:	Sample 2
Customer:	Hetronic	EUT Part #:	None
Project Number:	16271-15	Test Technician:	Eric Lifsey
Purchase Order #:	Not Listed	Supervisor:	Lisa Ardnt
Equip. Under Test:	RX-MFS-ESCAN-HS-1	Witness' Name:	None

Radiated Emissions Photographs


Page: 1 of 1




Front 1-18 GHz



Back 1-18 GHz





Front 18-25 GHz



Back 18-25 GHz

9.3 Conducted Port Setup, Power, PSD, Timing and Bandwidth



10.0 Antenna Construction Requirements

The design was investigated for meeting the antenna construction requirements of the applicable rules.

10.1 Procedure

A direct examination of the antenna construction is performed and compared to rule criteria that prevent wireless device antennas from being modified by end users in ways that would void their authorization to use the device.

10.2 Criteria

47 CFR (USA) // IC (Canada)		
Section Reference	Parameter	Date(s)
15.203 // RSS-210 Issue 8, A2.9	Antenna Construction	2014-10-04

10.3 Results

Table 9.3.1 Antenna Construction Details	
Antenna Manufacturer and Model	Specifications
Antenna is Model: 56506605 Manufacturer: APEX - Gainflex Type GK 442TF R	Half wave flexible dipole – maximum power 10W – TNC Plug Reverse Polarity Gain 3 dBi

- Antenna connector uses reverse polarity center pin.
- Antenna is provided with the device.

The antenna design above satisfies the requirements of the rules.

11.0 Equipment

11.1 Spurious Radiated Emissions 30 MHz to 25 GHz

Professional Testing, EMI, Inc.					
Test Method:		ANSI C63.4–2003: “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz” (incorporated by reference, FCC Part 15.109 - Code of Federal Regulations Part 47, Subpart B - Unintentional Radiators,			
In accordance with:		Radiated Emissions Limits			
Section:		15.109			
Test Date(s):		8/27/2014	EUT Serial #:	None	
Customer:		Hetronic	EUT Part #:	None	
Project Number:		16271-15	Test Technician:	Bob Redoutey	
Purchase Order #:		Not Listed	Supervisor:	Rob McCollough	
Equip. Under Test:		RX-MFS-ESCAN-HS-1 Receiver	Witness' Name:	None	
Radiated Emissions Test Equipment List					
Title! Software Version:		4.2.A, May 23, 2010, 08:38:52 AM			
Test Profile:		Radiated Emissions_Profile Version October 12, 2011			
Asset #	Manufacturer	Model	Equipment Nomenclature	Serial Number	Calibration Due Date
1509A	Braden	N/A	TDK 10M Chamber, NSA < 1 GHz	DAC-012915-005	11/29/2014
1890	HP	8447F	Preamp/Amp, 9kHz-1300MHz, 28/25dB	3313A05298	1/22/2015
1937	Agilent	E4440A	Spectrum Analyzer, 3 Hz - 26.5 GHz	MY44303298	12/2/2015
1926	ETS-Lindgren	3142D	Antenna, Biconilog, 26 MHz - 6 GHz	00135454	10/29/2014
C027	N/A	RG214	Cable Coax, N-N, 25m	none	10/22/2015
1327	EMCO	1050	Controller, Antenna Mast	none	N/A
0942	EMCO	11968D	Turntable, 4ft.	9510-1835	N/A
1969	HP	11713A	Attenuator/Switch Driver	3748A04113	N/A
1509B	Braden	N/A	TDK 10M Chamber, VSWR > 1 GHz	DAC-012915-005	11/16/2014
2004	Miteq	AFS44-00101800-2S-10P-44	Amplifier, 40dB, .1-18GHz	0	11/19/2014
C030	N/A	0	Cable Coax, N-N, 30m	none	10/10/2015
1780	ETS-Lindgren	3117	Antenna, Double Ridged Guide Horn, 1 - 18 GHz	00110313	1/21/2015
1325	EMCO	1050	Controller, Antenna Mast	9003-1461	N/A

11.2 Timing and Bandwidth Measurements

Asset #	Manufacturer	Model #	Description	Calibration Due
ALN-077	Rohde & Schwarz	FSP-30	Spectrum Analyzer	2015-01-29

12.0 Measurement Bandwidths, Radiated Emissions, Spurious

Radiated Emissions Spectrum Analyzer Bandwidth and Measurement Time - Peak Scan				
Frequency Band Start (MHz)	Frequency Band Stop (MHz)	6 dB Bandwidth (kHz)	Number of Ranges Used	Measurement Time per Range
0.009	0.15	0.3	2	Multiple Sweeps
0.15	30	9	6	Multiple Sweeps
30	1000	120	2	Multiple 800 mS Sweeps
1000	6000	1000	2	Multiple Sweeps
6000	18000	300	2	Multiple Sweeps

*Notes:

1. The settings above are specifically calculated for the E4440A series of spectrum analyzers, which have 8,000 data points per range.
2. The measurement receiver resolution bandwidth setting was 300 Hz for quasi-peak measurements from 9-150 kHz.
3. The measurement receiver resolution bandwidth setting was 9 kHz for quasi-peak measurements from 0.15-30 MHz.
4. The measurement receiver resolution bandwidth setting was 120 kHz for quasi-peak measurements from 30-1000 MHz.
5. The measurement receiver resolution bandwidth setting was 1 MHz for average measurements from 1-18 GHz.

Appendix: Policy, Rationale, and Evaluation of EMC Measurement Uncertainty

All uncertainty calculations, estimates and expressions thereof shall be in accordance with NIST policy. Since PTI operates in accordance with NIST (NVLAP) Handbook 150-11: 2007, all instrumentation having an effect on the accuracy or validity of tests shall be periodically calibrated or verified traceable to national standards by a competent calibration laboratory. The certificates of calibration or verification on this instrumentation shall include estimates of uncertainty as required by NIST Handbook 150-11.

1. Rationale and Summary of Expanded Uncertainty.

Each piece of instrumentation at PTI that is used in making measurements for determining conformance to a standard (or limit), shall be assessed to evaluate its contribution to the overall uncertainty of the measurement in which it is used. The assessment of each item will be based on either a type A evaluation or a type B evaluation. Most of the evaluations will be type B, since they will be based on the manufacturer's statements or specifications of the calibration tolerances, or uncertainty will be stated along with a brief rationale for the type of evaluation and the resulting stated uncertainties.

The individual uncertainties included in the combined standard uncertainty for a specific test result will depend on the configuration in which the item of instrumentation is used. The combination will always be based on the law of propagation of uncertainty. Any systematic effects will be accommodated by including their uncertainties, in the calculation of the combined standard uncertainty; except that if the direction and amount of the systematic effect cannot be determined and separated from its uncertainty, the whole effect will be treated as uncertainty and combined along with the other elements of the test setup.

Type A evaluations of standard uncertainty will usually be based on calculating the standard deviation of the mean of a series of independent observations, but may be based on a least-squares curve fit or the analysis of variance for unusual situations. Type B evaluations of standard uncertainty will usually be based on manufacturer's specifications, data provided in calibration reports, and experience. The type of probability distribution used (normal, rectangular, a priori, or u-shaped) will be stated for each Type B evaluation.

In the evaluation of the uncertainty of each type of measurement, the uncertainty caused by the operator will be estimated. One notable operator contribution to measurement uncertainty is the manipulation of cables to maximize the measured values of radiated emissions. The operator contribution to measurement uncertainty is evaluated by having several operators independently repeat the same test. This results in a Type A evaluation of operator-contributed measurement uncertainty.

A summary of the expanded uncertainties of PTI measurements is shown as Table 1. These are the worst-case uncertainties considering all operative influence factors.

Table 1: Summary of Measurement Uncertainties for Site 45

Type of Measurement	Frequency Range	Meas. Dist.	Expanded Uncertainty U, dB (k=2)
Mains Conducted Emissions	150 kHz to 30 MHz	N/A	2.9
Telecom Conducted Emissions	150 kHz to 30 MHz	N/A	2.8
Radiated Emissions	30 to 1,000 MHz	10 m	4.8
	1 to 18 GHz	3 m	5.7

End of Report

(This page intentionally left blank.)