


**This document/data record is the property of PCI LTD, and is confidential material.**

3RD ANGLE 	MATERIAL OR SOURCE See Note	GENERAL TOLERANCE ±0.5
	SCALE 1 : 1	FINISH See Note
		ONE DECIMAL PL
		TWO DECIMAL PL
		ANGULAR

REV	DESCRIPTION	DATE
-----	-------------	------

Model : PCI-TP1  
 MCN : P18-TP001-300  
 SN : 100YYWWXXXXXX  
 IMEI : XXXXXXXXXXXXXXXX  
 Contains FCC ID : LY5-PCITP100  
 Contains IC : 5113A-PCITP100

FCC ID : LY5-PCITP1  
 IC : 5113A-PCITP1  
 Class : CAN ICES-3(A)/NMB-3(A)  
 ICC ID : XXXXXXXXXXXXXXXX  
 Input : DC 12V --- 0.5A or 24V --- 0.25A  
 MADE IN INDONESIA

2D  
Barcode

REVISIONS ARE INDICATED BY TRIANGLED LETTERS  
ALL DIMENSIONS IN MILLIMETRES

**NOTES :**

1. Refer to separate drawing for blank label material spec (HQLB000100)
2. This part must comply with RoHS

**Label Contents :**

Serial Number : 100YYWWXXXXXX  
 100 - Hardware Version  
 YYWW - Date Code  
 XXXXXX- 6 Digits Running Number  
 Starting from 000001

MCN : P18-TP001-100  
 P - PCI Design  
 18 - FY18 Project  
 TP001 - Product Code  
 100 - Build Version  
 (i.e. 100 for P1, 120 for P1.2 build, ...)

Content	Info	Format	Font	Size
Model	PCI-TP1	7 characters	Arial Narrow, Bold	8
MCN	P18-TP001-200	13 characters	Arial Narrow, Bold	6
Serial Number	100YYWWXXXXXX	13 characters	Arial Narrow, Bold	6
Serial Number Barcode	Barcode Symbiology Code 128	13 characters	-	-
IMEI	XXXXXXXXXXXXXX	15 characters	Arial Narrow	6
IMEI Barcode	Barcode Symbiology Code 128	15 characters	-	-
Contains FCC ID	LY5-PCITP100	12 characters	Arial Narrow	5
Contains IC	5113A-PCITP100	14 characters	Arial Narrow	5
FCC ID	LY5-PCITP1	10 characters	Arial Narrow	6
IC	5113A-PCITP1	12 characters	Arial Narrow	6
Class	CAN ICES-3(A)/NMB-3(A)	22 characters	Arial Narrow	6
ICC ID	XXXXXXXXXXXXXX	20 characters	Arial Narrow	6
Input	DC 12V --- 0.5A or 24V --- 0.25A	-	Arial Narrow	5
Country of Origin	MADE IN INDONESIA	17 characters	Arial Narrow	5
2D Barcode	See 2D Barcode Definition	-	-	-

**2D Barcode Contents :**

Position	Description	Content
1-13	MCN	13 characters MCN #
14	Semicolon	;
15-27	Serial Number	13 characters Serial Number
28	Semicolon	;
29-43	IMEI	15 characters IMEI
44	Semicolon	;
45-64	ICC ID	20 characters ICC ID
65	Semicolon	;
66-77	MAC Address (Ethernet)	12 digits MAC Address
78	Semicolon	;
79-90	MAC Address (Bluetooth Modem)	12 digits MAC Address
91	Semicolon	;
92-103	MAC Address (Wi-Fi Modem)	12 digits MAC Address
104	Semicolon	;
105-121	MADE IN INDONESIA	17 characters Country of Origin
122	Semicolon	;

A	Initial Issue	11 Mar 2019
---	---------------	-------------

DRAWN BY: TELLY K. DATE: 11 Mar 2019

APPROVED BY (ORIGINATOR'S DEPT. HEAD): T. NATHAN

RELEASED BY (ORIGINATOR): SYED SHARFUDEEN



TITLE: Printing for TP1 ID LABEL

CUSTOMER:

SPEC OR DWG NUMBER	SHT	1	1
			SHT