

**This document/data record is the property of
PCI Private Limited, and is confidential material.**

3RD ANGLE 	MATERIAL OR SOURCE See Note	GENERAL TOLERANCE	
SCALE 1 : 1	FINISH See Note	ONE DECIMAL PL	
		TWO DECIMAL PL	
		ANGULAR	

REVISIONS ARE INDICATED BY TRIANGLED LETTERS
ALL DIMENSIONS IN MILLIMETRES

REV	DESCRIPTION	DATE
-----	-------------	------

A	Initial Issue	07 AUG 2024
---	---------------	-------------

Model : PCI-TP2
MCN : P22-TP002
SN : XXXYYWWnnnnnn
IMEI : XXXXXXXXXXXXX
Input : DC 12V --- 0.5A or 24V --- 0.25A
MADE IN INDONESIA

Model : PCI-TP2V2
ICC ID : XXXXXXXXXXXXXXXX
FCC ID : LY5-PCITP2V2
IC : 5113A-PCITP2V2
Class : CAN ICES-3(A)/NMB-3(A)

2D
Code

NOTES :

- All printed text and bar code shall be permanent, resistant to smearing
- Refer to separate drawing for blank label material spec (HQLB000100)
- This part must comply with RoHS

Label Contents :

Serial Number : XXXYYWWnnnnnn
XXX - Hardware Version
YYWW - Date Code
nnnnnn - 6 Digits Running Number
Starting from 000001

MCN : P22-TP002
P - PCI Design
22 - FY22 Project
TP002 - Product Code

Content	Info	Format	Font	Size
Model	PCI-TP2	7 characters	Arial Narrow, Bold	8
MCN	P22-TP002	9 characters	Arial Narrow, Bold	6
Serial Number	XXXYYWWnnnnnn	13 characters	Arial Narrow, Bold	6
Serial Number Barcode	Barcode Symbiology Code 128	13 characters	-	-
IMEI	XXXXXXXXXXXXXX	15 characters	Arial Narrow	6
IMEI Barcode	Barcode Symbiology Code 128	15 characters	-	-
FCC ID	LY5-PCITP2V2	12 characters	Arial Narrow	6
IC	5113A-PCITP2V2	14 characters	Arial Narrow	6
Class	CAN ICES-3(A)/NMB-3(A)	22 characters	Arial Narrow	6
ICC ID	XXXXXXXXXXXXXX	20 characters	Arial Narrow	6
Input	DC 12V --- 0.5A or 24V --- 0.25A	-	Arial Narrow	5
Country of Origin	MADE IN INDONESIA	17 characters	Arial Narrow	5
2D Code	See 2D Code Definition	-	-	-

2D Code Contents :

Position	Description	Content
1-9	MCN	9 characters MCN #
10	Semicolon	;
11-23	Serial Number	13 characters Serial Number
24	Semicolon	;
25-39	IMEI	15 characters IMEI
40	Semicolon	;
41-60	ICC ID	20 characters ICC ID
61	Semicolon	;
62-73	MAC Address (Ethernet)	12 digits MAC Address
74	Semicolon	;
75-86	MAC Address (Bluetooth Modem)	12 digits MAC Address
87	Semicolon	;
88-99	MAC Address (Wi-Fi Modem)	12 digits MAC Address
100	Semicolon	;
101-117	MADE IN INDONESIA	17 characters Country of Origin
118	Semicolon	;

Hardware Version:

BUILD	XXX
P1	100
P2	200
P3	300
P4	400
MP	400

DRAWN BY
M. RADITIYA D.

DATE
07 Aug 2024

APPROVED BY (ORIGINATOR'S DEPT. HEAD)
TETEN MASDAR

RELEASED BY (ORIGINATOR)
TELLY K.



TITLE
DWG LH LHP22-TP002-10
ID LABEL

CUSTOMER
LHP TELEMATICS LLC

SPEC OR DWG NUMBER
-

SHT
1

SHT
1