

<p><b>APPLICANT</b></p> <p>Fomotech International Corporation  2F-1, 286-3, Hsin Ya Road  Chein Chen District  Kaohsing, Taiwan</p>	<p><b>MANUFACTURER</b></p> <p>Fomotech International Corporation  2F-1, 286-3, Hsin Ya Road  Chein Chen District  Kaohsing, Taiwan</p>
---	--

TEST SPECIFICATION: FCC Rules and Regulations Part 15, Subpart C, Para. 15.231

TEST PROCEDURE: ANSI C63.4:1992

**TEST SAMPLE DESCRIPTION**

BRANDNAME: Fomotech International Corp. MODEL: Alpha 520

TYPE: 301.105 MHz RF Transmitter

POWER REQUIREMENTS: 4.5 VDC via 3X "AA" Batteries

FREQUENCY OF OPERATION: 301.4 MHz

**TESTS PERFORMED**

Para. 15.231(b), Radiated Emissions, Fundamental and Harmonics

Para. 15.231(c), Occupied Bandwidth

Duty Cycle

## REPORT OF MEASUREMENTS

Applicant: Fomotech International Corp.  
Device: 301.105 MHz RF Transmitter  
FCC ID: LZ6ALPHA504SERIES  
Power Requirements: 4.5 VDC via 3X "AA" Batteries  
Applicable Rule Section: Part 15, Subpart C, Section 15.231

### TEST RESULTS

- 15.231 (a) - The device is used for industrial remote control/security applications (ie: remote control of cranes, hoists, trolleys, etc.)
- 15.231 (a)(1) & - The transmitter is manually operated and ceases transmission within 5  
15.231(2) seconds after deactivation.
- 15.231 (a)(3) - The transmitter does not perform periodic transmissions.
- 15.231 (a)(4)- The device is employed for RC purposes involving security as described in Paragraph 15.231(a) above.
- 15.231 (b) - The fundamental field strength did not exceed 5460  $\mu$ V/M (Average) at a test distance of 3 meters. In addition, the requirements of section 15.35 for averaging pulsed emissions and for limiting peak emissions were met.
- The field strength of harmonic and spurious emissions did not exceed 546  $\mu$ V/M (AVERAGE).
- 15.231 (c) - The device operates at 301.105 MHz. The bandwidth of emissions did not exceed 0.25% of the operating frequency (752.7Hz).

## REPORT OF MEASUREMENTS (continued)

### DETERMINATION OF FIELD STRENGTH LIMITS

The field strength limits shown below are found in Section 15.231.

Frequency		Limit	
F1	= 260	3750	= L1
Fo	= 301.105		Lo
F2	= 470	12500	= L2

The formula below was utilized to determine the limits:

$$\text{Limit} = L1 + [(Fo-F1)(L2-L1)/(F2-F1)]$$

Solving yields:

$$\text{Fundamental Limit} = 5,460 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

$$\text{Harmonic Limit} = 546 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

### DETERMINATION OF DUTY CYCLE

The unit's RF output was directly coupled to the input of the spectrum analyzer. The analyzer was set for a frequency span of 0Hz. The sweep time was then adjusted in order to display one full pulse train. The transmitter on time was then summed and compared to the time for one full cycle in order to obtain the duty cycle.

$$\text{Transmitter On Time} = >100.0 \text{ milliseconds (maximum- worst case in 100 ms)}$$

$$\text{Transmitter Cycle Time} = >100 \text{ milliseconds}$$

$$\text{Transmitter Duty Cycle} = 100 \%$$

$$\text{Correction Factor} = -0.0 \text{ dB}$$

### SPECTRUM ANALYZER DESENSITIZATION CONSIDERATIONS

NOT APPLICABLE - The device transmits a Continuous Wave (CW) signal.

## GENERAL NOTES

1. All readings were taken utilizing a peak detector function at a test distance of 3 meters.
2. The duty cycle was applied to the peak readings in order to determine the average value of the emissions.
3. All measurements were made with (3) new "AA" batteries installed in the unit.
4. The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not reported were more than 10 dB below the specified limit.

Exhibit 6

Report of Measurements

Radiated Emissions Data, Para. 15.231(a)  
(Please see separate e-file attachment named RE data.doc)

Exhibit 6

Report of Measurements

Occupied Bandwidth, Para. 15.231(c)  
(Please see separate e-file attachment named Occbw.doc)

## EQUIPMENT LIST

### FCC Paragraph 15.231(b) Radiated Emissions. 30 MHz to 3.1 GHz

<b>EN</b>	<b>Type</b>	<b>Manufacturer</b>	<b>Frequency Range</b>	<b>Model No.</b>	<b>Cal Date</b>	<b>Due Date</b>
067	Open Area Test Site	Retlif	3 Meter	RNY	8/30/97	8/30/99
128C	Double Ridge Guide	Eaton Corporation	1 GHz - 18 GHz	96001	10/6/98	10/6/99
133	Broadband Pre-Amplifier	Electro-Metrics	10 kHz - 1 GHz, 26dB	BPA-1000	6/22/98	6/22/99
141	Spectrum Analyzer	Hewlett Packard	100 Hz - 40 GHz	8566B	3/16/99	9/16/99
141A	Graphics Plotter	Hewlett Packard	N/A	7470A	3/5/99	3/5/00
141B	Quasi-Peak Adaptor	Hewlett Packard	100 Hz - 1 GHz	85650A	3/16/99	9/16/99
206B	6.0 dB Attenuator	Texscan	0 - 1.0 GHz	FP-50 - 6 dB	6/22/98	6/22/99
523	Biconilog	Electro-Mechanics	26 - 2000 MHz	3142B	10/22/98	4/22/00
543	Preamplifier	Hewlett Packard	1.0 GHz - 26.5 GHz	8449B	9/3/98	9/3/99