

Test Method:	FCC Part 15 Subpart C, Spurious Case Radiated Emissions, Paragraph 15.209(a)		
Customer:	Fomotech International Corp.	Job No.	R-8697-1
Test Sample:	Pulsed RF Transmitter		
Model No.:	Twister 2X	Serial No.	N/A
Operating Mode:	Continuously transmitting a pulsed signal at 434 MHz		
Technician:	Peter Lananna	Date:	December 7, 2000

Notes: Test Distance: 3 Meters Temp:10C Humidity: 34%
 Detector: Quasi-Peak Below 30 MHz to 1 GHz, Peak above 1 GHz

Test Freq.	Antenna Position	EUT Orientation	Meter Readings	Correction Factor	Corrected Reading	Converted Reading	LIMIT
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uV/m	uV/m
30.00							100
88.00							100
88.00							150

No emissions detected at specified test distance.

216.00							150
216.00							200
960.00							200
960.00							500
4340.0							500

The EUT was scanned from 30 MHz to 4.34 GHz

The emissions observed from the EUT do not exceed the specified limits. Emissions not recorded were more than 10dB under the specified limit



Retlif Testing Laboratories

Retlif Job Number R-8697-1