



<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
<b>Customer:</b>	Fomotech International Corp.				<b>Job No.</b>	R-8697-1	
<b>Test Sample:</b>	Pulsed RF Transmitter				<b>Paragraph:</b>	15.231	
<b>Model No.:</b>	Twister 2X				<b>FCC ID:</b>		
<b>Operating Mode:</b>	Continuously Transmitting a 434 MHz Signal						
<b>Technician:</b>	Peter Lananna				<b>Date:</b>	December 8, 2000	
<b>Notes:</b>	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
434	H / 2.3	X	70.5	-0.6	69.9	3126.1	109600
	H / 2.3	Y	69.6	-0.6	69.0	2818.4	
	H / 2.5	Z	74.9	-0.6	74.3	5188.0	
	V / 1.0	X	71.0	-0.6	70.4	3311.3	
	V / 1.5	Y	71.6	-0.6	71.0	3548.1	
434	V / 1.0	Z	78.6	-0.6	78.0	7943.3	109600
868	H / 1.0	X	41.0	8.9	49.9	312.6*	10960
	H / 1.0	Y	41.0	8.9	49.9	312.6*	
	H / 1.0	Z	41.0	8.9	49.9	312.6*	
	V / 1.0	X	41.0	8.9	49.9	312.6*	
	V / 1.0	Y	41.0	8.9	49.9	312.6*	
868	V / 1.0	Z	41.0	8.9	49.9	312.6*	10960
1303	H / 1.0	X	42.0	-3.0	39.0	89.1*	5000
	H / 1.0	Y	42.0	-3.0	39.0	89.1*	
	H / 1.0	Z	42.0	-3.0	39.0	89.1*	
	V / 1.0	X	42.0	-3.0	39.0	89.1*	
	V / 1.0	Y	42.0	-3.0	39.0	89.1*	
1303	V / 1.0	Z	42.0	-3.0	39.0	89.1*	5000
1736	H / 1.0	X	42.0	2.3	44.3	164.1*	10960
	H / 1.0	Y	42.0	2.3	44.3	164.1*	
	H / 1.0	Z	42.0	2.3	44.3	164.1*	
	V / 1.0	X	42.0	2.3	44.3	164.1*	
	V / 1.0	Y	42.0	2.3	44.3	164.1*	
1736	V / 1.0	Z	42.0	2.3	44.3	164.1*	10960
2170	H / 1.0	X	38.0	1.2	39.2	91.2*	10960
	H / 1.0	Y	38.0	1.2	39.2	91.2*	
	H / 1.0	Z	38.0	1.2	39.2	91.2*	
	V / 1.0	X	38.0	1.2	39.2	91.2*	
	V / 1.0	Y	38.0	1.2	39.2	91.2*	
2170	V / 1.0	Z	38.0	1.2	39.2	91.2*	10960
The frequency range was scanned from 30 MHz to 4.34 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-8697-1


<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
<b>Customer:</b>	Fomotech International Corp.	<b>Job No.</b>	R-8697-1				
<b>Test Sample:</b>	Pulsed RF Transmitter	<b>Paragraph:</b>	15.231				
<b>Model No.:</b>	Twister 2X	<b>FCC ID:</b>					
<b>Operating Mode:</b>	Continuously Transmitting a 434 MHz Signal						
<b>Technician:</b>	Peter Lananna	<b>Date:</b>	December 8, 2000				
<b>Notes:</b>	Test Distance: 3 Meters Detector: Peak, unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
2604	H / 1.0	X	38.0	4.8	42.8	138.0*	10960
	H / 1.0	Y	38.0	4.8	42.8	138.0*	
	H / 1.0	Z	38.0	4.8	42.8	138.0*	
	V / 1.0	X	38.0	4.8	42.8	138.0*	
	V / 1.0	Y	38.0	4.8	42.8	138.0*	
2604	V / 1.0	Z	38.0	4.8	42.8	138.0*	10960
3038	H / 1.0	X	38.0	6.4	44.4	166.0*	10960
	H / 1.0	Y	38.0	6.4	44.4	166.0*	
	H / 1.0	Z	38.0	6.4	44.4	166.0*	
	V / 1.0	X	38.0	6.4	44.4	166.0*	
	V / 1.0	Y	38.0	6.4	44.4	166.0*	
3038	V / 1.0	Z	38.0	6.4	44.4	166.0*	10960
3472	H / 1.0	X	38.0	8.3	46.3	206.5*	10960
	H / 1.0	Y	38.0	8.3	46.3	206.5*	
	H / 1.0	Z	38.0	8.3	46.3	206.5*	
	V / 1.0	X	38.0	8.3	46.3	206.5*	
	V / 1.0	Y	38.0	8.3	46.3	206.5*	
3472	V / 1.0	Z	38.0	8.3	46.3	206.5*	10960
3906	H / 1.0	X	38.0	9.8	47.8	245.5*	5000
	H / 1.0	Y	38.0	9.8	47.8	245.5*	
	H / 1.0	Z	38.0	9.8	47.8	245.5*	
	V / 1.0	X	38.0	9.8	47.8	245.5*	
	V / 1.0	Y	38.0	9.8	47.8	245.5*	
3906	V / 1.0	Z	38.0	9.8	47.8	245.5*	5000
4340	H / 1.0	X	38.0	10.9	48.9	278.6*	5000
	H / 1.0	Y	38.0	10.9	48.9	278.6*	
	H / 1.0	Z	38.0	10.9	48.9	278.6*	
	V / 1.0	X	38.0	10.9	48.9	278.6*	
	V / 1.0	Y	38.0	10.9	48.9	278.6*	
4340	V / 1.0	Z	38.0	10.9	48.9	278.6*	5000
The frequency range was scanned from 30 MHz to 4.34 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements ( Minimum system sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-8697-1


<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
<b>Customer:</b>	Fomotech International Corp.	<b>Job No.</b>	R-8697-1				
<b>Test Sample:</b>	Pulsed RF Transmitter	<b>Paragraph:</b>	15.231				
<b>Model No.:</b>	Twister 2X	<b>FCC ID:</b>					
<b>Operating Mode:</b>	Continuously Transmitting a 434 MHz Signal						
<b>Technician:</b>	Peter Lananna	<b>Date:</b>	December 8, 2000				
<b>Notes:</b>	Test Distance: 3 Meters		Duty Cycle: 50%				
	Detector: Peak, unless otherwise specified		Duty Cycle Correction: -6.0 dB				
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
434	H / 2.3	X	69.9	-6.0	63.9	1566.8	10960
	H / 2.3	Y	69.0	-6.0	63.0	1412.5	
	H / 2.5	Z	74.3	-6.0	68.3	2600.2	
	V / 1.0	X	70.4	-6.0	64.4	1659.6	
	V / 1.5	Y	71.0	-6.0	65.0	1778.3	
434	V / 1.0	Z	78.0	-6.0	72.0	3981.1	10960
868	H / 1.0	X	49.9	-6.0	43.9	156.7*	1096
	H / 1.0	Y	49.9	-6.0	43.9	156.7*	
	H / 1.0	Z	49.9	-6.0	43.9	156.7*	
	V / 1.0	X	49.9	-6.0	43.9	156.7*	
	V / 1.0	Y	49.9	-6.0	43.9	156.7*	
868	V / 1.0	Z	49.9	-6.0	43.9	156.7*	1096
1303	H / 1.0	X	39.0	-6.0	33.0	44.7*	500
	H / 1.0	Y	39.0	-6.0	33.0	44.7*	
	H / 1.0	Z	39.0	-6.0	33.0	44.7*	
	V / 1.0	X	39.0	-6.0	33.0	44.7*	
	V / 1.0	Y	39.0	-6.0	33.0	44.7*	
1303	V / 1.0	Z	39.0	-6.0	33.0	44.7*	500
1736	H / 1.0	X	44.3	-6.0	38.3	82.2*	1096
	H / 1.0	Y	44.3	-6.0	38.3	82.2*	
	H / 1.0	Z	44.3	-6.0	38.3	82.2*	
	V / 1.0	X	44.3	-6.0	38.3	82.2*	
	V / 1.0	Y	44.3	-6.0	38.3	82.2*	
1736	V / 1.0	Z	44.3	-6.0	38.3	82.2*	1096
2170	H / 1.0	X	39.2	-6.0	33.2	45.7*	1096
	H / 1.0	Y	39.2	-6.0	33.2	45.7*	
	H / 1.0	Z	39.2	-6.0	33.2	45.7*	
	V / 1.0	X	39.2	-6.0	33.2	45.7*	
	V / 1.0	Y	39.2	-6.0	33.2	45.7*	
2170	V / 1.0	Z	39.2	-6.0	33.2	45.7*	1096
The frequency range was scanned from 30 MHz to 4.34 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements ( Minimum system sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-8697-1

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
<b>Customer:</b>	Fomotech International Corp.			<b>Job No.</b>	R-8697-1		
<b>Test Sample:</b>	Pulsed RF Transmitter			<b>Paragraph:</b>	15.231		
<b>Model No.:</b>	Twister 2X			<b>FCC ID:</b>			
<b>Operating Mode:</b>	Continuously Transmitting a 434 MHz Signal						
<b>Technician:</b>	Peter Lananna			<b>Date:</b>	December 8, 2000		
<b>Notes:</b>	Test Distance: 3 Meters			Duty Cycle: 50%			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - 6.0 dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
2604	H / 1.0	X	42.8	-6.0	36.8	69.2*	1096
	H / 1.0	Y	42.8	-6.0	36.8	69.2*	
	H / 1.0	Z	42.8	-6.0	36.8	69.2*	
	V / 1.0	X	42.8	-6.0	36.8	69.2*	
	V / 1.0	Y	42.8	-6.0	36.8	69.2*	
2604	V / 1.0	Z	42.8	-6.0	36.8	69.2*	1096
3038	H / 1.0	X	44.4	-6.0	38.4	83.2*	1096
	H / 1.0	Y	44.4	-6.0	38.4	83.2*	
	H / 1.0	Z	44.4	-6.0	38.4	83.2*	
	V / 1.0	X	44.4	-6.0	38.4	83.2*	
	V / 1.0	Y	44.4	-6.0	38.4	83.2*	
3038	V / 1.0	Z	44.4	-6.0	38.4	83.2*	1096
3472	H / 1.0	X	46.3	-6.0	40.3	103.5*	1096
	H / 1.0	Y	46.3	-6.0	40.3	103.5*	
	H / 1.0	Z	46.3	-6.0	40.3	103.5*	
	V / 1.0	X	46.3	-6.0	40.3	103.5*	
	V / 1.0	Y	46.3	-6.0	40.3	103.5*	
3472	V / 1.0	Z	46.3	-6.0	40.3	103.5*	1096
3906	H / 1.0	X	47.8	-6.0	41.8	123.0*	500
	H / 1.0	Y	47.8	-6.0	41.8	123.0*	
	H / 1.0	Z	47.8	-6.0	41.8	123.0*	
	V / 1.0	X	47.8	-6.0	41.8	123.0*	
	V / 1.0	Y	47.8	-6.0	41.8	123.0*	
3906	V / 1.0	Z	47.8	-6.0	41.8	123.0*	500
4340	H / 1.0	X	48.9	-6.0	42.9	139.6*	500
	H / 1.0	Y	48.9	-6.0	42.9	139.6*	
	H / 1.0	Z	48.9	-6.0	42.9	139.6*	
	V / 1.0	X	48.9	-6.0	42.9	139.6*	
	V / 1.0	Y	48.9	-6.0	42.9	139.6*	
4340	V / 1.0	Z	48.9	-6.0	42.9	139.6*	500
The frequency range was scanned from 30 MHz to 4.34 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements ( Minimum system sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-8697-1