

## KDB 447498 guidance

## Section 4.3 General SAR test reduction and exclusion

For Standalone SAR exclusion consideration, when SAR Exclusion Threshold requirement in KDB 447498 is satisfied, standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

In the frequency range below 100 MHz to 6 GHz and test separation distance of 50mm, the SAR Test Exclusion Threshold for operation in the 2400 – 2483.5 MHz band will be determined as follows

SAR Exclusion Threshold (SARET)

SAR Exclusion Threshold = Step 1 + Step 2

### Step 1

$$NT = [(MP/TSD^A) * \sqrt{f_{GHz}}]$$

NT = Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)

MP = Max Power of channel (mW) (inc tune up)

TSD<sup>A</sup> = Min Test separation Distance or 50mm (whichever is lower) = 5

We can transpose this formula to allow us to find the maximum power of a channel allowed and compare this to the measured maximum power.

$$= [(NT \times TSD^A) / \sqrt{f_{GHz}}]$$

For Distances Greater than 50 mm Step 2 applies

### Step 2

$$(TSD^B - 50mm) * 10\}$$

Where:

TSD<sup>B</sup> = Min Test separation Distance (mm) = 50

**Operating Frequency 0.418 GHz**

SARET =  $[(3.0 \times 5) / \sqrt{0.418}]$   
SARET =  $[15 / 0.647]$   
SARET = 23.2 mW

<b>KDB 447498</b>		
Evaluation Frequency	418.0	MHz
SAR Exclusion Threshold	23.2	mW
EIRP	0.21	mW
<b><i>Exempt</i></b>		