

STATEMENT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No.500212-4U

EQUIPMENT

Type of equipment	S1500 TagMaster Reader
Brand name	TagMaster
Type / Model	S1500/00
Manufacturer	TagMaster AB
By request of:	TagMaster AB

DIRECTIVE

OET Bulletin 65, supplement C

CALCULATIONS

The product has an EIRP of less than 288 mW. According to the manufacturer, during normal use the operator is not closer than (r) 20 cm to the transmitter antenna. Assuming the duty cycle (dc) of 100%, the worst calculation is as follows:

$$S = \frac{dc \times 4 \times EIRP}{4 \times \pi \times r^2} \quad (\text{Power density with 100 \% reflection})$$

$$S = 1 \times 4 \times 288 / (4 \times \pi \times 20^2) = 0,23 \text{ mW/cm}^2$$

Reference level limit according to OET Bulletin 65, supplement C for power density at 2450 MHz is 1 mW/cm²

In considering the calculations above it is determined that the requirements according to the referred directive is fulfilled without testing.



Intertek Semko AB, Radio & EMC
Date of issue: June 12, 2006

Björn Utermöhl
Björn Utermöhl

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address

STATEMENT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No.500212-5U

EQUIPMENT

Type of equipment	S1500 TagMaster Reader
Brand name	TagMaster
Type / Model	S1513/00
Manufacturer	TagMaster AB
By request of:	TagMaster AB

DIRECTIVE

OET Bulletin 65, supplement C

CALCULATIONS

The product has an EIRP of less than 263 mW. According to the manufacturer, during normal use the operator is not closer than (r) 20 cm to the transmitter antenna. Assuming the duty cycle (dc) of 100%, the worst calculation is as follows:

$$S = \frac{dc \times 4 \times EIRP}{4 \times \pi \times r^2} \quad (\text{Power density with 100 \% reflection})$$


$$S = 1 \times 4 \times 263 / (4 \times \pi \times 20^2) = 0,21 \text{ mW/cm}^2$$

Reference level limit according to OET Bulletin 65, supplement C for power density at 2450 MHz is 1 mW/cm²

In considering the calculations above it is determined that the requirements according to the referred directive is fulfilled without testing.



Intertek Semko AB, Radio& EMC
Date of issue: June 12, 2006


Björn Utermöhl

Intertek Semko AB

STATEMENT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No.500212-6U

EQUIPMENT

Type of equipment	S1500 TagMaster Reader
Brand name	TagMaster
Type / Model	S1566/00
Manufacturer	TagMaster AB
By request of:	TagMaster AB

DIRECTIVE

OET Bulletin 65, supplement C

CALCULATIONS

The product has an EIRP of less than 288 mW. According to the manufacturer, during normal use the operator is not closer than (r) 20 cm to the transmitter antenna. Assuming the duty cycle (dc) of 100%, the worst calculation is as follows:

$$S = \frac{dc \times 4 \times EIRP}{4 \times \pi \times r^2} \quad (\text{Power density with 100 \% reflection})$$

$$S = 1 \times 4 \times 288 / (4 \times \pi \times 20^2) = 0,23 \text{ mW/cm}^2$$

Reference level limit according to OET Bulletin 65, supplement C for power density at 2450 MHz is 1 mW/cm²

In considering the calculations above it is determined that the requirements according to the referred directive is fulfilled without testing.



Intertek Semko AB, Radio& EMC

Date of issue: June 12, 2006

Björn Utermöhl

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden

Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com

Registered in Sweden: No SE558024059901, Registered office: As address