

# RADIO TEST REPORT

No. 1510902STO-001, Ed. 1

## RF Performance

### EQUIPMENT UNDER TEST

Equipment: RFID reader for automatic vehicle identification  
Type/Model: **XT Mini** Reader us  
Manufacturer: TagMaster AB  
Tested by request of: TagMaster AB

### SUMMARY

Referring to the emission limits, and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards:

47 CFR Part 15 (2014);, Subpart C: Intentional radiators. Section 15.247  
For details, see clause 2 – 4.

Date of issue: 2015-07-08

Tested by:



Matti Virkki

Approved by:



Stefan Andersson

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden

Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address

**Revision History**

Edition	Date	Description	Changes
1	2015-07-08	First release	

Version 1.00

**CONTENTS**

	<b>Page</b>
1 Client Information.....	5
2 Equipment under test (EUT).....	5
2.1 Identification of the EUT .....	5
2.2 Additional information about the EUT .....	6
2.3 Test signals and operation modes .....	6
2.4 Modifications made to improve EMC-characteristics .....	6
3 Test Specifications.....	7
3.1 Standards .....	7
3.2 Additions, deviations and exclusions from standards and accreditation.....	7
3.3 Test site .....	7
4 Test Summary .....	8
5 Field strength of fundamental and at band edge .....	9
5.1 Operating environment.....	9
5.2 Test set-up and test procedure.....	9
5.3 Test conditions.....	9
5.4 Requirement .....	10
5.5 Test results .....	10
6 Radiated rf Emission in the frequency-range 30 MHz to 10 GHz.....	11
6.1 Operating environment.....	11
6.2 Test set-up and test procedure.....	11
6.3 Test conditions.....	11
6.4 Radiated Emission requirements.....	12
6.5 Test results 30 MHz – 1000 MHz.....	13
6.6 Test results 1 GHz – 10 GHz.....	17
7 Occupied bandwidth.....	20
7.1 Operating environment.....	20
7.2 Test set-up and test procedure.....	20
7.3 Test conditions.....	20
7.4 Requirement .....	20
7.5 Test results .....	20
8 Number of hopping frequencies.....	22
8.1 Operating environment.....	22
8.2 Test set-up and test procedure.....	22
8.3 Test conditions.....	22
8.4 Requirement .....	22
8.5 Test results .....	23
9 Carrier separation .....	24
9.1 Operating environment.....	24
9.2 Test set-up and test procedure.....	24
9.3 Test conditions.....	24
9.4 Requirement .....	24
9.5 Test results .....	25
10 Transmitter time of occupancy.....	26
10.1 Operating environment.....	26
10.2 Test set-up and test procedure.....	26
10.3 Test conditions.....	26
10.4 Requirement .....	26
10.5 Test results .....	27

11	maximum peak conducted output power .....	28
11.1	Operating environment.....	28
11.2	Test set-up and test procedure.....	28
11.3	Test conditions.....	28
11.4	Requirement .....	28
11.5	Test results .....	29
12	Band edge conducted .....	31
12.1	Operating environment.....	31
12.2	Test set-up and test procedure.....	31
12.3	Test conditions.....	31
12.4	Requirement .....	31
12.5	Test results .....	31
13	Test equipment .....	33
14	Measurement uncertainty.....	34
15	Test set up photos .....	34

## 1 CLIENT INFORMATION

The EUT has been tested by request of

Company TagMaster AB  
Kronborgsgränd 11  
16446 Kista  
Sweden

Name of contact Mattias Gyllenros

## 2 EQUIPMENT UNDER TEST (EUT)

### 2.1 Identification of the EUT

Equipment: RFID reader for automatic vehicle identification

Product marketing name/Model: **XT Mini** reader us

Brand name: TagMaster

Serial number: R&D Proto 2

Manufacturer: TagMaster AB

Transmitter frequency range: 902.75 – 927.75 MHz

Receiver frequency range: 902 – 928 MHz

Frequency agile or hopping:  Yes  No

Antenna:  Internal antenna  External antenna

Antenna connector:  None, internal antenna  Yes,

Antenna gain: 4 dBi

Rating RF output power: 28 dBm

Type of modulation: ASK

Temperature range:  Category I (General): -20°C to +55°C  
 Category II (Portable equipment): -10°C to +55°C  
 Category III (Equipment for normal indoor use): +5°C to +35°C  
 Other: -40°C to +60°C

Power rating: 12 – 24 VDC

Transmitter standby mode supported:  Yes  No

## 2.2 Additional information about the EUT

The EUT consists of the following units:

Unit	Type	Serial number
RFID Reader	XT Mini us	R&D Proto 2

During the tests the EUT supported following software:

Software	Version	Comment
Vigilant FW, 1.1.2-pre,	SVN rev.5790	

## 2.3 Test signals and operation modes

Continuous signal with ASK modulation on highest, middle and low channels.  
Hopping mode with ASK modulation

## 2.4 Modifications made to improve EMC-characteristics

The following modifications were required to obtain the results presented in this report.

- A piece of dielectric absorber was introduced in the RF shield-box to attenuate box-resonances in the 8 GHz range.
- A 1pF capacitor to gnd was added to the RF\_Vout terminal of Q502 inside the shield-box to eliminate conduction in the 7-9 GHz range
- 1 pF capacitors to gnd was added at bias terminals for all semiconductor circuits within the shield-box for the same reason.

### 3 TEST SPECIFICATIONS

#### 3.1 Standards

Requirements:

47 CFR Part 15: Radio frequency device, Subpart C: Unintentional radiators (2014).

Test methods:

ANSI C63.10-2009: American National Standard for testing Unlicensed Wireless Devices

#### 3.2 Additions, deviations and exclusions from standards and accreditation

No additions, deviations or exclusions have been made from standards and accreditation.

#### 3.3 Test site

Measurements were performed at:

Intertek Semko AB.  
Torshamnsgatan 43,  
P.O. Box 1103  
SE-164 22 Kista

Intertek Semko AB is a FCC listed test site with site registration number 90913

Intertek Semko AB is a FCC accredited conformity assessment body with designation number SE0002

Intertek Semko AB is an Industry Canada listed test facility with IC assigned code 2042G

Measurement chambers

Measurement Chamber	Type of chamber	IC Site filing #
STORA HALLEN	Semi-anechoic 10 m and 3 m	2042G-2

#### 4 TEST SUMMARY

The results in this report apply only to sample tested:

Requirement	Description	Result
FCC §15.203	<b>Antenna requirement</b> EUT uses internal antenna which is not user removable	<b>PASS</b>
FCC §15.207	<b>Conducted continuous emission in the frequency range 150 kHz to 30 MHz, AC Power input port</b>	<b>NA</b>
FCC §15.247(e) 15.209(a)	<b>Field strength of fundamental and radiated band edge</b>	<b>PASS</b>
FCC §15.247 (d), 15.209(a)	<b>Radiated emission of electromagnetic fields in the frequency range 30 – 1000 MHz</b>	<b>PASS</b>
FCC §15.247(d), 15.209(a)	<b>Radiated emission of electromagnetic fields in the frequency range above 1 GHz</b>	<b>PASS</b>
FCC §15.247(a)(2)	<b>Occupied bandwidth</b>	<b>PASS</b>
FCC §15.247(b)	<b>Conducted output power</b>	<b>PASS</b>
FCC §15.247(e)	<b>Carrier separation</b>	<b>PASS</b>
FCC §15.247(e)	<b>Number of hopping frequencies</b>	<b>PASS</b>
FCC §15.247(e)	<b>Band edge</b>	<b>PASS</b>



## 5 FIELD STRENGTH OF FUNDAMENTAL AND AT BAND EDGE

### 5.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-19	21 [°C]	34 [%]	KAF	Pass	46.9 dB

### 5.2 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10. and ANSI C63.4

The EUT was set up in order to emit maximum disturbances.

The EUT was placed on an insulating support 0.8 m above the turntable which is part of the reference ground plane.

Overview sweeps were performed with the measurement receiver in max-hold mode and the peak detector activated in the frequency-range 30 – 1000 MHz.

Above 1 GHz additionally the average detector was activated.

### 5.3 Test conditions

#### Test set-up:

#### 30 MHz to 1000 MHz

Test receiver set-up:

Preview test:

Peak, RBW 120 kHz. VBW 1 MHz

Final test:

QP, RBW 120 kHz.

Measuring distance:

3 m

Measuring angle:

0 – 359°

Antenna

Height above ground plane:

1 – 4 m

Polarisation:

Vertical and Horizontal

Type:

Bilog

#### Test set-up:

#### 1 GHz – 10 GHz

Test receiver set-up:

Preview test:

Peak, RBW 1 MHz. VBW 3 MHz

Final test:

Peak, RBW 1 MHz

Average RBW 1 MHz

Measuring distance:

3 m

Measuring angle:

0 – 359°

Antenna

Height above ground plane:

1 – 4 m

Polarisation:

Vertical and Horizontal

Type:

Horn

Antenna tilt:

Activated

## 5.4 Requirement

The EUT shall meet the following limits.

Reference: 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

## 5.5 Test results

### Measurement results,

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Detector	Polarization H/V	Margin [dB]
902.75	121.8	--	QP	V	--
902	54.9	101.8	QP	V	46.9
927.25	123.7	--	QP	V	--
928	55.9	103.7	QP	V	47.8

Emissions do not fall on restricted band and are attenuated more than 20 dB from carrier.

**6 RADIATED RF EMISSION IN THE FREQUENCY-RANGE 30 MHZ TO 10 GHZ**

**6.1 Operating environment**

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-19 /2015-06-25	21 / 22[°C]	34 / 46 [%]	KAF / MTV	Pass	0.2 dB

**6.2 Test set-up and test procedure.**

The test method is in accordance with ANSI C63.10. and ANSI C63.4  
 The EUT was set up in order to emit maximum disturbances.  
 The EUT was placed on an insulating support 0.8 m above the turntable which is part of the reference ground plane.  
 Overview sweeps were performed with the measurement receiver in max-hold mode and the peak detector activated in the frequency-range 30 – 1000 MHz.  
 Above 1 GHz additionally the average detector was activated.

**6.3 Test conditions**

**Test set-up: 30 MHz to 1000 MHz**  
 Test receiver set-up:  
 Preview test: Peak, RBW 120 kHz. VBW 1 MHz  
 Final test: Peak, RBW 120 kHz. VBW 1 MHz  
 Measuring distance: 3 m  
 Measuring angle: 0 – 359°  
 Antenna  
     Height above ground plane: 1 – 4 m  
     Polarisation: Vertical and Horizontal  
     Type: Bilog

**Test set-up: 1 GHz – 10 GHz**  
 Test receiver set-up:  
 Preview test: Peak, RBW 1 MHz. VBW 3 MHz  
 Final test: Peak, RBW 1 MHz  
                   Average RBW 1 MHz  
 Measuring distance: 3 m  
 Measuring angle: 0 – 359°  
 Antenna  
     Height above ground plane: 1 – 4 m  
     Polarisation: Vertical and Horizontal  
     Type: Horn  
     Antenna tilt: Activated

**6.4 Radiated Emission requirements**

Outside restricted bands

§15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits is not required.

Within restricted bands

§15.209, RSS-Gen section 8.9


Field strength of emissions must comply with limits shown in table below

Frequency range [MHz]	Field strength at 3 m (dB $\mu$ V/m)	Field strength at 10 m (dB $\mu$ V/m)	Detector (dB $\mu$ V/m)
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.0	Quasi Peak
216 – 960	46.0	35.5	Quasi Peak
960 – 1000	54.0	43.5	Quasi Peak
Above 1000	54.0 / 74.0	43.5 / 63.5	Average / Peak

The values for 10 m measuring distance are calculated by subtracting 10.5 dB from the 3 m limit. (i.e. an extrapolation factor of 20 dB/decade according to §15.31(f)(1)) and RSS-Gen section 6.5.


**6.5 Test results 30 MHz – 1000 MHz**

FCC 30 - 1000 MHz FCC class B 3m




**Diagram, Peak overview sweep, 30 – 800 MHz at 3 m distance on low channel.**

FCC 30 - 1000 MHz FCC class B 3m




**Diagram, Peak overview sweep, 800 – 1000 MHz at 3 m distance on low channel.**  
Carrier level is being attenuated with notch filter

FCC 30 - 1000 MHz FCC class B 3m




**Diagram, Peak overview sweep, 30 – 900 MHz at 3 m distance on middle channel.**

FCC 30 - 1000 MHz FCC class B 3m




**Diagram, Peak overview sweep, 900 - 1000 MHz at 3 m distance on middle channel.**  
Carrier level is being attenuated with notch filter

FCC 30 - 1000 MHz FCC class B 3m



**Diagram, Peak overview sweep, 30 – 900 MHz at 3 m distance on high channel.**

FCC 30 - 1000 MHz FCC class B 3m



**Diagram, Peak overview sweep, 900 - 1000 MHz at 3 m distance on high channel.**  
Carrier level is being attenuated with notch filter

**Measurement results, Quasi Peak**  
**Low channel**

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)
43.129	32.0	1000.0	120	100.0	V	263.0	-21.5	8.0
349.988	42.3	1000.0	120	100.0	H	-3.0	-16.2	3.7
395.781	40.4	1000.0	120	100.0	V	272.0	-14.7	5.6
450.005	39.1	1000.0	120	151.0	H	234.0	-13.0	6.9
752.769	38.8	1000.0	120	133.0	V	93.0	-5.4	7.2
790.534	43.5	1000.0	120	170.0	H	159.0	-5.3	2.5

**Middle channel**

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)
43.101	33.2	1000.0	120	100.0	V	-7.0	-21.5	6.8
81.643	25.5	1000.0	120	100.0	V	-1.0	-25.1	14.5
349.988	41.9	1000.0	120	100.0	H	-26.0	-16.2	4.1
396.642	41.4	1000.0	120	122.0	V	237.0	-14.6	4.6
518.991	37.9	1000.0	120	121.0	V	228.0	-11.0	8.1
791.752	43.7	1000.0	120	170.0	H	151.0	-5.3	2.3
835.605	31.5	1000.0	120	121.0	V	225.0	-4.0	14.5

**High channel**


Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)
349.988	41.9	1000.0	120	100.0	H	-21.0	-16.2	4.1
395.869	42.1	1000.0	120	121.0	V	250.0	-14.7	3.9
450.004	39.0	1000.0	120	151.0	H	228.0	-13.0	7.0
790.665	44.2	1000.0	120	168.0	H	153.0	-5.3	1.8
845.968	37.2	1000.0	120	114.0	V	232.0	-4.0	8.8
859.505	33.7	1000.0	120	115.0	V	234.0	-4.0	12.3

Result [dB $\mu$ V/m] = Analyser reading [dB $\mu$ V] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]



**6.6 Test results 1 GHz – 10 GHz**


FCC 1 G - 18 G class B 3m ESU40



**Diagram, Peak overview sweep, 1 – 10 GHz at 3 m distance. Low channel**

An additional 10 dB attenuator was used to eliminate carrier influence to pre-amplifier. Because of this the graph shows 10 dB too low values.


FCC 1 G - 18 G class B 3m ESU40



**Diagram, Peak overview sweep, 1 – 10 GHz at 3 m distance. Middle channel**

An additional 10 dB attenuator was used to eliminate carrier influence to pre-amplifier. Because of this the graph shows 10 dB too low values.

FCC 1 G - 18 G class B 3m ESU40



**Diagram, Peak overview sweep, 1 – 10 GHz at 3 m distance high channel**

An additional 10 dB attenuator was used to eliminate carrier influence to pre-amplifier. Because of this the graph shows 10 dB too low values.

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1186.3	55.9	1000.0	1000.000	207.0	V	9.0	18.1	74.0
1581.6	54.7	1000.0	1000.000	205.0	V	35.0	19.3	74.0
2708.2	57.1	1000.0	1000.000	169.0	H	313.0	16.9	74.0
8124.8	62.1	1000.0	1000.000	265.0	V	7.0	11.9	74.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

Frequency (MHz)	Average (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1186.4	50.0	1000.0	1000.000	169.0	V	11.0	4.0	54.0
1581.7	46.7	1000.0	1000.000	151.0	V	37.0	7.3	54.0
2708.1	51.4	1000.0	1000.000	169.0	H	312.0	2.6	54.0
8124.7	52.6	1000.0	1000.000	134.0	H	308.0	1.4	54.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

**Measurement results, Peak middle channel**

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1188.3	57.8	1000	1000.000	217.0	V	10.0	16.2	74.0
1583.6	56.1	1000	1000.000	151.0	V	35.0	17.9	74.0
2748.6	58.1	1000	1000.000	115.0	H	313.0	15.9	74.0
7569.6	56.1	1000	1000.000	169.0	V	141.0	17.9	74.0
8246.2	51.4	1000	1000.000	133.0	H	-16.0	12.6	74.0
9308.6	57.8	1000	1000.000	243.0	V	317.0	16.2	74.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

**Measurement results, Average middle channel**

Frequency (MHz)	Average (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1187.7	49.9	1000	1000.000	170.0	V	10.0	4.1	54.0
1583.9	46.8	1000	1000.000	151.0	V	37.0	7.2	54.0
2748.7	52.8	1000	1000.000	115.0	H	312.0	1.2	54.0
6413.8	43.4	1000	1000.000	189.0	H	311.0	10.6	54.0
7329.9	46.3	1000	1000.000	168.0	V	332.0	17.7	54.0
8246.2	53.8	1000	1000.000	127.0	H	-16.0	0.2	54.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

**Measurement results, Peak high channel**

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1187.5	55.3	1000	1000.000	193.0	V	10.0	18.7	74.0
1582.5	54.6	1000	1000.000	193.0	V	35.0	19.4	74.0
1854.4	54.5	1000	1000.000	157.0	V	184.0	19.6	74.0
2781.5	56.7	1000	1000.000	100.0	H	315.0	17.3	74.0
7417.8	59.1	1000	1000.000	157.0	V	333.0	14.9	74.0
8345.3	60.3	1000	1000.000	127.0	H	-16.0	13.7	74.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

Frequency (MHz)	Average (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dBµV/m)
1187.1	50.0	1000	1000.000	169.0	V	11.0	4.0	54.0
1583.3	44.1	1000	1000.000	100.0	V	35.0	9.9	54.0
1854.5	49.5	1000	1000.000	150.0	V	186.0	4.5	54.0
2781.7	51.8	1000	1000.000	115.0	H	311.0	2.2	54.0
7417.9	49.5	1000	1000.000	157.0	V	338.0	4.5	54.0
8345.1	50.7	1000	1000.000	242.0	V	188.0	3.3	54.0

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB] + attenuator loss [dB] + high pass filter loss[dB]

**7 OCCUPIED BANDWIDTH**

**7.1 Operating environment**

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	452.81 kHz

**7.2 Test set-up and test procedure.**

The test method is in accordance with ANSI C63.10 section 6.9  
 Marker delta method is used to determine the 20dB bandwidth

**7.3 Test conditions**

Detector: Peak,  
 RBW 1 kHz  
 VBW 3 x RBW  
 Span 150 kHz

**7.4 Requirement**

§15.247 (a)(1)

The bandwidth of a frequency hopping channel is the -20 dB emission bandwidth, measured with the hopping stopped.


The bandwidth of a frequency hopping channel is the -20 dB emission bandwidth, measured with the hopping stopped. The system radio frequency (RF) bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset.

902–928 MHz The maximum allowed -20 dB bandwidth of the hopping channel is 500 kHz.


5725–5850 MHz maximum allowed -20 dB bandwidth is 1 MHz

**7.5 Test results**


**Screenshot: Occupied bandwidth Measurement low channel**



**Screenshot: Occupied bandwidth Measurement middle channel**



**Screenshot: Occupied bandwidth Measurement high channel**



**Test result**

20 dB bandwidth (kHz)	Limit (kHz)	Margin (kHz)
47.20	< 500 kHz	452.80
47.19	< 500 kHz	452.81
47.20	< 500 kHz	452.80

## 8 NUMBER OF HOPPING FREQUENCIES

### 8.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	0 ch

### 8.2 Test set-up and test procedure.

Spectrum analyser with occupied bandwidth measurement function is used to determine the occupied bandwidth.

### 8.3 Test conditions

Detector: Peak  
Trace Max hold  
RBW 300 kHz  
VBW 300 kHz  
Span 30 MHz  
Sweep Auto

### 8.4 Requirement


For frequency hopping systems in the band 902–928 MHz: if the -20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the -20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period. The maximum allowed -20 dB bandwidth of the hopping channel is 500 kHz.

Frequency hopping systems operating in the band 2400–2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that a minimum of 15 hopping channels are used.

Frequency hopping systems operating in the band 5725–5850 MHz shall use at least 75 hopping channels. The maximum -20 dB bandwidth of the hopping channel shall be 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30-second period.

**8.5 Test results**

**Screenshot: Number of hopping frequencies**



Date: 20.MAY.2015 12:02:51

**Test result**

number of hopping frequencies	Limit
50	At least 50

## 9 CARRIER SEPARATION

### 9.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	453.8 kHz

### 9.2 Test set-up and test procedure.

The EUT was connected to spectrum analyser via rf-cable and attenuator

### 9.3 Test conditions

Detector: Peak  
 Trace Max hold  
 RBW 20 dB bw / 3  
 VBW 3 x RBW  
 Span 5 x 20 dB bw  
 Sweep Auto

### 9.4 Requirement


#### §15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the band 2400–2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.



**9.5 Test results**

**Screenshot: Carrier separation**



Date: 20.MAY.2015 12:01:01

**Test result**

Carrier separation kHz	Limit kHz
501	47.2

## 10 TRANSMITTER TIME OF OCCUPANCY

### 10.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	7 ms

### 10.2 Test set-up and test procedure.

Spectrum analyser is used to determine the transmitter duty cycle.  
The EUT is connected to the anasyr via rf-cable and attenuator.

### 10.3 Test conditions

Detector: Peak  
RBW 100 kHz  
VBW 3 x RBW  
Span 0 Hz  
Sweep time 500 ms

### 10.4 Requirement

§15.247(a)(1)

902–928 MHz:

If the -20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period.

If the -20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period.

2400–2483.5 MHz:


The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

5725–5850 MHz:


The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30-second period.

**10.5 Test results**

**Screenshot: time of occupancy single transmission.**



**Screenshot: number of transmissions / 20 s**



**Test result**

Number of transmissions	Transmission time (ms)	Time of occupancy /20 s (ms)	Limit (ms)	Margin (ms)
1	393	393	400	7

## 11 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 11.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	7.04 dB

### 11.2 Test set-up and test procedure.

The EUT is connected to the analyser via rf-cable and attenuator.  
Spectrum analyser's reference level offset was used to compensate cable and attenuator losses.

### 11.3 Test conditions

Detector: Peak,  
Trace Max hold  
RBW 100 kHz  
VBW 300 kHz  
Span 250 kHz  
Marker was used to detect peak power.

The EUT was set up in order to emit maximum disturbances.

### 11.4 Requirement

§15.247(b)(1)


(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.


(2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

**11.5 Test results**

**Screenshot: maximum peak conducted output power Measurement**




**Screenshot: maximum peak conducted output power Measurement**



S 114 10-06 Strömberg 164234

**Screenshot: maximum peak conducted output power Measurement**



**Test result**

Low channel (dBm)	Middle channel (dBm)	High channel (dBm)	Limit (dBm)	Margin (dB)
22.96	22.81	22.85	30	7.04

## 12 BAND EDGE CONDUCTED

### 12.1 Operating environment

Date of test:	Temperature:	Relative Humidity:	Tested by	Result	Margin
2015-05-20	21 [°C]	31 [%]	KAF	Pass	26.96 dB

### 12.2 Test set-up and test procedure.

The EUT is connected to the analyser via rf-cable and attenuator.

### 12.3 Test conditions

Detector: Peak  
Trace Max hold  
RBW 100 kHz  
VBW 3 x RBW  
Span 50 MHz

The EUT was set up in order to emit maximum disturbances.

### 12.4 Requirement

§15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits is not required.

### 12.5 Test results

#### Test result


902.75 MHz (dBm)	902 MHz Attenuation (dB)	927.75 MHz (dBm)	928 MHz Attenuation (dB)	Limit (dB)	Margin (dB)
23.53	56.96	22.84	58.03	20	26.96

**Screenshot: Band edge low**



Date: 20.MAY.2015 11:07:17

**Screenshot: Band edge high**



Date: 20.MAY.2015 11:09:35



## 13 TEST EQUIPMENT

## Stora hallen

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - 8.51	--	--	--
Receiver	Rohde & Schwarz	ESU 8	12866	7/2014	1 year
Receiver	Rohde & Schwarz	ESU 40	13178	7/2014	1 year
BiLog antenna	Chase	CBL6110A	971	8/2012	3 years
Preamplifier	SEMKO	AM1331	7992	7/2014	1 year
Horn antenna	Rohde & Schwarz	HF907	31245	11/2013	3 years
Preamplifier	Bonn-Elektronik	BLMA 0118-M	31246	7/2014	1 year
1 GHz high pass filter	Microwave Circuits Inc.		13142		
Horn antenna	EMCO	3160-09	30101	10/2013	3 years
10 dB Attenuator:	Huber+Suhner	5910_N-50-010	32696	7/2014	1 year
Tunable Notch filter	K&L	3TNF-500/1000-N	7078	-	-

## Wireless centre and 3m FAC

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Signal analyser	Rohde & Schwarz	FSIQ 40	12793	7 / 2014	1 year
10 dB Attenuator:	Huber+Suhner	5910_N-50-010	32696	7 / 2014	1 year

## 14 MEASUREMENT UNCERTAINTY

Continuous conducted disturbances with AMN in the frequency range 9 kHz to 30 MHz  $\pm 3.6$  dB

Measurement uncertainty for radiated disturbance

Uncertainty for the frequency range 30 to 1000 MHz at 3 m	$\pm 4.9$ dB
Uncertainty for the frequency range 30 to 1000 MHz at 10 m	$\pm 4.8$ dB
Uncertainty for the frequency range 1.0 to 18 GHz at 3 m	$\pm 5.4$ dB
Uncertainty for the frequency range 18 to 26 GHz at 3 m	$\pm 5.5$ dB
Uncertainty for the frequency range 26 to 40 GHz at 3 m	$\pm 5.6$ dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2:2011.  
The measurement uncertainty is given with a confidence of 95 %.

## 15 TEST SET UP PHOTOS

Test set up photos are in separate document 1510902STO-001 Annex 1