



The University of Michigan  
Radiation Laboratory  
3228 EECS Building  
Ann Arbor, MI 48109-2122  
Tel: (734) 764-0500

Measured Radio Frequency Emissions  
From

**Siemens/Continental Transmitter**  
**FCC ID: M3N5WY8145**  
**IC: 267F-5WY8145**

Report No. 415031-420  
April 25, 2008


Copyright © 2008

For:  
Siemens Automotive Corp./ Continental  
4685 Investment Drive  
Troy, MI 48098

Contact:  
Aris Lambropoulos  
Aris.Lambropoulos@continental-corporation.com  
Tel: (248) 764-6771  
Fax: (248) 764-7247  
PO: verbal

Measurements made by: Valdis V. Liepa  
Test Report Prepared by: Joseph D. Brunett

Tests supervised by:  
Report approved by:

  
Valdis V. Liepa  
Research Scientist

---

### Summary

Tests for compliance with FCC Regulations Part 15, Subpart C, and Industry Canada RSS-210/GEN, were performed on Siemens/Continental model/PN(s) 72147-TK4A-A010-M1, 72147-TK4A-A110-M1. This device is subject to the Rules and Regulations as a Transmitter.

In testing completed on March 17, 2008, the device tested in the worst case met the allowed FCC specifications for radiated emissions by 1.2 dB (see p. 6). Besides harmonics, there were no other significant spurious emissions found; emissions from digital circuitry were negligible. The conducted emission tests do not apply, since the device is powered from a 3 VDC battery.

*University of Michigan Radiation Laboratory  
FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-420*

**1. Introduction**

Siemens/Continental model/PN(s) 72147-TK4A-A010-M1, 72147-TK4A-A110-M1 was tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989 as subsequently amended, and with Industry Canada RSS-210/Gen, Issue 7, June 2007. The tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Area Test Site are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057A-1).

**2. Test Procedure and Equipment Used**

The pertinent test equipment commonly used in our facility for measurements is listed in Table 2.1 below. The middle column identifies the specific equipment used in these tests.

**Table 2.1 Test Equipment.**

Test Instrument	Eqpt. Used	Manufacturer/Model
Spectrum Analyzer (0.1-1500 MHz)		Hewlett-Packard, 182T/8558B
Spectrum Analyzer (9kHz-22GHz)	X	Hewlett-Packard 8593A SN: 3107A01358
Spectrum Analyzer (9kHz-26GHz)	X	Hewlett-Packard 8593E, SN: 3412A01131
Spectrum Analyzer (9kHz-26GHz)		Hewlett-Packard 8563E, SN: 3310A01174
Spectrum Analyzer (9kHz-40GHz)		Hewlett-Packard 8564E, SN: 3745A01031
Power Meter		Hewlett-Packard, 432A
Power Meter		Anritsu, ML4803A/MP
Harmonic Mixer (26-40 GHz)		Hewlett-Packard 11970A, SN: 3003A08327
Harmonic Mixer (40-60 GHz)		Hewlett-Packard 11970U, SN: 2332A00500
Harmonic Mixer (75-110 GHz)		Hewlett-Packard 11970W, SN: 2521A00179
Harmonic Mixer (140-220 GHz)		Pacific Millimeter Prod., GMA, SN: 26
S-Band Std. Gain Horn		S/A, Model SGH-2.6
C-Band Std. Gain Horn		University of Michigan, NRL design
XN-Band Std. Gain Horn		University of Michigan, NRL design
X-Band Std. Gain Horn		S/A, Model 12-8.2
X-band horn (8.2- 12.4 GHz)		Narda 640
X-band horn (8.2- 12.4 GHz)		Scientific Atlanta , 12-8.2, SN: 730
K-band horn (18-26.5 GHz)		FXR, Inc., K638KF
Ka-band horn (26.5-40 GHz)		FXR, Inc., U638A
U-band horn (40-60 GHz)		Custom Microwave, HO19
W-band horn(75-110 GHz)		Custom Microwave, HO10
G-band horn (140-220 GHz)		Custom Microwave, HO5R
Bicone Antenna (30-250 MHz)	X	University of Michigan, RLBC-1
Bicone Antenna (200-1000 MHz)	X	University of Michigan, RLBC-2
Dipole Antenna Set (30-1000 MHz)	X	University of Michigan, RLDP-1,-2,-3
Dipole Antenna Set (30-1000 MHz)		EMCO 2131C, SN: 992
Active Rod Antenna (30 Hz-50 MHz)		EMCO 3301B, SN: 3223
Active Loop Antenna (30 Hz-50 MHz)		EMCO 6502, SN:2855
Ridge-horn Antenna (300-5000 MHz)	X	University of Michigan
Amplifier (5-1000 MHz)	X	Avantak, A11-1, A25-1S
Amplifier (5-4500 MHz)	X	Avantak
Amplifier (4.5-13 GHz)		Avantek, AFT-12665
Amplifier (6-16 GHz)		Trek
Amplifier (16-26 GHz)		Avantek
LISN Box		University of Michigan
Signal Generator		Hewlett-Packard 8657B

### 3. Device Under Test

#### 3.1 Identification

The DUT is a 313.85 MHz transmitter, 2 x 1 x 0.5 inches in size and the carrier is FSK modulated. The antenna is a trace on the PCB. The DUT was designed and manufactured by Siemens Automotive Corp./Continental, 4685 Investment Drive, Troy, MI 48098. It is identified as:

Siemens/Continental Transmitter  
Model/PN(s): 72147-TK4A-A010-M1, 72147-TK4A-A110-M1  
FCC ID: M3N5WY8145  
IC: 267F-5WY8145

#### 3.2 Variants

There is only a single variant of the DUT. The two part numbers associated with this variant are used to indicate the device belonging to driver 1 and driver 2 for a given vehicle, but both devices are electrically and structurally identical.

#### 3.3 Modes of Operation

The DUT is capable of two primary modes of operation. In the first mode the DUT is activated by button press. In the second mode the DUT is activated by encoded LF interrogation, which is manually induced by the user when they lift a door handle on the vehicle. In both cases the DUT is manually activated and ceases to transmit within 5 seconds of deactivation. See Figure 6.1.

#### 3.4 EMI/EMC Relevant Modifications

There were no modifications made to the DUT by this laboratory.

### 4. Emission Limits

The DUT tested falls under the category of an Intentional Radiators and the Digital Devices. For FCC, it is subject to Part 15, Subpart C, (Section 15.231(a-c), 15.209), and Subpart A, (Section 15.33). For Industry Canada it is subject to RSS-210 (Section 2.6 and 2.7). The applicable testing frequencies with corresponding emission limits are given in Tables 4.1 and 4.2 below.

#### 4.1 Radiated Emission Limits

Table 4.1. Radiated Emission Limits (FCC: 15.33, 15.35, 15.209; IC: RSS-210, 2.7 Table 2).  
(Digital Class B)

Freq. (MHz)	$E_{lim}$ (3m) $\mu$ V/m	$E_{lim}$ dB( $\mu$ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW)  
Quasi-Peak readings apply to 1000 MHz (120 kHz BW)

Table 4.2. Radiated Emission Limits (FCC: 15.231(b), 15.205(a); IC: RSS-210; 2.7 Table 4).  
 (Transmitter)

Frequency (MHz)	Fundamental Ave. E <sub>lim</sub> (3m)		Spurious** Ave. E <sub>lim</sub> (3m)	
	( $\mu$ V/m)	dB ( $\mu$ V/m)	( $\mu$ V/m)	dB ( $\mu$ V/m)
260.0-470.0	3750-12500*		375-1250	
315	6042	75.6	604.2	55.6
433.9	10966	80.8	1096.6	60.8
322-335.4 399.9-410 608-614	Restricted Bands		200	46.0
960-1240/1427(IC) 1300-1427 1435-1626.5 1645.5-1646.5 (IC) 1660-1710 1718.9-1722.2 2200-2300	Restricted Bands		500	54.0

\* Linear interpolation, formula:  $E = -7083 + 41.67 * f$  (MHz)

\*\* Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

### 4.3 Exemptions

None.

### 4.4 Power Line Conducted Emission Limits

The power line conducted emission limits and tests do not apply here, as the DUT is powered by a 3 VDC battery.

### 4.5 Supply Voltage Variation

Measurements of the variation in the fundamental radiated emission shall be performed with the supply voltage varied between 85% and 115% of the nominal rated value. For battery operated equipment, the equipment tests shall be performed using a new battery.

## 5. Test Procedures

### 5.1 Semi-Anechoic Chamber Radiated Emission Testing

To become familiar with the emission behavior of the DUT, the DUT was first studied and measured in a shielded semi-anechoic chamber. In the chamber is set-up similar to that of an outdoor 3-meter site, with a turntable, antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

In testing for radiated emissions, a transmitter was provided by the manufacturer that is capable of repeated emissions. It was placed on the test table flat, on its side, and on its end. In the chamber we studied and recorded all the emissions using a Bicone antenna up to 300 MHz and a ridged horn antenna above 200 MHz. The measurements made in the chamber below 1 GHz are used for pre-test evaluation only. The measurements made above 1 GHz are used in pre-test evaluation and in final compliance assessment. We note that for the horn antenna, the antenna pattern is directive and the measurement is essentially that of free space (no ground reflection). Consequently, it is not essential to measure the DUT for both antenna polarizations, as long as the DUT is measured on all three of its major axis. In the chamber we also recorded the spectrum and modulation characteristics of the carrier. These data are presented in subsequent sections.

## 5.2 Open Area Test Site (OATS) Radiated Emission Testing

After the chamber measurements are complete, emissions are re-measured on the outdoor 3-meter open area test site at the fundamental and harmonics up to 1 GHz using tuned dipoles and/or a high frequency biconical antenna. The DUT is placed on the test table flat, on its side, and on its end, and worst case emissions are recorded. Photographs included in this filing show the DUT on the OATS.

## 5.3 Field Calculation for Radiated Emission Measurements

To convert the dBm's measured on the spectrum analyzer to dB( $\mu$ V/m), we use expression

$$E_3(\text{dB}\mu\text{V/m}) = 107 + P_R + K_A - K_G$$

where  $P_R$  = power recorded on spectrum analyzer, dB, measured at 3m  
 $K_A$  = antenna factor, dB/m  
 $K_G$  = pre-amplifier gain, including cable loss, dB

When presenting the data, at each frequency the highest measured emission under all of the possible orientations is given. Computations and results are given in Table 5.1. There we see that the DUT meets the limit by 1.2 dB dB.

## 5.4 Power Line Conducted Emission Testing

These tests do not apply, since the DUT is powered from a 3 VDC battery.

## 6. Test Results

### 6.1 Correction For Pulse Operation

When the transmitter is activated by button press, it can, in the worst case, transmit 3 pulses of Manchester encoded FSK data. The longest of these pulses has an on time of 162.5 ms, resulting in a duty factor of 0 dB. When activated by manual LF interrogation, the DUT will, in the worst case, transmit one (1) 20 ms pulse. However, since the peak output power rating for the device does not vary between these modes,  $K_E = 0$  dB duty is employed during testing. In this See Figure 6.1.

### 6.2 Emission Spectrum

Using the ridge-horn antenna and DUT placed in its aperture, emission spectrum was recorded and is shown in Figure 6.2. We note that in scanning from 30 MHz to 4.5 GHz using Bicone and the ridge horn antennas, there were no other significant spurious emissions observed.

### 6.3 Bandwidth of the Emission Spectrum

The measured spectrum of the signal is shown in Figure 6.3 for both the button and LF activated modes. The allowed (-20 dB, 99%) bandwidth is 0.25% of 313.85 MHz, or 784.6 kHz. From the plot we see that the worst case -20 dB bandwidth is 113.0 kHz, and the center frequency is 313.85 MHz.

### 6.4 Effect of Supply Voltage Variation and Test Battery Voltages

The DUT has been designed to be powered by a 3 VDC battery. For this test, the battery was replaced by a laboratory variable power supply. Relative power radiated was measured at the fundamental as the voltage was varied from 2 to 4 volts. The emission variation is shown in Figure 6.4.

Batteries:	before testing	$V_{oc} = 3.27$ V
	after testing	$V_{oc} = 3.01$ V
Ave. current from batteries		$I = 4.8$ mA (cw)

**Table 5.1 Highest Emissions Measured**

Radiated Emission - RF											iem./Cont. 09 Acura; FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dBµV/m	E3lim dBµV/m	Pass dB	Comments
1	313.9	Dip	H	-28.6	Pk	18.5	22.6	74.4	75.6	1.2	flat
2	313.9	Dip	V	-31.8	Pk	18.5	22.6	71.2	75.6	4.4	end
3	627.8	Dip	H	-57.7	Pk	24.3	19.5	54.2	55.6	1.4	flat
4	627.8	Dip	V	-62.7	Pk	24.3	19.5	49.2	55.6	6.4	end
5	941.7	Dip	H	-64.4	Pk	28.8	17.5	53.9	55.6	1.7	flat
6	945.0	Dip	V	-65.5	Pk	28.8	17.5	52.9	55.6	2.7	end
7	1255.6	Horn	H	-61.7	Pk	20.6	28.1	37.8	54.0	16.2	flat
8	1569.5	Horn	H	-63.5	Pk	21.5	28.1	36.9	54.0	17.1	side
9	1883.4	Horn	H	-58.4	Pk	22.2	28.1	42.7	55.6	12.9	flat
10	2197.3	Horn	H	-59.2	Pk	23.0	26.5	44.3	55.6	11.2	flat
11	2511.2	Horn	H	-61.2	Pk	23.8	26.0	43.6	55.6	11.9	flat
12	2825.1	Horn	H	-61.8	Pk	24.8	24.8	45.2	54.0	8.8	flat
13	3139.0	Horn	H	-62.5	Pk	25.8	23.6	46.7	55.6	8.9	flat
14											
15											
16											
17											
18	* Includes 0 dB duty factor										
19											
20											
21											
22											
23											
24											
25											
26											
27											
Digital Radiated Emissions											
#	Freq. kHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3 dBµV/m	E3lim dBµV/m	Pass dB	Comments
1											
2											
3											
4	Digital emissions more than 20 dB below FCC/IC Class B Limit.										
5											
6											
7											
8											
9											

Meas. 03/17/2008; U of Mich.

University of Michigan Radiation Laboratory  
 FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-420




Figure 6.1(a). Transmissions modulation characteristics: (top) complete transmission, (center) expanded dataset, (bottom) duty.




Figure 6.1(b). Transmissions modulation characteristics: (top) LF transmission, (center) expanded bit, (bottom) expanded period.




Figure 6.2. Emission spectrum of the DUT (pulsed emission), amplitudes are only indicative, not calibrated.



University of Michigan Radiation Laboratory  
 FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-420




Figure 6.3. Measured bandwidth of the DUT.  
 (top) RKE transmission, (bottom) LF activated transmission




Figure 6.5. Relative emission at 315 MHz vs. supply voltage (pulsed emission).



DUT on OATS – one of 3 axes tested



DUT on OATS (close-up) – one of 3 axes tested