Report No.: E2/2017/90022



# 15 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## 14.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time			
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm <sup>2</sup> )	(minute)			
Limits for General Population/Uncontrolled Exposure							
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30-300	27.5	0.073	0.2	30			
300-1500	/	/	F/1500	30			
1500-15000	/	/	1.0	30			

F = frequency in MHz

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Offices there we stated the results shown in this test report relief they to the sample(s) tested and such carriers of the format of the following the first part of the first part of the following the first part of the following the first part of the pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.

<sup>\* =</sup> Plane-wave equipment power density

Report No.: E2/2017/90022



# 15.2 14.2 Maximum Permissible Exposure (MPE) Evaluation (Worst Case)

#### 802.11n\_HT20\_MIMO

СН	Frequency (MHz)	Data Rate	Avg. POWER (dBm)		TOTAL POWER	REQUIRED LIMIT	RESULT	
			CH 0	CH 1	CH 2	(dBm)	(dBm)	RESULI
36	5180	MCS16	22.13	20.81	20.29	25.93	26.19	PASS
44	5220	MCS16	22.03	20.74	20.23	25.85	26.19	PASS
48	5240	MCS16	21.93	20.58	20.08	25.72	26.19	PASS
149	5745	MCS16	20.78	20.66	20.09	25.30	26.33	PASS
157	5785	MCS16	20.31	20.26	19.57	24.84	26.33	PASS
165	5825	MCS16	20.16	20.01	19.46	24.67	26.33	PASS

## MPE Prediction (802.11n HT20)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$ 

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

#### 5150~5250MHz

Max. output power including tune-up tolerancel:	25.93	(dBm)
Max. output power including tune-up tolerancel:		(mW)
Duty cycle:	99.75	(%)
Maximum Pav :	390.76252	(mW)
Peak Antenna gain (Maximum):	5.04	(dBi)
Peak Antenna gain (linear):	3.1915379	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5180	(MHz)
MPE limit for uncontrolled exposure at prediction	1	
frequency:		(mW/cm2)
Power density at predication frequency at 20 (cm)	0.248	
distance		(mW/cm2)

### **Measurement Result**

The predicted power density level at 20 cm is 0.248 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5180MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Striet we stated the testites shrive it the state report report report in the sample(s) tested and such carriers of the state of the stripe of the state of the stripe of pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.

f (886-2) 2298-0488