



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Z-Com, Inc.
Applicant Address	7F-2, No. 9. Prosperity RD.I Science-Based Industrial, Park Hsinchu, 300 Taiwan
FCC ID	M4Y-GZ901
Manufacturer's company	Z-Com, Inc.
Manufacturer Address	7F-2, No. 9. Prosperity RD.I Science-Based Industrial, Park Hsinchu, 300 Taiwan

Product Name	900MHz Wireless miniPCI Module
Brand Name	ZCOM
Model Name	GZ-901
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	902 ~ 928 MHz
Received Date	Nov. 29, 2006
Final Test Date	Dec. 9, 2006
Submission Type	Original Equipment



Statement

Test result included is only for the DSSS/OFDM part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies	3
3.5. Table for Test Modes.....	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units	4
3.8. Table for Parameters of Test Software Setting	5
3.9. Test Configurations	6
4. TEST RESULT	8
4.1. AC Power Line Conducted Emissions Measurement.....	8
4.2. Maximum Peak Output Power Measurement	12
4.3. Power Spectral Density Measurement	14
4.4. 6dB Spectrum Bandwidth Measurement	19
4.5. Radiated Emissions Measurement	24
4.6. Band Edge Emissions Measurement	40
4.7. Antenna Requirements	47
5. LIST OF MEASURING EQUIPMENTS	48
6. TEST LOCATION.....	50
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A4
APPENDIX B. TEST PHOTOS.....	B1 ~ B7
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3



1. CERTIFICATE OF COMPLIANCE

Product Name : 900MHz Wireless miniPCI Module
Brand Name : ZCOM
Model Name : GZ-901
Applicant : Z-Com, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 29, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sharon Jiang 13.12.06 Steven Lu 13.12.06

Prepared By:

Sharon Jiang / Specialist

Tested By:

Steven Lu / Engineer

Wayne Hsu 13.12.06

Reviewed By:

Wayne Hsu

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	17.14 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	2.34 dB
4.3	15.247(e)	Power Spectral Density	Complies	2.01 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	2.46 dB
4.6	15.247(d)	Band Edge Emissions	Complies	-
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From Host System
Modulation	DSSS ; OFDM
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	902 ~ 928 MHz
Channel Number	DSSS: 2 ; OFDM: 4
Channel Band Width (99%)	DSSS: 16.05 MHz ; OFDM: 7.30 MHz Note: DSSS:20MHz, OFDM:5MHz
Conducted Output Power	DSSS: 25.67 dBm ; OFDM: 27.66 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	FRE	W1048	Dipole Antenna	Reversed-SMA	3.79663

3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
902 ~ 928MHz (OFDM)	1	908 MHz	3	918 MHz
	2	913 MHz	4	923 MHz
902 ~ 928MHz (DSSS)	2	913 MHz	3	918 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	OFDM/BPSK	6 Mbps	2	1
Maximum Peak Conducted Output Power	DSSS/BPSK	1 Mbps	2/3	NA
Power Spectral Density	OFDM/BPSK	6 Mbps	1/2/4	NA
6dB Spectrum Bandwidth				
Radiated Emissions 9kHz~1GHz	OFDM/BPSK	6 Mbps	2	1
Radiated Emissions 1GHz~10 th Harmonic	DSSS/BPSK	1 Mbps	2/3	1
	OFDM/BPSK	6 Mbps	1/2/4	1
Band Edge Emissions	DSSS/BPSK	1 Mbps	2/3	1
	OFDM/BPSK	6 Mbps	1/4	1

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	E2K24GBRL
Modem	ACEEX	DM1414	IFAXDM1414
Printer	EPSON	LQ-300	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters

Test Software Version	ART		
Frequency	913 MHz	918 MHz	
DSSS Mode	24	24.5	
Frequency	908 MHz	913 MHz	923 MHz
OFDM Mode	25	25	25

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.
- c. The NB sends " H " messages to the printer, then the printer prints them on the paper.
- d. The NB sends " H " messages to the modem.
- e. Repeat the steps from b to d.


At the same time, the following programs were executed:

Executed " ART " to control the EUT continuously transmit RF signal.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9kHz~1GHz



Test Configuration: Above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Phase	Line
Configuration	OFDM CTX CH2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.16155	28.22	-27.16	55.38	27.85	0.17	0.20	AVERAGE	LINE
2	0.16155	44.26	-21.12	65.38	43.89	0.17	0.20	QP	LINE
3	0.17491	26.17	-28.56	54.72	25.82	0.15	0.20	AVERAGE	LINE
4	0.17491	44.53	-20.20	64.72	44.18	0.15	0.20	QP	LINE
5	0.20944	39.20	-24.02	63.23	38.91	0.09	0.20	QP	LINE
6	0.20944	22.61	-30.61	53.23	22.32	0.09	0.20	AVERAGE	LINE
7	0.24037	22.03	-23.97	46.00	21.92	0.00	0.11	Average	LINE
8	0.24037	32.70	-29.38	62.08	32.43	0.07	0.20	QP	LINE
9	1.698	27.24	-18.76	46.00	27.10	0.00	0.14	AVERAGE	LINE
10	1.698	37.49	-18.51	56.00	37.35	0.00	0.14	QP	LINE
11	1.878	37.47	-18.53	56.00	37.29	0.00	0.18	QP	LINE
12	1.878	22.55	-23.45	46.00	22.37	0.00	0.18	AVERAGE	LINE

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Phase	Neutral
Configuration	OFDM CTX CH2		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark	Pol/Phase
	MHz	dBuV	Limit	Line	Level	Factor	Loss		
			dB	dBuV	dBuV	dB	dB		
1	0.15485	48.59	-17.15	65.74	48.20	0.19	0.20	QP	NEUTRAL
2	0.15485	32.68	-23.06	55.74	32.29	0.19	0.20	AVERAGE	NEUTRAL
3	0.16677	46.86	-18.26	65.12	46.50	0.16	0.20	QP	NEUTRAL
4	0.16677	31.38	-23.74	55.12	31.02	0.16	0.20	AVERAGE	NEUTRAL
5	0.21967	40.46	-22.38	62.83	40.17	0.09	0.20	QP	NEUTRAL
6	0.21967	24.82	-28.02	52.83	24.53	0.09	0.20	AVERAGE	NEUTRAL
7	0.25078	38.33	-23.40	61.73	38.06	0.07	0.20	QP	NEUTRAL
8	0.25078	22.74	-28.99	51.73	22.47	0.07	0.20	AVERAGE	NEUTRAL
9	1.725	28.86	-17.14	46.00	28.71	0.00	0.15	AVERAGE	NEUTRAL
10 @	1.725	39.27	-16.73	56.00	39.12	0.00	0.15	QP	NEUTRAL
11	2.023	38.40	-17.60	56.00	38.20	0.00	0.20	QP	NEUTRAL
12	2.023	28.35	-17.65	46.00	28.15	0.00	0.20	AVERAGE	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 902-928MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	24°C	Humidity	62%
Test Engineer	Leo Hung	Configurations	DSSS/OFDM

Configuration DSSS

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
2	913 MHz	25.32	30.00	Complies
3	918 MHz	25.67	30.00	Complies

Configuration OFDM

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	908 MHz	27.37	30.00	Complies
3	913 MHz	27.18	30.00	Complies
4	923 MHz	27.66	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	62%
Test Engineer	Leo Hung	Configurations	DSSS/OFDM


Configuration DSSS

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
2	913 MHz	- 0.63	8.00	Complies
3	918 MHz	- 0.48	8.00	Complies

Configuration OFDM


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	908 MHz	5.75	8.00	Complies
3	913 MHz	5.03	8.00	Complies
4	923 MHz	5.99	8.00	Complies

Power Density Plot on Configuration DSSS / 913 MHz




Date: 9.DEC.2006 09:15:48

Power Density Plot on Configuration DSSS / 918 MHz




Date: 9.DEC.2006 09:19:45

Power Density Plot on Configuration OFDM / 908 MHz




Date: 9.DEC.2006 09:11:54

Power Density Plot on Configuration OFDM / 913 MHz



Date: 9.DEC.2006 09:02:19

Power Density Plot on Configuration OFDM / 923 MHz



Date: 9.DEC.2006 09:11:17

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24°C	Humidity	62%
Test Engineer	Leo Hung	Configurations	DSSS/OFDM


Configuration DSSS

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
2	913 MHz	12.59	16.05	500	Complies
3	918 MHz	11.60	15.54	500	Complies

Configuration OFDM


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	908 MHz	4.19	6.28	500	Complies
3	913 MHz	4.16	6.76	500	Complies
4	923 MHz	4.14	7.30	500	Complies

6 dB Bandwidth Plot on Configuration DSSS / 913 MHz




Date: 9.DEC.2006 09:15:04

6 dB Bandwidth Plot on Configuration DSSS / 918 MHz




Date: 9.DEC.2006 09:19:02

6 dB Bandwidth Plot on Configuration OFDM / 908 MHz




Date: 9.DEC.2006 08:55:22

6 dB Bandwidth Plot on Configuration OFDM / 913 MHz



Date: 9.DEC.2006 09:00:17

6 dB Bandwidth Plot on Configuration OFDM / 923 MHz



Date: 9.DEC.2006 09:10:34

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 2

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 2

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	30.000	34.06	-5.94	40.00	44.83	0.80	31.67	Peak	---	---	20.10
2	98.870	26.76	-16.74	43.50	45.96	1.50	31.72	Peak	---	---	11.02
3	164.830	26.90	-16.60	43.50	46.00	2.00	31.54	Peak	---	---	10.45
4	230.790	34.06	-11.94	46.00	52.03	2.21	31.38	Peak	---	---	11.20
5	265.710	27.13	-18.87	46.00	42.33	2.50	31.34	Peak	---	---	13.64
6	299.660	27.68	-18.32	46.00	42.80	2.20	31.32	Peak	---	---	14.00

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB	dB		cm	deg	dB/m
1	30.000	31.18	-8.82	40.00	41.95	0.80	31.67	Peak	---	---	20.10
2	98.870	33.56	-9.94	43.50	52.76	1.50	31.72	Peak	---	---	11.02
3	164.830	35.98	-7.52	43.50	55.07	2.00	31.54	Peak	---	---	10.45
4	198.780	33.90	-9.60	43.50	53.21	2.00	31.45	Peak	---	---	10.14
5 *	230.790	42.60	-3.40	46.00	60.58	2.21	31.38	QP	105	156	11.20
6	264.740	37.89	-8.11	46.00	53.03	2.50	31.34	Peak	---	---	13.70
7	299.660	33.46	-12.54	46.00	48.58	2.20	31.32	Peak	---	---	14.00
8	365.620	30.65	-15.35	46.00	43.56	2.49	31.17	Peak	---	---	15.78
9	497.540	31.95	-14.05	46.00	41.76	3.27	30.94	Peak	---	---	17.86
10	680.870	39.05	-6.95	46.00	46.21	3.56	30.44	Peak	---	---	19.72
11	960.230	35.62	-18.38	54.00	39.25	3.92	29.49	Peak	---	---	21.94

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	DSSS CH 2

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	1544.000	50.16	-3.84	54.00	57.11	2.23	34.69	AVERAGE	123	35	25.50
2	1544.000	51.04	-22.96	74.00	57.99	2.23	34.69	PEAK	123	35	25.50
3	4632.000	46.03	-7.97	54.00	44.26	4.30	35.21	AVERAGE	150	21	32.68
4	4632.000	49.77	-24.23	74.00	48.00	4.30	35.21	PEAK	150	21	32.68
5 !	7720.000	49.09	-4.91	54.00	42.00	5.80	35.18	AVERAGE	130	332	36.47
6	7720.000	51.20	-22.80	74.00	44.11	5.80	35.18	PEAK	130	332	36.47
7	9263.932	47.49	-6.51	54.00	37.44	7.05	35.36	AVERAGE	133	30	38.36
8	9263.932	54.05	-19.95	74.00	44.00	7.05	35.36	PEAK	133	30	38.36


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	1544.008	47.31	-6.69	54.00	54.26	2.23	34.69	AVERAGE	106	185	25.50
2	1544.008	48.92	-25.08	74.00	55.87	2.23	34.69	PEAK	106	185	25.50
3	4631.954	39.13	-14.87	54.00	37.36	4.30	35.21	AVERAGE	163	108	32.68
4	4631.954	44.77	-29.23	74.00	43.00	4.30	35.21	PEAK	163	108	32.68
5 !	7719.964	50.35	-3.65	54.00	43.26	5.80	35.18	AVERAGE	162	104	36.47
6	7719.964	53.97	-20.03	74.00	46.88	5.80	35.18	PEAK	162	104	36.47
7	9263.970	46.31	-7.69	54.00	36.26	7.05	35.36	AVERAGE	161	138	38.36
8	9263.970	54.16	-19.84	74.00	44.11	7.05	35.36	PEAK	161	138	38.36


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	DSSS CH 3

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	1544.000	51.31	-2.69	54.00	58.26	2.23	34.69	AVERAGE	128	35	25.50
2	1544.000	53.28	-20.72	74.00	60.23	2.23	34.69	PEAK	128	35	25.50
3	4632.000	47.88	-6.12	54.00	46.11	4.30	35.21	AVERAGE	160	21	32.68
4	4632.000	51.99	-22.01	74.00	50.22	4.30	35.21	PEAK	160	21	32.68
5 !	7720.000	50.35	-3.65	54.00	43.26	5.80	35.18	AVERAGE	140	332	36.47
6	7720.000	56.53	-17.47	74.00	49.44	5.80	35.18	PEAK	140	332	36.47
7 !	9263.932	48.71	-5.29	54.00	38.66	7.05	35.36	QP	130	26	38.36
8	9263.932	54.34	-19.66	74.00	44.29	7.05	35.36	PEAK	130	26	38.36


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	1544.008	46.38	-7.62	54.00	53.33	2.23	34.69	AVERAGE	100	185	25.50
2	1544.008	47.31	-26.69	74.00	54.26	2.23	34.69	PEAK	100	185	25.50
3	4631.954	37.40	-16.60	54.00	35.63	4.30	35.21	AVERAGE	160	108	32.68
4	4631.954	44.44	-29.56	74.00	42.67	4.30	35.21	PEAK	160	108	32.68
5	7719.964	47.53	-6.47	54.00	40.44	5.80	35.18	AVERAGE	155	104	36.47
6	7719.964	52.08	-21.92	74.00	44.99	5.80	35.18	PEAK	155	104	36.47
7	9263.970	44.64	-9.36	54.00	34.59	7.05	35.36	AVERAGE	160	138	38.36
8	9263.970	51.46	-22.54	74.00	41.41	7.05	35.36	PEAK	160	138	38.36


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 1

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	1544.000	51.54	-2.46	54.00	58.49	2.23	34.69	AVERAGE	123	35	25.50
2	1544.000	52.42	-21.58	74.00	59.37	2.23	34.69	PEAK	123	35	25.50
3	4632.000	47.38	-6.62	54.00	45.62	4.30	35.21	AVERAGE	153	21	32.68
4	4632.000	50.90	-23.10	74.00	49.13	4.30	35.21	PEAK	153	21	32.68
5 !	7720.000	50.51	-3.49	54.00	43.42	5.80	35.18	AVERAGE	133	332	36.47
6	7720.000	55.60	-18.40	74.00	48.52	5.80	35.18	PEAK	133	332	36.47
7 !	9263.932	48.18	-5.82	54.00	38.14	7.05	35.36	AVERAGE	133	26	38.36
8	9263.932	54.70	-19.30	74.00	44.66	7.05	35.36	PEAK	133	26	38.36


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	1544.008	47.32	-6.68	54.00	54.27	2.23	34.69	AVERAGE	103	185	25.50
2	1544.008	48.15	-25.85	74.00	55.10	2.23	34.69	PEAK	103	185	25.50
3	4631.954	38.13	-15.87	54.00	36.36	4.30	35.21	AVERAGE	157	108	32.68
4	4631.954	45.53	-28.47	74.00	43.76	4.30	35.21	PEAK	157	108	32.68
5 !	7719.964	48.39	-5.61	54.00	41.30	5.80	35.18	AVERAGE	160	104	36.47
6	7719.964	52.26	-21.74	74.00	45.17	5.80	35.18	PEAK	160	104	36.47
7	9263.970	45.51	-8.49	54.00	35.46	7.05	35.36	AVERAGE	162	138	38.36
8	9263.970	52.86	-21.14	74.00	42.82	7.05	35.36	PEAK	162	138	38.36


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 3

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp	Remark	Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor		Pos	Pos	Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	1544.000	51.16	-2.84	54.00	58.11	2.23	34.69	AVERAGE	123	35	25.50
2	1544.000	52.04	-21.96	74.00	58.99	2.23	34.69	PEAK	123	35	25.50
3	4632.000	47.03	-6.97	54.00	45.26	4.30	35.21	AVERAGE	150	21	32.68
4	4632.000	50.77	-23.23	74.00	49.00	4.30	35.21	PEAK	150	21	32.68
5 !	7720.000	50.09	-3.91	54.00	43.00	5.80	35.18	AVERAGE	130	332	36.47
6	7720.000	52.20	-21.80	74.00	45.11	5.80	35.18	PEAK	130	332	36.47
7 !	9263.932	48.49	-5.51	54.00	38.44	7.05	35.36	AVERAGE	133	30	38.36
8	9263.932	55.05	-18.95	74.00	45.00	7.05	35.36	PEAK	133	30	38.36


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	1544.008	47.05	-6.95	54.00	54.00	2.23	34.69	AVERAGE	100	185	25.50
2	1544.008	48.71	-25.29	74.00	55.66	2.23	34.69	PEAK	100	185	25.50
3	4631.954	37.99	-16.01	54.00	36.22	4.30	35.21	AVERAGE	161	108	32.68
4	4631.954	44.88	-29.12	74.00	43.11	4.30	35.21	PEAK	161	108	32.68
5 !	7719.964	49.21	-4.79	54.00	42.12	5.80	35.18	AVERAGE	170	104	36.47
6	7719.964	53.97	-20.03	74.00	46.88	5.80	35.18	PEAK	170	104	36.47
7	9263.970	46.04	-7.96	54.00	35.99	7.05	35.36	AVERAGE	165	138	38.36
8	9263.970	53.56	-20.44	74.00	43.51	7.05	35.36	PEAK	165	138	38.36


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 4

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 !	1544.000	51.36	-2.64	54.00	58.31	2.23	34.69	AVERAGE	132	35	25.50
2	1544.000	53.41	-20.59	74.00	60.36	2.23	34.69	PEAK	132	35	25.50
3	4632.000	47.00	-7.00	54.00	45.23	4.30	35.21	AVERAGE	155	21	32.68
4	4632.000	51.65	-22.35	74.00	49.88	4.30	35.21	PEAK	155	21	32.68
5 !	7720.000	50.27	-3.73	54.00	43.18	5.80	35.18	AVERAGE	136	332	36.47
6	7720.000	56.08	-17.92	74.00	48.99	5.80	35.18	PEAK	136	332	36.47
7 !	9263.932	48.61	-5.39	54.00	38.56	7.05	35.36	QP	130	26	38.36
8	9263.932	54.96	-19.04	74.00	44.91	7.05	35.36	PEAK	130	26	38.36

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	1544.008	47.38	-6.62	54.00	54.33	2.23	34.69	AVERAGE	100	185	25.50
2	1544.008	48.31	-25.69	74.00	55.26	2.23	34.69	PEAK	100	185	25.50
3	4631.954	38.40	-15.60	54.00	36.63	4.30	35.21	AVERAGE	160	108	32.68
4	4631.954	45.44	-28.56	74.00	43.67	4.30	35.21	PEAK	160	108	32.68
5 !	7719.964	48.53	-5.47	54.00	41.44	5.80	35.18	AVERAGE	155	104	36.47
6	7719.964	53.08	-20.92	74.00	45.99	5.80	35.18	PEAK	155	104	36.47
7	9263.970	45.64	-8.36	54.00	35.59	7.05	35.36	AVERAGE	160	138	38.36
8	9263.970	52.46	-21.54	74.00	42.41	7.05	35.36	PEAK	160	138	38.36

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band.

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.


4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Fundamental Emissions


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	DSSS CH 2, 3

Channel 2



2 *	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
	914.000	114.15			88.42	4.04	0.00	PEAK	132	257	21.68


Channel 3



	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna	
Freq	Level	Limit	Level	Loss	Factor	Remark	Pos	Pos	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	dB/m	
2 *	921.000	115.44		89.69	4.02	0.00	PERK	129	328	21.73


Temperature	24°C	Humidity	62%
Test Engineer	Beck Wu	Configurations	OFDM CH 1, 4

Channel 1



	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
Freq	Level	Limit	Level	Loss	Factor	Remark	Pos	Pos	Factor
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	dB/m
2 *	906.000	119.09	93.38	4.08	0.00	PEAK	127	334	21.64

Channel 4



2 *	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
	924.200	118.99			93.23	4.00	0.00	PEAK	128	332	21.75


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration DSSS / 913MHz




Date: 9.DEC.2006 09:16:47

High Band Edge Plot on Configuration DSSS / 918 MHz




Date: 9.DEC.2006 09:18:12

Low Band Edge Plot on Configuration OFDM / 908 MHz



Date: 9.DEC.2006 08:59:09

High Band Edge Plot on Configuration OFDM / 923 MHz



Date: 9.DEC.2006 09:09:50

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	18667	9 kHz - 2 GHz	Jan. 18, 2006	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 24, 2006*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 21, 2006	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Jul. 24, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 27, 2006	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec.02, 2006	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec.02, 2006	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
EMC Receiver	R&S	ESCS 30	100174	9kHz - 2.75GHz	Feb. 22, 2006	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz - 30MHz	Dec. 19, 2005	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9708-1839	9kHz - 30MHz	Mar. 18, 2006	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz - 30MHz	Apr. 20, 2006	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Nov. 26, 2006	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100764	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 10, 2006	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Dec. 28, 2005	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 02, 2006	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 1, 2006	Conducted (TH01-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 1, 2006	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Dec. 30, 2005	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 7248, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085