

△	ECO NO.	REVISION	APP.	DES.	DATE	TOLERANCE GRADE () ±			
						LENGTH	GRADE	A	B
						~ 6	0.05	0.08	0.20
						6 ~ 18	0.08	0.10	0.30
						18 ~ 50	0.10	0.15	0.40
						50 ~ 180	0.20	0.30	0.80

備註 :

1. 材質 : 50# 白色特多龍
2. 印刷顏色 : 黑色印刷
3. 印刷圖案及字體需清晰
4. 保護膜 : 打字亮模
5. 紙張厚度 (含背膠) : 0.12mm +/- 0.05mm
6. 公差 : +0.1/-0.2mm
7. 需捲狀入料

廠商製作

Model : ZC-3635-5-23

Power Rating : See the label on the PoE Injector
ZC-3635 Default Settings :
IP Address : 192.168.1.1 **Password :** password
Domain :



FCC ID : M4Y-ZC3635-5V02

Size : 70x30 mm
4R-1.5

廠內打印CODE示意圖--正確請依照BARCODE 對照表

Model : ZC-3635-5-23

Power Rating : See the label on the PoE Injector
ZC-3625 Default Settings :
IP Address : 192.168.1.1 **Password :** password
Domain :




MAC : XXXXXX-XXXXXX
SN : XXXXXXXXXXXXXXX



FCC ID : M4Y-ZC3635-5V02

貼紙黏處-示意圖



V 3.0

DWG NO.

SCALE	UNITS	TOLERANCE			Z-C om , Inc.			A
1 / 1	M. M.	GRADE	ANGLE		MODEL	ZC-3635-5-23	SHEET	1 / 1
DRW.	DES.	CKD.	RECKD.	APP.				
JULIE					NAME	IXP-3635 Pro LABEL		
10/28/2009					PAR T NO.	55-000040-IZN		