



FCC TEST REPORT

REPORT NO.: RF920815H04B

MODEL NO.: R-WL11.B

RECEIVED: Jun. 21, 2004

TESTED: Jun. 24 to 28, 2004

APPLICANT: Z-COM, INC.

ADDRESS: 7F-2, No.9. Prosperity RD. I , Science-Based
Industrial Park Hsinchu, 300 Taiwan

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.

This test report consists of 33 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, or any government agencies. The test results in the report only apply to the tested sample.



0536
ILAC MRA



Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST.....	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT.....	9
4.1.1	TEST INSTRUMENTS.....	9
4.1.2	TEST PROCEDURES	10
4.1.3	DEVIATION FROM TEST STANDARD.....	10
4.1.4	TEST SETUP.....	11
4.1.5	EUT OPERATING CONDITIONS	12
4.1.6	TEST RESULTS	13
4.2	RADIATED EMISSION MEASUREMENT.....	15
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	15
4.2.2	TEST INSTRUMENTS.....	16
4.2.3	TEST PROCEDURES	17
4.2.4	DEVIATION FROM TEST STANDARD.....	17
4.2.5	TEST SETUP.....	18
4.2.6	EUT OPERATING CONDITIONS	18
4.2.7	TEST RESULTS	19
4.2.8	TEST RESULTS	20
4.3	MAXIMUM PEAK OUTPUT POWER.....	23
4.3.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	23
4.3.2	TEST INSTRUMENTS.....	23
4.3.3	TEST PROCEDURES	24
4.3.4	TEST SETUP.....	24
4.3.5	EUT OPERATING CONDITIONS	24
4.3.6	TEST RESULTS	25
4.4	BAND EDGES MEASUREMENT	26
4.4.1	LIMITS OF BAND EDGES MEASUREMENT	26
4.4.2	TEST INSTRUMENTS.....	26



4.4.3	TEST PROCEDURE	26
4.4.4	DEVIATION FROM TEST STANDARD	26
4.4.5	EUT OPERATING CONDITION	27
4.4.6	TEST RESULTS	27
4.5	ANTENNA REQUIREMENT	30
4.5.1	STANDARD APPLICABLE	30
4.5.2	ANTENNA CONNECTED CONSTRUCTION	30
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	31
6	INFORMATION ON THE TESTING LABORATORIES.....	33



1 CERTIFICATION

PRODUCT : 11 Mbps 802.11b Wireless PCMCIA Card
MODEL NO. : R-WL11B
BRAND : RICOH
TESTED: Jun. 24 to 28, 2004
APPLICANT : Z-COM, INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

The above equipment (Model: R-WL11B) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Carol Liao, **DATE:** Jul. 02, 2004
(Carol Liao)

APPROVED BY: Eric Lin, **DATE:** Jul. 02, 2004
(Eric Lin, Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -15.07dBuV at 0.181MHz
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.30dBuV at 528.00MHz
15.247(c)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

NOTE: This report is prepared for FCC class II permissive change. Only conducted emission, radiated emission, Maximum Peak Output Power and Band Edge Measurement conducted emission were presented in this test report.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11 Mbps 802.11b Wireless PCMCIA Card
MODEL NO.	R-WL11B
POWER SUPPLY	5.0VDC from host equipment
MODULATION TYPE	DBPSK for 1Mbps DQPSK for 2Mbps CCK for 5.5/11Mbps
RADIO TECHNOLOGY	DSSS, CCK
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	16.40dBm
DATA CABLE	NA
ANTENNA TYPE	Detachable Dipole Antenna
I/O PORTS	PCMCIA interface
ASSOCIATED DEVICES	NA

NOTE:

1. This report is prepared for FCC class II permissive change. The difference compared with the original design is as the following:

◆ Add one new antenna:

<i>Model No.</i>	<i>Gain (dBi)</i>	<i>Antenna Type / Connector</i>
XI-XA-150	0.66	Detachable Dipole Antenna / without connector

2. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an 11 Mbps 802.11b Wireless PCMCIA Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook Computer	DELL	C600	6DRV601	FCC DoC
2	PRINTER	HP	C2642A	MY79F1C3MZ	B94C2642X
3	MODEM	ACEEX	1414	0206026776	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8 m foil shielded wire, terminal by frame, PS2 Connector, w/o Core.
3	1.0 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core

NOTE: All power cords of the above support units are non-shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



NOTE: 1. Please refer to the photos of test configuration in Item 5 also.



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- NOTES:**
- (1) The lower limit shall apply at the transition frequencies.
 - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.1 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Dec. 04, 2004
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 04, 2004
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 27, 2004
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 03, 2004
Terminator(for KYORITSU)	50	3	May 10, 2005
Software	Cond-V2e	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in ADT Shielded Room No. A.
 3. The VCCI Con A Registration No. is C-817.




4.1.2 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Plug the EUT into the support unit 1 (Notebook computer) which placed on a testing table.
- b. The support unit 1 (Notebook computer) ran a test program “ PRISM TEST APPLIANCE (V3.1.3)” to enable EUT under transmission condition continuously at specific channel frequency.
- c. Notebook computer sends "H" messages to modem.
- d. Notebook computer sends "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS

EUT	11 Mbps 802.11b Wireless PCMCIA Card		
MODEL	R-WL11B	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	26 deg. C, 65%RH, 954 hPa	TESTED BY	Sky Liao

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.26	49.10	-	49.36	-	64.43	54.43	-15.07	-
2	0.388	0.21	35.32	-	35.53	-	58.10	48.10	-22.57	-
3	0.594	0.23	32.48	-	32.71	-	56.00	46.00	-23.29	-
4	2.709	0.34	33.95	-	34.29	-	56.00	46.00	-21.71	-
5	4.820	0.45	34.30	-	34.75	-	56.00	46.00	-21.25	-
6	11.137	0.89	27.98	-	28.87	-	60.00	50.00	-31.13	-

- NOTES:** (1) "**": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value






EUT	11 Mbps 802.11b Wireless PCMCIA Card		
MODEL	R-WL11B	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	26 deg. C, 65%RH, 954 hPa	TESTED BY	Sky Liao

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.25	46.30	-	46.55	-	64.79	54.79	-18.25	-
2	0.263	0.27	35.99	-	36.26	-	61.33	51.33	-25.07	-
3	0.529	0.22	36.76	-	36.98	-	56.00	46.00	-19.02	-
4	2.873	0.34	35.33	-	35.67	-	56.00	46.00	-20.33	-
5	5.883	0.49	33.40	-	33.89	-	60.00	50.00	-26.11	-
6	9.383	0.67	30.40	-	31.07	-	60.00	50.00	-28.93	-

- NOTES:** (1) "-": Undetectable
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.
 (4) The emission levels of other frequencies were very low against the limit.
 (5) Correction Factor = Insertion loss + Cable loss
 (6) Margin value = Emission level - Limit value





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8594ER	3829U04676	Aug. 30, 2004
ADVANTEST Spectrum Analyzer	R3271A	85060311	Jun. 16, 2005
CHASE RF Pre_Amplifier	CPA9232	1057	May. 10, 2005
HP Pre_Amplifier	8449B	3008A01922	Oct. 13, 2004
ROHDE & SCHWARZ Test Receiver	ESVS 10	849231 /019	Sep. 30, 2004
CHASE Broadband Antenna	CBL6111c	2730	Jul. 30, 2004
Schwarzbeck Horn_Antenna	3115	5619	Jul. 17, 2004
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170192	Feb. 16, 2005
SCHWARZBECK Tunable Dipole Antenna	UHAP	897	Mar. 07, 2005
SCHWARZBECK Tunable Dipole Antenna	VHAP	880	Mar. 07, 2005
RF Switches (ARNITSU)	CS-201	1565157	Dec. 01, 2004
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Feb. 10, 2005
RF Cable(RICHTEC)	9913-30M	STCCAB-30M- 1GHz-021	Dec. 01, 2004
Software	AS60P8	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Dipole Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. * = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. C.
5. The FCC Site Registration No. is 656396.
6. The VCCI Site Registration No. is R-1626.
7. The CANADA Site Registration No. is IC 4824-3.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

EUT	11 Mbps 802.11b Wireless PCMCIA Card	MODEL	R-WL11B
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	27 deg. C, 59%RH, 954 hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	198.00	32.20 QP	43.50	-11.30	1.41 H	334	22.30	9.90
2	220.00	40.30 QP	46.00	-5.70	1.15 H	314	29.80	10.40
3	264.00	33.10 QP	46.00	-12.90	1.00 H	325	17.70	15.40
4	308.00	40.30 QP	46.00	-5.70	1.09 H	348	24.70	15.70
5	484.00	35.90 QP	46.00	-10.10	1.00 H	219	14.90	21.00
6	528.00	40.30 QP	46.00	-5.70	1.00 H	162	17.90	22.40
7	572.00	38.70 QP	46.00	-7.30	1.11 H	149	15.80	22.90
8	616.00	36.70 QP	46.00	-9.30	1.01 H	141	13.70	23.00
9	704.00	30.20 QP	46.00	-15.80	1.00 H	111	5.90	24.40
10	792.00	31.40 QP	46.00	-14.60	1.16 H	29	5.30	26.10
11	880.00	30.60 QP	46.00	-15.40	1.06 H	90	2.50	28.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	73.87	33.40 QP	40.00	-6.60	1.17 V	14	26.30	7.10
2	176.00	27.00 QP	43.50	-16.50	1.05 V	51	16.80	10.20
3	198.00	32.00 QP	43.50	-11.50	1.13 V	12	22.10	9.90
4	220.00	37.30 QP	46.00	-8.70	1.06 V	6	26.80	10.40
5	264.00	30.40 QP	46.00	-15.60	1.90 V	8	15.00	15.40
6	308.00	41.30 QP	46.00	-4.70	1.83 V	23	25.70	15.70
7	484.00	38.60 QP	46.00	-7.40	1.24 V	0	17.50	21.00
8	528.00	44.70 QP	46.00	-1.30	1.12 V	348	22.30	22.40
9	572.00	39.90 QP	46.00	-6.10	1.09 V	1	17.00	22.90
10	616.00	37.40 QP	46.00	-8.60	1.00 V	15	14.40	23.00

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



4.2.8 TEST RESULTS

EUT	11 Mbps 802.11b Wireless PCMCIA Card	MODEL	R-WL11B
MODE	Channel 1	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	27 deg. C, 59%RH, 954 hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2374.00	45.40 PK	74.00	-28.60	1.20 H	346	14.70	30.70
2	2390.00	40.30 PK	74.00	-33.70	1.14 H	120	6.50	33.80
3	*2412.00	100.50 PK			1.75 H	12	70.60	29.90
3	*2412.00	91.40 AV			1.75 H	12	61.50	29.90
4	4824.00	43.70 PK	74.00	-30.30	1.68 H	166	7.50	36.20
5	7236.00	49.10 PK	74.00	-24.90	1.31 H	175	7.40	41.70
6	9648.00	53.50 PK	74.00	-20.50	1.22 H	94	8.60	44.90
6	9648.00	41.30 AV	54.00	-12.70	1.22 H	94	-3.60	44.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2374.00	52.10 PK	74.00	-21.90	1.59 V	215	21.40	30.70
1	2374.00	44.60 AV	54.00	-9.40	1.59 V	215	13.90	30.70
2	2390.00	52.40 PK	74.00	-21.60	1.24 V	224	18.60	33.80
2	2390.00	43.30 AV	54.00	-10.70	1.24 V	224	9.50	33.80
3	*2412.00	111.50 PK			1.22 V	360	81.60	29.90
3	*2412.00	103.80 AV			1.22 V	360	73.90	29.90
4	4824.00	44.90 PK	74.00	-29.10	1.17 V	135	8.60	36.20
5	7236.00	49.20 PK	74.00	-24.80	1.00 V	185	7.50	41.70
6	9648.00	53.50 PK	74.00	-20.50	1.03 V	87	8.60	44.90
6	9648.00	41.50 AV	54.00	-12.50	1.03 V	87	-3.40	44.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	11 Mbps 802.11b Wireless PCMCIA Card	MODEL	R-WL11B
MODE	Channel 6	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	27 deg. C, 59%RH, 954 hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	97.50 PK			1.72 H	15	67.50	30.00
1	*2437.00	89.60 AV			1.72 H	15	59.60	30.00
2	4874.00	45.00 PK	74.00	-29.00	1.12 H	50	8.50	36.50
3	7311.00	49.30 PK	74.00	-24.70	1.29 H	217	7.50	41.80
4	9748.00	53.00 PK	74.00	-21.00	1.03 H	190	8.40	44.60
4	9748.00	41.50 AV	54.00	-12.50	1.03 H	190	-3.10	44.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.00 PK			1.22 V	44	79.00	30.00
1	*2437.00	102.40 AV			1.22 V	44	72.40	30.00
2	4874.00	46.10 PK	74.00	-27.90	1.38 V	240	9.60	36.50
3	7311.00	50.10 PK	74.00	-23.90	1.04 V	259	8.40	41.80
4	9748.00	53.30 PK	74.00	-20.70	1.61 V	166	8.70	44.60
4	9748.00	41.60 AV	54.00	-12.40	1.61 V	166	-3.00	44.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

EUT	11 Mbps 802.11b Wireless PCMCIA Card	MODEL	R-WL11B
MODE	Channel 11	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	27 deg. C, 59%RH, 954 hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.80 PK			1.69 H	16	68.70	30.10
1	*2462.00	91.40 AV			1.69 H	16	61.40	30.10
2	2483.50	41.30 PK	74.00	-32.70	1.24 H	245	11.20	30.10
3	2499.00	42.30 PK	74.00	-31.70	1.12 H	344	11.20	31.10
4	4924.00	45.70 PK	74.00	-28.30	1.62 H	211	9.00	36.70
5	7386.00	49.60 PK	74.00	-24.40	1.04 H	190	7.80	41.80
6	9848.00	53.20 PK	74.00	-20.80	1.49 H	307	8.80	44.40
6	9848.00	41.50 AV	54.00	-12.50	1.49 H	307	-2.90	44.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.10 PK			1.21 V	12	82.10	30.10
1	*2462.00	103.90 AV			1.21 V	12	73.90	30.10
2	2483.50	52.30 PK	74.00	-21.70	1.24 V	210	22.20	30.10
2	2483.50	43.10 AV	54.00	-10.90	1.24 V	210	13.00	30.10
3	2499.00	52.60 PK	74.00	-21.40	1.42 V	135	21.50	31.10
3	2499.00	43.90 AV	54.00	-10.10	1.42 V	135	12.90	31.10
4	4924.00	45.10 PK	74.00	-28.90	1.62 V	345	8.40	36.70
5	7386.00	49.40 PK	74.00	-24.60	1.16 V	360	7.60	41.80
6	9848.00	54.20 PK	74.00	-19.80	1.26 V	238	9.90	44.40
6	9848.00	41.70 AV	54.00	-12.30	1.26 V	238	-2.70	44.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



4.3 MAXIMUM PEAK OUTPUT POWER

4.3.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 27, 2004
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Jan. 1, 2005
TEKTRONIX OSCILLOSCOPE	TDS 220	B027241	Jun. 30, 2005
NARDA DETECTOR	4503A	FSCM99899	NA


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.3.4 TEST SETUP



4.3.5 EUT OPERATING CONDITIONS

Same as Item 4.3.6



4.3.6 TEST RESULTS

EUT	11 Mbps 802.11b Wireless PCMCIA Card		
MODEL	R-WL11B	ENVIRONMENTAL CONDITIONS	28 deg. C, 65%RH, 954 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Tony Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.10	30	PASS
6	2437	16.40	30	PASS
11	2462	16.15	30	PASS



4.4 BAND EDGES MEASUREMENT

4.4.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 27, 2004

NOTE:

- 1.The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation



4.4.5 EUT OPERATING CONDITION

Same as Item 4.3.6


4.4.6 TEST RESULTS


The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (1): The band edge emission plot on the following first page shows 60.63dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 103.8dBuV/m, so the maximum field strength in restrict band is $103.8-60.63=43.17$ dBuV/m which is under 54 dBuV/m limit.

NOTE (2): The band edge emission plot on the following second page shows 60.85dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2. is 103.9dBuV/m, so the maximum field strength in restrict band is $103.9-60.85=43.05$ dBuV/m which is under 54 dBuV/m limit.







4.5 ANTENNA REQUIREMENT

4.5.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.5.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Detachable Dipole Antenna with MMCX connector. The maximum Gain of the antenna is 0.66dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.