

10 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: M5LROX20**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

- >> The fundamental frequency of the EUT is 2457MHz, the test separation distance is ≤ 50 mm. (Manufacturer specified the separation distance is: 5mm) (5mm is the worst case according to the KDB)

Step b)

- >> Numeric threshold (2457MHz), $\text{mW} / 5\text{mm} \cdot \sqrt{2.457\text{GHz}} \leq 3.0$
 Numeric threshold (2457MHz) $\leq 9.569\text{mW}$

- >> The power (calculated power + tune up tolerance) of EUT at 2457MHz is: 0.18mW
 Which is smaller than the Numeric threshold.
 Therefore, the device is exempt from stand-alone SAR test requirements.


Power calculation (According to C63.10 chapter 9.5)

	Value	Unit
Field Strength Measured (E)	87.67	dB μ V/m
Measurement Distance (D)	3	m
Equivalent Isotropically Radiated Power (E.I.R.P in dBm)	-7.49	dBm
Equivalent Isotropically Radiated Power (E.I.R.P in mW)	0.18	mW

Remark: $\text{EIRP} = E + 20\log(D) - 104.7$


(EIRP is in dBm, E is in dB μ V/m, D is in metres)

Reviewed by:



Eric LI
EMC Project Manager

Prepared by:

Hosea CHAN
EMC Project Engineer