

## 10 Appendix A - General Product Information

### Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: M5LROX20**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances  $\leq 50$  mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

- >> The fundamental frequency of the EUT is 2402-2480MHz, the test separation distance is  $\leq 50$ mm.  
(Manufacturer specified the separation distance is: 5mm)  
(5mm is the worst case according to the KDB)

Step b)

- >> Numeric threshold (2402MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.402\text{GHz}} \leq 3.0$   
Numeric threshold (2402MHz)  $\leq 9.678\text{mW}$

- >> Numeric threshold (2440MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.440\text{GHz}} \leq 3.0$   
Numeric threshold (2440MHz)  $\leq 9.602\text{mW}$

- >> Numeric threshold (2480MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.480\text{GHz}} \leq 3.0$   
Numeric threshold (2480MHz)  $\leq 9.525\text{mW}$

- >> The power (measured + tune up tolerance) of EUT at 2402MHz is: 3.83dBm = 2.42mW  
The power (measured + tune up tolerance) of EUT at 2440MHz is: 3.54dBm = 2.26mW  
The power (measured + tune up tolerance) of EUT at 2480MHz is: 3.00dBm = 2.00mW

Which is smaller than the Numeric threshold.


Therefore, the device is exempt from stand-alone SAR test requirements.

Reviewed by:



Eric LI  
EMC Project Manager

Prepared by:

Hosea CHAN  
EMC Project Engineer