

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

## **Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product  
Product description: Digital Handheld Transmitter  
Model No: ACT-580H

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product : Digital Handheld Transmitter will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M22103-20783-C-54 and the accompanying calculations.

Company: MIPRO Electronics Co., Ltd.  
Address: 814 Beigang Rd., Chiayi City 600079 Taiwan, R.O.C

Date: 2021-05-31

MIPRO ELECTRONICS CO.,LTD.





Registration number: W6M22103-20783-C-54  
FCC ID: M5X-ACT580H

**3.6 Automatic Discontinuation of transmission, FCC 15.407 (c)**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure.

This function will be declared by manufacturer.

**3.7 Reserved, FCC 15.407 (d)**

**3.8 Indoor Operation Restriction, FCC 15.407 (e)**

Within the 5.15–5.25 GHz band, U- NII devices will be restricted to indoor operations to reduce any potential for harmful interference to co-channel MSS operations. This equipment has to be declared by manufacturer of the final product as content of the user manual.

**3.9 Equivalent Isotropic Radiated Power (EIRP), FCC 15.407 (f)**

EIRP = max. conducted output power + antenna gain

EIRP = 6.51 dBm + 0 dBi [antenna gain claimed by manufacturer] = 6.51 dBm = 4.48 mW

Test equipment used: ETSTW-RE 055



Registration number: W6M22103-20783-C-54  
 FCC ID: M5X-ACT580H

**3.10 Exemption Limits for Routine Evaluation according to FCC KDB Publication**

**RESULT:**

Test standard : FCC KDB Publication  
 447498 D01 General RF Exposure Guidance v06

According to 447498 D01 General RF Exposure Guidance v06:  
 SAR evaluation, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

**3.10.1 Exemption Limits for Routine Evaluation – SAR Evaluation**

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table .

Table: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance

MHz	5	10	15	20	25	mm
5787	6	12.03	19	25.03	31.03	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
5787	37.03	44.03	50.07	56.07	62.10	SAR Test Exclusion Threshold (mW)

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.

Established separation distance is 5 mm.

BLE

Operating frequency band : 5735-5839 MHz

Max. output power level at 5 mm separation distance at 5787 MHz according to table is: 6 mW

The product is exempt from SAR Evaluation/Testing because the output power of 4.48 mW is below the exemption limit of 6 mW.