



ETS Dr.GenZ Taiwan PS Co., LTD.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

A2LA Cert.No.: 2300.01

PTCRB Accredited Type Certification Test House

FCC TEST - REPORT

FCC RULES PARTS 74 Subpart H, Section 74.861

Test report no.:W6M20611-7597-C-1

FCC ID: M5X-ACT8H

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	NOTES.....	3
1.2	TESTING LABORATORY	4
1.2.1	<i>Location</i>	4
1.2.2	<i>Details of accreditation status</i>	4
1.3	DETAILS OF APPROVAL HOLDER.....	4
1.4	APPLICATION DETAILS	5
1.5	GENERAL INFORMATION OF TEST ITEM	5
1.6	TEST STANDARDS.....	6
2	TECHNICAL TEST	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST	7
2.4	GENERAL TEST PROCEDURE	7
3	TEST RESULTS (ENCLOSURE)	10
4	RF POWER OUTPUT (CONDUCTED) , FCC 2.1046 (A) ; 74.861 (E).....	11
4.1	TEST PROCEDURE.....	11
4.2	TEST RESULTS	11
5	RADIATED POWER	12
5.1	TEST PROCEDURE	12
5.2	TEST RESULTS	13
6	MODULATION DEVIATION , FCC 2.1047 (B) ; 74.861(E).....	14
6.1	TEST PROCEDURE.....	14
6.2	TEST RESULTS	14
7	AUDIO FREQUENCY RESPONSE , FCC 2.1047 (A).....	15
7.1	TEST PROCEDURE.....	15
7.2	TEST RESULTS	15
8	OCCUPIED BANDWIDTH/EMISSION MASK, FCC 2.1049 (C) ; 74.861 (E)(5)	16
8.1	TEST PROCEDURE.....	16
8.2	TEST RESULTS	16
9	SPURIOUS EMISSIONS AT ANTENNA TERMINALS FCC2.1051 ; 74.861 (E).....	17
9.1	TEST PROCEDURE.....	17
9.2	TEST RESULTS	17
9.3	LIMIT	17

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

- 10 RADIATED SPURIOUS EMISSION , FCC 2.1053 ; 74.861 (E) 18**
 - 10.1 TEST PROCEDURE..... 18
 - 10.2 TEST RESULTS 18
 - 10.3 EXPLANATION OF TEST RESULT..... 18
 - 10.4 LIMITS 20

- 11 LINE CONDUCTED EMISSION , FCC 15.207..... 21**
 - 11.1 TEST PROCEDURE..... 21
 - 11.2 TEST RESULTS 21

- 12 FREQUENCY STABILITY VS. TEMPERATURE , FCC 2.1055 , 74.861 (E)..... 22**
 - 12.1 TEST PROCEDURE..... 22
 - 12.2 TEST RESULTS 22

- 13 FREQUENCY STABILITY VS. VOLTAGE , FCC 2.1055 (D) ; 74.861 (E)..... 24**
 - 13.1 TEST PROCEDURE..... 24
 - 13.2 TEST RESULTS 24

- APPENDIX..... 25**
 - APPENDIX A..... 26
 - APPENDIX B 27
 - APPENDIX C 28
 - APPENDIX D..... 29
 - APPENDIX E 30
 - APPENDIX F 31
 - APPENDIX G..... 32
 - APPENDIX H..... 33
 - APPENDIX I 34

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Tester:

January 04, 2007

Jay Chaing



Date

ETS-Lab.


Name

Signature

Technical responsibility for area of testing:

January 04, 2007

Steven Chuang



Date

ETS

Name

Signature

Registration number: W6M20611-7597-C-1

FCC ID: M5X-ACT8H

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company

ETS DR. GENZ TAIWAN PS CO., LTD.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

PTCRB Accredited Type Certification Test House

1.3 Details of approval holder

Name : MIPRO Electronics Co., Ltd.

Street : 814 Pei-kang Road

Town : Chia-yi, 600

Country : Taiwan, R.O.C.

Telephone : +886-5-238-0809

Fax : +886-5-238-0803

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

1.4 Application details

Date of receipt of application : November 27, 2006
 Date of receipt of test sample : November 30, 2006
 Date of test : From December 01, 2006 to January 3, 2007

1.5 General information of Test item

Type of test item : TRANSMITTER
 Model Number : ACT-8H
 Brand Name : MIPRO
 Serial number : without
 Photos : see Annex

Technical data

Frequency band :

Frequency(MHz)	TV Band	Used Band
26.100-26.480	<input type="checkbox"/>	<input type="checkbox"/>
54.000-72.000	<input checked="" type="checkbox"/>	<input type="checkbox"/>
76.000-88.000	<input checked="" type="checkbox"/>	<input type="checkbox"/>
161.625-161.775	<input type="checkbox"/>	<input type="checkbox"/>
174.000-216.000	<input checked="" type="checkbox"/>	<input type="checkbox"/>
450.000-451.000	<input type="checkbox"/>	<input type="checkbox"/>
455.000-456.000	<input type="checkbox"/>	<input type="checkbox"/>
470.000-488.000	<input type="checkbox"/>	<input type="checkbox"/>
488.000-494.000	<input checked="" type="checkbox"/>	<input type="checkbox"/>
494.000-608.000	<input checked="" type="checkbox"/>	<input type="checkbox"/>
614.000-806.000	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
944.000-952.000	<input type="checkbox"/>	<input type="checkbox"/>

Frequency (ch A) : 615MHz
 Frequency (ch B) : 711MHz
 Frequency (ch C) : 805MHz

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Antenna Type : helical antenna
Antenna Gain : 2.4 dBi
Power supply : 6~8.4 VDC
Operation modes : Simplex

Manufacturer:
(if applicable)

Name : ./.
Street : ./.
Town : ./.
Country : ./.

1.6 Test standards

Technical standard : FCC Part 74 Subpart H , section 74.861
Additional information : none

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature : 23 °C
Relative humidity content : 20 ... 75 %
Air pressure : 86-103 KPa

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2006/10/16	2007/10/15
ETSTW-CE 002	PREREGULATOR MODE DC POWER SUPPLY	None	None		Function Test	
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2006/10/16	2007/10/15
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2006/10/16	2007/10/15
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	In House Certificate	
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS-MESSWANDLER-ZANGE	2005/10/24	2007/10/23
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2006/8/17	2007/8/16
ETSTW-CE 012	Dual-Phase-V-Network	NNB-2/16Z	03/10201	Telemeter	2006/6/13	2007/6/12
ETSTW-CE 013	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T4-02	20242	FCC	2005/12/8	2007/12/7
ETSTW-CE 014	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T2-02	20241	FCC	2005/12/7	2007/12/6
ETSTW-CE 015	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T8-02	20307	FCC	2006/11/7	2008/11/6
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2006/11/21	2007/11/20
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/10/14	2007/10/13
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2006/10/20	2007/10/19
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2006/10/30	2007/10/29
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2006/10/12	2007/10/11
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH	Function Test	
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	Function Test	
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	2006/5/4	2008/5/3
ETSTW-RE 018	ANTENNA	AT4560	27212	AR	2004/11/8	2007/11/7
ETSTW-RE 021	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	Function Test	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2006/10/11	2007/10/10
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	2004/6/30	2007/6/29
ETSTW-RE 028	Log-Periodic Dipole Array Antenna	3148	34429	EMCO	2006/5/26	2008/5/25
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2006/5/26	2008/5/25
ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	2006/5/3	2008/5/2

Registration number: W6M20611-7597-C-1

FCC ID: M5X-ACT8H

ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2006/10/11	2007/10/10
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14508	LeCroy	2006/7/27	2007/7/26
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/10/17	2007/10/16
ETSTW-RE 042	ANTENNA	HK116	100172	R&S	2005/1/14	2007/1/13
ETSTW-RE 043	ANTENNA	HL223	100166	R&S	2006/5/8	2008/5/7
ETSTW-RE 044	ANTENNA	HL050	100094	R&S	2006/5/29	2008/5/28
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2005/3/22	2008/3/21
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2005/5/19	2007/5/18
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2006/7/28	2007/7/27
ETSTW-GSM 18	AUDIO ANALYZER	UPL16	100173	R&S	2006/10/28	2007/10/27

Registration number: W6M20611-7597-C-1

FCC ID: M5X-ACT8H

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by at the registered open field test site located at The Registration Number: When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANTENNA & GROUND:

This unit uses helical antenna. (see photo).

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
RF Power Output	2.1046 (a); 74.861 (e)(1)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Modulation Deviation	2.1047 (b); 74.861 (e)(2)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Audio Frequency Response	2.1047 (a)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Occupied Bandwidth / Emission Mask	2.1049 (c)(1); 74.861 (e)(5)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions at Antenna Terminals	2.1051 74.861(e)(6)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Spurious Emission	2.1053 74.861(e)(6)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Line Conducted Emissions	15.207	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Frequency Stability vs. Temperature	2.1055 (b); 74.861(e)(4)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency Stability vs. Voltage	2.1055 (a)(1); 74.861 (e)(4)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

4 RF Power Output (conducted) , FCC 2.1046 (a) ; 74.861 (e)

4.1 Test procedure

This transmitter output was connected to a calibrated coaxial attenuator, the other end of which was connected to a spectrum analyzer. Transmitter output was derived with the spectrum analyzer in dBm. The power output at the transmitter antenna port was determined by assign the value of the attenuator to the spectrum analyzer reading.

An HP power meter was also used to measure the RF power.

Tests were performed with an unmodulated carrier at three frequencies (low , middle and high channels) and on all power levels , which can be set-up on the transmitters.

4.2 Test Results

Frequency Channel	Peak Output Power (dBm)
615 MHz	--
711 MHz	--
805 MHz	--

Limits:

LPAS operating in TV bands	
Frequency [MHz]	Conducted output power [mW]
54 – 72 76 – 88 174 - 216	50 (17 dBm)
470 – 608 614 - 806	250 (24 dBm)

LPAS operating in other than TV bands	
Conducted power [W]	1

Comment :This test is not required.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

5 Radiated Power

5.1 Test Procedure

The EUT was positioned on a non-conductive turntable, 0.8m above the ground on an open test site. The radiated emission at the fundamental frequency was measured at 3m distance with a test antenna and spectrum analyzer.


Worst case emission was recorded with the rotation of the turntable and the raising and lowering of the test antenna.

Substitution RF power Measurement at ETS Taiwan

General :

The applied substitution method follows ANSI/TIA/EIA-603, ANSI/TIA/EIA-102.CAAA or the appropriate ETSI rules respectively.

The actual signal generated by the EUT can be determined by means of a substitution measurement in which a known signal source replaces the device to be measured.



- 1) Signal generator ;
- 2) Substitution antenna ;
- 3) Test antenna ;
- 4) Spectrum analyzer or selective voltmeter.

The substitution antenna replaces the transmitter antenna at the same position and in vertical polarization. The frequency of the signal generator shall be adjusted to the measurement frequency.

The test antenna shall be raised or lowered, if necessary, to ensure that the maximum signal is still received. The input signal to the substitution antenna shall be adjusted in level until an equal or a known related level to that detected from the transmitter is obtained in the measurement receiver.

If a fully anechoic chamber is used as test site in order to provide free space conditions there is no need to change the height of the antenna.

The measurement will be repeated in horizontal position.

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

Calibration :

In order to make this kind of measurement more effective and to avoid subjective measurement faults ETS has installed automatic computer controlled measurement procedures.

With the above described substitution method a test site is calibrated over the full frequency range which is used in suitable frequency steps. For a certain power level on the substitution antenna the received power over the whole frequency range is documented. All necessary antenna gains, cable losses, filter losses and amplifications of preamplifiers are taken in consideration. The summary of this calibration measurement performs a transducer factor that is related to the considered test site and a certain measurement distance. Differences of the radiated power levels of different test samples are determined by internal attenuation of measurement receiver . The proper function of such test site will be maintained by short term plausibility checks and periodical re-calibration.

Testing :

Now the test sample will be putted on the table at the defined position and the radiated power will be receiver and documented by the measurement receiver.

On test sites with ground plane the measurement antenna will be lowered and raised to maximum values at significant frequencies.

For peak power measurements the sample is turned by the turntable over 360 degree in order to find the direction with the maximum radiation or to document the max reading with the MAXHOLD function during the rotation.

5.2 Test results

Radiated Power (dBm)	
615 MHz	14.58
711 MHz	7.16
805 MHz	10.36

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 021
 ETSTW-RE 028 ETSTW-RE 029 ETSTW-RE 030 ETSTW-RE 042
 ETSTW-RE 043 ETSTW-RE 044

Comment: Please see attached diagram as appendix .

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H


6 Modulation Deviation , FCC 2.1047 (b) ; 74.861(e)

6.1 Test procedure

Modulation limiting is the transmitter circuit’s ability to limit the transmitter from producing deviations in excess of rated system deviation.

The audio signal generator is connected to the audio input of the EUT with its full rating.

The modulation response is measured at certain modulation frequencies, related to 1000Hz reference signal. Tests are performed for positive and negative modulation.



6.2 Test results

Limits : ± 75 kHz

Comment : This test is not applicable because this device is digital modulation.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-GSM 18

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

7 Audio frequency response , FCC 2.1047 (a)

7.1 Test procedure


The audio frequency response is the degree of closeness to which the frequency deviation of the transmitter follows a prescribed characteristic.

The frequency response of the audio modulation part is measured over a frequency range of 100 Hz to 5000Hz.

For 1000Hz tone reference signal the audio generator level is adjusted to get 20% of the rated system deviation.

The deviations obtained over the frequency range from 100Hz to 5000Hz are recorded and compared with the reference deviation as follows :

$$\text{Audio Frequency Response} = 20 \log [\text{DEV}_{\text{Freq}} / \text{DEV}_{\text{ref}}].$$



7.2 Test results

Comment : This test is not applicable because this device is digital modulation.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-GSM 18

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

8 Occupied Bandwidth/Emission Mask, FCC 2.1049 (c) ; 74.861 (e)(5)

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power. Near the carrier an Emission Mask is defined by the standard.

8.1 Test procedure

The RF output of the transceiver was connected to the input of the spectrum analyzer through sufficient attenuation.

Occupied Bandwidth was measured with a occupied bandwidth function of the analyzer. The near the carrier emissions are measured by normal power measurement function of the analyzer.

8.2 Test Results

1000 Hz Modulation

Occupied Channel Bandwidth (kHz)	
Channel A	--
Channel B	--
Channel C	--

2500 Hz Modulation

Occupied Channel Bandwidth (kHz)	
Channel A	--
Channel B	--
Channel C	--

Comment : This test is not applicable because this device is digital modulation.

99% Occupied Channel Bandwidth

99% Occupied Channel Bandwidth (kHz)	
Channel A	165.064
Channel B	165.064
Channel C	168.269

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055

Comment : Please see attached diagram as appendix .

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

9 Spurious Emissions at Antenna Terminals FCC2.1051 ; 74.861 (e)

9.1 Test procedure

This transmitter output was connected to a calibrated coaxial attenuator, the other end of which was connected to a spectrum analyzer. Transmitter output was derived with the spectrum analyzer in dBm.

The Spurious Emissions at Antenna Terminals was measured by the spectrum analyzer with a suitable notch filter and high-pass filter.

Tests were performed with an unmodulated carrier at three frequencies (low , middle and high channels) and on all power levels , which can be set-up on the transmitters.

9.2 Test Results

Summary table with conducted data of the test plots for Carrier Test Frequency

Frequency Marker Indication [MHz]	Indication Power Level [dBm]	Compliance Limit [dBm]	Margin
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

9.3 Limit

Compliance with § 74.861 requires that any emission be attenuated below the transmitter power at least $43 + 10 \log_{10} P$ (P = transmitter power in Watts).

The compliance limit was calculated as an example per the following table :

Maximum transmitter output power	-- dBm
Required attenuation	$43 + 10 \log_{10} \text{--}W = \text{--} \text{dB}$
Maximum transmitter output power	-- dBm
<u>Required attenuation</u>	<u>-- dB</u>
Compliance limit	-13 dBm

Comment : This test is not applicable.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055

Registration number: W6M20611-7597-C-1

FCC ID: M5X-ACT8H

10 Radiated Spurious Emission , FCC 2.1053 ; 74.861 (e)

10.1 Test procedure

The EUT was positioned on a non-conductive turntable , 0.8m above the ground plane.

The radiated emission at the fundamental frequency was measured at 3 m distance with a test antenna and spectrum analyzer.

Worst case emission was recorded with the rotation of the turntable and the raising and lowering of the test antenna.

ERP was measured using a substitution method. The EUT was replaced by reference antenna connected to a signal generator.

The test of spurious radiated emission have been carried out with the ESK-Software from Rode & Schwarz. The measurements below 1GHz were performed with a measurement bandwidth of 100kHz, above 1GHz with a bandwidth of 1 MHz.

Spurious emission limits near the carrier are defined by a emission mask. This measurements are done in conducted mode.

10.2 Test Results

The measurements of the spurious emission at the upper , center and lower channel.

The measurement diagrams show that all significant spurs are well below the limit line.

Summary table with radiated data of the test plots for Carrier Test Frequency

615 MHz

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
H	436.7820	-89.79	26.37	PK	-63.42	-13.0	50.42	246
	712.5330	-95.33	31.08	PK	-64.25	-13.0	51.25	289
	1229.7462	-53.79	1.48	PK	-52.31	-13.0	39.31	193
	1843.5722	-59.54	5.21	PK	-54.33	-13.0	41.33	317

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
V	1229.7462	-49.53	1.06	PK	-48.47	-13.0	35.47	190
	1843.5722	-57.83	2.45	PK	-55.38	-13.0	42.38	326

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

711 MHz

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
H	355.1627	-89.15	29.12	PK	-60.03	-13.0	47.03	189
	642.7430	-101.84	31.92	PK	-69.92	-13.0	56.92	274
	949.7690	-97.15	33.39	PK	-63.76	-13.0	50.76	301

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
V	524.7370	-90.67	29.64	PK	-61.03	-13.0	48.03	286
	949.7690	-97.86	31.99	PK	-65.87	-13.0	52.87	297
	3550.1627	-61.87	12.14	PK	-49.73	-13.0	36.73	191

805 MHz

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
H	948.4890	-99.91	33.39	PK	-66.52	-13.0	53.52	321
	1608.2913	-46.88	5.67	PK	-41.21	-13.0	28.21	225
	2416.5612	-54.35	5.72	PK	-48.63	-13.0	35.63	165

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBm)	Correction Factor (dB)	Detector	Test Result (dBm)	Compliance Limit (dBm)	Margin (dB)	Table Azimuth (degree)
V	948.4890	-100.31	32.00	PK	-68.31	-13.0	55.31	318
	1608.2913	-40.81	1.64	PK	-39.17	-13.0	26.17	231
	2416.5612	-45.09	4.83	PK	-40.26	-13.0	27.26	172

- Note:**
1. Correction Factor = Antenna Gain + Cable Loss + Amplifier Gain
 2. The formula of measured value as: Test Result = Corrected Reading + Correction Factor
 3. Detector function in the form : P = Peak, AV = Average

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

10.3 Explanation of test result

The measurements of the spurious emissions at the equipment output terminals were performed pursuant to the test procedure above in order to verify that any emissions are below the limits given by § 74.861 (6).

Calculation of test results :

Such factors like antenna correction , cable loss , external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

10.4 Limits

Compliance with § 74.861 requires that any emission be attenuated below the transmitter power at least $43 + 10 \log_{10} P$ (P = transmitter power in Watts).

The compliance limit was calculated as an example per the following table :

Maximum transmitter output power	14.58 dBm
Required attenuation	$43 + 10 \log_{10} 0.0287W = 27.58 \text{ dB}$
Maximum transmitter output power	14.58 dBm
<u>Required attenuation</u>	<u>27.58 dB</u>
Compliance limit	-13 dBm

Comment : see attached diagrams in appendix.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 021
 ETSTW-RE 028 ETSTW-RE 029 ETSTW-RE 030 ETSTW-RE 042
 ETSTW-RE 043 ETSTW-RE 044

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

11 Line Conducted Emission , FCC 15.207

11.1 Test procedure

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

11.2 Test Results

Frequency	Max. Level (dB μ V)	
	quasi-peak	average
-- kHz	--	--

Limits:

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- Note: 1. The formula of measured value as: Test Result = Corrected Reading + Correction Factor**
- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss**
- 3. Detector function in the form : P = Peak, QP = Quasi Peak, AV = Average**

Comment : This is not required the sample is battery used.

Test equipment used: ETSTW-CE 001 ETSTW-CE 003 ETSTW-CE 004 ETSTW-CE 006

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

12 Frequency Stability vs. Temperature , FCC 2.1055 , 74.861 (e)

12.1 Test procedure

The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable, exited the chamber through an opening made for that purpose.

After the temperature stabilized the frequency output was recorded from the counter.

12.2 Test Results

615 MHz

°C	Frequency Error (kHz)	Frequency Error (ppm)
-30	-4.8	7.80
-20	-3.6	5.85
-10	-2.7	4.39
0	-1.3	2.11
10	0.2	0.33
20	1.1	1.79
30	2.4	3.9
40	3.2	5.2
50	3.9	6.3

25°C: 615.0013

Limit: 30.75KHz(±0.005%)

711 MHz

°C	Frequency Error (kHz)	Frequency Error (ppm)
°C	-8.9	12.52
-30	-7.6	10.69
-20	-6.1	8.58
-10	-4.9	6.89
0	-2.8	3.94
10	-0.7	0.98
20	1.3	1.83
30	2.7	3.79
40	3.6	5.06

25°C: 711.0012

Limit: 35.55KHz(±0.005%)

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

805 MHz

°C	Frequency Error (kHz)	Frequency Error (ppm)
-30	-4.6	5.71
-20	-3.3	4.09
-10	-2.5	3.11
0	-1.2	1.49
10	-0.3	0.37
20	0.8	1.13
30	1.2	1.49
40	2.7	3.35
50	3.9	4.84

25°C: 805.0016

Limit: 40.25KHz(±0.005%)

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-CE 009

Registration number: W6M20611-7597-C-1
 FCC ID: M5X-ACT8H

13 Frequency Stability vs. Voltage , FCC 2.1055 (d) ; 74.861 (e)

13.1 Test procedure

An external variable DC power supply was connected to the battery terminals of the equipment under test.

For hand carried , battery powered equipment primary supply voltage was reduced to the battery operating end point as specified by the manufacturer. The output frequency was recorded for each battery voltage.

13.2 Test Results

Frequency in MHz	Frequency Error (kHz)	Frequency Error (ppm)
615.0073	6	9.75
711.0066	5.4	7.59
805.0079	6.3	7.82

Limit : ±0.005%

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-CE 009

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix

- A RF Power Output
- B Audio frequency response
- C Occupied Bandwidth / Emission Mask
- D Spurious Emissions at Antenna Terminals
- E Radiation Spurious Emission
- F Line Conducted Emissions
- G Frequency Stability vs. Temperature
- H Frequency Stability vs. Voltage
- I Pictures


Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix A

RF Power Output


**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:614.960MHz Pmax:4.14dBm RBW: 100 kHz




**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:615.000MHz Pmax:14.58dBm RBW: 100 kHz




**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:710.990MHz Pmax:-0.14dBm RBW: 100 kHz




**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:710.958MHz Pmax:7.16dBm RBW: 100 kHz




**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:804.990MHz Pmax:2.35dBm RBW: 100 kHz



**Transmitter carrier power under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223
Freq:804.972MHz Pmax:10.36dBm RBW: 100 kHz



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix B

Audio frequency response

This test is not applicable, the EUT is digital modulation.

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix C

Occupied Bandwidth / Emission Mask




*RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz -22.40 dBm
*SWT 100 ms 614.985576923 MHz

Ref 0 dBm

Att 5 dB

1 PK
MAXH



Center 615 MHz

100 kHz/

Span 1 MHz

Occupied bandwidth

Date: 5.DEC.2006 14:38:12




*RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz -17.85 dBm
*SWT 100 ms 710.979166667 MHz

Ref 0 dBm

Att 5 dB

1 PK
MAXH



Center 711 MHz

100 kHz/

Span 1 MHz

Occupied bandwidth

Date: 5.DEC.2006 14:37:00




*RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz -20.40 dBm
*SWT 100 ms 804.990384615 MHz

Ref 0 dBm

Att 5 dB

1 PK
MAXH



Center 805 MHz

100 kHz/

Span 1 MHz


Occupied bandwidth

Date: 5.DEC.2006 14:40:20



*RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz -1.40 dBm
SWT 2 s 615.00000000 MHz

Ref 17.9 dBm Att 20 dB




Mask

Date: 28.DEC.2006 12:05:14



Ref 18.9 dBm *Att 20 dB *RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz 5.30 dBm
*SWT 2 s 711.00000000 MHz




Occupied bandwidth

Date: 14.DEC.2006 08:26:47



Ref 17.9 dBm *Att 20 dB *RBW 10 kHz Marker 1 [T1]
*VBW 10 kHz 9.45 dBm
*SWT 2 s 805.003205128 MHz



Occupied bandwidth

Date: 14.DEC.2006 08:34:03

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix D

Spurious Emissions at Antenna Terminals

This test is not applicable

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H


Appendix E

Radiation Spurious Emission

The measurement diagrams plots attached below are preliminary wideband scan with a peak detector for reference only. The final test results are listed on section 10


**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:197.896MHz Pmax:-57.37dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:182.114MHz Pmax:-56.50dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:435.671MHz Pmax:-64.31dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:554.309MHz Pmax:-57.33dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:3.976GHz Pmax:-48.27dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:1.228GHz Pmax:-49.58dBm RBW: 1 MHz




Spurious emissions under normal conditions
in according to FCC Part 74.861

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.527GHz Pmax:-43.45dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 615MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.567GHz Pmax:-43.32dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:196.844MHz Pmax:-57.46dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:193.337MHz Pmax:-57.55dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:948.697MHz Pmax:-64.57dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:523.848MHz Pmax:-62.30dBm RBW: 100 kHz




Spurious emissions under normal conditions
in according to FCC Part 74.861

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:3.922GHz Pmax:-49.04dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:3.549GHz Pmax:-50.37dBm RBW: 1 MHz




Spurious emissions under normal conditions
in according to FCC Part 74.861

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.471GHz Pmax:-42.86dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 711MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.503GHz Pmax:-42.53dBm RBW: 1 MHz




Spurious emissions under normal conditions
in according to FCC Part 74.861

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:191.232MHz Pmax:-58.08dBm RBW: 100 kHz



**Spurious emissions under normal conditions
in according to FCC Part 74.861**


Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:200.000MHz Pmax:-57.47dBm RBW: 100 kHz



Spurious emissions under normal conditions


in according to FCC Part 74.861

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:947.094MHz Pmax:-67.25dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.: 0.1-1GHz
Freq:555.912MHz Pmax:-61.67dBm RBW: 100 kHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:1.607GHz Pmax:-42.94dBm RBW: 1 MHz




Spurious emissions under normal conditions
in according to FCC Part 74.861

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.: 1-4GHz
Freq:1.607GHz Pmax:-40.71dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.463GHz Pmax:-42.69dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 4-8GHz
Freq:7.495GHz Pmax:-43.61dBm RBW: 1 MHz




**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 8-18GHz
Freq:12.148GHz Pmax:-36.37dBm RBW: 1 MHz



**Spurious emissions under normal conditions
in according to FCC Part 74.861**

Order Number : W6M20611-7597 805MHz
Test Site / Operator: ETS / Michael
Temperature:: Temp.: 23.9°C
74.861
Comment 1: Dist.: 1m, Ant.: HL 025, ampl.: 8-18GHz
Freq:12.198GHz Pmax:-35.79dBm RBW: 1 MHz



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix F

Line Conducted Emissions

This is not required the sample is battery used.

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix G

Frequency Stability vs. Temperature

No diagrams
Refer to point 12.2

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix H

Frequency Stability vs. Voltage

No diagrams
Refer to point 13.2

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Appendix I

Pictures

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

External Photos

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Internal Photos

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H




Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H



Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

Setup Photos

Registration number: W6M20611-7597-C-1
FCC ID: M5X-ACT8H

