

**FCC Part 15.236 Test Report**  
**for**  
**Wireless Digital Stereo Transmitter**  
**Model No.: MI-909T**  
**FCC ID: M5X-MI909T18**

of

Applicant: **MIPRO Electronics Co., Ltd.**  
Address: **814 Pei-kang Road Chia-yi 600 Taiwan, R.O.C**

Tested and Prepared

by

**Worldwide Testing Services (Taiwan) Co., Ltd.**

**FCC Registration No.: TW1477, TW1111, TW1072, TW1110**


**Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1**

**A2LA Accredited No.: 2732.01**



**Report No.: W6M21801-17839-C-1**

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.  
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: [wts@wts-lab.com](mailto:wts@wts-lab.com)



## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL INFORMATION.....</b>	<b>2</b>
1.1	NOTES.....	2
1.2	TESTING LABORATORY .....	3
1.2.1	Location .....	3
1.2.2	Details of accreditation status .....	3
1.3	DETAILS OF APPROVAL HOLDER.....	3
1.4	APPLICATION DETAILS .....	4
1.5	GENERAL INFORMATION OF TEST ITEM .....	4
1.6	TEST STANDARDS.....	4
<b>2</b>	<b>TECHNICAL TEST.....</b>	<b>5</b>
2.1	SUMMARY OF TEST RESULTS .....	5
2.2	TEST ENVIRONMENT .....	5
2.3	TEST EQUIPMENT LIST .....	6
2.4	GENERAL TEST PROCEDURE .....	9
<b>3</b>	<b>TEST RESULTS (ENCLOSURE) .....</b>	<b>10</b>
<b>4</b>	<b>RF POWER OUTPUT, FCC15.236 (D) .....</b>	<b>11</b>
4.1	TEST PROCEDURE.....	11
4.2	TEST RESULTS .....	12
<b>5</b>	<b>OCCUPIED BANDWIDTH, FCC15.236 (F) //EMISSION MASK, FCC15.236 (G)..</b>	<b>18</b>
5.1	TEST PROCEDURE .....	18
5.2	TEST RESULTS.....	18
<b>6</b>	<b>RADIATED SPURIOUS EMISSION , FCC 15.236(G).....</b>	<b>23</b>
6.1	TEST PROCEDURE.....	23
6.2	TEST RESULTS.....	23
<b>7</b>	<b>FREQUENCY STABILITY, FCC 15.236(F)(3) .....</b>	<b>24</b>
7.1	TEST PROCEDURE.....	24
7.2	TEST RESULTS.....	24
<b>8</b>	<b>LINE CONDUCTED EMISSION , FCC 15.207.....</b>	<b>26</b>
8.1	TEST PROCEDURE.....	26
8.2	TEST RESULTS .....	26



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18

## 1 General Information

### 1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.


Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services (Taiwan) Co., Ltd.

### Tester:

March 20, 2018	Kent Lin	
----------------	----------	--

Date	WTS-Lab.	Name	Signature
------	----------	------	-----------

### Technical responsibility for area of testing:

March 20, 2018	Kevin Wang	
----------------	------------	--

Date	WTS	Name	Signature
------	-----	------	-----------



# **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

## **1.2 Testing laboratory**

### **1.2.1 Location**

OATS

No.5-1, Lishui, Shuang Sing Village,

Wanli Dist., New Taipei City 207,

Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

### **1.2.2 Details of accreditation status**

**Accredited testing laboratory**

**A2LA accredited number: 2732.01**

**FCC filed test laboratory Reg. No. TW1477, TW1111, TW1072, TW1110**

**Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1**

**Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :**

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.

Country: ./.

Telephone: ./.

Fax: ./.

## **1.3 Details of approval holder**

Name: MIPRO Electronics Co., Ltd.

Street: 814 Pei-kang Road

Town: Chia-yi 600

Country: Taiwan, R.O.C

Telephone: +886-5-238-0809

Fax: +886-5-238-0803



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18

## 1.4 Application details

Date of receipt of test sample: February 09, 2018  
Date of test: from February 12, 2018 to March 20, 2018

## 1.5 General information of Test item

Type of test item: Wireless Digital Stereo Transmitter  
Model Number: MI-909T  
Brand Name: MIPRO  
Multi-listing model number: MI-XXXXXX(X=0~9,A~Z,a~z or Blank)  
Photos: see Annex

### Technical data

Frequency band : 470-608 MHz  
Frequency ( ch A): 470.1 MHz  
Frequency ( ch B): 538.8 MHz  
Frequency ( ch C): 607.925 MHz  
Antenna Type:  $1/2 \lambda$  Dipole Antenna  
Antenna Gain: 2.4 dBi  
Power supply: Adaptor (I/P:100-240 V~, 1.0A MAX, 50-60 Hz  
O/P: 12 V, 2.0A)

Operation modes: Simplex

### Manufacturer: (if applicable)

Name: ./.  
Street: ./.  
Town: ./.  
Country: ./.

## 1.6 Test standards

Technical standard: FCC RULES PART 15 SUBPART C § 15.236 (2016-10)



Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**2 Technical test**

**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

**or**

The deviations as specified in 3 were ascertained in the course of the tests performed.


**2.2 Test environment**

Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Power supply: Adaptor (I/P: 100-240 V~, 1.0A MAX, 50-60 Hz  
O/P: 12 V, 2.0A)

Air pressure: 86-103 KPa




Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

## 2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2017/5/26	2018/5/25
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2017/10/26	2018/10/25
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2017/8/22	2018/8/21
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2017/7/14	2018/7/13
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2017/8/31	2018/8/30
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2017/7/11	2018/7/10
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2017/5/26	2018/5/25
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2017/5/17	2018/5/16
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2017/8/25	2018/8/24
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2017/7/4	2018/7/3
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2017/7/3	2018/7/2
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2017/3/22	2018/3/21
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2018/1/23	2019/1/22
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2017/4/10	2018/4/9
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2017/4/27	2018/4/26
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2018/2/21	2019/2/20
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2018/3/1	2019/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2017/4/12	2018/4/11
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2017/9/11	2018/9/10
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2017/9/19	2018/9/18
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2017/4/6	2018/4/5



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18

ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2018/2/23	2019/2/22
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2018/1/15	2019/1/14
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2017/5/26	2018/5/25
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2017/8/9	2018/8/8
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2017/8/9	2018/8/8
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2018/2/21	2019/2/20
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2017/8/9	2018/8/8
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2017/8/9	2018/8/8
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2017/4/12	2018/4/11
ETSTW-RE 147	Bi-log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2017/3/22	2018/3/21
ETSTW-RE 151	Thermohyrometer	608-h1	45104376	TESTO	2017/8/30	2018/8/29
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2017/5/10	2018/5/9
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2018/2/27	2019/2/26
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2018/3/2	2019/3/1
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2017/10/16	2018/10/15
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2018/1/11	2019/1/10
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2018/1/11	2019/1/10
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2018/1/11	2019/1/10
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2018/1/11	2019/1/10
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2017/9/13	2018/9/12
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2017/7/3	2018/7/2
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2017/4/6	2018/4/5
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2018/2/21	2019/2/20
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2017/5/12	2018/5/11
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2017/9/7	2018/9/6
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2017/9/7	2018/9/6
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S Cable 9)	279067	HUBER+SUHNER	2018/2/21	2019/2/20





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S_Cable 10)	238092	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2018/2/21	2019/2/20
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2017/8/31	2018/8/30
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM- NM-25000	170239	EMCI	2018/2/21	2019/2/20
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18

## **2.4 General Test Procedure**

**POWER LINE CONDUCTED INTERFERENCE:** The procedure used was ANSI STANDARD C63.10-2013 6.2 using a 50 $\mu$ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

**RADIATION INTERFERENCE:** The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100 kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by at the registered open field test site located at The Registration Number: When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



# Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

## 3 Test results (enclosure)

Test case	Para. Number	Required	Test passed	Test failed
RF Power Output	§15.236(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Occupied Bandwidth	§15.236(f)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Emission Mask	§15.236(g) ETSI EN 300 422-1 v1.4.2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Spurious Emission	§15.236(g)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Line Conducted Emissions	15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency Stability vs. Temperature Frequency Stability vs. Voltage	§15.236(f)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The following is intentionally left blank.



Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**4 RF Power Output, FCC15.236 (d)**

**4.1 Test procedure**

§ 2.1046 Measurements required: RF power output.

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

(b) For single sideband, independent sideband, and single channel, controlled carrier radiotelephone transmitters the procedure specified in paragraph (a) of this section shall be employed and, in addition, the transmitter shall be modulated during the test as follows. In all tests, the input level of the modulating signal shall be such as to develop rated peak envelope power or carrier power, as appropriate, for the transmitter.

(1) Single sideband transmitters in the A3A or A3J emission modes - by two tones at frequencies of 400 Hz and 1800 Hz (for 3.0 kHz authorized bandwidth), or 500 Hz and 2100 Hz (3.5 kHz authorized bandwidth), or 500 Hz and 2400 Hz (for 4.0 kHz authorized bandwidth), applied simultaneously, the input levels of the tones so adjusted that the two principal frequency components of the radio frequency signal produced are equal in magnitude.

(2) Single sideband transmitters in the A3H emission mode - by one tone at a frequency of 1500 Hz (for 3.0 kHz authorized bandwidth), or 1700 Hz (for 3.5 kHz authorized bandwidth), or 1900 Hz (for 4.0 kHz authorized bandwidth), the level of which is adjusted to produce a radio frequency signal component equal in magnitude to the magnitude of the carrier in this mode.

(3) As an alternative to paragraphs (b) (1) and (2) of this section other tones besides those specified may be used as modulating frequencies, upon a sufficient showing of need. However, any tones so chosen must not be harmonically related, the third and fifth order intermodulation products which occur must fall within the -25 dB step of the emission bandwidth limitation curve, the seventh and ninth order intermodulation product must fall within the 35 dB step of the referenced curve and the eleventh and all higher order products must fall beyond the -35 dB step of the referenced curve.

(4) Independent sideband transmitters having two channels by 1700 Hz tones applied simultaneously in both channels, the input levels of the tones so adjusted that the two principal frequency components of the radio frequency signal produced are equal in magnitude.

(5) Independent sideband transmitters having more than two channels by an appropriate signal or signals applied to all channels simultaneously. The input signal or signals shall simulate the input signals specified by the manufacturer for normal operation.


(6) Single-channel controlled-carrier transmitters in the A3 emission mode - by a 2500 Hz tone.

(c) For measurements conducted pursuant to paragraphs (a) and (b) of this section, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. Under the test conditions specified, no components of the emission spectrum shall exceed the limits specified in the applicable rule parts as necessary for meeting occupied bandwidth or emission limitations.



Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18

## 4.2 Test Results



Site : Chamber  
 Condition : FCC 15.236 POWER  
 EUT : W6M21801-17839  
 M/N:  
 Test Mode : TX 470.1MHz  
 Note :

Polarization: *Horizontal*  
 Power : 120 Va.c.  
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	470.1555	-33.82	peak	33.03	-0.79	17.00	150	220	-17.79	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


### Radiated Emission Measurement

Operator: Kent  
 Temperature: 24 °C  
 Humidity: 60 %

File :4701  
 30.0 dBm

Data :#2

Date: 2018/3/9  
 Time: 下午 07:36:08



Site : Chamber

Condition : FCC 15.236 POWER

EUT : W6M21801-17839

M/N:

Test Mode : TX 470.1MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	470.1211	-17.51	peak	31.43	13.92	17.00	150	230	-3.08	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


### Radiated Emission Measurement

Operator: Kent  
 Temperature: 24 °C  
 Humidity: 60 %

File :5388  
 30.0 dBm

Data :#1

Date: 2018/3/9  
 Time: 下午 07:39:21



Site : Chamber

Condition : FCC 15.236 POWER

EUT : W6M21801-17839

M/N:

Test Mode : TX 538.8MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	538.8241	-21.41	peak	33.85	12.44	17.00	150	80	-4.56	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


### Radiated Emission Measurement

Operator: Kent  
 Temperature: 24 °C  
 Humidity: 60 %

File :5388  
 30.0 dBm

Data :#2

Date: 2018/3/9  
 Time: 下午 07:40:23



Site : Chamber

Condition : FCC 15.236 POWER

EUT : W6M21801-17839

M/N:

Test Mode : TX 538.8MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	538.7486	-19.32	peak	32.65	13.33	17.00	150	220	-3.67	





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


## Radiated Emission Measurement

Operator: Rick  
 Temperature: 24 °C  
 Humidity: 60 %

File :607925  
 20.0 dBm

Data :#1

Date: 2018/3/14  
 Time: 下午 05:31:35



Site : Chamber

Condition : FCC 15.236 POWER

EUT : W6M21801-17839

M/N:

Test Mode : TX 607.925MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	607.9737	-24.78	peak	35.50	10.72	17.00	150	100	-6.28	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


## Radiated Emission Measurement

Operator: Rick  
 Temperature: 24 °C  
 Humidity: 60 %

File :607925  
 20.0 dBm

Data :#2

Date: 2018/3/14  
 Time: 下午 05:29:45



Site : Chamber

Condition : FCC 15.236 POWER

EUT : W6M21801-17839

M/N:

Test Mode : TX 607.925MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	607.9778	-20.45	peak	32.54	12.09	17.00	150	250	-4.91	

Test equipment used: ETSTW-RE 004, ETSTW-RE 122, ETSTW-RE 042, ETSTW-RE 043

Limit According to FCC PART 15.236(d): The output power limit: 50 mW (17 dBm)



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18

## 5 Occupied Bandwidth, FCC15.236 (f) / Emission Mask, FCC15.236 (g)


### 5.1 Test Procedure

#### Occupied Bandwidth

- (f) The operating frequency within a permissible band of operation as defined in paragraph (c) must comply with the following requirements.
- (1) The frequency selection shall be offset from the upper or lower band limits by 25 kHz or an integral multiple thereof.
  - (2) One or more adjacent 25 kHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz. The operating bandwidth shall not exceed 200 kHz.
  - (3) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.005\%$  of the operating frequency over a temperature variation of - 20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. Battery (1) In the bands allocated and assigned for broadcast television and in the 600 MHz service band: 50 mW EIRP
  - (2) In the 600 MHz guard bands including the duplex gap: 20 mW EIRP (e) Operation is limited to locations separated from licensed services by the following distances. (1) Four kilometers outside the following protected service contours of co-channel TV stations. operated equipment shall be tested using a new battery.

### 5.2 Test results


#### Occupied Bandwidth




OCCUPIED BANDWIDTH 470.1MHZ  
Date: 9.MAR.2018 13:35:15



Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18



OCCUPIED BANDWIDTH 538.8MHZ  
 Date: 9.MAR.2018 13:34:30



OCCUPIED BANDWIDTH 607.925MHZ  
 Date: 9.MAR.2018 13:36:36

## Limit

The operating bandwidth shall not exceed 200 kHz.

Test equipment used: ETSTW-RE 055 , ETSTW-RE 072, ETSTW-RE 050


Measurement uncertainty = ±0.45 kHz



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18

## Emission Mask


(g) Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in Section 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08) (incorporated by reference, see § 15.38). Emissions outside this band shall comply with the limit specified at the edges of the ETSI mask.



NECESSARY BANDWIDTH 470.1MHZ  
Date: 8.MAR.2018 19:55:16




Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18



NECESSARY BANDWIDTH 538.8MHZ

Date: 8.MAR.2018 20:06:22



NECESSARY BANDWIDTH 607.925MHZ


Date: 8.MAR.2018 19:52:46

Test equipment used: ETSTW-RE 055 , ETSTW-RE 072

Measurement uncertainty =  $\pm 0.45$  kHz

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18


LIMIT acc. Subclause 8.3.1.2



**Figure 1: Spectrum mask for analogue systems in all bands**

LIMIT acc. Subclause 8.3.2.2

The transmitter output spectrum shall be within the mask defined in figure 2. This mask may also be used for both analogue and digital Assistive Listening Devices.



**Figure 2: Spectrum mask for digital systems below 1 GHz**



Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

## 6 Radiated Spurious Emission , FCC 15.236(g)

### 6.1 Test procedure

(g) Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in Section 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08) (incorporated by reference, see § 15.38). Emissions outside this band shall comply with the limit specified at the edges of the ETSI mask.

### 6.2 Test results

The measurements of the spurious emission at the upper , center and lower channel.  
The measurement diagrams show that all significant spurs are well below the limit line.

#### Summary table with radiated data of the test plots for Carrier Test Frequency

Model: MI-909T Date: --  
 Mode: -- Temperature: -- °C Engineer: --  
 Polarization: Horizontal Humidity: -- %

Frequency (MHz)	Reading (dBm) Peak	Factor (dB) Corr.	Result (dBm)	Limit (dBm)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--

Polarization: Vertical

Frequency (MHz)	Reading (dBm) Peak	Factor (dB) Corr.	Result (dBm)	Limit (dBm)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--

#### Note:

1. Correction Factor = Antenna Gain + Cable Loss + Amplifier Gain
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. All not in the table noted test results are more than 20 dB below the relevant limits.
4. Measurement uncertainty: 30-200MHz : ±2.32 dB, 200-1000MHz : ±2.3 dB, 1-18GHz : ±3.25 dB  
Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
5. See the attached diagram as appendix.

Test equipment used: ETSTW-RE 004, ETSTW-RE 122, ETSTW-RE 030, ETSTW-RE 042, ETSTW-RE 043, ETSTW-RE 044





Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**7 Frequency Stability, FCC 15.236(f)(3)**

**7.1 Test procedure**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.005\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. Battery operated equipment shall be tested using a new battery.

**7.2 Test results**

470.1MHz			
Test Temp	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
-20	470.102403	5.111678366	50
-10	470.102404	5.113805573	50
0	470.102404	5.113805573	50
10	470.101602	3.407785578	50
20	470.101602	3.407785578	50
30	470.100801	1.703892789	50
40	470.099198	-1.706019996	50
50	470.099198	-1.706019996	50

538.8MHz			
Test Temp	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
-20	538.803205	5.948403861	50
-10	538.803205	5.948403861	50
0	538.803205	5.948403861	50
10	538.801602	2.973273942	50
20	538.801602	2.973273942	50
30	538.801602	2.973273942	50
40	538.8008005	1.485708983	50
50	538.8008005	1.485708983	50

607.925MHz			
Test Temp	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
-20	607.922596	-3.954435169	50
-10	607.922596	-3.954435169	50
0	607.922596	-3.954435169	50
10	607.920993	-6.591273595	50
20	607.920993	-6.591273595	50
30	607.920993	-6.591273595	50
40	607.920993	-6.591273595	50
50	607.920993	-6.591273595	50

**Limit According to FCC 15.236(f)(3)**

Test equipment used: ETSTW-RE 055, ETSTW-CE 009



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18

## **Voltage**

470.1MHz			
Test Volt	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
102Va.c.	470.101602	3.407785578	50
120Va.c.	470.101602	3.407785578	50
138Va.c.	470.101602	3.407785578	50

538.8MHz			
Test Volt	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
102Va.c.	538.801602	2.973273942	50
120Va.c.	538.801602	2.973273942	50
138Va.c.	538.801602	2.973273942	50

607.925MHz			
Test Volt	Carrier Freq.(MHz)	Result(ppm)	limit(ppm)
102Va.c.	607.920993	-6.591273595	50
120Va.c.	607.920993	-6.591273595	50
138Va.c.	607.920993	-6.591273595	50

Limit :  $\pm 0.005\%$

### **Limit According to FCC 15.236(f)(3)**

**The frequency tolerance of the transmitter shall be 0.005 percent.**

Test equipment used: ETSTW-RE 055

Measurement uncertainty =  $\pm 6.09$  Hz



Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

## 8 Line Conducted Emission , FCC 15.207


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power. Near the carrier an Emission Mask is defined by the standard.

### 8.1 Test procedure

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

### 8.2 Test Results




File : AC  
 Data : #2  
 Date: 2018/3/20  
 Time: 下午 03:18:07  
 Operator: Kent  
 Temperature: 25 °C  
 Humidity: 53 %  
 Site : Chamber\_03  
 Condition : FCC Part 15C Conduction (QP)  
 EUT : W6M21801-17839  
 M/N:  
 Test Mode :  
 Note :  
 Phase: N  
 Power : 120 Va.c.

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
*	0.1551	50.54	QP	9.74	60.28	65.72	-5.44	
	0.1551	27.49	AVG	9.74	37.23	55.72	-18.49	
	0.1750	47.48	QP	9.74	57.22	64.72	-7.50	
	0.1750	25.85	AVG	9.74	35.59	54.72	-19.13	
	0.1925	44.53	QP	9.73	54.26	63.93	-9.67	
	0.1925	22.85	AVG	9.73	32.58	53.93	-21.35	
	0.2044	42.98	QP	9.73	52.71	63.43	-10.72	
	0.2044	25.22	AVG	9.73	34.95	53.43	-18.48	
	0.2231	39.98	QP	9.73	49.71	62.70	-12.99	
	0.2231	19.17	AVG	9.73	28.90	52.70	-23.80	
	0.2331	39.30	QP	9.73	49.03	62.34	-13.31	
	0.2331	19.65	AVG	9.73	29.38	52.34	-22.96	



Registration number: W6M21801-17839-C-1  
 FCC ID: M5X-MI909T18



Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
*	0.1533	51.10	QP	9.73	60.83	65.82	-4.99	
	0.1533	28.75	AVG	9.73	38.48	55.82	-17.34	
	0.1610	48.18	QP	9.73	57.91	65.41	-7.50	
	0.1610	25.02	AVG	9.73	34.75	55.41	-20.66	
	0.1708	48.24	QP	9.73	57.97	64.92	-6.95	
	0.1708	26.14	AVG	9.73	35.87	54.92	-19.05	
	0.1976	43.91	QP	9.72	53.63	63.71	-10.08	
	0.1976	24.11	AVG	9.72	33.83	53.71	-19.88	
	0.2170	41.13	QP	9.72	50.85	62.93	-12.08	
	0.2170	18.30	AVG	9.72	28.02	52.93	-24.91	
	0.2307	39.82	QP	9.72	49.54	62.42	-12.88	
	0.2307	18.57	AVG	9.72	28.29	52.42	-24.13	
	0.2430	37.48	QP	9.72	47.20	61.99	-14.79	
	0.2430	13.96	AVG	9.72	23.68	51.99	-28.31	
	0.2641	34.17	QP	9.72	43.89	61.30	-17.41	
	0.2641	13.27	AVG	9.72	22.99	51.30	-28.31	

- Note:**
1. The formula of measured value as: Test Result = Reading + Correction Factor
  2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
  3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
  4. All not in the table noted test results are more than 20 dB below the relevant limits.
  5. Measurement uncertainty = ±1.54 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
  6. Up Line: QP Limit Line, Down Line: Ave Limit Line.

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18


## **Appendix**

### **A Photos**

1. External Photos
2. Internal Photos
3. Set Up Photo of Radiated Emission
4. Set Up Photo of Conducted Emission

### **B Measurement diagrams**


Radiation Spurious Emission




Registration number: W6M21801-17839-C-1


FCC ID: M5X-MI909T18


**External Photos**





Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18





Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18








# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18





Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18





Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18






Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**Internal Photos**







Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18






Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18







Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18





Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18






Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18



Registration number: W6M21801-17839-C-1  
FCC ID: M5X-MI909T18






Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**Set Up Photo of Radiated Emission**





Registration number: W6M21801-17839-C-1

FCC ID: M5X-MI909T18

**Set Up Photo of Conducted Emission**





Radiated Emission Measurement

Operator: Kent

File :1

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 03:53:51

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	97.4550	-102.70	peak	23.56	-79.14	-54.00	150	120	-25.14	
*	189.0982	-99.94	peak	23.76	-76.18	-54.00	150	330	-22.18	



Radiated Emission Measurement

Operator: Kent

File :1

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 03:55:17

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

EUT : W6M21801-17839

M/N:

Test Mode : TX470.1MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	54.1884	-93.52	peak	23.58	-69.94	-54.00	150	305	-15.94	
*	56.2325	-90.67	peak	23.64	-67.03	-54.00	150	160	-13.03	





Radiated Emission Measurement

Operator: Kent

File :2

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:34:40

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	523.8477	-62.86	peak	-6.28	-69.14	-54.00	150	330	-15.14	
*	551.1022	-61.47	peak	-5.40	-66.87	-54.00	150	160	-12.87	



Radiated Emission Measurement

Operator: Kent

File :2

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:36:30

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	523.8477	-58.61	peak	-4.29	-62.90	-54.00	150	185	-8.90	
*	746.6934	-56.86	peak	-1.47	-58.33	-54.00	150	245	-4.33	



Radiated Emission Measurement

Operator: Kent

File :3

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:41:26

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1835.671	-53.94	peak	2.17	-51.77	-30.00	150	175	-21.77	
*	2412.826	-53.84	peak	5.48	-48.36	-30.00	150	220	-18.36	



Radiated Emission Measurement

Operator: Kent

File :3

Data :#3


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:01:37

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1835.671	-54.06	peak	3.62	-50.44	-30.00	150	330	-20.44	
*	1955.912	-45.77	peak	4.24	-41.53	-30.00	150	185	-11.53	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:43:02

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#4


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:02:22

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX470.1MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Kent

File :1

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 03:52:40

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

EUT : W6M21801-17839

M/N:

Test Mode : TX538.8MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	91.3226	-100.90	peak	23.11	-77.79	-54.00	150	245	-23.79	
	104.6092	-102.29	peak	23.43	-78.86	-54.00	150	110	-24.86	



Radiated Emission Measurement

Operator: Kent

File :1

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:02:43

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

EUT : W6M21801-17839

M/N:

Test Mode : TX538.8MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	58.2766	-90.99	peak	23.70	-67.29	-54.00	150	245	-13.29	
	67.8156	-92.49	peak	23.27	-69.22	-54.00	150	185	-15.22	





Radiated Emission Measurement

Operator: Kent

File :2

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:26:49

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	592.7856	-59.88	peak	-4.07	-63.95	-54.00	150	275	-9.95	
	620.0401	-62.20	peak	-2.51	-64.71	-54.00	150	110	-10.71	



Radiated Emission Measurement

Operator: Kent

File :2

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:29:08

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	485.3707	-54.28	peak	-5.11	-59.39	-54.00	150	130	-5.39	
	620.0401	-57.35	peak	-2.97	-60.32	-54.00	150	220	-6.32	



Radiated Emission Measurement

Operator: Kent

File :3

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:11:13

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1757.515	-53.16	peak	1.65	-51.51	-30.00	150	330	-21.51	
	1835.671	-56.22	peak	2.17	-54.05	-30.00	150	160	-24.05	



Radiated Emission Measurement

Operator: Kent

File :3

Data :#3


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:13:23

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: **Vertical**

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1835.671	-57.09	peak	3.62	-53.47	-30.00	150	110	-23.47	
*	1955.912	-54.47	peak	4.24	-50.23	-30.00	150	185	-20.23	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:11:56

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#4


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:14:07

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX538.8MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Kent

File :1

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 03:51:20

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	97.7956	-101.62	peak	23.59	-78.03	-54.00	150	245	-24.03	
	103.2464	-101.94	peak	23.52	-78.42	-54.00	150	185	-24.42	



Radiated Emission Measurement

Operator: Kent

File :1

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:03:50

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	55.2104	-94.44	peak	23.61	-70.83	-54.00	150	110	-16.83	
*	57.5952	-92.01	peak	23.68	-68.33	-54.00	150	245	-14.33	





Radiated Emission Measurement

Operator: Kent

File :2

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:16:34

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	527.0541	-50.67	peak	-6.17	-56.84	-54.00	150	160	-2.84	
*	608.8176	-52.31	peak	-3.25	-55.56	-54.00	150	245	-1.56	



Radiated Emission Measurement

Operator: Kent

File :2

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 04:18:05

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

EUT : W6M21801-17839

M/N:

Test Mode : TX 607.925MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	661.7234	-53.21	peak	-1.99	-55.20	-54.00	150	220	-1.20	
*	688.9780	-53.58	peak	-1.28	-54.86	-54.00	150	130	-0.86	



Radiated Emission Measurement

Operator: Kent

File :3

Data :#1


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:16:41

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1835.671	-54.43	peak	2.17	-52.26	-30.00	150	245	-22.26	
*	3651.302	-58.77	peak	9.66	-49.11	-30.00	150	110	-19.11	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

**Radiated Emission Measurement**

Operator: Kent

File :3

Data :#3


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:18:44

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: **Vertical**

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3038.076	-56.87	peak	7.48	-49.39	-30.00	150	330	-19.39	
*	3651.302	-57.64	peak	9.70	-47.94	-30.00	150	255	-17.94	

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#2


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:17:23

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Horizontal*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Kent

File :3

Data :#4


Date: 2018/3/16

Temperature:24 °C

-20.0 dBm

Time: 下午 05:19:27

Humidity:60 %



Site : Chamber

Condition : ETSI EN300\_422-TX\_Spurious\_OP

Polarization: *Vertical*

EUT : W6M21801-17839

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 607.925MHz

Note :

Mk.	Frequency (MHz)	Reading (dBm)	Detector	Corr. factor (dB)	Result (dBm)	Limit (dBm)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	---------------	----------	-------------------	--------------	-------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin