

FCC ID: M5ZWOWTHL

Modified Test Results Table for Model WOW-RHT

Harmonic	Freq. (MHz)	Meter Peak dB	Ant & Cable Factors dB/uV/m	Total Peak dB/uV/m	Limit Peak dB/uV/m	Total Average dB/uV/m	Limit Average dB/uV/m
1	418	65.00	19.28	84.28	92.30	62.38	72.30
2	836	12.60 QP	25.16	37.76 QP	46.00 QP	-	-
3	1254	10.60	24.60	35.20	74.00	13.30	54.00
4	1672	12.08	26.50	38.58	74.00	16.68	54.00
5	2090	12.80	28.10	40.90	74.00	19.00	54.00
6	2508	13.04	29.80	42.84	74.00	20.94	54.00
7	2926	13.15	31.50	44.65	74.00	22.75	54.00
8	3344	12.48	31.90	44.38	74.00	22.48	54.00
9	3762	12.70	32.40	45.10	74.00	23.20	54.00
10	4180	12.57	32.90	45.47	74.00	23.57	54.00

Modified Test Results Table for Model WOW-LGT

Harmonic	Freq. (MHz)	Meter Peak dB	Ant & Cable Factors dB/uV/m	Total Peak dB/uV/m	Limit Peak dB/uV/m	Total Average dB/uV/m	Limit Average dB/uV/m
1	418	67.10	19.28	86.38	92.30	64.48	72.30
2	836	2.0 QP	25.16	27.16 QP	46.00 QP	-	-
3	1254	10.74	24.60	35.34	74.00	13.44	54.00
4	1672	11.38	26.50	37.88	74.00	15.98	54.00
5	2090	11.42	28.10	39.52	74.00	17.62	54.00
6	2508	10.87	29.80	40.67	74.00	18.77	54.00
7	2926	11.14	31.50	42.64	74.00	20.74	54.00
8	3344	11.12	31.90	43.02	74.00	21.12	54.00
9	3762	11.32	32.40	43.72	74.00	21.82	54.00
10	4180	11.23	32.90	44.13	74.00	22.23	54.00