



Polycom, Inc.  
6001 America Center Drive  
San Jose, CA 95002

TEL 408-586-6000

www.poly.com

Applicant: Polycom Inc.	
FCC ID: M72-PS21	
Date: 2021-05-04	
RF Exposure Requirements ( FCC KDB 680106 D01 v03r01)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	Then frequency of the power transfer 110kHz to 190kHz
(b) Output power from each primary coil is less than 15 watts	Yes
(c) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Only one primary coil for this product
(d) Client device is placed directly in contact with the transmitter.	Client device is placed directly in contact with the transmitter
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Mobile device, and provided RF exposure report to evaluate
(f) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Please refer to RF Exposure Report.

Name: Yuk Wan

Title: Director, Corporate Technical Compliance

Tel: +44 1753 723 174

Fax: +44 1600 715 799

E-mail: yuk.wan@poly.com