

# T9560 Multitouch

Paging System Transmitter

## USER MANUAL



Usage, Installation, Warranty and Service Information



Long Range Systems, LLC  
4550 Excel Parkway, Suite 200  
Addison, TX 75001  
800.437.4996 • [www.page.net](http://www.page.net)

# Table Of Contents

<b>Long Range Systems</b> .....	<b>2</b>
<b>Keypad Operation</b> .....	<b>2</b>
<b>Setting Operation Mode</b> .....	<b>2</b>
<b>Paging Your Pager</b> .....	<b>3</b>
<b>Message to Your Pager</b> .....	<b>3</b>
<b>Configuring Your Message</b> .....	<b>4</b>
System ID .....	4
Range Test .....	4
<b>Pager Programming</b> .....	<b>5</b>
<b>Group Paging and Programming</b> .....	<b>5</b>
<b>Low Battery Alert</b> .....	<b>5</b>
<b>Factory Reset</b> .....	<b>5</b>
<b>Cleaning &amp; Charging Instructions for LRS Paging Equipment</b> .....	<b>6</b>
<b>Troubleshooting</b> .....	<b>7</b>
Transmitter Unit .....	7
<b>Service Questions and Answers</b> .....	<b>8</b>
<b>FCC Statement</b> .....	<b>8</b>
<b>Warranty</b> .....	<b>9</b>

# Long Range Systems

Thank you for choosing Long Range Systems to provide your on-premise paging solution. We provide cutting edge products and first-rate service to satisfy your needs for years to come. Please familiarize yourself and your staff with the contents of this instruction in order to properly operate and maintain your system. For help operating your system or for any service problems, please call:

**(800) 437-4996**



**NOTE:** Please keep this instruction in a safe place that is available to managers and key staff.

## Keypad Operation

**Number Keys 0-9** – used to type numeric information onto the LCD

**CLR** – Clear Key – Delete the previous typed entry

**SEND** – Sends the numeric entry for the pager

**G** – Group function Key

**PROG** – Program Button

**Message Keys M1-M6** – sends preset message to pagers

## Setting Operation Mode

The T9560 has 4 operational modes to work with the different LRS Pager types:

- LRS Guest
- POCSAG Staff
- 3 Digit Pager
- SP4 Staff

Please note that when a mode of operation is selected, only pagers of that type can be paged from the transmitter.

If LRS Guest mode is turned on, only LRS Coasters and Paddle Pagers can be paged, SP4's and Alpha Pagers cannot. Likewise if POCSAG Staff is enabled, SP4's and Guest Pagers cannot be paged

To turn on LRS Guest, press 9-9-6-PROG

To turn on POCSAG Staff, press 9-9-7-PROG

To turn on 3 Digit Pager, press 9-9-8-PROG

To turn on SP4 Staff, press 9-9-9-PROG

# Paging Your Pager

The T9560 will page single pagers numbered from 1-799.

To page a pager, press the pager number followed by a message key.

Example: To page pager #22 with Message 1, press 2-2-M1. Message 1-6 - message key.  
Default message - send key.

Alternatively, you can press the pager number and send to immediately send a page but only using the defaulted message 1.

Example: To page pager #22, press 2-2-Send

To use the All Page, press 9-1-1.

This will immediately send a page to all pagers.

# Messages to Your Pager

The Message Keys M1 through M6 store 6 presets paging messages for each mode of operation (3 Digit Pager, POCSAG Staff, etc.) Alpha Pagers and 3 Digit Pagers will send a default message when the user presses the pager number followed by the send key.

## **Guest Paging Mode**

- M1 – Flash/Vibe 1 Second
- M2 – Flash/Vibe 30 Seconds
- M3 – Flash/Vibe 5 Minutes
- M4 – Flash/Beep/Vibe 5 Minutes
- M5 – Glow/Vibe 15 times
- M6 – Glow/Vibe 5 Minutes

## **POCSAG Staff Paging Mode**

- M1 – Message 1
- M2 – Message 2
- M3 – Message 3
- M4 – Message 4
- M5 – Message 5
- M6 – Message 6
- Default – Manager Needed

## **3 Digit Pager Paging Mode**

- M1 – 001
- M2 – 002
- M3 – 003
- M4 – 004
- M5 – 005
- M6 – 006
- Default – 000

#### **SP4 Staff Paging Mode**

- M1 – Vibe 1 Time, LED 1 lights
- M2 – Vibe 2 Times, LED 2 lights
- M3 – Vibe 3 Times, LED 3 lights
- M4 – Vibe/Beep 1 Time, LED 1 lights
- M5 – Vibe/Beep 2 Times, LED 2 lights
- M6 – Vibe/Beep 3 Times, LED 2 lights

## Configuring Your Messages

The POCSAG Staff and 3 Digit Pager message can be edited and changed to a user defined set of messages.

Please refer to LRS Programmer instructions for changing messages.

### **System ID**

To change the System ID, press 9-0-x-Prog (x = sys ID from 0 to 49).

Please contact Long Range Systems before changing the System ID of your transmitter.

### **Range Test**

The Range Test feature is used to broadcast a continuous signal.

To turn on Range Test, press 9-9-2-Prog

When the range test is active, the LCD will display an 8 moving across screen. Then the red LED will transmit once every 10 seconds.

## Pager Programming

The T9560 can program any LRS Pager type. The transmitter's current mode of operation must match the desired pager to program. (Example: To program an SP4, the transmitter must be set to the SP4 Staff Mode.)

To program an SP4, coaster, or paddle pager:

- 1) Remove the pager from the charger
- 2) Allow the pager to complete the vibration and flashing sequence
- 3) Press into the keypad a number from 1-799 and press PROG. (Example: For Pager #200, press 2-0-0-PROG)
- 4) The red LED in the top right corner of the transmitter will light up once.
- 5) The pager will glow once cycle to indicate it received the programming.

To program an Alpha Pager or 3 Digit Pager:

- 1) Remove the battery from the pager
- 2) Re-insert the battery into the pager

- 3) Press into the keypad a number from 1-799 and press PROG. (Example: For Pager #200, press 2-0-0-PROG)
- 4) The red LED on the top right corner of the transmitter will light up three times.
- 5) The pager will beep three times to indicate the single pager capcode, all page capcode, and system ID.

## Group Paging and Programming

The T9560 has the ability to program groups into the LRS POCSAG Staff and 3 Digit Pagers.

Up to 5 groups can be programmed into the transmitter and pager.

Please note that when Groups is enabled, groups are numbered 1-9, and paged using 001 through 009.

Any POCSAG Staff Pager or 3 Digit Pager with a programmed pager number 1-9 matching a set group number, will be programmed +100 to the pager number.

Example:

If any Group is set, Pagers 1-9 become 101-109, and pager is programmed as #1, the pager will display Pager #101 for the individual pager number and 1 for group number.

To turn on Group Paging, press 9-9-1-PROG.

To turn off Group Paging, press 9-9-0-PROG.

When Group Paging is enabled, select up to 5 group numbers to set into the transmitter.

To set press G-0-0-#-PROG, where # is a number from 1 to 9.

Repeat for up to 5 group numbers.

Example, to set Group 2, press G-0-0-2-PROG.

To program Groups to a POCSAG or 3 Digit Pager, refer to pager programming section.

While the pager is programmed, the red LED on the transmitter will blink 1 additional time for each group to program.

The pager will beep an additional time for each group programmed.

Example: If 3 groups are set, the red LED will blink 6 times on the 9560, and the pager will beep 6 times.

To Page a group, press the G key, followed by the group number, then a message key.

Example: To Page Group 2 with Message 2, press G-2-M2 or G-002-M2.

Each Group must be individually set into The Transmitter and then that Group of pager programmed.

## Low Battery Alert

When the transmitter's battery is low, the LCD will display "Low Bat"

## Factory Reset

To reset the transmitter factory defaults, press 0-0-0-Prog. 1 + h.w. button for system reset, 2 + h.w. button for factory reset.

# Cleaning & Charging Instructions For LRS Paging Equipment

## Cleaning:

LRS pagers are made from industrial-strength, polycarbonate material. However, this material is susceptible to hairline cracking if non-approved cleaners are used. When cleaning LRS pagers, we recommend only using ISOPROPYL ALCOHOL-BASED CLEANERS.

To clean the equipment:

1. Take a clean rag and an isopropyl-alcohol based cleaner
2. Soak the clean rag with the isopropyl alcohol cleaner
3. Wipe down the pagers or equipment.

Cleaning equipment with any other non-approved cleaners can weaken plastic and cause hairline cracks. Pagers and equipment that are cleaned with unapproved cleaners and suffer cracking will not be covered under warranty.

Do not submerge any LRS paging equipment in any type of liquid as this will also damage the equipment and is not covered under the standard warranty.

## Charging:

Place rechargeable pagers on the charger and let them charge for 8 hours prior to first use.

Rechargeable pagers should be kept on charge even during extremely long periods of inactivity.

Should you have any questions, please contact the LRS Customer Service Department at 800.437.4996.

# Troubleshooting

## Transmitter Unit

### Transmitter Display does not light when a key is pressed

- The proper power supply for this transmitter is 12VDC 2.0A
- Ensuring that the proper power supply is in use, plug the T9560 into that power supply and allow it to charge for 30 minutes
- If the unit still is blank and has no power, substitute the power supply being used with the power supply used for the pager charging base (this is meant as a test only and not as a permanent replacement)
- If substituting with another power supply results in a T9560 that is working properly, please call LRS to purchase a new power supply for the T9560

### Transmitter Display is okay, but the pager does not receive the page

Check whether this affects all pagers or just one pager

- If only **one pager** is affected:
  - Ensure that the pager is properly charged and initiates a vibrate/flash sequence when removed from the charging base
    - If the pager does not vibrate and flash when removed from the charging base, please charge it overnight before troubleshooting further
    - If the pager initiates the vibrate/flash sequence when removed from the charging base, please continue with the next steps
- If **ALL pagers** are affected and none of them will page:
  - Check the Restaurant ID on the T9560 to ensure that it matches the Restaurant ID for the pagers (please call LRS if you do not have this information on file)
  - If the Restaurant ID is correct, all pagers are appropriately charged yet none of the pagers page, please contact LRS

### Pager(s) not charging:

When placed in the charging base, do all pagers have a single red charge light lit up?

- If no pagers have a charge light, this may be an issue with the power supply (please contact LRS)
- If only some pagers have a charge light that is lit, please do the following:
  - Remove the main power supply and all jumper wires (all pagers will go off at once and this is ok)
  - Insert the power supply into each individual row (or base for Coasters) to see if the pagers on that row/Coaster base all light up
    - If all pagers on that row or Coaster base light up, please test the next row/base with the power supply until you have tested each one
    - If some of the pagers do not light up but those specific pagers light up on other rows/bases, please call LRS to have this row/base replaced
- If all pagers have the charge light lit up as you test the individual rows/bases, you may have a jumper wire that is not connecting properly or causing a short. Please contact LRS to purchase additional jumper wires to replace ones that are not working as they should.

### Note Regarding Pagers: Please be sure that all pagers are plugged in and charging when not in use.

Please also note that a maximum of 60 Coasters or 25 Paddle Pagers or 30 Lobster Pagers or 30 Pizza Pagers can be on one 10V power supply. If you are exceeding any of these limits, it may have long term effects on your pagers' ability to charge properly. Please contact LRS to purchase additional charging bases to supplement your entire inventory.

# Service Questions and Answers

Should your paging system ever fail or should you need additional paging supplies, please call Long Range Systems at (800) 437-4996. Our office is open Monday through Friday 8:30 am to 5:00 pm Central Standard Time.

## For weekend or evening emergencies:

Long Range Systems has 24/7 live Technical Support available via (800) 437-4996. Please be ready to provide the following information when calling:

- Contact Name
- Contact Phone
- Name of Business

Please keep in mind that only troubleshooting will be done in the evenings or on the weekend. Any items that require shipping will be taken care of on the next business day.

## FCC STATEMENT

1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
  - (1) This device may not cause harmful interference.
  - (2) This device must accept any interference received, including interference that may cause undesired operation.
2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## RF warning statement:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

# Warranty

Long Range Systems, LLC permits a one-year manufacturer's warranty following the original consumer purchase date of any LRS system. Any individual components or products purchased will receive a 30-day manufacturer warranty. This warranty covers any defects due to faulty material or workmanship, but does not include damage to the product resulting from accident, misuse or improper electrical connection. If the product or system should become defective within the warranty period, we will repair or replace with equivalent equipment, free of charge. We will pay transportation charges to return your product via standard FedEx Ground shipping, provided the product is shipped prepaid to:

**Long Range Systems, LLC**  
4550 Excel Pkwy, Suite 200  
Addison, TX 75001

No return or replacement can be received without prior authorization from the LRS Customer Support department or without the proper RMA# posted on the outside of the shipping container. Contact Customer Support at 800.437.4996 or [www.page.net](http://www.page.net). This warranty gives you specific legal rights and you may also have rights that vary by state.

## **Copyright © 2013, Long Range Systems, LLC All Rights Reserved**

This manual contains proprietary information of Long Range Systems, LLC (LRS) and is intended for use only by its employees or customers. None of the material contained herein may be copied, reproduced, republished, downloaded, displayed, posted, or transmitted in any form or by any means, including but not limited to, electronic, mechanical, photocopying, recording, or otherwise without the prior written permission of LRS. Additional copies of this manual may be obtained by contacting LRS.

Screen displays, keyboard layouts, hardware descriptions, or software are proprietary to LRS and are subject to copyright and other intellectual property rights of LRS and shall be treated in accordance with the previous paragraph.

All attempts have been made to make the information in this document complete and accurate. LRS is not responsible for any direct or indirect damages or loss of business resulting from inaccuracies or omissions. Specifications and other information contained within this document are subject to change without notice.

Long Range Systems, LLC reserves the right to make changes without further notice to any products herein. LRS, LLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LRS, LLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in LRS, LLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. LRS, LLC products are not designed, intended, or authorized for use as components in systems intended to support or sustain life, or for any other application in which the failure of the LRS, LLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use LRS, LLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold LRS, LLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that LRS, LLC was negligent regarding the design or manufacture of the part, device or system.

## **EU DECLARATION OF CONFORMITY**

We, Long Range Systems hereby declare under our sole responsibility that the T9560 paging transmitters and on-site pagers comply with the essential requirements in the European RE&TTE Directive 1999/5/EC of the European Parliament of the Council of 9 March 1999 on radio equipment and telecommunication terminal equipment and the mutual recognition of their conformity. The following standards were utilized:

<b>ETS 300 224: 1998</b>	<b>EN 301 489-2: 2002</b>
<b>EN61000-3-2: 1998</b>	<b>EN 61000-3-3: 1995</b>
<b>EN 60950: 1992 with A1, A2, &amp; A3.</b>	

XU-0130 053013