




FCC Radio Test Report

FCC ID: M82-AIM10W

This report concerns (check one): Original Grant Class I Change Class II Change

Project No. : 1710083
Equipment : Computer
Test Model : AIM 10W
Series Model : AIM 10WXXXXXXXXXXXXXXXXXX (where X may be any alphanumeric character , blank or "-".)
Applicant : Advantech Co., Ltd.
Address : No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 11491, Taiwan, R.O.C.

Date of Receipt : Nov. 13, 2017
Date of Test : Nov. 13, 2017 ~ Feb. 27, 2018
Issued Date : Mar. 01, 2018
Tested by : BTL Inc.

Testing Engineer : 
 (Kenji Lin)
Technical Manager : 
 (James Chiu)
Authorized Signatory : 
 (Andy Chiu)

B T L I N C .

No.18, Ln. 171, Sec. 2, Jiuzong Rd.,
 Neihu Dist., Taipei City, Taiwan (R.O.C.)
 TEL:+886-2-2657-3299 FAX: +886-2-2657-3331



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents

Page

1 . CERTIFICATION	7
2 . SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 . GENERAL INFORMATION	11
3.1 GENERAL DESCRIPTION OF EUT	11
3.2 DESCRIPTION OF TEST MODES	13
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 DUTY CYCLE	14
3.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	15
3.6 DESCRIPTION OF SUPPORT UNITS	15
4 . EMC EMISSION TEST	16
4.1 CONDUCTED EMISSION MEASUREMENT	16
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	16
4.1.2 TEST PROCEDURE	16
4.1.3 DEVIATION FROM TEST STANDARD	16
4.1.4 TEST SETUP	17
4.1.5 EUT OPERATING CONDITIONS	17
4.1.6 EUT TEST CONDITIONS	17
4.1.7 TEST RESULTS	17
4.2 RADIATED EMISSION MEASUREMENT	18
4.2.1 RADIATED EMISSION LIMITS	18
4.2.2 TEST PROCEDURE	19
4.2.3 DEVIATION FROM TEST STANDARD	19
4.2.4 TEST SETUP	20
4.2.5 EUT OPERATING CONDITIONS	21
4.2.6 EUT TEST CONDITIONS	21
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	21
4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)	21
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	21
5 . NUMBER OF HOPPING CHANNEL	22
5.1 APPLIED PROCEDURES	22
5.1.1 TEST PROCEDURE	22
5.1.2 DEVIATION FROM STANDARD	22
5.1.3 TEST SETUP	22
5.1.4 EUT OPERATION CONDITIONS	22
5.1.5 EUT TEST CONDITIONS	22

Table of Contents	Page
5.1.6 TEST RESULTS	22
6 . AVERAGE TIME OF OCCUPANCY	23
6.1 APPLIED PROCEDURES / LIMIT	23
6.1.1 TEST PROCEDURE	23
6.1.2 DEVIATION FROM STANDARD	23
6.1.3 TEST SETUP	23
6.1.4 EUT OPERATION CONDITIONS	24
6.1.5 EUT TEST CONDITIONS	24
6.1.6 TEST RESULTS	24
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	25
7.1 APPLIED PROCEDURES / LIMIT	25
7.1.1 TEST PROCEDURE	25
7.1.2 DEVIATION FROM STANDARD	25
7.1.3 TEST SETUP	25
7.1.4 EUT TEST CONDITIONS	25
7.1.5 TEST RESULTS	25
8 . BANDWIDTH TEST	26
8.1 APPLIED PROCEDURES	26
8.1.1 TEST PROCEDURE	26
8.1.2 DEVIATION FROM STANDARD	26
8.1.3 TEST SETUP	26
8.1.4 EUT OPERATION CONDITIONS	26
8.1.5 EUT TEST CONDITIONS	26
8.1.6 TEST RESULTS	26
9 . PEAK OUTPUT POWER TEST	27
9.1 APPLIED PROCEDURES / LIMIT	27
9.1.1 TEST PROCEDURE	27
9.1.2 DEVIATION FROM STANDARD	27
9.1.3 TEST SETUP	27
9.1.4 EUT OPERATION CONDITIONS	27
9.1.5 EUT TEST CONDITIONS	27
9.1.6 TEST RESULTS	27
10 . ANTENNA CONDUCTED SPURIOUS EMISSION	28
10.1 APPLIED PROCEDURES / LIMIT	28
10.1.1 TEST PROCEDURE	28
10.1.2 DEVIATION FROM STANDARD	28
10.1.3 TEST SETUP	28
10.1.4 EUT OPERATION CONDITIONS	28
10.1.5 EUT TEST CONDITIONS	28
10.1.6 TEST RESULTS	28

Table of Contents	Page
11 . MEASUREMENT INSTRUMENTS LIST	29
12 . EUT TEST PHOTO	31
APPENDIX A - CONDUCTED EMISSION	41
APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)	48
APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)	61
APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)	68
APPENDIX E - NUMBER OF HOPPING CHANNEL	93
APPENDIX F - AVERAGE TIME OF OCCUPANCY	95
APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT	98
APPENDIX H - BANDWIDTH	101
APPENDIX I - PEAK OUTPUT POWER	104
APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION	107

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1710083	Original Issue.	Mar. 01, 2018

1. CERTIFICATION

Equipment : Computer
Brand Name : ADVANTECH
Test Model : AIM 10W
Series Model : AIM 10WXXXXXXXXXXXXXXXXX (where X may be any alphanumeric character , blank or “-”.)
Applicant : Advantech Co., Ltd.
Manufacturer : Advantech Co., Ltd.
Address : No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 11491, Taiwan, R.O.C.
Factory : N/A
Address : N/A
Date of Test : Nov. 13, 2017 ~ Feb. 27, 2018
Test Sample : Production Unit
Standard(s) : FCC Part15, Subpart C (15.247)/ ANSI C63.10-2013

The above equipment has been tested and found in compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1710083) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Test results included in this report is only for the Bluetooth EDR part.

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.247)			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Conducted emission Test:

C05: (VCCI RN: C-4742; FCC RN:674415; FCC DN:TW0659)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

Radiated emission Test (Below 1 GHz):

CB15: (VCCI RN: G-20020; FCC RN:674415; FCC DN:TW0659; ISED Assigned Code:20088-5)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):

CB15: (VCCI RN: G-20031; FCC RN:674415; FCC DN:TW0659; ISED Assigned Code:20088-5)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{cispr} requirement.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted emission test:

Test Site	Method	Measurement Frequency Range	U,(dB)
C05	CISPR	150 kHz ~ 30MHz	2.68

B. Radiated emission test:

Test Site	Method	Measurement Frequency Range	U,(dB)
CB15 (3m)	CISPR	9kHz ~ 150kHz	2.82
		150kHz ~ 30MHz	2.58

Test Site	Method	Measurement Frequency Range	Ant.	U,(dB)
CB15 (3m)	CISPR	30MHz ~ 200MHz	V	4.20
		30MHz ~ 200MHz	H	3.64
		200MHz ~ 1,000MHz	V	4.56
		200MHz ~ 1,000MHz	H	3.90

Test Site	Method	Measurement Frequency Range	Ant.	U,(dB)
CB15 (3m)	CISPR	1GHz ~ 6GHz	V	4.46
		1GHz ~ 6GHz	H	4.40
		6GHz ~ 18GHz	V	3.88
		6GHz ~ 18GHz	H	4.00

Test Site	Method	Measurement Frequency Range	U,(dB)
CB15 (1m)	CISPR	18 ~ 26.5 GHz	4.62
		26.5 ~ 40 GHz	5.12

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz: 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

Note: unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Computer	
Brand Name	ADVANTECH	
Test Model	AIM 10W	
Series Model	AIM 10WXXXXXXXXXXXXXXXXXX (where X may be any alphanumeric character , blank or "-".)	
Model Difference	The market distribution is different only.	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) π /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	10.57 dBm(1Mbps) 9.57 dBm(3Mbps)
Power Source	DC Voltage supplied from AC/DC adapter.	
Power Rating	I/P: AC 100-240V~, 1.5A, 50~60Hz, 1.5A O/P: DC 19V---3.42A	
Products Covered	1 * AC Adapter: TAMURA / XEW1934N 2* Dock: 1) Desk Docking: ADVANTECH/AIM-OFD-0000 2) VESA Docking: ADVANTECH/AIM-DOC-0001	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant.	Brand	Model	Antenna Type	Connector	Gain (dBi)
1	INPAQ	WA-F-LB-02-113	PIFA	I-pex	0.65

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode Note (1)

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode Note (1)

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	DOC		
	2402 MHz	2441 MHz	2480 MHz
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	Default	Default	Default
Parameters(3Mbps)	Default	Default	Default

3.4 DUTY CYCLE


If duty cycle is $\geq 98\%$, duty factor is not required.
 If duty cycle is $< 98\%$, duty factor shall be considered.

Bluetooth_1M	Bluetooth_3M
Date: 27.JAN.2018 10:22:39 Duty cycle = $2.900 \text{ ms} / 3.760 \text{ ms} = 77.13\%$ Duty Factor = $10 * \log(1 / 0.7713) = 1.13$	Date: 27.JAN.2018 10:41:28 Duty cycle = $2.900 \text{ ms} / 3.760 \text{ ms} = 77.13\%$ Duty Factor = $10 * \log(1 / 0.7713) = 1.13$

Note:

For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1/3 MHz and the video bandwidth is 3 kHz (Duty cycle $< 98\%$).

3.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	YES	NO	1.7m	Power Cable

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Appendix A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Appendix C.

4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Appendix D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable. For fundamental signal judgment was referred to Peak output test.

5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

5.1.6 TEST RESULTS

Please refer to the Appendix E

6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.
- j. DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
- k. DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

6.1.6 TEST RESULTS

Please refer to the Appendix F

7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
 - Resolution (or IF) Bandwidth (RBW) \geq 1% of the span
 - Video (or Average) Bandwidth (VBW) \geq RBW
 - Sweep = Auto
 - Detector function = Peak
 - Trace = Max Hold

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

7.1.5 TEST RESULTS

Please refer to the Appendix G

8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

8.1.6 TEST RESULTS

Please refer to the Appendix H

9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	1 Watt or 30dBm (hopping channel >75) 0.125Watt or 21dBm (hopping channel <75)	2400-2483.5	PASS

9.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

9.1.2 DEVIATION FROM STANDARD

No deviation.

9.1.3 TEST SETUP



9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: AC 120V/60Hz

9.1.6 TEST RESULTS

Please refer to the Appendix I

10. ANTENNA CONDUCTED SPURIOUS EMISSION

10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


10.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.
- c. Offset=antenna gain+cable loss

10.1.2 DEVIATION FROM STANDARD

No deviation.

10.1.3 TEST SETUP



10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

10.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: AC 120V/60Hz

10.1.6 TEST RESULTS

Please refer to the Appendix J

11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TWO-LINE V-NETWORK	R&S	ENV216	101050	Jan. 24, 2019
2	Test Cable	TIMES	CFD300-NL	C02	Jun. 13, 2019
3	EMI Test Receiver	R&S	ESR7	101433	Dec. 07, 2019
4	Measurement Software	EZ	EZ EMC (Version NB-03A)	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Preamplifier	EMCI	012645B	980267	Feb. 28, 2018
2	Preamplifier	EMCI	EMC02325	980217	Dec. 27, 2019
3	Preamplifier	EMCI	EMC2654045	980030	Feb. 13, 2019
4	Test Cable	EMCI	EMC104-SM-S M-8000	8m	Jan. 03, 2019
5	Test Cable	EMCI	EMC104-SM-S M-800	150207	Jan. 03, 2019
6	Test Cable	EMCI	EEMC104-SM-S M-3000	151205	Jan. 03, 2019
7	MXE EMI Receiver	Agilent	N9038A	MY55420127	Jan. 08, 2019
8	Signal Analyzer	Agilent	N9010A	MY52220990	Feb. 21, 2019
9	Loop Ant	EMCO	6502	42960	Nov. 23, 2018
10	Horn Ant	SCHWARZBECK	BBHA 9120D	9120D-1342	Feb. 28, 2018
11	Horn Ant	Schwarzbeck	BBHA 9170	187	Dec. 05, 2019
12	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-548	Jan. 15, 2019
13	5dB Attenuator	EMCI	EMCI-N-6-05	AT-N0623	Jan. 15, 2019

Number of Hopping Channel					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018

Average Time of Occupancy					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018

Hopping Channel Separation Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018

Peak Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018
2	Power Meter	Anritsu	ML2495A	1128008	Aug. 16, 2018
3	Power Sensor	Anritsu	MA2411B	1126001	Aug. 16, 2018


Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 25, 2018

Remark: "N/A" denotes no model name, serial no. or calibration specified.
 All calibration period of equipment list is one year.

APPENDIX A - CONDUCTED EMISSION

Test Mode: TX Mode


Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.5990	26.10	9.74	35.84	56.00	-20.16	QP	
2	*	0.5990	21.90	9.74	31.64	46.00	-14.36	AVG	
3		1.2110	8.80	9.74	18.54	56.00	-37.46	QP	
4		1.2110	7.90	9.74	17.64	46.00	-28.36	AVG	
5		1.6790	6.60	9.76	16.36	56.00	-39.64	QP	
6		1.6790	2.60	9.76	12.36	46.00	-33.64	AVG	
7		4.5500	6.50	9.81	16.31	56.00	-39.69	QP	
8		4.5500	3.00	9.81	12.81	46.00	-33.19	AVG	
9		13.5500	2.20	9.98	12.18	60.00	-47.82	QP	
10		13.5500	-2.10	9.98	7.88	50.00	-42.12	AVG	
11		15.7500	15.50	9.98	25.48	60.00	-34.52	QP	
12		15.7500	9.70	9.98	19.68	50.00	-30.32	AVG	

Test Mode: TX Mode


Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2256	27.60	9.66	37.26	62.61	-25.35	QP	
2		0.2270	7.90	9.66	17.56	52.56	-35.00	AVG	
3		0.5990	21.90	9.68	31.58	56.00	-24.42	QP	
4	*	0.5990	14.90	9.68	24.58	46.00	-21.42	AVG	
5		1.1750	8.10	9.69	17.79	56.00	-38.21	QP	
6		1.1750	-0.50	9.69	9.19	46.00	-36.81	AVG	
7		1.6160	8.00	9.71	17.71	56.00	-38.29	QP	
8		1.6160	4.20	9.71	13.91	46.00	-32.09	AVG	
9		13.5500	1.80	9.98	11.78	60.00	-48.22	QP	
10		13.5500	-1.90	9.98	8.08	50.00	-41.92	AVG	
11		16.0000	15.80	9.99	25.79	60.00	-34.21	QP	
12		16.0000	10.70	9.99	20.69	50.00	-29.31	AVG	

Test Mode: TX Mode_Desk Docking


Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1857	38.80	9.72	48.52	64.23	-15.71	QP	
2		0.1857	22.50	9.72	32.22	54.23	-22.01	AVG	
3		0.5450	24.40	9.74	34.14	56.00	-21.86	QP	
4		0.5450	19.40	9.74	29.14	46.00	-16.86	AVG	
5		1.4270	14.80	9.75	24.55	56.00	-31.45	QP	
6		1.4270	10.30	9.75	20.05	46.00	-25.95	AVG	
7		2.4170	9.70	9.78	19.48	56.00	-36.52	QP	
8		2.4170	3.20	9.78	12.98	46.00	-33.02	AVG	
9		15.6500	13.90	9.98	23.88	60.00	-36.12	QP	
10		15.6500	7.40	9.98	17.38	50.00	-32.62	AVG	
11		23.8500	-1.60	9.93	8.33	60.00	-51.67	QP	
12		23.8500	-4.30	9.93	5.63	50.00	-44.37	AVG	

Test Mode: TX Mode_Desk Docking


Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1801	37.70	9.65	47.35	64.48	-17.13	QP	
2		0.1801	21.00	9.65	30.65	54.48	-23.83	AVG	
3		0.5540	20.20	9.68	29.88	56.00	-26.12	QP	
4		0.5540	1.20	9.68	10.88	46.00	-35.12	AVG	
5		1.1300	9.30	9.69	18.99	56.00	-37.01	QP	
6		1.1300	-5.50	9.69	4.19	46.00	-41.81	AVG	
7		2.0030	7.80	9.71	17.51	56.00	-38.49	QP	
8		2.0030	2.20	9.71	11.91	46.00	-34.09	AVG	
9		4.7570	8.40	9.79	18.19	56.00	-37.81	QP	
10		4.7570	1.80	9.79	11.59	46.00	-34.41	AVG	
11		15.8500	12.70	9.99	22.69	60.00	-37.31	QP	
12		15.8500	6.60	9.99	16.59	50.00	-33.41	AVG	

Test Mode: TX Mode_VESA Docking


Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2137	31.10	9.71	40.81	63.06	-22.25	QP	
2		0.2137	12.10	9.71	21.81	53.06	-31.25	AVG	
3		0.5900	26.10	9.74	35.84	56.00	-20.16	QP	
4	*	0.5900	18.20	9.74	27.94	46.00	-18.06	AVG	
5		1.0400	7.80	9.74	17.54	56.00	-38.46	QP	
6		1.0400	0.20	9.74	9.94	46.00	-36.06	AVG	
7		1.4360	5.10	9.75	14.85	56.00	-41.15	QP	
8		1.4360	1.00	9.75	10.75	46.00	-35.25	AVG	
9		2.0030	8.50	9.77	18.27	56.00	-37.73	QP	
10		2.0030	5.70	9.77	15.47	46.00	-30.53	AVG	
11		15.7500	15.10	9.98	25.08	60.00	-34.92	QP	
12		15.7500	9.40	9.98	19.38	50.00	-30.62	AVG	

Test Mode: TX Mode_VESA Docking

Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1864	33.60	9.65	43.25	64.20	-20.95	QP	
2		0.1864	12.30	9.65	21.95	54.20	-32.25	AVG	
3		0.5900	25.70	9.68	35.38	56.00	-20.62	QP	
4	*	0.5900	17.80	9.68	27.48	46.00	-18.52	AVG	
5		0.9320	8.10	9.69	17.79	56.00	-38.21	QP	
6		0.9320	2.80	9.69	12.49	46.00	-33.51	AVG	
7		1.4720	10.00	9.69	19.69	56.00	-36.31	QP	
8		1.4720	5.50	9.69	15.19	46.00	-30.81	AVG	
9		3.1550	10.20	9.74	19.94	56.00	-36.06	QP	
10		3.1550	6.50	9.74	16.24	46.00	-29.76	AVG	
11		15.9500	16.20	9.99	26.19	60.00	-33.81	QP	
12		15.9500	10.70	9.99	20.69	50.00	-29.31	AVG	

APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0724	37.94	12.60	50.54	110.41	-59.87	peak	

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2	*	0.9261	30.79	11.97	42.76	68.27	-25.51	peak	
3		2.2096	22.66	11.46	34.12	69.54	-35.42	peak	
4		5.0750	16.98	11.40	28.38	69.54	-41.16	peak	
5		6.1497	15.55	11.38	26.93	69.54	-42.61	peak	
6		8.4184	13.23	11.33	24.56	69.54	-44.98	peak	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0637	40.61	12.75	53.36	111.52	-58.16	peak	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2	*	1.1350	28.52	11.94	40.46	66.50	-26.04	peak	
3		2.6274	21.29	11.27	32.56	69.54	-36.98	peak	
4		6.1497	15.55	11.38	26.93	69.54	-42.61	peak	
5		7.9706	13.82	11.34	25.16	69.54	-44.38	peak	
6		11.1942	12.82	11.26	24.08	69.54	-45.46	peak	

Test Mode: TX Mode_Desk Docking


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0670	38.25	12.69	50.94	111.08	-60.14	peak	

Test Mode: TX Mode_Desk Docking


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2		0.4485	37.41	11.80	49.21	94.57	-45.36	peak	
3	*	2.3887	22.56	11.38	33.94	69.54	-35.60	peak	
4		3.9110	18.67	11.24	29.91	69.54	-39.63	peak	
5		6.8960	14.14	11.36	25.50	69.54	-44.04	peak	
6		11.1942	12.82	11.26	24.08	69.54	-45.46	peak	

Test Mode: TX Mode_Desk Docking


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0670	38.04	12.69	50.73	111.08	-60.35	peak	

Test Mode: TX Mode_Desk Docking


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2	*	1.3440	27.36	11.85	39.21	65.04	-25.83	peak	
3		2.1200	23.06	11.50	34.56	69.54	-34.98	peak	
4		5.0750	16.98	11.40	28.38	69.54	-41.16	peak	
5		6.8960	14.14	11.36	25.50	69.54	-44.04	peak	
6		11.1942	12.82	11.26	24.08	69.54	-45.46	peak	

Test Mode: TX Mode_VESA Docking


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0630	39.39	12.77	52.16	111.62	-59.46	peak	

Test Mode: TX Mode_VESA Docking


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2	*	0.5675	35.40	11.83	47.23	72.52	-25.29	peak	
3		2.1200	23.06	11.50	34.56	69.54	-34.98	peak	
4		3.9110	18.67	11.24	29.91	69.54	-39.63	peak	
5		6.1497	15.55	11.38	26.93	69.54	-42.61	peak	
6		11.1942	12.82	11.26	24.08	69.54	-45.46	peak	

Test Mode: TX Mode_VESA Docking


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0763	37.36	12.53	49.89	109.95	-60.06	peak	

Test Mode: TX Mode_VESA Docking

Ant 90°




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2		0.2691	41.84	11.85	53.69	99.01	-45.32	peak	
3	*	1.8810	24.44	11.60	36.04	69.54	-33.50	peak	
4		3.5825	18.91	11.19	30.10	69.54	-39.44	peak	
5		5.5230	15.90	11.39	27.29	69.54	-42.25	peak	
6		6.6272	15.26	11.37	26.63	69.54	-42.91	peak	

APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode	TX 2480MHz _CH79_3Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		44.5500	38.60	-8.58	30.02	40.00	-9.98	QP	
2	*	50.3700	44.53	-8.32	36.21	40.00	-3.79	peak	
3		64.9200	37.65	-9.37	28.28	40.00	-11.72	peak	
4		126.0300	40.61	-9.81	30.80	43.50	-12.70	peak	
5		246.3100	35.95	-9.19	26.76	46.00	-19.24	peak	
6		318.0900	34.68	-7.04	27.64	46.00	-18.36	peak	

Test Mode	TX 2480MHz _CH79_3Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		67.8300	38.48	-9.83	28.65	40.00	-11.35	peak	
2	*	127.0000	44.36	-9.75	34.61	43.50	-8.89	peak	
3		248.2500	40.20	-9.14	31.06	46.00	-14.94	peak	
4		339.4300	35.00	-6.50	28.50	46.00	-17.50	peak	
5		405.3900	32.23	-4.79	27.44	46.00	-18.56	peak	
6		600.3600	32.34	-0.42	31.92	46.00	-14.08	peak	

Test Mode	TX 2480MHz _CH79_3Mbps_Desk Docking	Polarization	Vertical
-----------	-------------------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		59.1000	41.49	-7.80	33.69	40.00	-6.31	QP	
2		67.8300	42.01	-9.13	32.88	40.00	-7.12	QP	
3	*	240.4900	51.53	-8.67	42.86	46.00	-3.14	peak	
4		337.4900	42.72	-5.84	36.88	46.00	-9.12	peak	
5	!	497.5400	43.67	-1.72	41.95	46.00	-4.05	peak	
6		600.3600	39.80	-0.19	39.61	46.00	-6.39	peak	

Test Mode	TX 2480MHz _CH79_3Mbps_Desk Docking	Polarization	Horizontal
-----------	-------------------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		63.9500	38.15	-8.50	29.65	40.00	-10.35	peak	
2		127.0000	45.16	-9.12	36.04	43.50	-7.46	peak	
3		187.1400	42.44	-9.74	32.70	43.50	-10.80	peak	
4		277.3500	44.31	-7.26	37.05	46.00	-8.95	peak	
5	*	323.9100	46.50	-6.16	40.34	46.00	-5.66	peak	
6		420.9100	39.51	-3.40	36.11	46.00	-9.89	peak	

Test Mode	TX 2480MHz _CH79_3Mbps_VESA Docking	Polarization	Vertical
-----------	-------------------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		53.2800	40.92	-7.47	33.45	40.00	-6.55	QP	
2		65.8900	41.29	-8.81	32.48	40.00	-7.52	QP	
3		123.1200	40.70	-9.52	31.18	43.50	-12.32	peak	
4		162.8900	37.62	-7.49	30.13	43.50	-13.37	peak	
5	!	251.1600	48.42	-8.40	40.02	46.00	-5.98	peak	
6	*	508.2100	42.50	-1.65	40.85	46.00	-5.15	peak	

Test Mode	TX 2480MHz _CH79_3Mbps_VESA Docking	Polarization	Horizontal
-----------	-------------------------------------	--------------	------------

Orthogonal Axis: X




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	!	63.9500	44.14	-8.50	35.64	40.00	-4.36	peak	
2		123.1200	45.31	-9.52	35.79	43.50	-7.71	peak	
3		170.6500	44.00	-7.86	36.14	43.50	-7.36	peak	
4	*	253.1000	51.50	-8.34	43.16	46.00	-2.84	peak	
5		321.9700	41.55	-6.21	35.34	46.00	-10.66	QP	
6		458.7400	41.67	-2.43	39.24	46.00	-6.76	peak	

APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2383.110	15.65	31.04	46.69	74.00	-27.31	peak	
2		2383.110	2.80	31.04	33.84	54.00	-20.16	AVG	
3	X	2402.000	61.54	31.11	92.65	74.00	18.65	peak	No Limit
4	*	2402.000	61.18	31.11	92.29	54.00	38.29	AVG	No Limit

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	52.84	-11.40	41.44	74.00	-32.56	peak	
2	*	4804.000	41.81	-11.40	30.41	54.00	-23.59	AVG	

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2388.908	15.69	31.06	46.75	74.00	-27.25	peak	
2		2388.908	3.03	31.06	34.09	54.00	-19.91	AVG	
3	X	2402.000	70.75	31.11	101.86	74.00	27.86	peak	No Limit
4	*	2402.000	70.43	31.11	101.54	54.00	47.54	AVG	No Limit

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	53.13	-11.40	41.73	74.00	-32.27	peak	
2	*	4804.000	41.33	-11.40	29.93	54.00	-24.07	AVG	

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	65.73	31.25	96.98	74.00	22.98	peak	No Limit
2	*	2441.000	65.36	31.25	96.61	54.00	42.61	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	4882.000	53.30	-11.28	42.02	74.00	-31.98	peak	
2 *	4882.000	43.33	-11.28	32.05	54.00	-21.95	AVG	

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	72.77	31.25	104.02	74.00	30.02	peak	No Limit
2	*	2441.000	72.78	31.25	104.03	54.00	50.03	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.000	53.18	-11.28	41.90	74.00	-32.10	peak	
2	*	4882.000	43.39	-11.28	32.11	54.00	-21.89	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	67.44	31.39	98.83	74.00	24.83	peak	No Limit
2	*	2480.000	67.11	31.39	98.50	54.00	44.50	AVG	No Limit
3		2483.909	15.86	31.41	47.27	74.00	-26.73	peak	
4		2483.909	3.87	31.41	35.28	54.00	-18.72	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.000	55.55	-11.15	44.40	74.00	-29.60	peak	
2	*	4960.000	47.13	-11.15	35.98	54.00	-18.02	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	73.25	31.39	104.64	74.00	30.64	peak	No Limit
2	*	2480.000	72.96	31.39	104.35	54.00	50.35	AVG	No Limit
3		2483.500	20.40	31.41	51.81	74.00	-22.19	peak	
4		2483.500	8.10	31.41	39.51	54.00	-14.49	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.000	55.01	-11.15	43.86	74.00	-30.14	peak	
2	*	4960.000	45.67	-11.15	34.52	54.00	-19.48	AVG	

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2380.939	15.73	31.04	46.77	74.00	-27.23	peak	
2		2380.939	2.76	31.04	33.80	54.00	-20.20	AVG	
3	X	2402.000	60.81	31.11	91.92	74.00	17.92	peak	No Limit
4	*	2402.000	56.99	31.11	88.10	54.00	34.10	AVG	No Limit

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4806.000	52.39	-11.40	40.99	74.00	-33.01	peak	
2	*	4806.500	41.12	-11.40	29.72	54.00	-24.28	AVG	

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2383.591	16.43	31.04	47.47	74.00	-26.53	peak	
2		2383.591	3.12	31.04	34.16	54.00	-19.84	AVG	
3	X	2402.000	69.13	31.11	100.24	74.00	26.24	peak	No Limit
4	*	2402.000	65.35	31.11	96.46	54.00	42.46	AVG	No Limit

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	52.62	-11.40	41.22	74.00	-32.78	peak	
2	*	4804.000	40.81	-11.40	29.41	54.00	-24.59	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	63.86	31.25	95.11	74.00	21.11	peak	No Limit
2	*	2441.000	60.12	31.25	91.37	54.00	37.37	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.000	52.64	-11.28	41.36	74.00	-32.64	peak	
2	*	4882.000	40.76	-11.28	29.48	54.00	-24.52	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	72.27	31.25	103.52	74.00	29.52	peak	No Limit
2	*	2441.000	68.57	31.25	99.82	54.00	45.82	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.000	52.39	-11.28	41.11	74.00	-32.89	peak	
2	*	4882.000	41.41	-11.28	30.13	54.00	-23.87	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	65.75	31.39	97.14	74.00	23.14	peak	No Limit
2	*	2480.050	62.05	31.39	93.44	54.00	39.44	AVG	No Limit
3		2483.693	16.49	31.41	47.90	74.00	-26.10	peak	
4		2483.693	3.51	31.41	34.92	54.00	-19.08	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.000	53.06	-11.15	41.91	74.00	-32.09	peak	
2	*	4960.000	41.58	-11.15	30.43	54.00	-23.57	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	71.75	31.39	103.14	74.00	29.14	peak	No Limit
2	*	2480.000	68.09	31.39	99.48	54.00	45.48	AVG	No Limit
3		2483.564	17.33	31.41	48.74	74.00	-25.26	peak	
4		2483.564	5.07	31.41	36.48	54.00	-17.52	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------

Orthogonal Axis: X




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4960.000	52.94	-11.15	41.79	74.00	-32.21	peak	
2 *	4960.000	41.67	-11.15	30.52	54.00	-23.48	AVG	

APPENDIX E - NUMBER OF HOPPING CHANNEL

Test Mode **Hopping Mode_1Mbps**


Number of Hopping Channel 79



Date: 26.JAN.2018 15:39:53

Test Mode **Hopping Mode_3Mbps**

Number of Hopping Channel 79




Date: 26.JAN.2018 16:23:16

APPENDIX F - AVERAGE TIME OF OCCUPANCY


Test Mode : TX Mode_1Mbps

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.8800	0.3072	0.4000	Pass
DH3	2402	1.6400	0.2624	0.4000	Pass
DH1	2402	0.3850	0.1232	0.4000	Pass
DH5	2441	2.8800	0.3072	0.4000	Pass
DH3	2441	1.6600	0.2656	0.4000	Pass
DH1	2441	0.3850	0.1232	0.4000	Pass
DH5	2480	2.8800	0.3072	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH1	2480	0.3850	0.1232	0.4000	Pass



Test Mode : TX Mode_3Mbps


Data Packet	Frequency	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6600	0.2656	0.4000	Pass
DH1	2402	0.3850	0.1232	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6400	0.2624	0.4000	Pass
DH1	2441	0.3900	0.1248	0.4000	Pass
DH5	2480	2.8800	0.3072	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH1	2480	0.3950	0.1264	0.4000	Pass



APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT


Test Mode : Hopping on _1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.002	0.669	Pass
2441	1.009	0.651	Pass
2480	0.993	0.664	Pass



Test Mode : Hopping on _3Mbps


Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.010	0.889	Pass
2441	1.010	0.889	Pass
2480	0.996	0.887	Pass



APPENDIX H - BANDWIDTH


Test Mode : TX Mode _1Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.003	0.908	Pass
2441	0.976	0.908	Pass
2480	0.996	0.900	Pass



Test Mode : TX Mode _3Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.334	1.220	Pass
2441	1.333	1.212	Pass
2480	1.330	1.216	Pass



APPENDIX I - PEAK OUTPUT POWER


Test Mode : TX Mode _1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	7.69	0.0059	30.00	1.00	Pass
2441	9.68	0.0093	30.00	1.00	Pass
2480	10.57	0.0114	30.00	1.00	Pass







Test Mode : TX Mode _3Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	6.86	0.0049	30.00	1.00	Pass
2441	8.93	0.0078	30.00	1.00	Pass
2480	9.57	0.0091	30.00	1.00	Pass




APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION


Test Mode : TX Mode _ 1Mbps




2402 MHz – 10 Harmonics



Date: 26.JAN.2018 15:24:59




Date: 26.JAN.2018 15:25:11




Date: 26.JAN.2018 15:25:23


2441 MHz – 10 Harmonics



Date: 26.JAN.2018 15:27:49




Date: 26.JAN.2018 15:28:01




Date: 26.JAN.2018 15:28:13


2480 MHz – 10 Harmonics



Date: 26.JAN.2018 15:30:37




Date: 26.JAN.2018 15:30:49




Date: 26.JAN.2018 15:31:01


Test Mode : TX Mode _3Mbps




Date: 26.JAN.2018 15:54:36



Date: 26.JAN.2018 15:59:13




Date: 26.JAN.2018 16:24:06




Date: 26.JAN.2018 16:24:50


2402 MHz – 10 Harmonics



Date: 26.JAN.2018 15:55:22




Date: 26.JAN.2018 15:55:33




Date: 26.JAN.2018 15:55:45


2441 MHz – 10 Harmonics



Date: 26.JAN.2018 15:57:32




Date: 26.JAN.2018 15:57:43




Date: 26.JAN.2018 15:57:55


2480 MHz – 10 Harmonics



Date: 26.JAN.2018 15:59:58



Date: 26.JAN.2018 16:00:10



Date: 26.JAN.2018 16:00:22