

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

INDUSTRY CANADA RSS-247

Test Standard	FCC Part 15.247 IC RSS-247 issue 2 and IC RSS-GEN issue 5
Product name	Tablet PC
Brand Name	ADVANTECH
Model No.	FCC: AIM-75S-6; AIM-75H-6; AIM-75S-6XXXXXXXXXXXXXXXXXX; AIM-75H-6XXXXXXXXXXXXXXXXXX; AIM75S-6XXXXXXXXXXXXXXXXXX; AIM75H-6XXXXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank) IC: AIM-75S-6; AIM-75H-6
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report. The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 7, 2021	Initial Issue	ALL	May Lin

Table of contents

1.	GENERAL INFORMATION.....	4
1.1	EUT INFORMATION.....	4
1.2	EUT CHANNEL INFORMATION.....	6
1.3	ANTENNA INFORMATION.....	7
1.4	MEASUREMENT UNCERTAINTY	7
1.5	FACILITIES AND TEST LOCATION.....	8
1.6	INSTRUMENT CALIBRATION	8
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	10
1.8	TEST METHODOLOGY AND APPLIED STANDARDS.....	10
2.	TEST SUMMARY.....	11
3.	DESCRIPTION OF TEST MODES.....	12
3.1	THE WORST MODE OF OPERATING CONDITION	12
3.2	THE WORST MODE OF MEASUREMENT.....	13
4.	EUT DUTY CYCLE	14
5.	TEST RESULT	15
5.1.	AC POWER LINE CONDUCTED EMISSION.....	15
5.2.	6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)	20
5.3.	OUTPUT POWER MEASUREMENT	38
5.4.	POWER SPECTRAL DENSITY	43
5.5.	CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....	54
5.6.	RADIATION BANDEDGE AND SPURIOUS EMISSION.....	79

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Advantech Co., Ltd. No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.
Manufacturer	Advantech Co., Ltd. No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.
Equipment	Tablet PC
Model No.	FCC: AIM-75S-6; AIM-75H-6; AIM-75S-6XXXXXXXXXXXXXXXXXX; AIM-75H-6XXXXXXXXXXXXXXXXXX; AIM75S-6XXXXXXXXXXXXXXXXXX; AIM75H-6XXXXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank) IC: AIM-75S-6; AIM-75H-6
Model Discrepancy	Please see remark as below.
Trade Name	ADVANTECH
Received Date	November 02, 2020
Date of Test	January 21 ~ April 23, 2021
Power Supply	1. EUT Power by Adapter. (1) FSP / FSP045-A1BR I/P: 100-240Vac, 50-60Hz, 1.2A O/P: 5Vdc, 3.0A, 15.0W; 9.0Vdc, 3.0A, 27.0W; 12.0Vdc, 3.0A, 36.0W; 15.0Vdc, 3.0A, 45.0W; 20.0Vdc, 2.25A, 45.0W (2) GlobTek, Inc / GTM96605-GEN2-A1-T2 I/P: 100-240Vac, 50-60Hz, 1.5A O/P: 5Vdc, 4.6A; 5.8Vdc, 4.6A; 9Vdc, 4.4A; 12Vdc, 4A; 15Vdc, 3.6A; 20Vdc, 3A (3) DELTA / MEA-045AA2C I/P: 100-240V~1.0A Max. 50-60Hz O/P: 5VDC, 3A; 9VDC, 3A; 10VDC, 3A; 12VDC, 3A; 15VDC, 3A; 20VDC, 2.25A 2. EUT Power by Rechargeable Li-ion Battery. ADVANTECH / AIM-BAT-8 Rating: 3.8Vdc, 4900mAh, 18.62Wh
HW Version	AX2
SW Version	0.3.6.9_20201021.021551
EUT Serial #	200CT32E00162
Module	Qualcomm / WCN3990
Operating conditions for the EUT	QRCT _ V3.0.303.0

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. Disclaimer: Variant information between/among model numbers / trademarks are provided by the applicant, test results of this report are applicable to the sample EUT received of main test model name.
4. Model Discrepancy:

Model	Adapter	Tablet color
AIM-75H-6	1. GlobTek, Inc / GTM96605-GEN2-A1-T2 I/P: 100-240VAC, 50-60Hz, 1.5A O/P: 5VDC, 4.6A; 5.8VDC, 4.6A; 9VDC, 4.4A; 12VDC, 4A; 15VDC, 3.6A; 20VDC, 3A 2. DELTA / MEA-045AA2C IP: 100-240V~1.0A Max. 50-60Hz O/P: 5VDC, 3A; 9VDC, 3A; 10VDC, 3A; 12VDC, 3A; 15VDC, 3A; 20VDC, 2.25A	White
AIM-75S-6	1. FSP / FSP045-A1BR I/P: 100-240VAC, 50-60Hz, 1.2A O/P: 5.0VDC, 3.0A 15.0W; 9.0VDC, 3.0A 27.0W; 12.0VDC, 3.0A 36.0W; 15.0VDC, 3.0A 45.0W; 20.0VDC, 2.25A 45.0W	Black
AIM-75S-6XXXXXXXXXXXXXXXXXX; AIM-75H-6XXXXXXXXXXXXXXXXXX; AIM75S-6XXXXXXXXXXXXXXXXXX; AIM75H-6XXXXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)	All the above models are identical except for the designation of model numbers. The suffix of (where "X" may be any alphanumeric character, "-" or blank) on model number is just for marketing purpose only.	

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20: 2412MHz ~ 2462MHz 802.11n HT40: 2422MHz ~ 2452MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM 4. IEEE 802.11n HT 40 MHz mode : OFDM
Number of channel	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels 4. IEEE 802.11n HT 40 MHz mode : 7 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 and RSS-GEN Table A1 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type	Omni-directional antenna
Antenna Gain	IEEE 802.11 b / g / n20 /n40 mode: Chain 0 Gain: 1.78 dBi Chain 1 Gain: 1.96 dBi Power Directional Gain: 1.87 dBi
Antenna Connector	N/A

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Jerry Chang	-
Radiation	Ray Li	-
RF Conducted	Dally Hong	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
Power Meter	Anritsu	ML2487A	6K00003260	05/21/2020	05/20/2021
Power Sensor	Anritsu	MA2490A	032910	05/21/2020	05/20/2021
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2021	02/24/2022
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2021	02/24/2022
Coaxial Cable	EMCI	EMC105	190914+327109/4	09/19/2020	09/18/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/06/2021	01/05/2022
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	09/30/2020	09/29/2021
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2021	02/24/2022
Pre-Amplifier	HP	8449B	3008A00965	02/25/2021	02/24/2022
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emission Room					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2020	02/12/2021
Software	EZ-EMC(CCS-3A1-CE)				

Test date for April 23, 2021

Conducted Emission Room					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/02/2021	02/01/2022
Software	EZ-EMC(CCS-3A1-CE-wugu)				

Remark: Each piece of equipment is scheduled for calibration once a year.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5.

2. TEST SUMMARY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	-	1.3	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	5.1	AC Conducted Emission	Pass
15.247(a)(2)	RSS-247(5.2)(a)	5.2	6 dB Bandwidth	Pass
-	RSS-GEN 6.7	5.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	RSS-247(5.4)(d)	5.3	Output Power Measurement	Pass
15.247(e)	RSS-247(5.2)(b)	5.4	Power Spectral Density	Pass
15.247(d)	RSS-247(5.5)	5.5	Conducted Band Edge	Pass
15.247(d)	RSS-247(5.5)	5.5	Conducted Emission	Pass
15.247(d)	RSS-GEN 8.9, 8.10	5.6	Radiation Band Edge	Pass
15.247(d)	RSS-GEN 8.9, 8.10	5.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS8 IEEE 802.11n HT40 Mode: MCS8
Test Channel Frequencies	IEEE 802.11b mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11g mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT20 mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT40 Mode: 1. Lowest Channel: 2422MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2452MHz
Operation Transmitter	IEEE 802.11b mode :1T1R IEEE 802.11g mode :1T1R IEEE 802.11n HT20 mode : 2T2R IEEE 802.11n HT20 mode : 2T2R

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Adapter. (GlobTek) 120VAC Mode 2: EUT power by Adapter. (GlobTek) 240VAC Mode 3: EUT power by Adapter. (FSP) 120VAC Mode 4: EUT power by Adapter. (FSP) 240VAC Mode 5: EUT power by Adapter. (DELTA) 120VAC Mode 6: EUT power by Adapter. (DELTA) 240VAC
Worst Mode	☐ Mode 1 ☐ Mode 2 ☒ Mode 3 ☒ Mode 4 ☐ Mode 5 ☐ Mode 6

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Adapter. (GlobTek) Mode 2: EUT power by Adapter. (FSP) Mode 3: EUT power by Adapter. (DELTA) Mode 4: EUT power by Battery
Worst Mode	☐ Mode 1 ☒ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter. (GlobTek) Mode 2: EUT power by Adapter. (FSP) Mode 3: EUT power by Adapter. (DELTA) Mode 4: EUT power by Battery
Worst Mode	☐ Mode 1 ☒ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

Report No.: T201102D09-RP3

4. EUT DUTY CYCLE


Temperature: 22.2°C

Humidity: 48% RH

Tested by: Dally Hong

Test date: March 15, 2021

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	99.54	0.02	0.08	0.01
802.11g	97.92	0.09	0.49	1.00
802.11n HT20	99.25	0.03	0.52	0.01
802.11n HT40	94.30	0.25	2.09	3.00



5. TEST RESULT

5.1. AC POWER LINE CONDUCTED EMISSION

5.1.1 Test Limit

According to §15.207(a)(2) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

5.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

5.1.3 Test Setup




5.1.4 Test Result

PASS

Test Data


Test Mode:	Mode 3	Temp/Hum	22.94(°C)/ 53%RH
Phase:	Line	Test Date	January 21, 2021
		Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1540	36.55	32.42	10.21	46.76	42.63	65.78	55.78	-19.02	-13.15	Pass
0.4540	28.75	16.91	10.22	38.97	27.13	56.80	46.80	-17.83	-19.67	Pass
0.4780	31.96	21.16	10.22	42.18	31.38	56.37	46.37	-14.19	-14.99	Pass
0.9100	26.27	18.96	10.24	36.51	29.20	56.00	46.00	-19.49	-16.80	Pass
0.9580	36.20	30.82	10.24	46.44	41.06	56.00	46.00	-9.56	-4.94	Pass
16.8700	7.13	-0.68	10.40	17.53	9.72	60.00	50.00	-42.47	-40.28	Pass

Note: Correction factor = LISN loss + Cable loss.


Test Mode:	Mode 3	Temp/Hum	22.94(°C)/ 53%RH
Phase:	Neutral	Test Date	January 21, 2021
		Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.2060	25.52	19.00	10.19	35.71	29.19	63.37	53.37	-27.66	-24.18	Pass
0.4380	35.86	29.00	10.19	46.05	39.19	57.10	47.10	-11.05	-7.91	Pass
0.4660	32.71	22.86	10.19	42.90	33.05	56.58	46.58	-13.68	-13.53	Pass
0.4900	30.33	19.50	10.19	40.52	29.69	56.17	46.17	-15.65	-16.48	Pass
0.9260	27.20	19.92	10.21	37.41	30.13	56.00	46.00	-18.59	-15.87	Pass
17.9620	28.22	27.96	10.40	38.62	38.36	60.00	50.00	-21.38	-11.64	Pass

Note: Correction factor = LISN loss + Cable loss.


Test Mode:	Mode 4	Temp/Hum	22.5(°C)/ 54%RH
Phase:	Line	Test Date	April 23, 2021
		Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1700	25.05	8.95	10.29	35.34	19.24	64.96	54.96	-29.62	-35.72	Pass
0.2380	20.20	8.36	10.29	30.49	18.65	62.17	52.17	-31.68	-33.52	Pass
0.4580	23.12	13.86	10.29	33.41	24.15	56.73	46.73	-23.32	-22.58	Pass
0.4820	21.53	12.86	10.29	31.82	23.15	56.30	46.30	-24.48	-23.15	Pass
3.5700	15.63	7.65	10.36	25.99	18.01	56.00	46.00	-30.01	-27.99	Pass
17.9580	17.36	16.65	10.44	27.80	27.09	60.00	50.00	-32.20	-22.91	Pass

Note: Correction factor = LISN loss + Cable loss.

Test Mode:	Mode 4	Temp/Hum	22.5(°C)/ 54%RH
Phase:	Neutral	Test Date	April 23, 2021
		Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1700	30.34	13.48	10.26	40.60	23.74	64.96	54.96	-24.36	-31.22	Pass
0.1780	29.93	12.06	10.26	40.19	22.32	64.58	54.58	-24.39	-32.26	Pass
0.2140	26.13	11.47	10.26	36.39	21.73	63.05	53.05	-26.66	-31.32	Pass
0.4580	26.86	17.01	10.26	37.12	27.27	56.73	46.73	-19.61	-19.46	Pass
0.5700	19.40	13.94	10.26	29.66	24.20	56.00	46.00	-26.34	-21.80	Pass
13.5340	14.25	6.92	10.45	24.70	17.37	60.00	50.00	-35.30	-32.63	Pass

Note: Correction factor = LISN loss + Cable loss.

5.2. 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

5.2.1 Test Limit

According to §15.247(a)(2) and RSS-247 section 5.2(a),

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------


Occupied Bandwidth(99%) : For reporting purposes only.

5.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

5.2.3 Test Setup



5.2.4 Test Result

Temperature: 22.2°C

Humidity: 48% RH

Tested by: Dally Hong

Test date: March 15, 2021

Test mode: IEEE 802.11b Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	6dB limit (kHz)
Low	2412	14.2402	13.7626	7.5652	7.1304	≥500
Mid	2437	14.0665	13.7626	8.6087	8.5217	
High	2462	13.5890	13.5890	8.5217	8.5217	

Test mode: IEEE 802.11g Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	6dB limit (kHz)
Low	2412	16.8017	16.6280	15.6957	15.6957	≥500
Mid	2437	16.7583	16.5412	15.7391	15.6957	
High	2462	16.4978	16.4978	15.6957	15.7391	


Test mode: IEEE 802.11n HT20 Mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	6dB limit (kHz)
Low	2412	17.8871	17.7568	16.3478	16.9565	≥500
Mid	2437	17.8437	17.7568	16.3478	16.913	
High	2462	17.7134	17.6700	15.3478	15.9565	


Test mode: IEEE 802.11n HT40 Mode / 2422-2452 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	6dB limit (kHz)
Low	2422	36.2373	36.1215	35.014	35.13	>500
Mid	2437	36.3531	36.2373	35.362	35.246	
High	2452	36.3531	36.1215	35.13	35.71	


Report No.: T201102D09-RP3


Test Data


6dB BANDWIDTH
















IEEE 802.11n HT20 mode- chain 1

Low CH




Date: 15.MAR.2021 11:00:29

Mid CH



Date: 15.MAR.2021 11:04:49


High CH




Date: 15.MAR.2021 11:16:48

IEEE 802.11n HT40 mode- chain 1


Low CH




Mid CH





High CH





Test Data
BANDWIDTH 99%




















5.3. OUTPUT POWER MEASUREMENT

5.3.1 Test Limit

According to §15.247(b) and RSS-247 section 5.4(d),

Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi : [Limit = 30 – (DG – 6)] ☐ Point-to-point operation :
-------	---


Average output power : For reporting purposes only.

5.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

5.3.3 Test Setup



5.3.4 Test Result

Temperature: 22.2°C

Humidity: 48% RH

Tested by: Dally Hong

Test date: March 15, 2021

Peak output power :

1TX:

Chain 0

Wifi 2.4G										
Config	CH	Freq. (MHz)	power setting	PK Power (dBm)	PK Total Power (dBm)	EIRP PK Total Power (dBm)	EIRP PK Total Power (W)	DG (dBi)	Limit (dBm)	EIRP Limit (dBm)
			chain0	chain0						
IEEE 802.11b Data rate: 1Mbps	Low	2412	16	19.52	19.52	21.30	0.1349	1.78	30	36
	Mid	2437	16.5	19.58	19.58	21.36	0.1368			
	High	2462	16	19.49	19.49	21.27	0.1340			
IEEE 802.11g Data rate: 6Mbps	Low	2412	16.5	21.57	21.57	23.35	0.2163			
	Mid	2437	17	21.85	21.85	23.63	0.2307			
	High	2462	16	21.25	21.25	23.03	0.2009			

Chain1

Wifi 2.4G										
Config	CH	Freq. (MHz)	power setting	PK Power (dBm)	PK Total Power (dBm)	EIRP PK Total Power (dBm)	EIRP PK Total Power (W)	DG (dBi)	Limit (dBm)	EIRP Limit (dBm)
			chain1	chain1						
IEEE 802.11b Data rate: 1Mbps	Low	2412	15	19.73	19.73	21.69	0.1476	1.96	30	36
	Mid	2437	15.5	19.69	19.69	21.65	0.1462			
	High	2462	15	19.61	19.61	21.57	0.1435			
IEEE 802.11g Data rate: 6Mbps	Low	2412	16	22.27	22.27	24.23	0.2649			
	Mid	2437	16.5	22.42	22.42	24.38	0.2742			
	High	2462	15	21.53	21.53	23.49	0.2234			

2TX:

Wifi 2.4G												
Config	CH	Freq. (MHz)	power setting		PK Power (dBm)		PK Total Power (dBm)	EIRP PK Total Power (dBm)	EIRP PK Total Power (W)	DG (dBi)	Limit (dBm)	EIRP Limit (dBm)
			chain0	chain1	chain0	chain1						
IEEE 802.11n HT20 Data rate: MCS8	Low	2412	15.5	15.5	20.53	21.46	24.03	25.90	0.3891	1.87	30	36
	Mid	2437	16	16	20.80	21.8	24.34	26.21	0.4177			
	High	2462	15.5	15.5	20.73	21.93	24.38	26.25	0.4219			
IEEE 802.11n HT40 Data rate: MCS8	Low	2422	14.5	14.5	21.39	22.44	24.96	26.83	0.4816			
	Mid	2437	15.5	15.5	22.40	23.05	25.75	27.62	0.5778			
	High	2452	15	15	22.55	23.07	25.83	27.70	0.5886			

Average output power :

1TX:

Chain 0

Wifi 2.4G				
Config	CH	Freq. (MHz)	AV Power(dBm)	AV Total Power (dBm)
			chain0	
IEEE 802.11b Data rate: 1Mbps	Low	2412	17.44	17.44
	Mid	2437	17.41	17.41
	High	2462	17.29	17.29
IEEE 802.11g Data rate: 6Mbps	Low	2412	17.11	17.11
	Mid	2437	17.47	17.47
	High	2462	16.55	16.55

Chain 1

Wifi 2.4G				
Config	CH	Freq. (MHz)	AV Power(dBm)	AV Total Power (dBm)
			chain1	
IEEE 802.11b Data rate: 1Mbps	Low	2412	17.34	17.34
	Mid	2437	17.38	17.38
	High	2462	17.30	17.30
IEEE 802.11g Data rate: 6Mbps	Low	2412	17.26	17.26
	Mid	2437	17.53	17.53
	High	2462	16.59	16.59

2TX:

Wifi 2.4G					
Config	CH	Freq. (MHz)	AV Power(dBm)		AV Total Power (dBm)
			chain0	chain1	
IEEE 802.11n HT20 Data rate: MCS8	Low	2412	15.87	16.34	19.12
	Mid	2437	16.19	16.74	19.49
	High	2462	15.83	16.74	19.32
IEEE 802.11n HT40 Data rate: MCS8	Low	2422	15.70	16.30	19.03
	Mid	2437	16.08	16.95	19.55
	High	2452	15.74	16.77	19.30

5.4. POWER SPECTRAL DENSITY

5.4.1 Test Limit

According to §15.247(e) and RSS-247 section 5.2(b),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


Limit	☒ Antenna not exceed 6 dBi : 8dBm ☐ Antenna with DG greater than 6 dBi : [Limit = 8 – (DG – 6)] ☐ Point-to-point operation :
-------	---

5.4.2 Test Procedure

Test method Refer as ANSI C63.10:2013

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

5.4.3 Test Setup



5.4.4 Test Result

Temperature: 22.2°C **Humidity:** 48% RH
Tested by: Dally Hong **Test date:** March 15, 2021

1TX Chain 0

Test mode: IEEE 802.11b Mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 0 PPSSD (dBm)	Total PPSSD (dBm)	Limit (dBm)
Low	2412	-9.94	-9.94	8
Mid	2437	-9.62	-9.62	
High	2462	-9.74	-9.74	

Test mode: IEEE 802.11g Mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 0 PPSSD (dBm)	Total PPSSD (dBm)	Limit (dBm)
Low	2412	-7.04	-7.04	8
Mid	2437	-8.5	-8.5	
High	2462	-7.8	-7.8	

Chain 1

Test mode: IEEE 802.11b Mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 1 PPSSD (dBm)	Total PPSSD (dBm)	Limit (dBm)
Low	2412	-8.27	-8.27	8
Mid	2437	-7.62	-7.62	
High	2462	-8.28	-8.28	

Test mode: IEEE 802.11g Mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 1 PPSSD (dBm)	Total PPSSD (dBm)	Limit (dBm)
Low	2412	-6.82	-6.82	8
Mid	2437	-6.47	-6.47	
High	2462	-6.88	-6.88	

2TX

Test mode: IEEE 802.11n HT20 Mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain 0 PPSS (dBm)	Chain 1 PPSS (dBm)	Total PPSS (dBm)	Limit (dBm)
Low	2412	-8.57	-6.48	-4.39	8
Mid	2437	-8.1	-6.27	-4.08	
High	2462	-7.39	-6.36	-3.83	

Test mode: IEEE 802.11n HT40 Mode / 2422-2452 MHz					
Channel	Frequency (MHz)	Chain 0 PPSS (dBm)	Chain 1 PPSS (dBm)	Total PPSS (dBm)	Limit (dBm)
Low	2422	-9.38	-9.17	-6.26	8
Mid	2437	-10.7	-9.35	-6.96	
High	2452	-10.35	-9.22	-6.74	

Test Data

