

# FCC Radio Test Report

## FCC ID: M82-DLM8110WL

This report concerns (check one): Original Grant Class I Change Class II Change

**Project No.** : 1603230  
**Equipment** : Computer  
**Test Model** : DLT-M8110  
**Series Model** : DLT-M8110XXXXXXXXXXXXXXXXXX,  
DLM8110XXXXXXXXXXXXXXXXXX (where "X" may be  
any alphanumeric character, "-" or blank)  
**Applicant** : Advantech Co., Ltd.  
**Address** : No.1, Alley 20, Lane 26, Rueiguang Road, NeiHu  
District, Taipei 11491, Taiwan, R.O.C.  
  
**Date of Receipt** : Mar. 29, 2016  
**Date of Test** : Mar. 29, 2016 ~ Jun. 30, 2016  
**Issued Date** : Jul. 04, 2016  
**Tested by** : BTL Inc.

**Testing Engineer** : Rush Kao  
(Rush Kao)  
**Technical Manager** : Jeff Yang  
(Jeff Yang)  
**Authorized Signatory** : Andy Chiu  
(Andy Chiu)

# **B T L I N C .**

B1, No.37, Lane 365, Yang Guang St.,  
Nei-Hu District, Taipei City 114, Taiwan.  
TEL:+886-2-2657-3299 FAX: +886-2- 2657-3331

### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

<b>Table of Contents</b>	<b>Page</b>
<b>1 . CERTIFICATION</b>	<b>6</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>7</b>
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	8
<b>3 . GENERAL INFORMATION</b>	<b>9</b>
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.2 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.3 DESCRIPTION OF SUPPORT UNITS	14
<b>4 . EMC EMISSION TEST</b>	<b>15</b>
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 EUT TEST CONDITIONS	16
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 TEST PROCEDURE	18
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	19
4.2.5 EUT OPERATING CONDITIONS	20
4.2.6 EUT TEST CONDITIONS	20
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	21
4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)	21
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	21
<b>5 . BANDWIDTH TEST</b>	<b>22</b>
5.1 APPLIED PROCEDURES	22
5.1.1 TEST PROCEDURE	22
5.1.2 DEVIATION FROM STANDARD	22
5.1.3 TEST SETUP	22
5.1.4 EUT OPERATION CONDITIONS	22
5.1.5 EUT TEST CONDITIONS	22
5.1.6 TEST RESULTS	22
<b>6 . MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST</b>	<b>23</b>

<b>Table of Contents</b>	<b>Page</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>23</b>
6.1.1 TEST PROCEDURE	23
6.1.2 DEVIATION FROM STANDARD	23
6.1.3 TEST SETUP	23
6.1.4 EUT OPERATION CONDITIONS	23
6.1.5 EUT TEST CONDITIONS	23
6.1.6 TEST RESULTS	23
<b>7 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>24</b>
7.1 APPLIED PROCEDURES / LIMIT	24
7.1.1 TEST PROCEDURE	24
7.1.2 DEVIATION FROM STANDARD	24
7.1.3 TEST SETUP	24
7.1.4 EUT OPERATION CONDITIONS	24
7.1.5 EUT TEST CONDITIONS	24
7.1.6 TEST RESULTS	24
<b>8 . POWER SPECTRAL DENSITY TEST</b>	<b>25</b>
8.1 APPLIED PROCEDURES / LIMIT	25
8.1.1 TEST PROCEDURE	25
8.1.2 DEVIATION FROM STANDARD	25
8.1.3 TEST SETUP	25
8.1.4 EUT OPERATION CONDITIONS	25
8.1.5 EUT TEST CONDITIONS	25
8.1.6 TEST RESULTS	25
<b>9 . MEASUREMENT INSTRUMENTS LIST</b>	<b>26</b>
<b>10 . EUT TEST PHOTO</b>	<b>28</b>
<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>42</b>
<b>ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)</b>	<b>51</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>76</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>89</b>
<b>ATTACHMENT E - BANDWIDTH</b>	<b>190</b>
<b>ATTACHMENT F – MAXIMUM PEAK CONDUCTED OUTPUT POWER</b>	<b>207</b>
<b>ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>216</b>
<b>ATTACHMENT H - POWER SPECTRAL DENSITY</b>	<b>241</b>



### REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-3-1603230	Original Issue.	Jul. 04, 2016

## 1. CERTIFICATION

Equipment : Computer  
Brand Name : ADVANTECH  
Test Model : DLT-M8110  
Series Model : DLT-M8110XXXXXXXXXXXXXXXX, DLM8110XXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)  
Applicant : Advantech Co., Ltd.  
Manufacturer : Advantech Co., Ltd.  
Address : No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 11491, Taiwan, R.O.C.  
Date of Test : Mar. 29, 2016 ~ Jun. 30, 2016  
Test Sample : Production Unit  
Standard(s) : FCC Part15, Subpart C (15.247) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-3-1603230) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

**Test results included in this report is only for the 2.4G WLAN part.**

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C				
Standard(s)	Section	Test Item	Judgment	Remark
15.207		Conducted Emission	PASS	
15.247(d)		Antenna conducted Spurious Emission	PASS	
15.247(a)(2)		6dB Bandwidth	PASS	
15.247(b)(3)		Peak Output Power	PASS	
15.247(e)		Power Spectral Density	PASS	
15.203		Antenna Requirement	PASS	
15.209/15.205		Transmitter Radiated Emissions	PASS	

**NOTE:**

(1) "N/A" denotes test is not applicable in this test report.

### 2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

**Conducted emission Test:**

**C05:** (VCCI RN: C-4742; FCC RN:965108; FCC DN:TW1082)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

**Radiated emission Test (Below 1 GHz):**

**CB11:** (VCCI RN: R-4260; FCC RN:949005; FCC DN:TW1082; IC Assigned Code:20088-2)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

**Radiated emission Test (Above 1 GHz):**

**CB11:** (VCCI RN: G-868; FCC RN:949005; FCC DN:TW1082; IC Assigned Code:20088-2)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

The BTL measurement uncertainty is less than the CISPR 16-4-2  $U_{CISPR}$  requirement.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

### A. Conducted emission test:

Test Site	Method	Measurement Frequency Range	U, (dB)
C05	CISPR	150 kHz~30MHz	2.04

### B. Radiated emission test:

Test Site	Method	Measurement Frequency Range	U, (dB)
CB11 (3m)	CISPR	9kHz ~ 150kHz	4.00
		150kHz ~ 30MHz	4.00

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
CB11 (3m)	CISPR	30 MHz ~ 200 MHz	V	3.06
		30 MHz ~ 200 MHz	H	2.58
		200 MHz ~ 1, 000 MHz	V	3.50
		200 MHz ~ 1, 000 MHz	H	3.10

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
CB11 (3m)	CISPR	1GHz ~ 6GHz	V	4.14
		1GHz ~ 6GHz	H	4.14

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
CB11 (1m)	CISPR	6GHz ~ 18GHz	V	5.34
		6GHz ~ 18GHz	H	5.34

Test Site	Method	Measurement Frequency Range	U, (dB)
CB08 (1m)	CISPR	18 ~ 26.5 GHz	4.66
		26.5 ~ 40 GHz	4.74

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our  $U_{lab}$  values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called  $U_{CISPR}$ , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz: 5.2 dB

It can be seen that our  $U_{lab}$  values are smaller than  $U_{CISPR}$ .

Note: unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Computer		
Brand Name	ADVANTECH		
Test Model	DLT-M8110		
Series Model	DLT-M8110XXXXXXXXXXXXXXXXXX, DLM8110XXXXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)		
Model Difference	Different model distribute to different area.		
EUT Power Rating	#1 I/P: DC 12.0V #2 I/P: DC 7.4V		
Power Adapter Manufacturer	FSP	Model	FSP060-DIBAN2
Power Adapter Power Rating	I/P: AC 100-240V 1.5A 50-60Hz O/P: DC 12.0V 5.0A		
Product Description	Operation Frequency	2412~2462 MHz	
	Modulation Technology	802.11b:DSSS 802.11g:OFDM 802.11n:OFDM	
	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n: MSC15	
	Output Power (Max.)	802.11b: 23.44 dBm 802.11g: 28.21 dBm 802.11n(20MHz): 25.93 dBm 802.11n(40MHz): 25.18dBm	
CPU Manufacturer	Intel	Model	ATOM E3827 1.75GHz
Main Board Manufacturer	ADVANTECH	Model	PCM-8408
WiFi module Manufacturer	SUMMIT	Model	SDC-PE15N
mSATA Manufacturer	ADVANTECH	Spec.	MLC-32G
Memory Manufacturer	DDR3L 1600Mhz(4GB)		
LCD Display Manufacturer	AUO	Model	G104XVN01.0
DC Dock Manufacturer	ADVANTECH	Model	DLT-M8110 Vehicle Docking
AC Dock Manufacturer	ADVANTECH	Model	DLT-M8110 Desk Docking
Battery Manufacturer	ADVANTECH	Model	DLT-M8110L (7.4V±0.8V 3800 mAh)
	ADVANTECH	Model	DLT-M8110S (7.4V±0.8V 1750 mAh)

**Note:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

CH01 – CH11 for 802.11b, 802.11g, 802.11n(20MHz) CH03 – CH09 for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	ADVANTECH	DLT-M8110(Modify)	PIFA	IPEX	4.77
2	ADVANTECH	DLT-M8110(Modify)	PIFA	IPEX	4.69

Note:

- (1) The EUT incorporates a MIMO function. Physically, the EUT provides two completed two transmitters and two receivers (2T2R).
- (2) Directional gain =  $G_{ANT} + 10 \log(N)$  dBi =  $4.77 + 10 \log(2) = 7.78$  dBi.  
Reduced value =  $7.78 - 6 = 1.78$  dB

4.

Operating Mode	2TX
TX Mode	
802.11b	V (ANT 1 + ANT 2)
802.11g	V (ANT 1 + ANT 2)
802.11n(20MHz)	V (ANT 1 + ANT 2)
802.11n(40MHz)	V (ANT 1 + ANT 2)

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Model 1	TX B MODE CHANNEL 01/06/11
Model 2	TX G MODE CHANNEL 01/06/11
Model 3	TX N-20MHZ MODE CHANNEL 01/06/11
Model 4	TX N-40MHZ MODE CHANNEL 03/06/09
Model 5	Normal Link

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Model 5	Normal Link

For Radiated Test	
Final Test Mode	Description
Model 1	TX B MODE CHANNEL 01/06/11
Model 2	TX G MODE CHANNEL 01/06/11
Model 3	TX N-20MHZ MODE CHANNEL 01/06/11
Model 4	TX N-40MHZ MODE CHANNEL 03/06/09

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)  
 802.11g mode: OFDM (6Mbps)  
 802.11n HT20 mode : BPSK (6.5Mbps)  
 802.11n HT20 mode : BPSK (13.5Mbps)  
 For radiated emission tests, the highest output powers were set for final test.
- (3) For 1TX radiated below 1G test, the 802.11b is found to be the worst case and recorded.
- (4) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.
- (5) The EUT includes two optional dockings: DLT-M8110 Desk Docking and DLT-M8110 Vehicle Docking.  
 Stand-alone mode is the worst mode for all test items.  
 With DLT-M8110 Desk Docking or DLT-M8110 Vehicle Docking mode only worst cases of spurious emissions are recorded.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	N/A		
Frequency (MHz)	2412	2437	2462
802.11b	100%	100%	100%
802.11g	100%	100%	100%
802.11n (20MHz)	100%	85%	95%
Frequency (MHz)	2422	2437	2452
802.11n (40MHz)	80%	100%	80%




### 3.2 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


#### Stand-alone



#### With DLT-M8110 Desk Docking



### With DLT-M8110 Vehicle Docking



### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	Adapter	FSP	FSP060-DIBAN2	N/A	H5341000278
B	A.C Dock	ADVANTECH	DLT-M8110 Vehicle Docking	DOC	N/A
C	D.C Dock	ADVANTECH	DLT-M8110 Desk Docking	DOC	N/A

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	YES	1.5m	Power Cable
2	NO	NO	1.8m	Power Cord
3	YES	NO	3m	ANT Cable

Note:

- (1) For detachable type I/O cable should be specified the length in m in 『Length』 column.

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



- Note: 1.Support units were connected to second LISN .  
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was placed on the test table and programmed in normal function.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C    Relative Humidity: 55%    Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

#### LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### 4.2.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

**4.2.4 TEST SETUP**


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



**4.2.5 EUT OPERATING CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.

**4.2.6 EUT TEST CONDITIONS**

Temperature: 25°C    Relative Humidity: 45%    Test Voltage: AC 120V/60Hz



#### **4.2.7 TEST RESULTS (9KHZ TO 30MHZ)**

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### **4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)**

Please refer to the Attachment C.

#### **4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

Please refer to the Attachment D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. BANDWIDTH TEST

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C    Relative Humidity: 55%    Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E.

## 6. MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r04.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 6.1.5 EUT TEST CONDITIONS

Temperature: 25°C    Relative Humidity: 55%    Test Voltage: AC 120V/60Hz

#### 6.1.6 TEST RESULTS

Please refer to the Attachment F.

## 7. ANTENNA CONDUCTED SPURIOUS EMISSION

### 7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


#### 7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.
- c. Offset=antenna gain+cable loss

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 7.1.5 EUT TEST CONDITIONS

Temperature: 25°C    Relative Humidity: 55%    Test Voltage: AC 120V/60Hz

#### 7.1.6 TEST RESULTS

Please refer to the Attachment G.

## 8. POWER SPECTRAL DENSITY TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


#### 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C    Relative Humidity: 55%    Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Attachment H.

## 9. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TWO-LINE V-NETWORK	R&S	ENV216	101050	Jan. 26, 2017
2	Test Cable	TIMES	CFD300-NL	C02	Jun. 13, 2017
3	EMI Test Receiver	R&S	ESR7	101433	Dec. 09, 2016
4	Power Dividers	HP	11636A	8103	May 03, 2017
5	Measurement Software	EZ	EZ EMC (Version NB-03A)	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jul. 30, 2016
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 19, 2017
3	Horn Antenna	Schwarzbeck	BBHA 9120	9120D-1333	May 19, 2017
4	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 15, 2017
5	Pre-Amplifier	Agilent	8449B	3008A01714	Apr. 13, 2017
6	Test Cable	LMR	LMR-400	01(10M)	May 11, 2017
7	Test Cable	LMR	LMR-400	01(3M)	May 11, 2017
8	Test Cable	Harbour industries	27478LL142	1M	May 12, 2017
9	Test Cable	Harbour industries	27478LL142	3M	May 12, 2017
10	Test Cable	AISI	S104-SMAP-1	8M	May 12, 2017
11	Spectrum Analyzer	Agilent	N9020A	MY51160196	Aug. 02, 2016
12	EMI Test Receiver	R&S	ESCI	100080	May 12, 2017
13	Measurement Software	Farad	EZ EMC (Version NB-03A)	N/A	N/A

6dB Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 17, 2017

Peak Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	May 18, 2017
2	Power Meter Sensor	Anritsu	MA2491A	034138	May 17, 2017

Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 17, 2017

Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 17, 2017

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of equipment list is one year.

## 10. EUT TEST PHOTO

### Conducted Measurement Photos Stand-alone






**Conducted Measurement Photos  
With DLT-M8110 Desk Docking**



### Conducted Measurement Photos With DLT-M8110 Vehicle Docking




**Radiated Measurement Photos  
9KHz to 30MHz  
Stand-alone (Battery only)**









**Radiated Measurement Photos  
9KHz to 30MHz  
Stand-alone (Battery+Adapter)**





**Radiated Measurement Photos  
9KHz to 30MHz  
With DLT-M8110 Desk Docking**



**Radiated Measurement Photos  
9KHz to 30MHz  
With DLT-M8110 Vehicle Docking**





**Radiated Measurement Photos  
30MHz to 1000MHz  
Stand-alone (Battery only)**







**Radiated Measurement Photos  
30MHz to 1000MHz  
Stand-alone (Battery+Adapter)**





**Radiated Measurement Photos  
30MHz to 1000MHz  
With DLT-M8110 Desk Docking**



**Radiated Measurement Photos  
30MHz to 1000MHz  
With DLT-M8110 Vehicle Docking**



**Radiated Measurement Photos  
Above 1000MHz  
Stand-alone (Battery+Adapter)**



**Radiated Measurement Photos  
Above 1000MHz  
With DLT-M8110 Desk Docking**






**Radiated Measurement Photos  
Above 1000MHz  
With DLT-M8110 Vehicle Docking**



## ATTACHMENT A - CONDUCTED EMISSION

Test Mode: Normal Link\_Stand-alone (Battery\_DLT-M8110L+Adapter)


**Line**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1577	32.70	9.68	42.38	65.58	-23.20	QP	
2		0.1577	14.70	9.68	24.38	55.58	-31.20	AVG	
3		0.3894	21.00	9.68	30.68	58.08	-27.40	QP	
4		0.3894	13.60	9.68	23.28	48.08	-24.80	AVG	
5		0.4671	24.00	9.69	33.69	56.57	-22.88	QP	
6	*	0.4671	17.00	9.69	26.69	46.57	-19.88	AVG	
7		0.5540	20.10	9.69	29.79	56.00	-26.21	QP	
8		0.5540	12.70	9.69	22.39	46.00	-23.61	AVG	
9		0.8330	15.20	9.70	24.90	56.00	-31.10	QP	
10		0.8330	7.80	9.70	17.50	46.00	-28.50	AVG	
11		13.8500	20.90	9.89	30.79	60.00	-29.21	QP	
12		13.8500	11.90	9.89	21.79	50.00	-28.21	AVG	

Test Mode: Normal Link\_Stand-alone (Battery\_DLT-M8110L+Adapter)

### Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	33.00	9.69	42.69	65.99	-23.30	QP	
2		0.1500	15.90	9.69	25.59	55.99	-30.40	AVG	
3		0.2186	27.80	9.68	37.48	62.87	-25.39	QP	
4		0.2186	10.50	9.68	20.18	52.87	-32.69	AVG	
5		0.4608	25.60	9.69	35.29	56.68	-21.39	QP	
6	*	0.4608	19.50	9.69	29.19	46.68	-17.49	AVG	
7		0.8690	20.90	9.71	30.61	56.00	-25.39	QP	
8		0.8690	13.30	9.71	23.01	46.00	-22.99	AVG	
9		1.1300	18.00	9.73	27.73	56.00	-28.27	QP	
10		1.1300	10.20	9.73	19.93	46.00	-26.07	AVG	
11		14.0500	19.40	9.89	29.29	60.00	-30.71	QP	
12		14.0500	8.70	9.89	18.59	50.00	-31.41	AVG	



Test Mode: Normal Link\_Stand-alone (Battery\_DLT-M8110S+Adapter)


### Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1640	34.70	9.68	44.38	65.25	-20.87	QP	
2		0.1640	17.70	9.68	27.38	55.25	-27.87	AVG	
3		0.3970	22.00	9.68	31.68	57.91	-26.23	QP	
4		0.3970	13.90	9.68	23.58	47.91	-24.33	AVG	
5		0.4706	23.00	9.69	32.69	56.50	-23.81	QP	
6	*	0.4706	16.90	9.69	26.59	46.50	-19.91	AVG	
7		0.8780	16.40	9.71	26.11	56.00	-29.89	QP	
8		0.8780	9.50	9.71	19.21	46.00	-26.79	AVG	
9		2.4800	13.90	9.79	23.69	56.00	-32.31	QP	
10		2.4800	7.70	9.79	17.49	46.00	-28.51	AVG	
11		13.8000	21.30	9.89	31.19	60.00	-28.81	QP	
12		13.8000	12.00	9.89	21.89	50.00	-28.11	AVG	

Test Mode: Normal Link\_Stand-alone (Battery\_DLT-M8110S+Adapter)


### Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1661	39.00	9.69	48.69	65.15	-16.46	QP	
2		0.1661	20.50	9.69	30.19	55.15	-24.96	AVG	
3		0.2235	31.30	9.68	40.98	62.68	-21.70	QP	
4		0.2235	15.60	9.68	25.28	52.68	-27.40	AVG	
5		0.4790	24.40	9.69	34.09	56.36	-22.27	QP	
6		0.4790	15.20	9.69	24.89	46.36	-21.47	AVG	
7		0.8690	21.00	9.71	30.71	56.00	-25.29	QP	
8		0.8690	13.70	9.71	23.41	46.00	-22.59	AVG	
9		3.1280	9.30	9.83	19.13	56.00	-36.87	QP	
10		3.1280	2.40	9.83	12.23	46.00	-33.77	AVG	
11		13.6000	19.50	9.89	29.39	60.00	-30.61	QP	
12		13.6000	9.70	9.89	19.59	50.00	-30.41	AVG	

Test Mode: Normal Link\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


### Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1500	36.20	9.68	45.88	65.99	-20.11	QP	
2		0.1500	15.80	9.68	25.48	55.99	-30.51	AVG	
3		0.4272	21.80	9.69	31.49	57.31	-25.82	QP	
4		0.4272	11.60	9.69	21.29	47.31	-26.02	AVG	
5		0.8690	17.00	9.70	26.70	56.00	-29.30	QP	
6		0.8690	8.40	9.70	18.10	46.00	-27.90	AVG	
7		1.2920	14.70	9.72	24.42	56.00	-31.58	QP	
8		1.2920	5.40	9.72	15.12	46.00	-30.88	AVG	
9		2.6060	15.70	9.80	25.50	56.00	-30.50	QP	
10		2.6060	8.20	9.80	18.00	46.00	-28.00	AVG	
11		13.7000	23.10	9.89	32.99	60.00	-27.01	QP	
12		13.7000	14.20	9.89	24.09	50.00	-25.91	AVG	

Test Mode: Normal Link\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


**Neutral**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1500	36.30	9.69	45.99	65.99	-20.00	QP	
2		0.1500	16.60	9.69	26.29	55.99	-29.70	AVG	
3		0.2977	22.00	9.69	31.69	60.30	-28.61	QP	
4		0.2977	9.00	9.69	18.69	50.30	-31.61	AVG	
5		0.4895	25.60	9.69	35.29	56.18	-20.89	QP	
6		0.4895	13.30	9.69	22.99	46.18	-23.19	AVG	
7		0.9230	22.30	9.72	32.02	56.00	-23.98	QP	
8		0.9230	11.70	9.72	21.42	46.00	-24.58	AVG	
9		2.8760	12.60	9.81	22.41	56.00	-33.59	QP	
10		2.8760	3.60	9.81	13.41	46.00	-32.59	AVG	
11		13.6000	22.70	9.89	32.59	60.00	-27.41	QP	
12		13.6000	12.10	9.89	21.99	50.00	-28.01	AVG	

Test Mode: Normal Link\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110S)


**Line**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	36.10	9.64	45.74	65.99	-20.25	QP	
2		0.1500	16.20	9.64	25.84	55.99	-30.15	AVG	
3	*	0.1787	42.00	9.64	51.64	64.54	-12.90	QP	
4		0.1787	20.90	9.64	30.54	54.54	-24.00	AVG	
5		0.3019	29.30	9.63	38.93	60.19	-21.26	QP	
6		0.3019	12.50	9.63	22.13	50.19	-28.06	AVG	
7		2.6510	15.60	9.65	25.25	56.00	-30.75	QP	
8		2.6510	6.40	9.65	16.05	46.00	-29.95	AVG	
9		13.8000	23.30	9.72	33.02	60.00	-26.98	QP	
10		13.8000	14.10	9.72	23.82	50.00	-26.18	AVG	
11		25.0000	23.70	9.72	33.42	60.00	-26.58	QP	
12		25.0000	21.50	9.72	31.22	50.00	-18.78	AVG	

Test Mode: Normal Link\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110S)

### Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	35.80	9.65	45.45	65.99	-20.54	QP	
2		0.1500	16.90	9.65	26.55	55.99	-29.44	AVG	
3		0.3103	29.10	9.63	38.73	59.96	-21.23	QP	
4		0.3103	13.40	9.63	23.03	49.96	-26.93	AVG	
5		0.4664	22.60	9.63	32.23	56.58	-24.35	QP	
6		0.4664	11.40	9.63	21.03	46.58	-25.55	AVG	
7		0.8600	19.90	9.64	29.54	56.00	-26.46	QP	
8		0.8600	9.50	9.64	19.14	46.00	-26.86	AVG	
9		14.0500	23.70	9.73	33.43	60.00	-26.57	QP	
10		14.0500	12.90	9.73	22.63	50.00	-27.37	AVG	
11		25.0000	22.90	9.73	32.63	60.00	-27.37	QP	
12	*	25.0000	20.90	9.73	30.63	50.00	-19.37	AVG	

**ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)**

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)

**Open**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0137	47.07	19.48	66.55	128.18	-61.63	peak	



Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1800	44.87	11.98	56.85	116.18	-59.33	peak	
2		0.2691	41.84	11.85	53.69	109.75	-56.06	peak	
3		0.4187	38.46	11.80	50.26	98.95	-48.69	peak	
4		0.6572	33.42	11.86	45.28	72.31	-27.03	peak	
5	*	1.0750	30.36	11.97	42.33	68.59	-26.26	peak	
6		1.3733	26.48	11.83	38.31	65.93	-27.62	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0204	44.71	17.64	62.35	127.70	-65.35	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.2691	42.03	11.85	53.88	109.75	-55.87	peak	
2		0.4485	37.06	11.80	48.86	96.80	-47.94	peak	
3		0.7470	32.44	11.90	44.34	71.51	-27.17	peak	
4	*	1.7020	24.41	11.68	36.09	63.00	-26.91	peak	
5		2.3887	22.98	11.38	34.36	69.54	-35.18	peak	
6		3.8812	18.31	11.23	29.54	69.54	-40.00	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0246	43.53	16.48	60.01	127.39	-67.38	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3291	40.93	11.80	52.73	105.41	-52.68	peak	
2	*	1.0750	30.36	11.97	42.33	68.59	-26.26	peak	
3		1.9708	23.01	11.56	34.57	69.54	-34.97	peak	
4		2.6274	21.29	11.27	32.56	69.54	-36.98	peak	
5		3.5825	18.91	11.19	30.10	69.54	-39.44	peak	
6		3.9110	18.67	11.24	29.91	69.54	-39.63	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0303	42.04	14.97	57.01	126.98	-69.97	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.2993	41.85	11.80	53.65	107.57	-53.92	peak	
2		0.3886	38.05	11.80	49.85	101.12	-51.27	peak	
3	*	0.9261	31.48	11.97	43.45	69.91	-26.46	peak	
4		1.5230	26.24	11.76	38.00	64.59	-26.59	peak	
5		2.2395	24.62	11.44	36.06	69.54	-33.48	peak	
6		2.8664	21.25	11.16	32.41	69.54	-37.13	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)

**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0360	41.75	14.40	56.15	126.57	-70.42	peak	



Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.5675	35.40	11.83	47.23	73.11	-25.88	peak	
2		1.0750	30.36	11.97	42.33	68.59	-26.26	peak	
3		2.6274	21.29	11.27	32.56	69.54	-36.98	peak	
4		5.1051	16.72	11.40	28.12	69.54	-41.42	peak	
5		8.4184	13.23	11.33	24.56	69.54	-44.98	peak	
6		10.4780	12.56	11.29	23.85	69.54	-45.69	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0380	43.20	14.20	57.40	126.43	-69.03	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)


**Close**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	0.3886	38.05	11.80	49.85	101.12	-51.27	peak	
2	0.9261	31.48	11.97	43.45	69.91	-26.46	peak	
3 *	1.4334	27.49	11.80	39.29	65.39	-26.10	peak	
4	1.8216	24.07	11.63	35.70	69.54	-33.84	peak	
5	2.2395	24.62	11.44	36.06	69.54	-33.48	peak	
6	2.8664	21.25	11.16	32.41	69.54	-37.13	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0437	40.68	13.63	54.31	126.02	-71.71	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.2691	41.84	11.85	53.69	109.75	-56.06	peak	
2		0.8660	30.84	11.95	42.79	70.45	-27.66	peak	
3	*	1.7020	25.41	11.68	37.09	63.00	-25.91	peak	
4		2.8065	20.46	11.19	31.65	69.54	-37.89	peak	
5		4.3290	18.38	11.30	29.68	69.54	-39.86	peak	
6		11.7911	12.65	11.25	23.90	69.54	-45.64	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0488	39.87	13.12	52.99	125.65	-72.66	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)

**Close**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.6873	34.17	11.87	46.04	72.04	-26.00	peak	
2		1.4334	27.49	11.80	39.29	65.39	-26.10	peak	
3		3.2244	19.70	11.13	30.83	69.54	-38.71	peak	
4		6.6573	14.15	11.37	25.52	69.54	-44.02	peak	
5		5.2842	16.97	11.39	28.36	69.54	-41.18	peak	
6		8.4780	13.54	11.33	24.87	69.54	-44.67	peak	



Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


**Open**



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	0.0670	38.04	12.69	50.73	124.33	-73.60	peak	

Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


**Open**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	0.2096	43.96	11.94	55.90	114.04	-58.14	peak	
2	0.3291	40.93	11.80	52.73	105.41	-52.68	peak	
3	1.1350	28.52	11.94	40.46	68.05	-27.59	peak	
4 *	1.3440	27.36	11.85	39.21	66.19	-26.98	peak	
5	2.6274	21.29	11.27	32.56	69.54	-36.98	peak	
6	2.8065	20.46	11.19	31.65	69.54	-37.89	peak	

Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0763	37.36	12.53	49.89	123.66	-73.77	peak	

Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	1.1050	29.36	11.95	41.31	68.32	-27.01	peak	No Limit
2		2.2395	24.62	11.44	36.06	69.54	-33.48	peak	
3		3.8812	18.31	11.23	29.54	69.54	-40.00	peak	
4		5.2842	16.97	11.39	28.36	69.54	-41.18	peak	
5		6.3887	15.28	11.37	26.65	69.54	-42.89	peak	
6		7.3437	14.47	11.35	25.82	69.54	-43.72	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0530	40.57	12.95	53.52	125.34	-71.82	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)


**Open**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.4485	37.41	11.80	49.21	96.80	-47.59	peak	
2	*	2.1200	23.06	11.50	34.56	69.54	-34.98	peak	
3		3.2244	19.31	11.13	30.44	69.54	-39.10	peak	
4		5.7618	14.96	11.38	26.34	69.54	-43.20	peak	
5		8.1797	12.99	11.34	24.33	69.54	-45.21	peak	
6		12.1493	10.57	11.24	21.81	69.54	-47.73	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)


**Close**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	0.0637	40.61	12.75	53.36	124.57	-71.21	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)

**Close**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1500	47.16	12.03	59.19	118.34	-59.15	peak	
2		0.3291	40.16	11.80	51.96	105.41	-53.45	peak	
3	*	0.6873	34.17	11.87	46.04	72.04	-26.00	peak	
4		2.2395	24.62	11.44	36.06	69.54	-33.48	peak	
5		2.8664	21.25	11.16	32.41	69.54	-37.13	peak	
6		5.2842	16.97	11.39	28.36	69.54	-41.18	peak	



**ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)**

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		666.3200	33.89	0.54	34.43	46.00	-11.57	peak	
2		709.9700	34.00	1.50	35.50	46.00	-10.50	peak	
3		839.9500	30.44	3.45	33.89	46.00	-12.11	peak	
4		896.2100	29.94	4.53	34.47	46.00	-11.53	peak	
5	*	916.5800	30.75	4.90	35.65	46.00	-10.35	peak	
6		946.6500	29.25	5.43	34.68	46.00	-11.32	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		749.7400	35.42	2.33	37.75	46.00	-8.25	peak	
2		812.7900	36.82	3.06	39.88	46.00	-6.12	peak	
3	!	833.1600	37.12	3.36	40.48	46.00	-5.52	peak	
4	!	896.2100	36.00	4.53	40.53	46.00	-5.47	peak	
5	*	916.5800	38.16	4.90	43.06	46.00	-2.94	peak	
6	!	955.3800	35.55	5.56	41.11	46.00	-4.89	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		391.8100	37.17	-5.08	32.09	46.00	-13.91	peak	
2		582.9000	35.37	-0.67	34.70	46.00	-11.30	peak	
3		812.7900	30.44	3.06	33.50	46.00	-12.50	peak	
4		833.1600	31.72	3.36	35.08	46.00	-10.92	peak	
5		898.1500	30.83	4.58	35.41	46.00	-10.59	peak	
6	*	952.4700	30.28	5.52	35.80	46.00	-10.20	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	!	749.7400	38.07	2.33	40.40	46.00	-5.60	peak	
2	!	789.5100	38.29	2.77	41.06	46.00	-4.94	peak	
3	*	833.1600	38.75	3.36	42.11	46.00	-3.89	peak	
4		872.9300	35.26	4.06	39.32	46.00	-6.68	peak	
5	!	898.1500	37.30	4.58	41.88	46.00	-4.12	peak	
6	!	955.3800	35.57	5.56	41.13	46.00	-4.87	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		460.6800	38.99	-3.32	35.67	46.00	-10.33	peak	
2		666.3200	33.47	0.54	34.01	46.00	-11.99	peak	
3		726.4600	31.90	1.84	33.74	46.00	-12.26	peak	
4		833.1600	32.06	3.36	35.42	46.00	-10.58	peak	
5		898.1500	31.76	4.58	36.34	46.00	-9.66	peak	
6	*	955.3800	33.71	5.56	39.27	46.00	-6.73	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		812.7900	35.62	3.06	38.68	46.00	-7.32	peak	
2		833.1600	36.03	3.36	39.39	46.00	-6.61	peak	
3		871.9600	35.45	4.04	39.49	46.00	-6.51	peak	
4	!	898.1500	37.08	4.58	41.66	46.00	-4.34	peak	
5	*	916.5800	38.09	4.90	42.99	46.00	-3.01	peak	
6	!	937.9200	35.88	5.28	41.16	46.00	-4.84	peak	

Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		61.0400	38.25	-9.00	29.25	40.00	-10.75	peak	
2		448.0700	37.81	-3.56	34.25	46.00	-11.75	peak	
3		654.6800	34.48	0.28	34.76	46.00	-11.24	peak	
4		839.9500	33.64	3.45	37.09	46.00	-8.91	peak	
5		896.2100	30.27	4.53	34.80	46.00	-11.20	peak	
6	*	955.3800	31.57	5.56	37.13	46.00	-8.87	peak	



Test Mode: TX Mode\_Stand-alone (Battery\_DLT-M8110S+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		789.5100	31.70	2.77	34.47	46.00	-11.53	peak	
2	*	812.7900	36.41	3.06	39.47	46.00	-6.53	peak	
3		839.9500	35.81	3.45	39.26	46.00	-6.74	peak	
4		896.2100	33.86	4.53	38.39	46.00	-7.61	peak	
5		916.5800	32.84	4.90	37.74	46.00	-8.26	peak	
6		952.4700	33.09	5.52	38.61	46.00	-7.39	peak	

Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	391.8100	43.91	-5.08	38.83	46.00	-7.17	peak	
2		448.0700	37.77	-3.56	34.21	46.00	-11.79	peak	
3		504.3300	37.20	-2.55	34.65	46.00	-11.35	peak	
4		550.8900	37.05	-1.51	35.54	46.00	-10.46	peak	
5		574.1700	37.01	-0.90	36.11	46.00	-9.89	peak	
6		951.5000	30.79	5.51	36.30	46.00	-9.70	peak	

Test Mode: TX Mode\_With DLT-M8110 Desk Docking (Battery\_DLT-M8110L)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	32.9100	46.76	-8.96	37.80	40.00	-2.20	peak	
2		417.0300	41.99	-4.43	37.56	46.00	-8.44	peak	
3		728.4000	34.38	1.88	36.26	46.00	-9.74	peak	
4		839.9500	35.27	3.45	38.72	46.00	-7.28	peak	
5		896.2100	31.12	4.53	35.65	46.00	-10.35	peak	
6		935.0100	30.24	5.23	35.47	46.00	-10.53	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		460.6800	42.32	-3.32	39.00	46.00	-7.00	peak	
2		499.4800	40.43	-2.66	37.77	46.00	-8.23	peak	
3		582.9000	39.05	-0.67	38.38	46.00	-7.62	peak	
4		871.9600	34.51	4.04	38.55	46.00	-7.45	peak	
5		898.1500	32.48	4.58	37.06	46.00	-8.94	peak	
6	*	955.3800	35.26	5.56	40.82	46.00	-5.18	peak	

Test Mode: TX Mode\_With DLT-M8110 Vehicle Docking (Battery\_DLT-M8110L)

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		434.4900	40.36	-3.94	36.42	46.00	-9.58	peak	
2		460.6800	41.41	-3.32	38.09	46.00	-7.91	peak	
3		500.4500	39.76	-2.64	37.12	46.00	-8.88	peak	
4		871.9600	32.07	4.04	36.11	46.00	-9.89	peak	
5		898.1500	32.87	4.58	37.45	46.00	-8.55	peak	
6	*	955.3800	35.31	5.56	40.87	46.00	-5.13	peak	

## ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2389.216	22.43	31.70	54.13	74.00	-19.87	peak	
2		2389.216	12.56	31.70	44.26	54.00	-9.74	AVG	
3	X	2412.000	72.70	31.79	104.49	74.00	30.49	peak	No Limit
4	*	2412.000	70.09	31.79	101.88	54.00	47.88	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	60.69	-10.48	50.21	74.00	-23.79	peak	
2	*	4824.000	55.04	-10.48	44.56	54.00	-9.44	AVG	



Orthogonal Axis :	X
Test Mode :	TX B MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2374.824	29.63	31.65	61.28	74.00	-12.72	peak	
2		2374.824	21.08	31.65	52.73	54.00	-1.27	AVG	
3	X	2412.000	79.63	31.79	111.42	74.00	37.42	peak	No Limit
4	*	2412.000	77.26	31.79	109.05	54.00	55.05	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	58.74	-10.48	48.26	74.00	-25.74	peak	
2	*	4824.000	51.53	-10.48	41.05	54.00	-12.95	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2437.000	74.38	31.88	106.26	74.00	32.26	peak	No Limit
2	*	2437.000	72.20	31.88	104.08	54.00	50.08	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	60.72	-10.40	50.32	74.00	-23.68	peak	
2	*	4874.000	55.18	-10.40	44.78	54.00	-9.22	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2437.000	79.73	31.88	111.61	74.00	37.61	peak	No Limit
2	*	2437.000	77.29	31.88	109.17	54.00	55.17	AVG	No Limit


Orthogonal Axis :	X
Test Mode :	TX B MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	60.00	-10.40	49.60	74.00	-24.40	peak	
2	*	4874.000	53.31	-10.40	42.91	54.00	-11.09	AVG	


Orthogonal Axis :	X
Test Mode :	TX B MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2462.000	74.53	31.98	106.51	74.00	32.51	peak	No Limit
2	*	2462.000	71.96	31.98	103.94	54.00	49.94	AVG	No Limit
3		2483.500	29.39	32.06	61.45	74.00	-12.55	peak	
4		2483.500	18.00	32.06	50.06	54.00	-3.94	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.000	61.46	-10.32	51.14	74.00	-22.86	peak	
2	*	4924.000	56.06	-10.32	45.74	54.00	-8.26	AVG	



Orthogonal Axis :	X
Test Mode :	TX B MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2462.000	79.80	31.98	111.78	74.00	37.78	peak	No Limit
2	*	2462.000	77.26	31.98	109.24	54.00	55.24	AVG	No Limit
3		2483.500	32.09	32.06	64.15	74.00	-9.85	peak	
4		2483.500	21.82	32.06	53.88	54.00	-0.12	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.000	59.83	-10.32	49.51	74.00	-24.49	peak	
2	*	4924.000	52.72	-10.32	42.40	54.00	-11.60	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.34	31.70	64.04	74.00	-9.96	peak	
2		2390.000	18.03	31.70	49.73	54.00	-4.27	AVG	
3	X	2412.000	73.59	31.79	105.38	74.00	31.38	peak	No Limit
4	*	2412.000	65.59	31.79	97.38	54.00	43.38	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	56.54	-10.48	46.06	74.00	-27.94	peak	
2	*	4824.000	43.30	-10.48	32.82	54.00	-21.18	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	34.92	31.70	66.62	74.00	-7.38	peak	
2		2390.000	20.06	31.70	51.76	54.00	-2.24	AVG	
3	X	2412.000	77.97	31.79	109.76	74.00	35.76	peak	No Limit
4	*	2412.000	70.34	31.79	102.13	54.00	48.13	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	56.08	-10.48	45.60	74.00	-28.40	peak	
2	*	4824.000	42.51	-10.48	32.03	54.00	-21.97	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2437.000	78.11	31.88	109.99	74.00	35.99	peak	No Limit
2	*	2437.000	70.11	31.88	101.99	54.00	47.99	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	58.58	-10.40	48.18	74.00	-25.82	peak	
2	*	4874.000	46.25	-10.40	35.85	54.00	-18.15	AVG	



Orthogonal Axis :	X
Test Mode :	TX G MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2437.000	82.55	31.88	114.43	74.00	40.43	peak	No Limit
2	*	2437.000	74.70	31.88	106.58	54.00	52.58	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	57.02	-10.40	46.62	74.00	-27.38	peak	
2	*	4874.000	44.91	-10.40	34.51	54.00	-19.49	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2462.000	74.20	31.98	106.18	74.00	32.18	peak	No Limit
2	*	2462.000	65.89	31.98	97.87	54.00	43.87	AVG	No Limit
3		2483.500	34.07	32.06	66.13	74.00	-7.87	peak	
4		2483.500	18.14	32.06	50.20	54.00	-3.80	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.94	-10.48	45.46	74.00	-28.54	peak	
2	*	4824.000	42.09	-10.48	31.61	54.00	-22.39	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2462.000	78.29	31.98	110.27	74.00	36.27	peak	No Limit
2	*	2462.000	70.60	31.98	102.58	54.00	48.58	AVG	No Limit
3		2483.600	37.72	32.06	69.78	74.00	-4.22	peak	
4		2483.600	21.31	32.06	53.37	54.00	-0.63	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Horizontal**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.85	-10.48	45.37	74.00	-28.63	peak	
2	*	4824.000	42.01	-10.48	31.53	54.00	-22.47	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2389.900	32.97	31.70	64.67	74.00	-9.33	peak	
2		2389.900	19.08	31.70	50.78	54.00	-3.22	AVG	
3	X	2412.000	74.34	31.79	106.13	74.00	32.13	peak	No Limit
4	*	2412.000	65.81	31.79	97.60	54.00	43.60	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.67	-10.48	45.19	74.00	-28.81	peak	
2	*	4824.000	41.94	-10.48	31.46	54.00	-22.54	AVG	



Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	35.38	31.70	67.08	74.00	-6.92	peak	
2		2390.000	21.88	31.70	53.58	54.00	-0.42	AVG	
3	X	2412.000	78.20	31.79	109.99	74.00	35.99	peak	No Limit
4	*	2412.000	69.73	31.79	101.52	54.00	47.52	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.68	-10.48	45.20	74.00	-28.80	peak	
2	*	4824.000	41.97	-10.48	31.49	54.00	-22.51	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2437.000	76.01	31.88	107.89	74.00	33.89	peak	No Limit
2	*	2437.000	67.60	31.88	99.48	54.00	45.48	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.30	-10.48	44.82	74.00	-29.18	peak	
2	*	4824.000	42.18	-10.48	31.70	54.00	-22.30	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2437.000	80.19	31.88	112.07	74.00	38.07	peak	No Limit
2	*	2437.000	71.67	31.88	103.55	54.00	49.55	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	55.51	-10.48	45.03	74.00	-28.97	peak	
2	*	4824.000	42.08	-10.48	31.60	54.00	-22.40	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2462 MHz_Stand-alone (Battery_DLT-M8110L+Adapter)

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2462.000	72.87	31.98	104.85	74.00	30.85	peak	No Limit
2	*	2462.000	64.67	31.98	96.65	54.00	42.65	AVG	No Limit
3		2483.500	31.69	32.06	63.75	74.00	-10.25	peak	
4		2483.500	19.27	32.06	51.33	54.00	-2.67	AVG	