

2000022231-01

62x105mm

ADVANTECH

ADVANTECH CO., LTD.
 研華股份有限公司
 研華股份有限公司
[Http://www.advantech.com](http://www.advantech.com)
 MADE IN TAIWAN 台灣製造 台灣製造

Product Name : Serial Device Server

品名 / 品名: 序列設備伺服器/串行設備伺服器

MODEL NO

型號 / 型號: EKI-1361

INPUT

電源 / 電源: 12-48Vdc === 0.65A max

1-port Industrial RS-232/422/485 to 802.11 b/g/n WLAN Serial Device Server

注意

產品避免撞擊, 勿自行拆卸機壳, 機台內部無客戶可自行處理部份, 若有問題請洽詢專業人員。

聲明

此為A級產品, 在生活環境中, 該產品可能會造成無線電干擾, 在這種情況下, 可能需要用戶對其干擾採取切实可行的措施。

CAUTION!

To prevent from electronic shock, do NOT open the case. For safety reasons, the device should be opened only by qualified service personnel.

This device is in complies with requestments in part 15 of the FCC rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

LAN MAC Address	WLAN MAC Address



FCC ID:M82-EKI1362

S/ N	
---------	--

Pin Assignments

Male DB9 (DB9-M)

1 2 3 4 5



6 7 8 9

Serial Pin Assignments

Pin	1	2	3	4	5	6	7	8	9
RS-232	DCD	RX	TX	DTR	GND	DSR	RTS	CTS	RI
RS-422	TX-	-	-	TX+	GND	-	RX+	-	RX-
RS-485	DATA-	-	-	DATA+	GND	-	-	-	-

銀底黑字

2013.11.20A

2000022232-01

62x105mm

ADVANTECH

ADVANTECH CO., LTD.
 研華股份有限公司
 研華股份有限公司
[Http://www.advantech.com](http://www.advantech.com)
 MADE IN TAIWAN 台灣製造 臺灣研華

Product Name : Serial Device Server

品名 / 品名: 序列設備伺服器/串行設備伺服器

MODEL NO :

型號 / 型號: EKI-1362

INPUT

電源 / 電源: 12-48Vdc === 0.8A max

2-port Industrial RS-232/422/485 to 802.11 b/g/n WLAN Serial Device Server

注意

產品避免撞擊，勿自行拆卸機壳，機台內部無客戶可自行處理部份，若有問題請洽詢專業人員。

聲明

此為A級產品，在生活環境中，該產品可能會造成無線電干擾，在這種情況下，可能需要用戶對其干擾採取切实可行的措施。

CAUTION!

To prevent from electronic shock, do NOT open the case. For safety reasons, the device should be opened only by qualified service personnel.

This device is in complies with requestments in part 15 of the FCC rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

LAN MAC Address	WLAN MAC Address



FCC ID:M82-EKI1362

S/ N	
---------	--

Pin Assignments

Male DB9 (DB9-M)

1 2 3 4 5



6 7 8 9

Serial Pin Assignments

Pin	1	2	3	4	5	6	7	8	9
RS-232	DCD	RX	TX	DTR	GND	DSR	RTS	CTS	RI
RS-422	TX-	-	-	TX+	GND	-	RX+	-	RX-
RS-485	DATA-	-	-	DATA+	GND	-	-	-	-

銀底黑字

2013.11.20A



Label Location