



# RF TEST REPORT



Report No.: 17070315-FCC-R4

Supersede Report No.: N/A

Applicant	Advantech Co Ltd	
Product Name	Mobile Data Terminal	
Model No.	PWS-472	
Serial No.	MICA-052, D300	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	April 22 to May 04, 2017	
Issue Date	May 05, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17070315-FCC-R4
Page	3 of 59

This page has been left blank intentionally.

# CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	9
6.1 ANTENNA REQUIREMENT .....	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH .....	10
6.3 MAXIMUM OUTPUT POWER.....	16
6.4 POWER SPECTRAL DENSITY.....	20
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS.....	24
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	30
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND .....	36
ANNEX A. TEST INSTRUMENT .....	42
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....	43
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....	54
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	58
ANNEX E. DECLARATION OF SIMILARITY.....	59



## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070315-FCC-R4	NONE	Original	May 05, 2017

## 2. Customer information

Applicant Name	Advantech Co Ltd
Applicant Add	No. 1, Alley 20, Lane 26, Rueiguang Road , Neihu District, Taipei , Taiwan
Manufacturer	DOFUNTECH CO., LTD.
Manufacturer Add	A401, No.189 Xinjunhuan Rd., Pujiang Town, Minhang District, Shanghai, China.

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

## 4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Data Terminal
Main Model:	PWS-472
Serial Model:	MICA-052, D300
Date EUT received:	April 21, 2017
Test Date(s):	April 22 to May 04, 2017
Equipment Category :	DTS
Antenna Gain:	BLE/Bluetooth(2.4G): 2.13dBi WIFI(2.4G): 2.13dBi WIFI(5150-5250MHz): 1.92dBi
Antenna Type:	PIFA antenna
Type of Modulation:	Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK 802.11b: DSSS 802.11a/g/n20/n40: OFDM BLE: GFSK
RF Operating Frequency (ies):	Bluetooth/BLE: 2402-2480 MHz 802.11b/g: 2412-2462 MHz (TX/RX) 802.11n20: 2412-2462MHz ; (TX/RX) 802.11n40: 2422-2452 MHz (TX/RX); 802.11 a: 5150-5250 MHz; (TX/RX)
Max. Output Power:	802.11b:13.05 dBm 802.11g: 10.68 dBm 802.11n(20M): 10.26 dBm 802.11n(40M): 10.40 dBm
Number of Channels:	Bluetooth: 79CH WIFI :802.11b/g: 11CH

WIFI :802.11a: 24CH  
WIFI :802.11n20: 11CH(2.4GHz); 24CH(5GHz)  
WIFI :802.11n40: 9CH(2.4GHz); 12CH(5GHz)  
BLE: 40CH

Port: USB Port

Adapter:  
Model: JHD-AP013U-050200BB-A  
Input: AC100-240V~50/60Hz,0.35A  
Output: DC 5.0V,2000mA

Input Power:  
Battery:  
Model: LBP300A  
Spec : 3.7V,3200mAh,11.84Wh  
Maximum chargeable voltage: 4.2V

Trade Name : ADVANTECH

FCC ID: M82-PWS472

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/2.4G WIFI/BLE, the gain is 2.13dBi for Bluetooth/2.4G WIFI/BLE.


A permanently attached PIFA antenna for 5G WIFI, the gain is 1.92dBi for 5G WIFI (5150-5250MHz).

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS Gen(4.6.1)	a)	6dB BW ≥ 500kHz; 20dB BW ≥ 500kHz;	<input checked="" type="checkbox"/>
	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> <li>a) Set RBW = 100 kHz.</li> <li>b) Set the video bandwidth (VBW) ≥ 3 × RBW.</li> <li>c) Detector = Peak.</li> <li>d) Trace mode = max hold.</li> <li>e) Sweep = auto couple.</li> <li>f) Allow the trace to stabilize.</li> <li>g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</li> </ol> <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> <li>1. Set RBW = 1%-5% OBW.</li> <li>2. Set the video bandwidth (VBW) ≥ 3 x RBW.</li> <li>3. Set the span range between 2 times and 5 times of the OBW.</li> <li>4. Sweep time=Auto, Detector=PK, Trace=Max hold.</li> <li>5. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst-</li> </ol>		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

### Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.087	14.26	≥ 0.5
	Mid	2437	9.557	14.27	≥ 0.5
	High	2462	9.542	14.23	≥ 0.5
802.11g	Low	2412	16.05	19.02	≥ 0.5
	Mid	2437	15.74	18.80	≥ 0.5
	High	2462	15.77	18.74	≥ 0.5
802.11n (20M)	Low	2412	16.34	19.43	≥ 0.5
	Mid	2437	17.27	19.34	≥ 0.5
	High	2462	16.92	19.26	≥ 0.5
802.11n (40M)	Low	2422	35.24	39.12	≥ 0.5
	Mid	2437	35.14	38.90	≥ 0.5
	High	2452	36.32	39.61	≥ 0.5

## Test Plots


### 6dB Bandwidth measurement result




802.11b 6dB Bandwidth - Low CH 2412




802.11b 6dB Bandwidth - Mid CH 2437




802.11b 6dB Bandwidth - High CH 2462



802.11g 6dB Bandwidth - Low CH 2412




802.11g 6dB Bandwidth - Mid CH 2437




802.11g 6dB Bandwidth - High CH 2462







802.11n20 6dB Bandwidth - Low CH 2412




802.11n20 6dB Bandwidth - Mid CH 2437




802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422




802.11n40 6dB Bandwidth - Mid CH 2437




802.11n40 6dB Bandwidth - High CH 2452


## 20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - Low CH 2412




802.11b 20dB Bandwidth - Mid CH 2437




802.11b 20dB Bandwidth - High CH 2462




802.11g 20dB Bandwidth - Low CH 2412




802.11g 20dB Bandwidth - Mid CH 2437




802.11g 20dB Bandwidth - High CH 2462




802.11n20 20dB Bandwidth - Low CH 2412




802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437




802.11n40 20dB Bandwidth - High CH 2452

### 6.3 Maximum Output Power

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Loren Luo

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $<50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq 1$ Watt	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set span to at least 1.5 times the OBW.</li> <li>- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.</li> <li>- c) Set VBW <math>\geq 3 \times</math> RBW.</li> <li>- d) Number of points in sweep <math>\geq 2 \times</math> span / RBW. (This gives bin-to-bin spacing <math>\leq</math> RBW/2, so that narrowband signals are not lost between frequency bins.)</li> <li>- e) Sweep time = auto.</li> <li>- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.</li> <li>- g) If transmit duty cycle <math>&lt; 98\%</math>, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum</li> </ul>
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle <math>\geq 98\%</math>, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to " free run" .</p> <ul style="list-style-type: none"> <li>- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.</li> <li>- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument' s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A


Test Plot     Yes (See below)             N/A

**Output Power measurement result**

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	12.42	30	Pass
		Mid	2437	<b>13.05</b>	30	Pass
		High	2462	12.26	30	Pass
	802.11g	Low	2412	9.53	30	Pass
		Mid	2437	<b>10.68</b>	30	Pass
		High	2462	9.85	30	Pass
	802.11n (20M)	Low	2412	9.43	30	Pass
		Mid	2437	<b>10.26</b>	30	Pass
		High	2462	9.62	30	Pass
	802.11n (40M)	Low	2422	9.49	30	Pass
		Mid	2437	<b>10.40</b>	30	Pass
		High	2452	9.61	30	Pass

## Test Plots


### The Average Power




802.11b - AV Output power - Low CH 2412




802.11b - AV Output power - Mid CH 2437




802.11b - AV Output power - High CH 2462




802.11g - AV Output power - Low CH 2412




802.11g - AV Output power - Mid CH 2437




802.11g - AV Output power - High CH 2462




802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437




802.11n20 - AV Output power - High CH 2462



802.11n40 - AV Output power - Low CH 2422



802.11n40 - AV Output power - Mid CH 2437




802.11n40 - AV Output power - High CH 2452



## 6.4 Power Spectral Density

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set analyzer center frequency to DTS channel center frequency.</li> <li>- b) Set the span to 1.5 times the DTS bandwidth.</li> <li>- c) Set the RBW to: <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>- d) Set the VBW <math>\geq 3 \times \text{RBW}</math>.</li> <li>- e) Detector = peak.</li> <li>- f) Sweep time = auto couple.</li> <li>- g) Trace mode = max hold.</li> <li>- h) Allow trace to fully stabilize.</li> <li>- i) Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		



Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A

**Power Spectral Density measurement result**


Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-9.862	8	Pass
		Mid	2437	-6.704	8	Pass
		High	2462	-7.830	8	Pass
	802.11g	Low	2412	-16.624	8	Pass
		Mid	2437	-14.194	8	Pass
		High	2462	-15.708	8	Pass
	802.11n (20M)	Low	2412	-15.603	8	Pass
		Mid	2437	-12.593	8	Pass
		High	2462	-15.705	8	Pass
	802.11n (40M)	Low	2422	-19.743	8	Pass
		Mid	2437	-15.963	8	Pass
		High	2452	-20.531	8	Pass

### Test Plots


#### Power Spectral Density measurement result




PSD - Low CH 2412 - 802.11b




PSD - Mid CH 2437 - 802.11b




PSD - High CH 2462 - 802.11b




PSD - Low CH 2412 - 802.11g




PSD - Mid CH 2437 - 802.11g




PSD - High CH 2462 - 802.11g




PSD - Low CH 2412 - 802.11n20




PSD - Mid CH 2437 - 802.11n20




PSD - High CH 2472 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 - 802.11n40




PSD - High CH 2452 - 802.11n40

## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	22 °C
Relative Humidity	58%
Atmospheric Pressure	1025mbar
Test date :	April 25, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	
------------	--------------------------------------------------------------------------------------


Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul>
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	<ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:               <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data     Yes                       N/A  
 Test Plot     Yes (See below)             N/A

### Test Plots

#### Band Edge measurement result



Date: 25.APR.2017 14:06:14



Date: 25.APR.2017 14:32:43

Band Edge, Left Side (Peak) - 802.11b

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11b


Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)


Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11b

Band Edge, Right Side (Average) - 802.11b



Date: 25.APR.2017 14:10:39



Date: 25.APR.2017 14:51:32

Band Edge, Left Side (Peak) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11g

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)



Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11g

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n20  
**Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz**

Band Edge, Right Side (Peak) - 802.11n20  
**Note: F1 is frequency 2483.5MHz**


Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)


Band Edge, Left Side (Average) - 802.11n20  
**Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz**

Band Edge, Right Side (Average) - 802.11n20  
**Note: F1 is frequency 2483.5MHz**





Date: 25.APR.2017 14:27:03



Date: 25.APR.2017 14:44:10

Band Edge, Left Side (Peak) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11n40

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11n40


Note: F1 is frequency 2483.5MHz

## 6.6 AC Power Line Conducted Emissions

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [μ] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<input checked="" type="checkbox"/>														
		<table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>		Frequency ranges (MHz)	Limit (dBμV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBμV)												
				QP	Average												
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															



Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>
-----------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Test Report No.	17070315-FCC-R4
Page	31 of 59

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot     Yes (See below)             N/A

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------




**Test Data**

**Phase Line Plot at 120Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.1578	37.33	QP	10.03	47.36	65.58	-18.22
2	L1	0.1578	18.26	AVG	10.03	28.29	55.58	-27.29
3	L1	0.4113	23.17	QP	10.03	33.20	57.62	-24.42
4	L1	0.4113	15.06	AVG	10.03	25.09	47.62	-22.53
5	L1	0.6531	31.20	QP	10.03	41.23	56.00	-14.77
6	L1	0.6531	23.20	AVG	10.03	33.23	46.00	-12.77
7	L1	0.9735	23.65	QP	10.03	33.68	56.00	-22.32
8	L1	0.9735	15.14	AVG	10.03	25.17	46.00	-20.83
9	L1	2.3379	21.71	QP	10.05	31.76	56.00	-24.24
10	L1	2.3379	13.72	AVG	10.05	23.77	46.00	-22.23
11	L1	13.5612	46.61	QP	10.20	56.81	60.00	-3.19
12	L1	13.5612	29.47	AVG	10.20	39.67	50.00	-10.33

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------




**Test Data**

**Phase Neutral Plot at 120Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.1578	40.91	QP	10.02	50.93	65.58	-14.65
2	N	0.1578	19.63	AVG	10.02	29.65	55.58	-25.93
3	N	0.3411	27.14	QP	10.02	37.16	59.18	-22.02
4	N	0.3411	6.89	AVG	10.02	16.91	49.18	-32.27
5	N	0.6531	24.90	QP	10.02	34.92	56.00	-21.08
6	N	0.6531	11.29	AVG	10.02	21.31	46.00	-24.69
7	N	2.4822	18.52	QP	10.04	28.56	56.00	-27.44
8	N	2.4822	3.04	AVG	10.04	13.08	46.00	-32.92
9	N	5.4804	17.71	QP	10.08	27.79	60.00	-32.21
10	N	5.4804	1.90	AVG	10.08	11.98	50.00	-38.02
11	N	13.5612	45.89	QP	10.18	56.07	60.00	-3.93
12	N	13.5612	26.08	AVG	10.18	36.26	50.00	-13.74

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------




**Test Data**

**Phase Line Plot at 240Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.2280	41.12	QP	10.03	51.15	62.52	-11.37
2	L1	0.2280	32.60	AVG	10.03	42.63	52.52	-9.89
3	L1	0.3216	40.63	QP	10.03	50.66	59.67	-9.01
4	L1	0.3216	34.32	AVG	10.03	44.35	49.67	-5.32
5	L1	0.6999	34.15	QP	10.03	44.18	56.00	-11.82
6	L1	0.6999	28.27	AVG	10.03	38.30	46.00	-7.70
7	L1	2.0961	29.98	QP	10.04	40.02	56.00	-15.98
8	L1	2.0961	22.95	AVG	10.04	32.99	46.00	-13.01
9	L1	13.5651	38.15	QP	10.20	48.35	60.00	-11.65
10	L1	13.5651	22.95	AVG	10.20	33.15	50.00	-16.85
11	L1	27.3945	19.66	QP	10.44	30.10	60.00	-29.90
12	L1	27.3945	10.78	AVG	10.44	21.22	50.00	-28.78

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------



**Test Data**

**Phase Neutral Plot at 240Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.2280	40.89	QP	10.02	50.91	62.52	-11.61
2	N	0.2280	30.45	AVG	10.02	40.47	52.52	-12.05
3	N	0.3255	37.44	QP	10.02	47.46	59.57	-12.11
4	N	0.3255	30.03	AVG	10.02	40.05	49.57	-9.52
5	N	0.7038	29.08	QP	10.02	39.10	56.00	-16.90
6	N	0.7038	15.56	AVG	10.02	25.58	46.00	-20.42
7	N	1.6515	27.14	QP	10.04	37.18	56.00	-18.82
8	N	1.6515	13.96	AVG	10.04	24.00	46.00	-22.00
9	N	2.8410	25.46	QP	10.05	35.51	56.00	-20.49
10	N	2.8410	10.33	AVG	10.05	20.38	46.00	-25.62
11	N	13.5417	35.81	QP	10.18	45.99	60.00	-14.01
12	N	13.5417	17.51	AVG	10.18	27.69	50.00	-22.31


## 6.7 Radiated Spurious Emissions & Restricted Band

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<input checked="" type="checkbox"/>
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
88 – 216	150												
216 960	200												
Above 960	500												
b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down      <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>											
c)	<p>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</p>	<input checked="" type="checkbox"/>											




<p>Test Setup</p>	
<p>Procedure</p>	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:             <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> <li>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</li> </ol>
<p>Remark</p>	<p>Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.</p>
<p>Result</p>	<p><input checked="" type="checkbox"/> Pass      <input type="checkbox"/> Fail</p>

Test Data     Yes                       N/A

Test Plot     Yes (See below)             N/A

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------

(Below 1GHz)




**Test Data**

**Vertical Polarity Plot @3m**

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	31.5095	38.17	QP	20.24	22.27	0.66	36.80	40.00	-3.20	100	305
2	V	49.5328	50.26	QP	8.61	22.37	0.80	37.30	40.00	-2.70	100	234
3	V	65.1145	51.05	QP	7.56	22.39	0.88	37.10	40.00	-2.90	100	193
4	V	92.4624	53.36	QP	8.59	22.32	0.97	40.60	43.50	-2.90	100	103
5	V	138.3873	46.95	QP	12.70	22.41	1.26	38.50	43.50	-5.00	100	46
6	V	177.5092	43.21	peak	11.20	22.25	1.36	33.52	43.50	-9.98	100	207

**(Below 1GHz)**



*Test Data*

**Horizontal Polarity Plot @3m**

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee (°)
1	H	43.8119	36.76	peak	11.38	22.29	0.76	26.61	40.00	-13.39	100	89
2	H	78.1389	42.39	peak	7.64	22.41	1.02	28.64	40.00	-11.36	100	275
3	H	118.6014	36.68	peak	13.66	22.36	1.16	29.14	43.50	-14.36	100	32
4	H	210.0482	37.01	peak	11.96	22.36	1.57	28.18	43.50	-15.32	100	357
5	H	306.7537	34.25	peak	13.74	22.27	1.82	27.54	46.00	-18.46	100	107
6	H	932.2715	31.96	peak	22.66	20.82	3.13	36.93	46.00	-9.07	100	333

**Above 1GHz**

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------

**Low Channel (2412 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	38.85	AV	V	33.8	6.86	32.69	46.82	54	-7.18
4824	38.19	AV	H	33.8	6.86	32.69	46.16	54	-7.84
4824	48.04	PK	V	33.8	6.86	32.69	56.01	74	-17.99
4824	47.71	PK	H	33.8	6.86	32.69	55.68	74	-18.32
17902	24.37	AV	V	45.12	11.57	32.11	48.95	54	-5.05
17902	22.98	AV	H	45.12	11.57	32.11	47.56	54	-6.44
17902	40.48	PK	V	45.12	11.57	32.11	65.06	74	-8.94
17902	39.19	PK	H	45.12	11.57	32.11	63.77	74	-10.23

**Middle Channel (2437 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	39.13	AV	V	33.6	6.82	32.71	46.84	54	-7.16
4874	38.89	AV	H	33.6	6.82	32.71	46.6	54	-7.4
4874	48.27	PK	V	33.6	6.82	32.71	55.98	74	-18.02
4874	47.56	PK	H	33.6	6.82	32.71	55.27	74	-18.73
17933	23.92	AV	V	45.17	11.63	32.18	48.54	54	-5.46
17933	22	AV	H	45.17	11.63	32.18	46.62	54	-7.38
17933	40.42	PK	V	45.17	11.63	32.18	65.04	74	-8.96
17933	39.73	PK	H	45.17	11.63	32.18	64.35	74	-9.65

**High Channel (2462 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4924	39.35	AV	V	33.83	6.95	32.79	47.34	54	-6.66
4924	38.76	AV	H	33.83	6.95	32.79	46.75	54	-7.25
4924	47.73	PK	V	33.83	6.95	32.79	55.72	74	-18.28
4924	47.81	PK	H	33.83	6.95	32.79	55.8	74	-18.2
17924	23.34	AV	V	45.19	11.61	32.24	47.9	54	-6.1
17924	22.8	AV	H	45.19	11.61	32.24	47.36	54	-6.64
17924	40.16	PK	V	45.19	11.61	32.24	64.72	74	-9.28
17924	39.55	PK	H	45.19	11.61	32.24	64.11	74	-9.89

**Note:**

- 1, The testing has been conformed to  $10 \times 2462 \text{ MHz} = 24,620 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>

## Annex B. EUT and Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View





EUT - Front View



EUT - Rear View






EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



**Annex B.ii. Photograph: EUT Internal Photo**

Cover Off - Top View 1



Cover Off - Top View 2






Test Report No.	17070315-FCC-R4
Page	48 of 59


Battery - Front View




Battery - Rear View



Barcode scanner engine board - Front View




Barcode scanner engine board - Rear View







Mainboard – Front View




Mainboard - Rear View



LCD – Front View




LCD – Rear View





BT/BLE/2.4 G WIFI/5G WIFI Antenna View







**Annex B.iii. Photograph: Test Setup Photo**




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz


## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


#### Block Configuration Diagram for AC Line Conducted Emissions



**Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .**



**Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .**



## **Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

### **Supporting Equipment:**

<b>Manufacturer</b>	<b>Equipment Description</b>	<b>Model</b>	<b>Serial No</b>
Advantech Co Ltd	Adapter	JHD-AP013U-050200BB-A	BE452

### **Supporting Cable:**

<b>Cable type</b>	<b>Shield Type</b>	<b>Ferrite Core</b>	<b>Length</b>	<b>Serial No</b>
USB Cable	Un-shielding	No	0.8m	BE452

Test Report No.	17070315-FCC-R4
Page	58 of 59

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

## Annex E. DECLARATION OF SIMILARITY

Advantech Co Ltd

To: SIEMIC, 775 Montague Expressway, Milpitas, CA 95035, USA

### Declaration Letter

Dear Sir,

For our business issue and marketing requirement, we would like to list (3) model numbers on the FCC certificates and reports, as following:

Model No.: PWS-472, MICA-052, D300


We declare that, all the model PCB, Antenna and Appearance shape, accessories are the same.

The difference of these is listed as below:

Main Model No	Serial Model No	Difference
PWS-472	MICA-052, D300	Different name and color

Thank you!

Signature:



Printed name/title: Lily Huang

Tel: 886-2-2218-4567-7293

Fax: 886-2-2794-7305

Address: No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei, Taiwan 114