RADIO TEST REPORT FCC 47 CFR PART 15 SUBPART E

Test Standard	FCC Part 15.407
FCC ID	M82-UTC520FPIKA0E
Product name	Computer
Brand Name	ADVANTECH
Model No.	UTC-520F, UTC-520FXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
Test Result	Pass

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)



Approved by:

ven Cleang

Sam Chuang Manager

Reviewed by:

eny Ching

Jerry Chuang Engineer





Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 31, 2018	Initial Issue	ALL	Allison Chen
01	March 28, 2018	 Removed AC function information. Added KDB 662911 V02r01. Removed the EIRP limit in section 4.3.1. Added test procedure for 99% OBW in section 4.2.2 and test plot for 99% OBW in section 4.2.4. Revised test plot of channel move time. 	P.5, P.8, P.10, P.16, P42-62, P.63, P.229	Allison Chen

Table of contents

1.	GENERAL INFORMATION
1.1	EUT INFORMATION
1.2	EUT CHANNEL INFORMATION
1.3	ANTENNA INFORMATION
1.4	MEASUREMENT UNCERTAINTY 6
1.5	FACILITIES AND TEST LOCATION7
1.6	INSTRUMENT CALIBRATION
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT
1.8	TEST METHODOLOGY AND APPLIED STANDARDS
2.	TEST SUMMERY9
3.	DESCRIPTION OF TEST MODES
3.1	THE WORST MODE OF OPERATING CONDITION 10
3 2	
J.Z	
3.3	EUT DUTY CYCLE
3.3 4.	EUT DUTY CYCLE
3.3 4. 4.1	THE WORST MODE OF MEASUREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13
 3.3 4. 4.1 4.2 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16
 3.3 4. 4.1 4.2 4.3 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT 63
 3.3 4. 4.1 4.2 4.3 4.4 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT 63 POWER SPECTRAL DENSITY 67
 3.3 4. 4.1 4.2 4.3 4.4 4.5 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT 63 POWER SPECTRAL DENSITY 67 RADIATION BANDEDGE AND SPURIOUS EMISSION 94
 3.3 4. 4.1 4.2 4.3 4.4 4.5 4.6 	THE WORST MODE OF MEASUREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT 63 POWER SPECTRAL DENSITY 67 RADIATION BANDEDGE AND SPURIOUS EMISSION 94 FREQUENCY STABILITY 214
 3.3 4. 4.1 4.2 4.3 4.4 4.5 4.6 4.7 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT. 63 POWER SPECTRAL DENSITY 67 RADIATION BANDEDGE AND SPURIOUS EMISSION 94 FREQUENCY STABILITY 214 DYNAMIC FREQUENCY SELECTION 217
 3.3 4. 4.1 4.2 4.3 4.4 4.5 4.6 4.7 API 	THE WORST MODE OF MEASOREMENT 11 EUT DUTY CYCLE 12 TEST RESULT 13 AC POWER LINE CONDUCTED EMISSION 13 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%) 16 OUTPUT POWER MEASUREMENT 63 POWER SPECTRAL DENSITY 67 RADIATION BANDEDGE AND SPURIOUS EMISSION 94 FREQUENCY STABILITY 214 DYNAMIC FREQUENCY SELECTION 217 PENDIX-A TEST PHOTO A-1

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Advantech Co.Ltd. No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.						
Manufacturer	Advantech Co.Ltd. No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.						
Equipment	Computer						
Model No.	UTC-520F, alphanumer	UTC-520FXXXXXXXX c character , "-" or blar	XXXXXXXXX (nk)	(where "X"	may be any		
Model Discrepancy	All the abo model num number is j	ve models are ident bers. The suffix of (ust for marketing pur	ical except f (X= a-z / 0- pose only.	for the de 9 or blank	signation of () on model		
Received Date	December 0	8, 2017					
Date of Test	January 18 ~ January 26, 2018						
Power Operation	Powered from AC adapter. Brand / Model: FSP / FSP084-DIBAN2 Input: 100-240Vac, 1.3A, 50-60Hz Output: 12Vdc, 7A						
	Band	Mode	Frequency Range (MHz)	Output Power (W)			
		IEEE 802.11a	5180 ~ 5240	0.0692			
	U-NII-1	IEEE 802.11n 20 MHz	5180 ~ 5240	0.1475			
		IEEE 802.11n 40 MHz	5190 ~ 5230	0.0522			
		IEEE 802.11a	5260 ~ 5320	0.0695			
	U-NII-2a	IEEE 802.11n 20 MHz	5260 ~ 5320	0.0646			
Output Power(vv)		IEEE 802.11n 40 MHz	5270 ~ 5310	0.0460			
		IEEE 802.11a	5500 ~ 5700	0.0508			
	U-NII-2c	IEEE 802.11n 20 MHz	5500 ~ 5700	0.0508			
		IEEE 802.11n 40 MHZ	5510 ~ 5670	0.0478			
			5745 ~ 5825	0.0341			
	U-INII-3		5745 ~ 5825	0.0391			
			3733 ~ 3793	0.0348			

1.2 EUT CHANNEL INFORMATION

	UNII-1				
	IEEE 802.11a	5180 ~ 5240 MHz			
	IEEE 802.11n 20 MHz	5180 ~ 5240 MHz			
	IEEE 802.11n 40 MHz	5190 ~ 5230 MHz			
	UNII-2a				
	IEEE 802.11a	5260 ~ 5320 MHz			
	IEEE 802.11n 20 MHz	5260 ~ 5320 MHz			
Fraguanay Panga	IEEE 802.11n 40 MHz	5270 ~ 5310 MHz			
Frequency Range	UNII-2c				
	IEEE 802.11a	5500 ~ 5700 MHz			
	IEEE 802.11n 20 MHz	5500 ~ 5700 MHz			
	IEEE 802.11n 40 MHz	5510 ~ 5670 MHz			
	UNII-3				
	IEEE 802.11a	5745 ~ 5825 MHz			
	IEEE 802.11n 20 MHz	5745 ~ 5825 MHz			
	IEEE 802.11n 40 MHz	5755 ~ 5795 MHz			
Modulation Type	1. IEEE 802.11a mode: OFDM 2. IEEE 802.11n 20 MHz mode: 3. IEEE 802.11n 40 MHz mode:	OFDM OFDM			

Remark:

Refer as ANSI 63.10:2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested					
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation			
1 MHz or less	1	Middle			
1 MHz to 10 MHz	2	1 near top and 1 near bottom			
More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom			

1.3 ANTENNA INFORMATION

Antenna Type	PIFA PCB Dipole Coils						
Antenna Gain	Ant 1	Description WIFI black	Type PIFA	Peak Gain 6.42dBi			
	Ant 2 Pow	WIFI white er Directional Gain	PIFA	5.50dBi			

Notes:

1. Power Directional Gain: 10LOG(((10^(Ant1/10)+10^(Ant2/10))/2))

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Eric Lee	-
Radiation	Jerry Chuang	-
RF Conducted	Jerry Chuang	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

3M 966 Chamber Test Site						
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due	
Bilog Antenna	Sunol Sciences	JB3	A030105	06/20/2017	06/19/2018	
Horn Antenna	EMCO	3117	55165	02/20/2017	02/19/2018	
Pre-Amplifier	EMEC	EM330	60609	06/07/2017	06/06/2018	
Spectrum Analyzer	Agilent	E4446A	US42510252	11/27/2017	11/26/2018	
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R	
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R	
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R	
Pre-Amplifier	HP	8449B	3008A00965	06/27/2017	06/26/2018	
Filter	N/A	2400-2500	N/A	N/A	N/A	
Filter	N/A	0-6000	N/A	N/A	N/A	
Cable	HUBER SUHNER	SUCOFLEX 104PEA	25157	07/31/2017	07/30/2018	
Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	07/31/2017	07/30/2018	

RF Conducted Test Site						
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due	
Power Meter	Anritsu	ML2495A	1033009	04/11/2017	04/10/2018	
Power Sensor	Anritsu	MA2411B	917072	07/03/2017	07/02/2018	
Spectrum Analyzer	R&S	FSV 40	101073	10/02/2017	10/01/2018	
Directional Coupler	Agilent	87301D	MY44350252	07/25/2017	07/24/2018	
SUCOFLEX Cable	HUBER SUHNER	SUCOFLEX 104PEA	25157	07/31/2017	07/30/2018	
Divider	Solvang Technology	2-18GHz 4Way	STI08-0015	07/26/2017	07/25/2018	

Remark: Each piece of equipment is scheduled for calibration once a year.

AC line Conduction Test Room						
Equipment Manufacturer Model S/N Cal Date Cal Due						
Bilog Antenna	Sunol Sciences	JB3	A030105	06/20/2017	06/19/2018	
Horn Antenna	EMCO	3117	55165	02/20/2017	02/19/2018	
Pre-Amplifier	EMEC	EM330	60609	06/07/2017	06/06/2018	

Remark: Each piece of equipment is scheduled for calibration once a year.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment								
No.	Equipment Brand Model Series No. FCC ID							
	N/A							

Support Equipment								
No.	No. Equipment Brand Model Series No. FCC ID							
	N/A							

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.407, KDB 789033 D02 v02r01, KDB 905462 D02 v02, KDB 662911D01 V02r01.

2. TEST SUMMERY

FCC Standard Sec.	Chapter	Test Item	Result
15.203	1.2	Antenna Requirement	Pass
15.207	4.1	AC Conducted Emission	Pass
15.403(i)	4.2	26dB Bandwidth	Pass
15.407(e)	4.2	6dB Bandwidth	Pass
15.403(i)	4.2	Occupied Bandwidth (99%)	Pass
15.407(a)	4.3	Output Power Measurement	Pass
15.407(a)	4.4	Power Spectral Density	Pass
15.407(b)	4.5	Radiation Band Edge	Pass
15.407(b)	4.5	Radiation Spurious Emission	Pass
15.407(g)	4.6	Frequency Stability	Pass
15.407(h)	4.7	Dynamic Frequency Selection	Pass

ELERF Compliance Certification Services Inc. FCC ID: M82-UTC520FPIKA0E

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	1. IEEE 802.11a mode: 6Mbps 2. IEEE 802.11n 20 MHz mode: MCS8 3. IEEE 802.11n 40 MHz mode: MCS8							
		Mode	Frequency Range (MHz)	Number of Channels				
		IEEE 802.11a	5180 ~ 5240	4 Channels				
	U-NII-1	IEEE 802.11n 20 MHz	5180 ~ 5240	4 Channels				
		IEEE 802.11n 40 MHz	5190 ~ 5230	2 Channels				
Operating Frequency		IEEE 802.11a	5260 ~ 5320	4 Channels				
	U-NII-2a	IEEE 802.11n 20 MHz	5260 ~ 5320	4 Channels				
Range &		IEEE 802.11n 40 MHz	5270 ~ 5310	2 Channels				
Number of Channels		IEEE 802.11a	5500 ~ 5700	11 Channels				
	U-NII-2c	IEEE 802.11n 20 MHz	5500 ~ 5700	11 Channels				
		IEEE 802.11n 40 MHz	5510 ~ 5670	5 Channels				
		IEEE 802.11a	5745 ~ 5825	5 Channels				
	U-NII-3	IEEE 802.11n 20 MHz	5745 ~ 5825	5 Channels				
		IEEE 802.11n 40 MHz	5755 ~ 5795	2 Channels				

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

2. Covered modes are test reduction modes. The output powers on the covered modes are equal to or less than the mode referenced and use the same module

3. The mode IEEE 802.11ac VHT20 and VHT40 are only different in control messages with IEEE 802.11n 20 MHz and HT40, and have same power setting. Therefore, the highest power(IEEE 802.11n 20 MHz and HT40) were test conducted and radiated measurement and recorded in this report.

Compliance Certification Services Inc. FCC ID: M82-UTC520FPIKA0E

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission				
Test Condition	AC Power line conducted emission for line and neutral			
Voltage/Hz	120V/60Hz			
Test Mode	Mode 1:EUT power by AC adapter via power cable.			
Worst Mode	🛛 Mode 1 🗌 Mode 2 🗌 Mode 3 🗌 Mode 4			

Radiated Emission Measurement Above 1G				
Test Condition	Band edge, Emission for Unwanted and Fundamental			
Voltage/Hz	120V/60Hz			
Test Mode	Test Mode Mode 1:EUT power by AC adapter via power cable.			
Worst Mode	Mode 1 🗌 Mode 2 🗌 Mode 3 🗌 Mode 4			
Worst Position	 Placed in fixed position. Placed in fixed position at X-Plane (E2-Plane) Placed in fixed position at Y-Plane (E1-Plane) Placed in fixed position at Z-Plane (H-Plane) 			
Worst Polarity	Horizontal 🗌 Vertical			

Radiated Emission Measurement Below 1G						
Test Condition Radiated Emission Below 1G						
Voltage/Hz 120V/60Hz						
Test Mode	Test Mode Mode 1:EUT power by AC adapter via power cable.					
Worst Mode	Worst Mode Mode 1 Mode 2 Mode 3 Mode 4					

Remark:

1. The worst mode was record in this test report.

2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, Horizontal and Vertical for radiated measurement. The worst case(Z-Plane and Horizontal) were recorded in this report

3. For below 1G, AC power line conducted emission and radiation emission were performed the EUT transmit at the highest output power channel as worse case.

3.3 EUT DUTY CYCLE

Duty Cycle						
Configuration	TX ON (ms)	TX ALL (ms)	Duty Cycle (%)	Duty Factor(dB)		
802.11a	2.0500	2.0700	99.03%	0.04		
802.11n 20	2.0500	2.0700	99.03%	0.04		
802.11n 40	0.9600	0.9700	98.97%	0.05		



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

Frequency Range	Limits(dB	μV)
(MHz)	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI 63.10:2013 clause 6.2,

- 1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
- 2. EUT connected to the line impedance stabilization network (LISN)
- 3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



Pass.

<u>Test Data</u>





4.2 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

4.2.1 Test Limit

26 dB Bandwidth : For reporting purposes only.

6 dB Bandwidth : Least 500kHz.

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as KDB 789033 D02 v02r01 Section C, D, and ANSI 63.10:2013 clause 6.9.2,

- 1. The EUT RF output connected to the spectrum analyzer by RF cable.
- 2. Setting maximum power transmit of EUT
- 3. UNII-1, UNII-2a and UNII-2c,

(1) BW=20MHz : SA set RBW = 300kHz, VBW = 1MHz and Detector = Peak, to measurement 26 dB Bandwidth.

(2) BW=40MHz : SA set RBW = 1MHz, VBW = 3MHz and Detector = Peak, to measurement 26 dB Bandwidth.

(3) BW=80MHz : SA set RBW = 1MHz, VBW = 3MHz and Detector = Peak, to measurement 26 dB Bandwidth.

- 4. UNII-3, SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 26 dB Bandwidth.
- 5. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth.
- 6. Measure and record the result of 6 dB, 26 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



4.2.4 Test Result

	UNII-1 5150-5250 MHz						
	Те	st mode: IEEE	802.11a mode				
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)		
Low	5180	17.0767	16.6425	26.4493	24.3478		
Mid	5220	16.7872	16.6425	24.058	24.5652		
High	5240	16.7872	16.7872	26.087	24.7826		
	Test m	ode: IEEE 802.	11n 20 MHz mo	ode			
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)		
Low	5180	17.9450	17.9450	30.4348	28.1884		
Mid	5220	17.8002	17.8002	29.5652	25.7971		
High	5240	17.9450	17.8002	27.7536	25.2174		
	Test m	ode: IEEE 802.	11n 40 MHz mo	ode			
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)		
Low	5190	36.5846	36.7004	50.087	50.667		
High	5230	36.9319	36.5846	49.623	49.623		



UNII-2a 5250-5350 MHz						
	1	est mode: IEEI	E 802.11a mode)		
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)	
Low	5260	17.0767	16.7149	28.1884	24.6337	
Mid	5280	17.0767	16.7872	29.7826	26.1594	
High	5320	17.2937	16.7872	33.4783	25.1449	
	Test	mode: IEEE 80	2.11n 20 MHz m	node		
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)	
Low	5260	17.9450	17.8002	32.2464	24.7826	
Mid	5280	18.0173	17.8002	31.8116	24.5652	
High	5320	18.2344	17.8726	28.9855	26.5217	
	Test	mode: IEEE 80	2.11n 40 MHz m	node		
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)	
Low	5270	36.7004	36.5846	49.739	49.855	
High	5310	36.7004	36.5846	50.435	50.087	

UNII-2c 5475-5725 MHz								
	Test mode: IEEE 802.11a mode							
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)			
Low	5500	17.0043	16.7872	30.3623	27.1014			
Mid	5580	17.0767	18.0173	29.058	34.1304			
High	5700	16.7872	16.9319	23.9855	29.7826			
	Test	mode: IEEE 80	2.11n 20 MHz m	node				
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)			
Low	5500	18.0897	17.8726	32.3188	29.8551			
Mid	5580	19.3198	18.5962	34.5652	32.6812			
High	5700	17.8002	17.8726	25.2174	27.5362			
	Test	mode: IEEE 80	2.11n 40 MHz m	node				
Channel	ChannelFrequency (MHz)Chain 0 OBW(99%) (MHz)Chain 1 OBW(99%) (MHz)Chain 1 OBW(99%) (MHz)Chain 0 26dB BW (MHz)Chain 1 26dB BW (MHz)							
Low	5510	36.7004	36.7004	49.855	50.319			
Mid	5500	36.8162	36.5846	49.971	51.594			
High	5670	37.6266	37.3950	50.319	49.971			

UNII-3 5725-5825MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	17.1490	16.7872	16.3478	16.0435
Mid	5785	17.0043	17.0767	16.2609	16.3043
High	5825	16.8596	17.0767	15.6957	15.913
Test mode: IEEE 802.11n 20 MHz mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	18.0897	17.8726	17.1739	16.913
Mid	5785	17.9450	18.2344	16.3043	16.913
High	5825	17.9450	18.4515	16.3043	16.6522
Test mode: IEEE 802.11n 40 MHz mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5755	37.2793	36.5846	35.478	35.478
High	5795	37.1635	36.5846	36.058	35.478

<u>26dB</u>

































Compliance Certification Services Inc. FCC ID: M82-UTC520FPIKA0E



Compliance Certification Services Inc. FCC ID: M82-UTC520FPIKA0E



6dB



























Compliance Certification Services Inc. FCC ID: M82-UTC520FPIKA0E

Test Data







