

# **RF Exposure Report**

Report No.: SABEAD-WTW-P22010204

FCC ID: M82-WIEE-2200

Test Model: WISE-2200-M

Received Date: Jan. 06, 2022

Date of Evaluation: Feb. 21, 2022

Issued Date: Mar. 03, 2022

Applicant: ADVANTECH CO., LTD

Address: No.1, Alley 20, Lane 26, Rueiguang Rd, Neihu District, Taipei, Taiwan 114

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN

FCC Registration /

788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABEAD-WTW-P22010204 Page No. 1 / 5 Report Format Version: 6.1.1



## **Table of Contents**

Rele	ease Control Record	3
1	Certificate of Conformity	4
	RF Exposure	
2.	1 Limits for Maximum Permissible Exposure (MPE)	5
	2 MPE Calculation Formula	
2.3	3 Classification	5
2.4	4 Calculation Result of Maximum Conducted Power	5



## **Release Control Record**

Issue No.	Description	Date Issued
SABEAD-WTW-P22010204	Original Release	Mar. 03, 2022

Report No.: SABEAD-WTW-P22010204 Page No. 3 / 5 Report Format Version: 6.1.1



### 1 Certificate of Conformity

Product: LoRaWAN Smart I/O Module

**Brand:** ADVANTECH

Test Model: WISE-2200-M

Sample Status: Engineering Sample

Applicant: ADVANTECH CO., LTD

Date of Evaluation: Feb. 21, 2022

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance:

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: \_\_\_\_\_\_, Date: \_\_\_\_\_\_, Mar. 03, 2022

Vera Huang / Specialist

Jeremy Lin / Project Engineer

Report No.: SABEAD-WTW-P22010204 Page No. 4 / 5 Report Format Version: 6.1.1



#### 2 RF Exposure

#### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	e Electric Field Magnetic Field Strength (V/m) Strength (A/m)		Power Density (mW/cm²)	Average Time (minutes)					
Limits For General Population / Uncontrolled Exposure									
0.3-1.34	614	1.63	(100)*	30					
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30					
30-300	27.5	0.073	0.2	30					
300-1500			f/1500	30					
1500-100,000			1.0	30					

f = Frequency in MHz; \*Plane-wave equivalent power density

## 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

#### 2.4 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm²)
(IVITZ)	(ubiii)	(ubi)	(cm)	(IIIVV/CIII-)	(11100/0111-)
902.3 ~ 914.9	18.01	1.06	20	0.016	0.60

#### Note:

- 1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible

--- END ---