

# **RF Exposure Report**

Report No.: SA190429C33A

FCC ID: M82-WISE-1840

Test Model: WISE-1840

Received Date: Jun. 22, 2020

Test Date: Aug. 05 ~ Sep. 30, 2020

**Issued Date:** Oct. 13, 2020

Applicant: ADVANTECH CO., LTD

Address: No. 1, Alley 20, Lane 26, Rueiguang Rd, Neihu District, Taipei, Taiwan 114

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN

FCC Registration / 788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of his report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SA190429C33A Page No. 1 / 6 Report Format Version: 6.1.1 Reference No.: 200618C06



# **Table of Contents**

Rele	ase Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2.2	Limits for Maximum Permissible Exposure (MPE)	. 5
3	Calculation Result of Maximum Conducted Power	. 6



# **Release Control Record**

Issue No.	Description	Date Issued
SA190429C33A	Original release	Oct. 13, 2020

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA190429C33A Reference No.: 200618C06



### 1 Certificate of Conformity

Product: Mini-PCle EPD control card

Brand: Advantech

Test Model: WISE-1840

Sample Status: Engineering sample

Applicant: ADVANTECH CO., LTD

**Test Date:** Aug. 05 ~ Sep. 30, 2020

Standards: FCC Part 2 (Section 2.1091)

IEEE C95.3 -2002

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance:

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Propagad by: Date: Oct 13 2020

Polly Chien / Specialist

Approved by: , Date: Oct. 13, 2020

Bruce Chen / Senior Project Engineer



### 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	. , ,		Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; \*Plane-wave equivalent power density

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

Report No.: SA190429C33A Page No. 5 / 6 Report Format Version: 6.1.1



#### 3 Calculation Result of Maximum Conducted Power

Module	Max AV. Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
1	15.14	5.03	20	0.021	1
2	14.36	5.03	20	0.017	1

#### Note

- 1. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
- 2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

#### Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Module 1+Module 2 = 0.021 / 1 + 0.017 / 1 = 0.038 < 1

---END---

Report No.: SA190429C33A Page No. 6 / 6 Report Format Version: 6.1.1 Reference No.: 200618C06