



FCC ID: M82-WP7610  
Report No.: T200207D01-MF

Page: 1 / 11  
Rev.: 03

**KDB 447498 D03**  
**47 C.F.R. Part 1, Subpart I, Section 1.1310**  
**47 C.F.R. Part 2, Subpart J, Section 2.1091**

## **RF EXPOSURE REPORT**

**For**

**Module**

**Model No.: WP7610**

**Trade Name: Advantech; Advantech Service-IoT**

*Issued to*

**Advantech Co., Ltd.**  
**No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114,**  
**Taiwan, R.O.C.**

*Issued by*

**Compliance Certification Services Inc.**  
**Wugu Laboratory**  
**No.11, Wugong 6th Rd., Wugu Dist.,**  
**New Taipei City 24891, Taiwan. (R.O.C.)**  
**Issue Date: January 14, 2021**

**Note:** *This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.*

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T200207D01-MF

Page: 2 / 11

Rev.: 03

### Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 12, 2020	Initial Issue	ALL	Angel Cheng
01	November 16, 2020	Add LTE Band 13, 14, 17, 66	ALL	Angel Cheng
02	December 22, 2020	Add section 6.	ALL	Angel Cheng
03	January 14, 2021	Revised section 6.	P.11	Angel Cheng



## TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION .....	4
2. LIMIT .....	5
3. EUT SPECIFICATION.....	6
4. TEST RESULTS.....	8
5. MAXIMUM PERMISSIBLE EXPOSURE.....	9
6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS.....	11



Report No.: T200207D01-MF

## 1. TEST RESULT CERTIFICATION

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
IEEE C95.1 2005 KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:

---

Kevin Tsai  
Deputy Manager  
Compliance Certification Services Inc.



Report No.: T200207D01-MF

Page: 5 / 11

Rev.: 03

## 2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

### 3. EUT SPECIFICATION

<b>EUT</b>	Module
<b>Model</b>	WP7610
<b>Model Discrepancy</b>	N/A
<b>Received Date</b>	February 7, 2020
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WCDMA / HSDPA / HSUPA Band II: 1852.4 ~ 1907.6 MHz <input checked="" type="checkbox"/> WCDMA / HSDPA / HSUPA Band V: 826.4 ~ 846.6MHz <input checked="" type="checkbox"/> WCDMA / HSDPA / HSUPA / HSPA+ Band IV: 1712.4-1752.6 MHz <input checked="" type="checkbox"/> LTE Band 2: 1850MHz ~ 1910MHz <input checked="" type="checkbox"/> LTE Band 4: 1710MHz ~ 1755MHz <input checked="" type="checkbox"/> LTE Band 5: 824MHz ~ 849MHz <input checked="" type="checkbox"/> LTE Band 12: 699 MHz ~ 716 MHz <input checked="" type="checkbox"/> LTE Band 13: 779.5MHz ~ 784.5MHz <input checked="" type="checkbox"/> LTE Band 14: 790.5MHz ~ 795.5MHz <input checked="" type="checkbox"/> LTE Band 17: 706.5MHz ~ 713.5MHz <input checked="" type="checkbox"/> LTE Band 66: 1710.7MHz ~1779.3MHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure Frequency Range 300MHz~1500MHz = f/1500 (mW/cm <sup>2</sup> ) Frequency Range 1500MHz~100000MHz = 1 (mW/cm <sup>2</sup> )
<b>Antenna Specification</b>	<b>WWAN</b> <b>PIFA Antenna</b> WCDMA Band II: Directional Gain : 1.37 dBi (Numeric gain: 1.37) Worst WCDMA Band IV: Directional Gain : 1.37 dBi (Numeric gain: 1.37) Worst WCDMA Band V: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 2: Directional Gain : 1.37 dBi (Numeric gain: 1.37) Worst LTE Band 4: Directional Gain : 1.37 dBi (Numeric gain: 1.37) Worst LTE Band 5: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 12: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 13: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 14: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 17: Directional Gain : 2.26 dBi (Numeric gain: 1.68) Worst LTE Band 66: Directional Gain : 1.37 dBi (Numeric gain: 1.37) Worst

<p><b>Maximum Measurement Average Power</b></p>	<p><b>WWAN</b></p> <p>WCDMA Band II: 23.00 dBm (199.526 mW)  WCDMA Band IV: 23.00 dBm (199.526 mW)  WCDMA Band V: 23.50 dBm (223.872 mW)  LTE Band 2: 22.32 dBm (170.608 mW)  LTE Band 4: 22.25 dBm (167.880 mW)  LTE Band 5: 22.67 dBm (184.927 mW)  LTE Band 12: 22.76 dBm (188.799 mW)  LTE Band 13: 23.77 dBm (238.232 mW)  LTE Band 14: 23.92 dBm (246.604 mW)  LTE Band 17: 23.55 dBm (226.464 mW)  LTE Band 66: 22.82 dBm (191.426 mW)</p>
<p><b>Maximum tune up power</b></p>	<p><b>WWAN</b></p> <p>WCDMA Band II: 24.00 dBm (251.189 mW)  WCDMA Band IV: 24.00 dBm (251.189 mW)  WCDMA Band V: 24.50 dBm (281.838 mW)  LTE Band 2: 24.00 dBm (251.189 mW)  LTE Band 4: 24.00 dBm (251.189 mW)  LTE Band 5: 24.50 dBm (281.838 mW)  LTE Band 12: 24.00 dBm (251.189 mW)  LTE Band 13: 24.00 dBm (251.189 mW)  LTE Band 14: 24.50 dBm (281.838 mW)  LTE Band 17: 24.00 dBm (251.189 mW)  LTE Band 66: 24.00 dBm (251.189 mW)</p>
<p><b>Evaluation applied</b></p>	<p><input checked="" type="checkbox"/> MPE Evaluation*  <input type="checkbox"/> SAR Evaluation  <input type="checkbox"/> N/A</p>

**Remark:**

1. *Disclaimer*

*Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.*

## 4. TEST RESULTS

**No non-compliance noted.**

### Calculation

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{377}$

Where  $E =$  Field strength in Volts / meter

$P =$  Power in Watts

$G =$  Numeric antenna gain

$d =$  Distance in meters

$S =$  Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where  $d =$  Distance in cm

$P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>



Report No.: T200207D01-MF

## 5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power density in mW / cm<sup>2</sup>

### WCDMA Band II mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
9262	1852.4	199.526	1.37	20	0.0544	1

### WCDMA Band IV mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
1312	1712.4	199.526	1.37	20	0.0544	1

### WCDMA Band V mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
4132	826.4	223.872	1.68	20	0.0748	0.55

### LTE Band 2 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
18900	1880	170.608	1.37	20	0.0465	1

### LTE Band 4 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
20050	1720	167.880	1.37	20	0.0458	1

### LTE Band 5 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
20450	829	184.927	1.68	20	0.0618	0.55

### LTE Band 12 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
23060	704	188.799	1.68	20	0.0631	0.469

Report No.: T200207D01-MF

**LTE Band 13 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
23230	782	238.232	1.68	20	0.0796	0.521

**LTE Band 14 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
23330	793	246.604	1.68	20	0.0824	0.529

**LTE Band 17 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
23780	709	226.464	1.68	20	0.0757	0.473

**LTE Band 66 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
72	1720	191.426	1.37	20	0.0522	1.147



## 6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS

Both of the WiFi、BT and WWAN can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

### WiFi、BT and WWAN

Therefore, the worst-case situation is  $0.13118 / 1 + 0.00666 / 1 + 0.0824 / 0.529 = 0.2936$ , which is less than "1".

Notes: Wifi module power form FCC ID: PPQ-QCNFA324.

**--End of Report--**