

Radio Satellite Communication

Untertürkheimer Straße 6-10 . D-66117 Saarbrücken Telefon: +49 (0)681 598-9100 Telefax: -9075

RSC11

issue test report consist of 72 Pages

Page 1 (72)



Accredited Bluetooth Test Facility (BQTF)

Test report no.: 3_3095-01-04/02 FCC Part 24 P52-0 FCC ID: M9H95370000

CETECOM – ICT Services GmbH Untertürkheimerstr. 6-10 66117 Saarbrücken, Germany

Telephone: + 49 (0) 681 / 598-0 Fax: + 49 (0) 681 / 9075



Test report no.:3 3095-01-04/02 Issue date: 2002-01-29 Page 2 (72)

Table of Contents

1 **General information**

- 1.1 **Notes**
- 1.2
- Testing laboratory Details of applicant Application details 1.3
- 1.4
- 1.5 **Test item**
- **Test standards**
- 2 **Technical test**
- 2.1 2.2 Summary of test results
- Test report
- 1 General information

1.1 **Notes**

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

1.2 **Testing laboratory**

CETECOM ICT Services GmbH Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Telefone : +49 681 598 - 9100 Telefax : +49 681 598 - 9075

E-mail : Michael.Berg@ict.cetecom.de

: www.cetecom.de Internet Accredited testing laboratory

DAR-registration number: TTI-P-G-166/98-30 Accredited Bluetooth[™] Test Facility (BQTF)

BLUETOOTH[™] is a trademark owned by Bluetooth SIG, Inc. and licensed to CETECOM



1.3 Details of applicant

Name : SAGEM SA

Street : 2-4 rue de Petit Albi

City : F-95800 Cergy Saint Christophe

Country: France

Telephone: +33 -1 -3073-7277 Telefax: +33 -1 -3425-7416 Contact: Mr. Jean Marquet Telephone: +33 -1 -3073-3737

1.4 Application details

Date of receipt of application : 22.01.2002
Date of receipt of test item : 22.01.2002
Date of test : 29.-30.01.2002
Re-issued : 05.06.2002

1.5 Test item

Type of equipment : **Dual Band GSM Mobile Phone (PCS 900/1900 MHz)**

Type designation : P52-0 (PW3020 / PW3030 / PW3040 / PW3050) tested with: Data

Cable 900; Hands-Free Kit 3000; Headset; DC-Cable

Manufacturer : Applicant

Street

City :

Country :

Serial number : IMEI 350704350000074

Additional informations::

Frequency : 1850 – 1910 MHz

Type of modulation : 300KGXW

Number of channels : 300

Antenna : Integral antenna and socket

Power supply : 3.6V Ni-MH accu

Output power : 31.54 dBm Peak, ERP : 29.0 dBm (Burst); EIRP:31.1 dBm (Burst)

Type of equipment : Temperature range : $-30^{\circ}\text{C} - +60^{\circ}\text{C}$

FCC – ID : M9H95370000

Hardware : V210x Software : D 3,5C

The differences between the families P52-0 with FCC ID M9H95370000, P52-2 with FCC ID M9H95370001 and P52-6 with FCC ID M9H95370006 are only the different design at housings. Because nor hardware configuration either any metal part aren't affected only one device was chosen for measurements. The results of PW3022, IMEI 350704350000074 represents devices at all tree filings.

Photographs at appendix shows design P52-0.

1.6 Test standards: FCC Part 24



2 Technical test

The radiated measurements were performed vertical andhorizontal over the whole frequency range. We start at 1 m high with vertical receiving antenna and rotate the dish continuously. During rotation we use the antenna lift system to vary the high from 1 to 4 m. So we find maximum radiation output. At this points we do manual remeasurements. After this we do the same measurements in horizontal position of the receiving antenna. This (horizontal and vertical) is made for all the three planes of the test sample. We use the maximum received results.

The detector function and selection of bandwidth are according ANSI C63.2-1996 item 8.2.1 and ANSI C63.4-1992 Item 4.2.

Antennas are conform with ANSI C63.2-1996 item 15.

150 kHz - 30 MHz: Quasi Peak measurement, 9kHz Bandwidth, passive loop antenna.

30 MHz - 200 MHz: Quasi Peak measurement, 120KHz Bandwidth, biconical antenna

200MHz - 1GHz: Quasi Peak measurement, 120KHz Bandwidth, log periodic antenna

1GHz: Average, RBW 1MHz, VBW 10 MHz, wave guide horn

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

FINAL VERDICT: PASS

Technical responsibility for area of testing:

2002-01-29 RSC 8411 Berg M.

Date Section Name Signature

Technical responsibility for area of testing:

Date Section Name Signature



2.2 Testreport

TEST REPORT

Test report no.: 3_3095-01-04/02



TEST REPORT REFERENCE

LIST OF MEASUREMENTS

PARAMETER TO BE MEASURED	PAGE	
POWER OUTPUT	SUBCLAUSE § 24.232	7
FREQUENCY STABILITY	SUBCLAUSE § 24.235	9
EMISSIONS LIMITS	§24.238	12
EMISSIONS LIMITS	§24.238	28
OCCUPIED BANDWIDTH	§2.989	48
CONDUCTED EMISSIONS	§ 15.107/207	55
TEST SITE		59
PHOTOGRAPHS OF THE EQ	UIPMENT	62
CUSTOMER STATEMENT		72



POWER OUTPUT

SUBCLAUSE § 24.232

Summery:

This paragraph contains both average, peak output powers and EIRP measurements for the mobile station. In all cases, the peak output power is wthin the required mask (this mask is specified in the JTC standarts, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Method of Measurements:

The mobile was set up for the max. output power with pseudo random data modulation.

The power was measured with R&S Spectrum Analyzer FSIQ 26 (peak and average)

This measurements were done at 3 frequencies, 1850,2 MHz, 1880,0 MHz and 1909,8 MHz (bottom, middle and top of operational frequency range)

Peak power and Average power was measured with a calibrated Signal Analyzer (FSIQ from R&S). Peak power: max Power of the Signal measured with 3 MHz ResBW and 3 MHz VBW. Average power is the integrated Power over Time from the modulated GSM Signal in the burst.

Limits:

Power Step	Nominal Peak Output Power	Tolerance (dB)
	(dBm)	
0	+30	± 2

Power Measurements:

Conducted:

		Peak	Burst Average
Frequency	Power Step	Output Power	Output Power
(MHz)		(dBm)	(dBm)
1850.2	0	30.65	30.55
1880.0	0	30.66	30.56
1909.8	0	31.54	31.44
Measuremen	t uncertainty	±0.	5 dB



EIRP Measurements

Description: This is the test for the maximum radiated power from the phone.

Rule Part 24.232(b) specifies that "Mobile/portable stations are limited to 2 watts e.i.r.p. peak power..." and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Method of Measurement:

- 1. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference center of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
- 2. A "reference path loss" is established as Pin + 2.1 Pr.
- 3. The EUT is substituted for the dipole at the reference centre of the chamber. The EUT is put into CW test mode and a scan is performed to obtain the radiation pattern.
- 4. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs is identified.
- 5. The EUT is then put into pulse mode at its maximum power level (Power Step 0).
- 6. "Gated mode" power measurements are performed with the receiving antenna placed at the co-ordinates determined in Step 3 to determine the output power as defined in FCC Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.
- 7. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.1 dBi) and known input power (Pin).
- 8. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.1dBi.

Limits:

Power Step	Burst Average EIRP (dBm)
0	<33

Power Measurements:

Radiated:

		BURST AVERAGE		MODULATIO	N AVERAGE
Frequency	Power Step	(dBm)		(dB	Sm)
(MHz)		EIRP	ERP	EIRP	ERP
1850.2	0	31.1	29.0	22.1	20.0
1880.0	0	30.8 28.7		21.8	19.7
1909.8	0	31.0	28.9	22.0	19.9
Measurement unce	±3 dB				



FREQUENCY STABILITY

SUBCLAUSE § 24.235

Method of Measurement:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMD 65 DIGITAL RADIOCOMMUNICATION TESTER..

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the mobile station to overnight soak at -30 C.
- 3. With the mobile station, powered with 3.6 Volts, connected to the CMD 65 and in a simulated call on channel 661 (center channel), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the mobile station, to prevent significant self warming.
- 4. Repeat the above measurements at 10 C increments from -30 C to +60 C. Allow at least $1 \frac{1}{2}$ hours at each temperature, unpowered, before making measurements.
- 5. Remeasure carrier frequency at room temperature with nominal 3.6 Volts. Vary supply voltage from minimum 3.4 Volts to maximum 4.4 Volts, in 0.1 Volt increments remeasuring carrier frequency at each voltage. Pause at 3.6 Volts for 1 1/2 hours unpowered, to allow any self heating to stabilize, before continuing.
- 6. Subject the mobile station to overnight soak at +60 C.
- 7. With the mobile station, powered with 3.6 Volts, connected to the CMD 65 and in a simulated call on channel 661 (center channel), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the mobile station, to prevent significant self warming.
- 8. Repeat the above measurements at 10 C increments from +60 C to -30 C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5 C during the measurement procedure.

Measurement Limit:

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment...," Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4 Vdc and 4.4 Vdc, with a nominal voltage of 3.6 Vdc (Li-Ploymer accu). Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of +22.2% and -5.4%. For the purposes of measuring frequency stability these voltage limits are to be used.




AFC FREQ ERROR vs. VOLTAGE


Voltage	Frequency Error	Frequency Error	Frequency Error
(V)	(Hz)	(ppm)	(%)
3.4	-7	-0,0037	-0,00000037
3.5	-8	-0,0043	-0,00000043
3.6	-10	-0,0053	-0,00000053
3.7	-8	-0,0043	-0,00000043
3.8	-2	-0,0011	-0,00000011
3.9	-1	-0,0005	-0,00000005
4.0	-2	-0,0011	-0,00000011
4.1	-2	-0,0011	-0,00000011
4.2	-3	-0,0016	-0,00000016
4.3	-5	-0,0027	-0,00000027
4.4	-5	-0,0027	-0,00000027

AFC FREQ ERROR vs. TEMPERATURE

TEMPERATURE	Frequency Error	Frequency Error	Frequency Error
(° C)	(Hz)	(ppm)	(%)
-30	-112	-0,0596	-0,00000596
-20	-12	-0,0064	-0,00000064
-10	-7	-0,0037	-0,00000037
±0.0	-3	-0,0016	-0,00000016
+10	-5	-0,0027	-0,00000027
+20	2	0,0011	0,00000011
+30	3	0,0016	0,00000016
+40	3	0,0016	0,00000016
+50	3	0,0016	0,00000016
+60	6	0,0032	0,00000032









EMISSIONS LIMITS

§24.238

Measurement Procedure:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4 – 1992 requirements and is recognised by the FCC to be in compliance for a 3 and a10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. This was rounded up to 20 GHz. The resolution bandwidth is set as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the USPCS band.

The final open field emission test procedure is as follows:

- a) The test item was placed on a 0. 8 meter high non-conductive stand at a 3 meter test distance from the receive antenna.
- b) The antenna output was terminated in a 50 ohm load.
- c) A double ridged waveguide antenna was placed on an adjustable height antenna mast 3 meters from the test item for emission measurements.
- d) Detected emissions were maximized at each frequency by rotating the test item and adjusting the receive antenna height and polarization. The maximum meter reading was recorded. The radiated emission measurements of the harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and I MHz bandwidth. If the harmonic could not be detected above the noise floor, the ambient level was recorded. The equivalent power into a dipole antenna was calculated from the field intensity levels measured at 3 meters using the equation shown below:

Pg = $E^2 4\pi d^2 / 120\pi = E^2 d^2 / 30$ where : P = power in watts

g = arithmetic gain of transmitting antenna over isotropic radiator.

E = maximum field strength in volts/meter

d = measurement distance in meter

Using a dipole gain of 1.67 or 2.2 dB and a test distance of 3 meters, this equation reduces to:

P(dBm) = E(dBuV/m) - 97.2dB

Measurement Limit:

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.



Measurement Results:

Radiated emissions measurements were made only at the upper, center, and lower carrier frequencies of the USPCS band (1850.2 MHz, 1879.8 MHz and 1909.8 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the USPCS band into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

RESULTS OF OPEN FIELD RADIATED TEST FOR FCC-24:

No Radiated Emissions less than 20 dB below the limit was found!

As can be seen from this data, the emissions from the test item were within the specification limit. Channel 512

Data	File : /33	3095_25.DOC		22 Ja:	n 2002	
No	EMISSION FREQUENCY MHz	SPEC ME LIMIT ABS dBuV	ASUREMENTS dLIM MODE dB	SITE POL HGT AZM cm deg	CORR FACTOR dB	COMMENTS
1 2 3 4	55.2 64.8 68.2 133.0	29.5 17.0 29.5 19.7	-12.0 PK -12.5 PK -9.9 PK -13.6 PK	V 100 360 V 100 360 V 100 360 V 100 360	N/T N/T N/T N/T	

Channel 661


Data File : /33095_30.DOC									22 Ja	n 2002
No	EMISSION FREQUENCY MHz	SPEC LIMIT dBu\	ABS	SUREME dLIM dB	NTS MODE	POL	-		CORR FACTOR dB	COMMENTS
1 2 3 4	54.5 65.0 68.2 133.7	29.5 29.5 29.5 33.0	16.9 18.8	-10.6 -12.6 -10.8 -12.4	PK PK PK PK	V V V V	97 97	360 360 360 360	N/T N/T N/T N/T	


Channel 810

Data	Data File : /33095_35.DOC								22 Ja	n 2002	
No	EMISSION FREQUENCY MHz	SPEC LIMIT dBu	ABS	SUREME dLIM dB	NTS MODE	POL	_		CORR FACTOR dB	COMMENTS	_
1 2 3	54.3 64.8 68.2	29.5 29.5 29.5	18.0	-12.0 -11.5 -11.3	PK PK PK	V V	97 97 97	131 80 32	N/T N/T N/T		-
											_




Channel 512 (up to 1 GHz)








Channel 512: 1-12 GHz




Peak at 1850.2 MHz shows the carrier frequency suppressed by narrow band rejection filter






Channel 512: 12 - 20 GHz




Date: 30.JAN.2002 11:21:15




Channel 661 (up to 1 GHz)








Channel 661: 1-12 GHz




Peak at 1880.0 MHz shows the carrier frequency suppressed by narrow band rejection filter







Channel 661: 12 - 20 GHz






Channel 810 up to 1 GHz








Channel 810: 1-12 GHz




Peak at 1909.8 MHz shows the carrier frequency suppressed by narrow band rejection filter





Channel 810: 12 - 20 GHz



Date: 30.JAN.2002 11:20:55



Channel 661 (this is valid for all 3 channels and up to 1 GHz) Idle-Mode

Data File : /33095_40.DOC


22 Jan 2002


No	EMISSION FREQUENCY	SPEC LIMIT	MEA ABS	SUREME dlim	NTS MODE	POL	SITI HGT	_	CORR FACTOR	COMMENTS
	MHz	dBu	V	dВ			cm	deg	dB	
1	46.7	29.5	21.2	-8.3	PK		97	360	N/T	
2	53.8	29.5	22.0	-7.6	PK	V	97	360	N/T	
3	68.2	29.5	17.0	-12.6	PK	V	97	360	N/T	

 ${\tt N/T}$ in CORR FACTOR column denotes a non-traceable signal.




Channel 661 (this is valid for all 3 channels and up to 1 GHz) Idle-Mode








Channel 661 (this is valid for all 3 channels and up to 4 GHz) Idle-Mode






Channel 661 (this is valid for all 3 channels and 4 to 12 GHz) Idle-Mode





Channel 661 (this is valid for all 3 channels and 12 to 20 GHz) Idle-Mode $\,$




Date: 30.JAN.2002 11:22:09




EMISSIONS LIMITS

§24.238

Additional Test Set-ups: P52 with Hands-Free Kit 3000 (DC powered)







Data File : /33095_50.DOC


25 Jan 2002

EMISSION	SPEC ME.	ASUREMENTS	SITE	CORR	COMMENTS
No FREQUENCY	LIMIT ABS	dLIM MODE	POL HGT AZM	FACTOR	
MHz	dBuV	dB	cm deg	dB	
1 38.351 2 39.398 3 39.9 4 51.8 5 68.2	29.5 13.7 29.5 25.4 29.5 19.7		V 97 184 V 97 184 V 97 0 V 97 0 V 97 0	14.8 14.3 N/T N/T N/T	


 $\ensuremath{\mathrm{N}/\mathrm{T}}$ in CORR FACTOR column denotes a non-traceable signal.



P52 with Hands-Free Kit 3000 (DC powered)




Peak at 1880.0 MHz shows the carrier frequency suppressed by narrow band rejection filter




 $\begin{array}{ccc} 3760 \ MHz & 28.0 \ dB \mu V / m \ AV \\ 5640 \ MHz & 15.5 \ dB \mu V / m \ AV \end{array}$



P52 with Hands-Free Kit 3000 (DC powered)







Above 12 GHz there were no peaks found (see other test set-up)



P52 with Headset (powered by Accu)






No	EMISSION FREQUENCY MHz	SPEC LIMIT dBu	ABS	SUREME dLIM dB		POL	SITE HGT A		CORR FACTOR dB	COMMENTS
1	114.5	33.0	17.4 	-15.6	PK	V	100 1	L65	N/T	


N/T in CORR FACTOR column denotes a non-traceable signal.



P52 with Headset (powered by Accu)




Peak at 1880.0 MHz shows the carrier frequency suppressed by narrow band rejection filter




 $\begin{array}{ccc} 3760 \ MHz & 27.6 \ dB \mu V / m \ AV \\ 5640 \ MHz & 15.0 \ dB \mu V / m \ AV \end{array}$



P52 with Headset (powered by Accu)







Above 12 GHz there were no peaks found (see other test set-up)



Test report no.:3_3095-01-04/02 Issue date: 2002-01-29 Page 35 (72)

P52 with DC Cable (Car charger)








Data File : /33095_A5.HGL 8 Feb 1903 11:36:5										
No	EMISSION FREQUENCY MHz	SPEC LIMIT dBu		SUREME dLIM dB		POL	SITE HGT cm	AZM	CORR FACTOR dB	COMMENTS
1	46.1 52.9	29.5 29.5	22.8	-6.7 -9.7	PK DK	V	102		N/T N/T	


N/T in CORR FACTOR column denotes a non-traceable signal.



P52 with DC Cable (Car charger)




Peak at 1880.0 MHz shows the carrier frequency suppressed by narrow band rejection filter




 $\begin{array}{ccc} 3760 \ MHz & 27.9 \ dB \mu V / m \ AV \\ 5640 \ MHz & 28.9 \ dB \mu V / m \ AV \end{array}$



P52 with DC Cable (Car charger)





Above 12 GHz there were no peaks found (see other test set-up)



Test report no.:3 3095-01-04/02 Issue date: 2002-04-26 Page 39 (72)

Conducted Spurious Emissions

Measurement Procedure:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 19.1 GHz, data taken from 10 MHz to 20 GHz.
- 2. Determine mobile station transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

USPCS Transmitter Channel Frequency

512 1850.2 MHz

661 1880.0 MHz

810 1909.8 MHz

Measurement Limit:

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to


dBm, this becomes a constant specification limit of -13 dBm.

	EM	ISSION LIMITAT	IONS	
f (MHz)	amplitude of emission (dBm)	max. allowed	actual attenuation below frequency of operation (dBc)	results
		CH 512		
1850	-17.02		47.67	Complies
3677	-30.66	-13 (43.65 dBc)	61.31	Complies
5316	-27.84		58.5	Complies
		CH 661		
3741	-27.03	-13 (43.66 dBc)	57.69	Complies
		CH 810		
1910	-14.35		45.89	Complies
3804	-24.84	-13 (44.53 dBc)	56.38	Complies
5724	-31.38		62.92	Complies
Measurement	uncertainty		± 0.5dB	




Measurements:

Channel: 512






Channel 512



Date: 30.JAN.2002 10:39:46




Channel 512



Date: 30.JAN.2002 10:42:14




Channel 661



Date: 30.JAN.2002 10:43:31




Channel 661






Channel 810






Channel 810





Channel 810



Date: 30.JAN.2002 10:50:21



OCCUPIED BANDWIDTH

§2.989

Occupied Bandwidth Results


Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. Table 8.2 below lists the measured 99% power and -26dBC occupied bandwidths. Spectrum analyzer plots are included on the following pages.

Frequency	99% Occupied Bandwidth	-26 dBc Bandwidth
1850.2 MHz	270.541	316.633
1880.0 MHz	276.553	316.633
1909.2 MHz	284.569	312.625

Part 24.238 (a) requires a measurement bandwidth of at least 1% of the occupied bandwidth. For ca. 290 kHz, this equates to a resolution bandwidth of at least 2.96 kHz. For this testing, a resolution bandwidth 3.0 kHz was used.




Channel 512 99% Occupied Bandwidth



Date: 30.JAN.2002 11:04:28




Channel 512 -26 dBc Bandwidth



Date: 30.JAN.2002 11:05:57




Channel 661 99% Occupied Bandwidth



Date: 30.JAN.2002 11:09:59




Channel 661 -26 dBc Bandwidth



Date: 30.JAN.2002 11:09:16




Channel 810 99% Occupied Bandwidth





Channel 810 -26 dBc Bandwidth




Date: 30.JAN.2002 11:13:17



Conducted emissions

§ 15.107/207

Conducted Emission or	main/ 230V/AC	Datum:8. Feb 2002
VgNr.3-3095	Typ: P52+AC-Charger	
Line L1, N Setup:		Mode : GSM 1900 TX Ch.661




Frequency MHz	Peak QP dBuV	Lim dBuV	QP D dBuV	DelLim-QP Avg dB	Lim dBuV	Avg dBuV	DelLim-Avg dB
========		======	======		======		=======================================
13.732182	2 18.48	48.00	15.35	-32.65	48.00	12.32	-35.68
13.943237	7 19.95	48.00	17.96	-30.04	48.00	16.17	-31.83
14.158443	3 20.02	48.00	17.95	-30.05	48.00	16.44	-31.56
14.371696	5 18.72	48.00	16.24	-31.76	48.00	14.14	-33.86
24.256124	18.64	48.00	15.01	-32.99	48.00	11.56	-36.44



Conducted Emission or	main/ 230V/AC	Datum:8. Feb 2002
VgNr.3-3095	Typ: P52+AC-Charger	
Line L1, N	Setup:	Mode : GSM 1900 TX Ch.661





Frequency MHz	Peak QE dBuV	Lim dBuV	QP dBuV	~	Avg L		<i>r</i> g dBuV	DelLim-Avg dB
========		======	=====		=====	======		=======================================
13.513638	3 15.48	48.00	12.63	3 -35.3	7 4	8.00 1	L0.82	-37.18
13.730630	18.19	48.00	14.6	4 -33.30	5 4	8.00 1	L2.91	-35.09
13.940983	3 19.31	48.00	16.63	3 -31.3	7 4	8.00 1	L4.39	-33.61
14.161015	5 19.56	48.00	16.98	3 -31.0	2 4	8.00 1	L4.01	-33.99
14.372076	5 18.31	48.00	15.7	7 -32.2	3 4	8.00 1	L3.90	-34.10



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	8566 A	Hewlett-Packard	1925A00257
02	Analyzer Display	8566 A	Hewlett-Packard	1925A00860
03	Oscilloscope	7633	Tektronix	230054
04	Radio Communication Analyzer	CMTA 54	Rohde & Schwarz	894 043/010
05	System Power Supply	6038 A	Hewlett-Packard	2848A07027
06	Signal Generator	8111 A	Hewlett-Packard	2215G00867
07	Signal Generator	8662 A	Hewlett-Packard	2224A01012
08	Function Generator	AFGU	Rohde & Schwarz	862 480/032
09	Regulating Transformer	MPL	Erfi	91350
10	LISN	NNLA 8120	Schwarzbeck	8120331
11	Relay-Matrix	PSU	Rohde & Schwarz	893 285/020
12	Power-Meter	436 A	Hewlett-Packard	2101A12378
13	Power-Sensor	8484 A	Hewlett-Packard	2237A10156
14	Power-Sensor	8482 A	Hewlett-Packard	2237A00616
15	Modulation Meter	9008	Racal-Dana	2647
16	Frequency Counter	5340 A	Hewlett-Packard	1532A03899
17	Anechoic Chamber		MWB	87400/002
18	Spectrum Analyzer	85660 B	Hewlett-Packard	2747A05306
19	Analyzer Display	85662 A	Hewlett-Packard	2816A16541
20	Quasi Peak Adapter	85650 A	Hewlett-Packard	2811A01131
21	RF-Preselector	85685 A	Hewlett-Packard	2833A00768
22	Biconical Antenna	3104	Emco	3758
23	Log. Per. Antenna	3146	Emco	2130
24	Double Ridged Horn	3115	Emco	3088
25	EMI-Testreceiver	ESAI	Rohde & Schwarz	863 180/013
26	EMI-Analyzer-Display	ESAI-D	Rohde & Schwarz	862 771/008
27	Biconical Antenna	HK 116	Rohde & Schwarz	888 945/013
28	Log. Per. Antenna	HL 223	Rohde & Schwarz	825 584/002
29	Relay-Switch-Unit	RSU	Rohde & Schwarz	375 339/002
30	Highpass	HM985955	FSY Microwave	001
31	Amplifier	P42-GA29	Tron-Tech	B 23602
32	Anechoic Chamber		Frankonia	
33	Control Computer	PSM 7	Rohde & Schwarz	834 621/004
34	EMI Test Receiver	ESMI	Rohde & Schwarz	827 063/010
35	EMI Test Receiver	Display	Rohde & Schwarz	829 808/010




TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Туре	Manufacturer	Serial No.
36	Control Computer	HD 100	Deisel	100/322/93
37	Relay Matrix	PSN	Rohde & Schwarz	829 065/003
38	Control Unit	GB 016 A2	Rohde & Schwarz	344 122/008
39	Relay Switch Unit	RSU	Rohde & Schwarz	316 790/001
40	Power Supply	6032A	Hewlett Packard	2846A04063
41	Spectrum Monitor	EZM	Rohde & Schwarz	883 720/006
42	Measuring Receiver	ESH 3	Rohde & Schwarz	890 174/002
43	Measuring Receiver	ESVP	Rohde & Schwarz	891 752/005
44	Bicon Ant. 20-300MHz	HK 116	Rohde & Schwarz	833 162/011
45	Logper Ant. 0.3-1 GHz	HL 223	Rohde & Schwarz	832 914/010
46	Amplifier 0.1-4 GHz	AFS4	Miteq Inc.	206461
47	Logper Ant. 1-18 GHz	HL 024 A2	Rohde & Schwarz	342 662/002
48	Polarisation Network	HL 024 Z1	Rohde & Schwarz	341 570/002
49	Double Ridged Horn	3115	EMCO	9107-3696
	Antenna 1-26.5 GHz			
50	Microw. Sys. Amplifier	8317A	Hewlett Packard	3123A00105
	0.5- 26.5 GHz			
51	Audio Analyzer	UPD	Rohde & Schwarz	1030.7500.04
52	Controler	PSM 7	Rohde & Schwarz	883 086/026
53	DC V-Network	ESH3-Z6	Rohde & Schwarz	861 406/005
54	DC V-Network	ESH3-Z6	Rohde & Schwarz	893 689/012
55	AC 2 Phase V-Network	ESH3-Z5	Rohde & Schwarz	861 189/014
56	AC 2 Phase V-Network	ESH3-Z5	Rohde & Schwarz	894 981/019
57	AC-3 Phase V-Network	ESH2-Z5	Rohde & Schwarz	882 394/007
58	Power Supply	6032A	Rohde & Schwarz	2933A05441
59	RF-Test Receiver	ESVP.52	Rohde & Schwarz	881 487/021
60	Spectrum Monitor	EZM	Rohde & Schwarz	883 086/026
61	RF-Test Receiver	ESH3	Rohde & Schwarz	881 515/002
62	Relay Matrix	PSU	Rohde & Schwarz	882 943/029
63	Relay Matrix	PSU	Rohde & Schwarz	828 628/007
64	Spectrum Analyzer	FSIQ 26	Rohde & Schwarz	119.6001.27
65	Spectrum Analyzer	HP 8565E	Hewlett Packard	3473A00773
66				
67				
68				




<u>Test site</u> RADIATED EMISSIONS













Test site







Photographs of the equipment





Photographs of the equipment





Photographs of the equipment





Photographs of the equipment






Photographs of the equipment






Test report no.:3_3095-01-04/02 Issue date: 2002-01-29 Page 67 (72)

Photographs of the equipment Photograph no.: 5a







Photographs of the equipment Hands-Free Kit Photograph no.: 6





Photographs of the equipment

Car charger Photograph no.: 7





Photographs of the equipment Data Cable PC (power supply)





Test report no.:3_3095-01-04/02 Issue date: 2002-01-29 Page 71 (72)

Photographs of the equipment Rapido Hands-Free Kit Photograph no.: 9





Customer Statement



SAGEM SA

Emblissement de Saint-Christophe 2, rue du Petit Albs RP E250 Curgy Saint-Christophe 95801 CERGY PONTOISE CEDEX FRANCE

Tal. +33 1 30 73 70 70 Fax: +33 1 30 73 16 60 http://www.aagon.com

Mobile Phone Versions COMPLIANCE STATEMENT

I, hereby undersigned Jean-Marc ROBERT - Chief Design Engineer - Mobile Phones R&D Unit, attest that :

- the mobile SAGEM GSM 1900 MHz P52 0, FCC ID M9H95370000
- the mobile SAGEM GSM 1900 MHz P52 2, FCC ID M9H95370002
- the mobile SAGEM GSM 1900 MHz P52 6, FCC ID M9H95370006

are using the same PCB with the same mounted components. All devices have the identical hardware configurations. The differences between the devices are only the design of housings. No metal parts are changed. Only plastic parts are affected.

Jean-Marc ROBERT Chief Design Engineer Mobile Phones R&D Unit

