



Supplemental “Dual Xmit” Test Report

REPORT NO.: RF950206H07-01
MODEL NO.: WA8011A-A
RECEIVED: Feb. 06, 2006
TESTED: Feb. 20 to March 3, 2006
ISSUED: March 3, 2006

APPLICANT: Microelectronics Technology Inc.

ADDRESS: 1, Innovation Road II, Hsinchu Science-based
Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.

This test report consists of 10 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



No. 2177-01



Table of Contents

| | | |
|-----|--|----|
| 1. | CERTIFICATION | 3 |
| 2. | DUAL XMIT, RADIATED EMISSION MEASUREMENT | 4 |
| 2.1 | LIMITS OF RADIATED EMISSION MEASUREMENT | 4 |
| 2.2 | TEST INSTRUMENTS..... | 5 |
| 2.3 | TEST PROCEDURES | 6 |
| 2.4 | DEVIATION FROM TEST STANDARD | 6 |
| 2.5 | TEST SETUP | 7 |
| 2.6 | EUT OPERATING CONDITIONS..... | 8 |
| 2.7 | TEST RESULTS | 9 |
| 3. | INFORMATION ON THE TESTING LABORATORIES | 10 |



1. CERTIFICATION

PRODUCT : A8 802.11ab/g AP BS/Bridge AC
BRAND NAME : MTI, ALTAI, ASTRI
MODEL NO. : WA8011A-A
TESTED: Feb. 20 to March 3, 2006
APPLICANT : Microelectronics Technology Inc.
TEST ITEM: ENGINEERING SAMPLE
STANDARDS : 47 CFR FCC Part 15, Subpart C
ANSI C63.4-2003

PREPARED BY : Carol Liao , **DATE:** March 3, 2006
(Carol Liao)

TECHNICAL ACCEPTANCE : Hank Chung , **DATE:** March 3, 2006
Responsible for RF (Hank Chung)

APPROVED BY : May Chen , **DATE:** March 3, 2006
(May Chen, Deputy Manager)

Note:

Per a request of the FCC, the access point radio was tested for radiated emissions in restricted bands while transmitting on both 2.4 GHz and 5 GHz at simultaneously.

2. DUAL XMIT, RADIATED EMISSION MEASUREMENT

2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

| Frequencies (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED UNTIL |
|--------------------------------|---------------------|---------------------|------------------|
| ADVANTEST Spectrum Analyzer | R3271A | 85060311 | July 07, 2006 |
| HP Pre_Amplifier | 8449B | 3008A01922 | Oct. 02, 2006 |
| ROHDE & SCHWARZ Test Receiver | ESCS30 | 100287 | Dec. 08, 2006 |
| CHASE Broadband Antenna | VULB9168 | 138 | Dec. 21, 2006 |
| Schwarzbeck Horn_Antenna | BBHA9120 | D124 | Dec. 11, 2006 |
| Schwarzbeck Horn_Antenna | BBHA 9170 | BBHA9170153 | Jan. 05, 2007 |
| SCHWARZBECK Biconical Antenna | VHBA9123 | 459 | Jun. 26, 2006 |
| SCHWARZBECK Periodic Antenna | UPA6108 | 1148 | Jun. 26, 2006 |
| RF Switches (ARNITSU) | CS-201 | 1565157 | NA |
| RF CABLE (Chaintek) 1GHz-20GHz | SF102 | 22054-2 | Nov. 16. 2006 |
| RF Cable(RICHTEC) | 9913-30M | STCCAB-30M-1GHz-021 | Jul. 16, 2006 |
| Software | ADT_Radiated_V 5.14 | NA | NA |
| CHANCE MOST Antenna Tower | AT-100 | 0203 | NA |
| CHANCE MOST Turn Table | TT-100 | 0203 | NA |

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Measurement | Value |
|-----------------------------------|---------|
| Radiated emissions (30MHz-1GHz) | 2.98 dB |
| Radiated emissions (1GHz ~18GHz) | 2.21 dB |
| Radiated emissions (18GHz ~20GHz) | 1.88 dB |

2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.
- g. The emissions up to 40 GHz were examined. Those emission falling within a restricted band were evaluated against the "restricted band emission limit" (54 dB μ V / 74 dB μ V).


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

2.4 DEVIATION FROM TEST STANDARD

No deviation

2.5 TEST SETUP



2.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table. (The configuration and photo, please refer to RF930929H03 test report)
- b. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run test program “ART_V48_build 13_Alpha” to enable EUT under transmission/receiving condition continuously at specific channel frequency via UTP cable.

Note:

The access point was tested for out of band radiated emissions with the unit transmitting on 802.11b, 2462 MHz and 802.11a on 5260 MHz. These frequencies and power levels were chosen because these frequencies produced the worst case radiated emissions during the radiated emissions in restricted bands test performed previously. The unit was set to transmit at the same power level as was used in the initial radiated emissions tests and was transmitting at the maximum data rate. (Please refer to RF950206H07 test report)

2.7 TEST RESULTS

| | | | |
|---------------------------------|---|--|------------------------------------|
| TEST MODE | Dual transmission 11b, 2437MHz 11a, 5825MHz | FREQUENCY RANGE | 1000MHz~40000MHz |
| INPUT POWER (SYSTEM) | 120Vac, 60Hz | DETECTOR FUNCTION & BANDWIDTH | Peak (PK) Average (AV) 1 MHz |
| ENVIRONMENTAL CONDITIONS | 26deg. C, 68%RH, 973 hPa | TESTED BY | Rex Huang |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 2688.00 | 59.00 PK | 79.40 | -20.40 | 1.53 H | 29 | 28.10 | 30.90 |
| 1 | 2688.00 | 57.60 AV | 71.40 | -13.80 | 1.53 H | 29 | 26.70 | 30.90 |
| 2 | 4874.00 | 43.20 PK | 74.00 | -30.80 | 1.64 H | 328 | 7.90 | 35.30 |
| 2 | 4874.00 | 31.80 AV | 54.00 | -22.20 | 1.64 H | 328 | -3.50 | 35.30 |
| 3 | 7311.00 | 48.20 PK | 74.00 | -25.80 | 1.47 H | 18 | 7.50 | 40.70 |
| 3 | 7311.00 | 36.60 AV | 54.00 | -17.40 | 1.47 H | 18 | -4.10 | 40.70 |
| 4 | 11650.00 | 61.70 PK | 74.00 | -12.30 | 1.62 H | 71 | 11.10 | 50.60 |
| 4 | 11650.00 | 48.90 AV | 54.00 | -5.10 | 1.62 H | 71 | -1.70 | 50.60 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 2688.00 | 59.40 PK | 98.40 | -39.00 | 1.44 V | 359 | 28.50 | 30.90 |
| 1 | 2688.00 | 57.80 AV | 89.60 | -31.80 | 1.44 V | 359 | 26.90 | 30.90 |
| 2 | 4874.00 | 44.50 PK | 74.00 | -29.50 | 1.57 V | 341 | 9.20 | 35.30 |
| 2 | 4874.00 | 32.60 AV | 54.00 | -21.40 | 1.57 V | 341 | -2.70 | 35.30 |
| 3 | 7311.00 | 49.20 PK | 74.00 | -24.80 | 1.64 V | 337 | 8.50 | 40.70 |
| 3 | 7311.00 | 37.40 AV | 54.00 | -16.60 | 1.64 V | 337 | -3.30 | 40.70 |
| 4 | 11650.00 | 66.70 PK | 74.00 | -7.30 | 1.50 V | 24 | 16.10 | 50.60 |
| 4 | 11650.00 | 53.30 AV | 54.00 | -0.70 | 1.50 V | 24 | 2.70 | 50.60 |

NOTE:

1. Emission level = Raw value + Correction Factor
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



3. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

| | |
|--------------------|-----------------------|
| USA | FCC, UL, A2LA |
| Germany | TUV Rheinland |
| Japan | VCCI |
| Norway | NEMKO |
| Canada | INDUSTRY CANADA , CSA |
| R.O.C. | CNLA, BSMI, DGT |
| Netherlands | Telefication |
| Singapore | PSB , GOST-ASIA(MOU) |
| Russia | CERTIS(MOU) |

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also