



- Note:**
1. MATERIAL:霧面PC(FR65),t 0.254,防火係數94-0, IT MUST BE APPROVED BY UL & CSA STANDARD
  2. LABEL SHOULD HAVE PRESSURE SENSITIVE ADHESIVE WITH PROTECTIVE RELEASE LINER ON THE BACK SIDE.
  3. COLORS:TEXT FOREGROUND : Pantone Cool Gray 3C  
BACKGROUND: Pantone black
  4. LABEL MANUFACTURER MUST USE A PROCESS & MATERIALS THOSE WHICH HAVE BEEN APPROVED BY UL & CSA
  5. 剖面線為印水膠區域 ( 3M 467).
  6. 依RD承認 SAMPLE 為準
  7. 成品需符合GP要求

ITEM	CONTENTS OF CHANGE	RVS	CHK	APV	M/D/Y	TOL ±											DATE	MATERIAL	SEE NOTES	TREATMENT	REMARK			
							Plc	Met	Ins	Por	Cab	Pac	Gas	PCB	UNIT	MM	SCALE	--	DRAWING NAME	MF	242	8144	00013	R
						RANGE	0~6	0.1	0.1	0.1	0.2	0.5	1	0.5	0.1					TF041-LABEL; RATING, PVT, B300				
							6~30	0.1	0.1	.15	.25	1	1	0.5	0.1									
							30~80	0.1	.15	0.2	0.3	2	1.5	1	0.1									
							80~180	.15	.15	.25	0.3	2	2	1	.15									
							180~315	.15	0.2	0.3	0.4	2.5	2	1	.15									
							315~800	0.2	0.3	0.4	0.5	3	3	2	.15									
																<b>MITAC</b> Technology Corp.								