

### FCC/IC TEST REPORT Report No.: EMC-FCC-R0149

# 5.8 RF Exposure

## 5.8.1 Regulation

According to \$15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See \$ 1.1307(b)(1) of this Chapter.

Emmes for Maximum 1	Emilis for Muximum remissive Exposure. Ar exposure is earediated.				
Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time	
	Strength [V/m]	Strength [A/m]	[mW/cm <sup>2</sup> ]	[minute]	
Limits for General Population / Uncontrolled Exposure					
0.3 ~ 1.34	614	1.63	*(100)	30	
1.34 ~ 30	824 /f	2.19/f	*(180/f <sup>2</sup> )	30	
30 ~ 300	27.5	0.073	0.2	30	
300 ~ 1500	/	/	f/1500	30	
1500 ~ 15000	/	/	1.0	30	

Limits for Maximum Permissive Exposure: RF exposure is calculated.

*f=frequency in MHz,* \*= *plane-wave equivalent power density* 

#### MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad \left(\Longrightarrow R = \sqrt{PG/4\pi S}\right)$$

S=power density [mW/cm<sup>2</sup>]

P=Power input to antenna [mW]

G=Power gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power = 2.42 [mW](= 3.84 dBm)				
Antenna gain= 0.48(= -3.23 [dBi])				
100 mW, at 20 cm from an antenna 6[dBi]	$S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400)$ = 0.079 18 [mW/cm <sup>2</sup> ] < 1.0 [mW/cm <sup>2</sup> ]			
2.239 mW, at 20 cm from an antenna -3.23 [dBi]	$S = PG/4\pi R^2 = 0.000 \ 23 \ [mW/cm^2] < 1.0 \ [mW/cm^2]$			
2.239 mW, at 2.5 cm from an antenna -3.23 [dBi]	$S = PG/4\pi R^2 = 0.014 65 [mW/cm^2] < 1.0 [mW/cm^2]$			

### 5.8.2 RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

## **EMC compliance Ltd.**

Page: 46 of 47

65, Sinwon-ro, Yeongtong-gu, Suwon- si, Gyeonggi-do, 443-390, Korea 82-31-336-9919 (Main) 82-505-299-8311 (Fax) This test report shall not be reproduced except in full, Without the written approval.