

SAR Exemption Exhibit

Certification

Applicant Name: Identiv, Inc.	Date of Issue: February 3, 2020
Address: 2201 Walnut Avenue, Suite #100, Fremont, CA 94538, USA	Test Site/Location: EMCE Engineering 1726 Ringwood Avenue San Jose, California USA
	Report No.: EMCE-R-2002-001

FCC ID:	MBPUT3720F-01
IC:	7485A-3720F01
APPLICANT:	Identiv Inc.

Model: uTrust 3720 F HF + LF
EUT Type: RFID Interface Reader
Frequency Range: 125 kHz, 13.56 MHz

The measurements shown in this report were made in accordance with the procedures specified in §2.947.
I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them



Steve In
Test Engineer
Certification Division



Sunwoo Kim
Technical Manager
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the EMCE Engineering, Inc.

Version

TEST REPORT NO.	DATE	DESCRIPTION
EMCE-R-2002-001	February 3, 2020	First Issue

RF Exposure Statement

The device is a mobile device intended to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure and the body of the user or nearby persons.

Limit

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

Note.

Limits are not defined for frequencies < 0.3MHz, however the output power of the 125 kHz transmitter is low. The limit for MPE at 300 kHz is applied to determine compliance.

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

EVALUATION RESULTS

Freq.(MHz)	Max Power (dBuV/m)	Max Power (dBm)	Max Power (mW)	Power density (mW/cm ²)	Limit (mW/cm ²)
0.125	64.1	-31.1	0.000776	0.00000015	100

Freq.(MHz)	Max Power (dBuV/m)	Max Power (dBm)	Max Power (mW)	Power density (mW/cm ²)	Limit (mW/cm ²)
13.56	76.4	-18.8	0.013182	0.00000262	0.979

-> Worst Case: Simultaneous MPE 20cm is

Simultaneous MPE 20cm is 0.125 MHz (0.0000000015) + 13.56 MHz (0.0000000262) = 0.000000028 < 1

MPE test exclusion applies for simultaneous transmission