



# RF EXPOSURE REPORT

**REPORT NO.:** SA971031L01

**MODEL NO.:** 74-4876-04

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** HON HAI Precision IND., CO., LTD.

**ADDRESS:** 5F-1, 5 Hsin-An Road Hsinchu, Science-Based  
Industrial Park Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan,  
R.O.C.



## RF EXPOSURE MEASUREMENT (MOBILE DEVICE)

### 1. INTRODUCTION

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

### 2. RF EXPOSURE LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
<b>(A)LIMITS FOR OCCUPATIONAL / CONTROL EXPOSURES</b>				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
<b>(B)LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz



### 3. FRIIS FORMULA

Friis transmission formula :  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

$P_d$  = power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance  $r$ .

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,  
Page 640, Eq. (11-133).

### 4. EUT OPERATING CONDITION

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 5. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



## 6. TEST RESULTS

### 6.1 ANTENNA GAIN

The maximum Gain measured in Fully Anechoic Chamber are 2dBi or 1.58489 (2.4GHz) & 5dBi or 3.16228(numeric) (5.0GHz).

### 6.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE VALUE AT DISTANCE 20cm:

#### 802.11b DSSS MODULATION: 1TX

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
1	2412	101.625	20.07	0.032	1.0
6	2437	102.802	20.12	0.032	1.0
11	2462	101.158	20.05	0.032	1.0

#### 802.11g OFDM MODULATION: 1TX

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
1	2412	226.986	23.56	0.072	1.0
6	2437	228.560	23.59	0.072	1.0
11	2462	225.424	23.53	0.071	1.0

#### DRAFT 802.11n (20MHz) OFDM MODULATION: 1TX

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
1	2412	160.694	22.06	0.051	1.0
6	2437	161.436	22.08	0.051	1.0
11	2462	159.956	22.04	0.050	1.0

#### DRAFT 802.11n (20MHz) OFDM MODULATION: 2TX

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
		CHAIN 0	CHAIN 1				
1	2412	22.05	22.07	321.389	25.07	0.101	1.0
6	2437	22.08	22.11	323.991	25.11	0.102	1.0
11	2462	22.02	22.05	319.545	25.05	0.101	1.0

**DRAFT 802.11n (40MHz) OFDM MODULATION: 1TX**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
1	2422	159.956	22.04	0.050	1.0
4	2437	161.808	22.09	0.051	1.0
7	2452	159.588	22.03	0.050	1.0

**DRAFT 802.11n (40MHz) OFDM MODULATION: 2TX**

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
		CHAIN 0	CHAIN 1				
1	2422	22.03	22.06	320.282	25.06	0.101	1.0
4	2437	22.07	22.09	322.873	25.09	0.102	1.0
7	2452	22.04	22.05	320.280	25.06	0.101	1.0

**802.11a OFDM MODULATION: 1TX**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
36	5180	31.769	15.02	0.020	1.0
40	5200	32.063	15.06	0.020	1.0
48	5240	31.915	15.04	0.020	1.0
149	5745	255.270	24.07	0.161	1.0
157	5785	257.632	24.11	0.162	1.0
165	5825	254.097	24.05	0.160	1.0

**DRAFT 802.11n (20MHz) OFDM MODULATION: 1TX**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
36	5180	12.677	11.03	0.008	1.0
40	5200	20.184	13.05	0.013	1.0
48	5240	20.230	13.06	0.013	1.0
149	5745	159.956	22.04	0.101	1.0
157	5785	162.555	22.11	0.102	1.0
165	5825	161.436	22.08	0.102	1.0

**DRAFT 802.11n (20MHz) OFDM MODULATION: 2TX**

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
		CHAIN 0	CHAIN 1				
36	5180	11.05	11.08	25.558	14.08	0.016	1.0
40	5200	13.04	13.06	40.367	16.06	0.025	1.0
48	5240	13.08	13.04	40.461	16.07	0.025	1.0
149	5745	22.06	22.02	319.915	25.05	0.201	1.0
157	5785	22.13	22.08	324.741	25.12	0.204	1.0
165	5825	22.03	22.05	319.912	25.05	0.201	1.0

**DRAFT 802.11n (40MHz) OFDM MODULATION: 1TX**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT OF POWER DENSITY (mW/cm <sup>2</sup> )
38	5190	12.647	11.02	0.008	1.0
46	5230	20.230	13.06	0.013	1.0
151	5755	159.588	22.03	0.100	1.0
159	5795	161.436	22.08	0.102	1.0

**DRAFT 802.11N (40MHz) OFDM MODULATION: 2TX**

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/cm <sup>2</sup> )	POWER DENSITY (mW/cm <sup>2</sup> )
		CHAIN 0	CHAIN 1				
38	5190	11.08	11.04	25.529	14.07	0.016	1.0
46	5230	13.05	13.08	40.507	16.08	0.025	1.0
151	5755	22.04	22.07	321.020	25.07	0.202	1.0
159	5795	22.08	22.05	321.760	25.08	0.202	1.0