



FCC TEST REPORT (BLUETOOTH)

REPORT NO.: RF111130E01B-1 R1

MODEL NO.: J20H045

FCC ID: MCLJ20H045

RECEIVED: July 17, 2012

TESTED: July 31 to Aug. 01, 2012

ISSUED: Aug. 30, 2012

APPLICANT: Hon Hai PRECISION IND.CO.,LTD

ADDRESS: 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (2): No.49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	8
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	9
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.5 DESCRIPTION OF SUPPORT UNITS	11
3.6 CONFIGURATION OF SYSTEM UNDER TEST.....	11
4 TEST PROCEDURES AND RESULTS	12
4.1 RADIATED EMISSION MEASUREMENT	12
4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT	12
4.1.2 TEST INSTRUMENTS.....	13
4.1.3 TEST PROCEDURES	14
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS.....	15
4.1.7 TEST RESULTS.....	16
4.2 MAXIMUM PEAK OUTPUT POWER	23
4.2.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	23
4.2.2 INSTRUMENTS	23
4.2.3 TEST PROCEDURES	23
4.2.4 DEVIATION FROM TEST STANDARD	23
4.2.5 TEST SETUP.....	24
4.2.6 EUT OPERATING CONDITION	24
4.2.7 TEST RESULTS.....	25
5 INFORMATION ON THE TESTING LABORATORIES.....	26
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	27



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF111130E01B-1	Original release	Aug. 28, 2012
RF111130E01B-1 R1	Modified Antenna Specification of the EUT	Aug. 30, 2012



1 CERTIFICATION

PRODUCT : WiFi Module
BRAND NAME : FOXCONN
MODEL NO. : J20H045
TEST SAMPLE : R&D SAMPLE
APPLICANT : Hon Hai PRECISION IND.CO.,LTD
TESTED DATE : July 31 to Aug. 01, 2012
STANDARDS : FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2009

The above equipment (Model: J20H045) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : *Lori Chung* , **DATE:** Aug. 30, 2012
(Lori Chung, Specialist)

APPROVED BY : *May Chen* , **DATE:** Aug. 30, 2012
(May Chen, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.0dB at 165.95MHz.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.

NOTE:

1. This report is prepared for FCC class II permissive change. Only radiated emission and Maximum Peak Output Power were presented in this test report.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	5.69 dB
Radiated emissions (1GHz -6GHz)	3.84 dB
Radiated emissions (6GHz -18GHz)	4.09 dB
Radiated emissions (18GHz -40GHz)	4.24 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WiFi Module
MODEL NO.	J20H045
POWER SUPPLY	DC 3.3V from host equipment
MODULATION TYPE	GFSK, $\pi/4$ -DQPSK, 8DPSK
MODULATION TECHNOLOGY	FHSS
DATE RATE	1/2/3Mbps
FREQUENCY RANGE	2402MHz ~ 2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	1.343mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA



NOTE:

1. This report is prepared for FCC class II permissive change. The difference compared with the Report No.: RF111130E01-1 design is as the following information:

u Added six antennas (No. 4 ~ No. 9) as following table:

Original Antennas									
No.	Brand	Model	Type	Connector	Gain (dBi)	Cable loss(dB)	Cable length (cm)	Diversity Function	For which port
1	ethertronics	1001215	PCB trace	U.FL	2.58	0.36	10	Yes	Wi-Fi AUX
2	ethertronics	1001212	PCB trace	U.FL	2.66	0.576	16	Yes	Wi-Fi main
3	ethertronics	1001218	PCB trace	U.FL	2.48	0.82	23	No	BT
Newly Antennas									
No.	Brand	Model	Type	Connector	Gain (dBi)	Cable loss(dB)	Cable length (mm)	Diversity Function	For which port
4	ethertronics	1001454	PCB trace	U.FL	2.22	0.36	95	Yes	Wi-Fi AUX
5	ethertronics	1001455	PCB trace	U.FL	2.27	0.2	60	Yes	Wi-Fi main
6	ethertronics	1001456	PCB trace	U.FL	2.19	0.55	160	No	BT
7	ethertronics	1001506	PCB trace	U.FL	2.36	0.8	260	Yes	Wi-Fi AUX
8	ethertronics	1001503	PCB trace	U.FL	2.5	0.7	175	Yes	Wi-Fi main
9	ethertronics	1001509	PCB trace	U.FL	4	0.82	210	No	BT

From the above new antennas, **antenna 9** was selected as representative for the test and its data was recorded in this report.

2. For the new antenna sources, WiFi antennas' types are identical to original and the gains are smaller, therefore no addition test has to be performed. Bluetooth antennas' types are identical to original but the gains are bigger, therefore only radiated emission and Maximum Peak Output Power need to be performed. And all data was verified to meet the requirements.

3. The EUT is 1 * 1 spatial SISO (1Tx & 1Rx) without beam forming function.

4. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.

5. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

Seventy-nine channels are provided for Bluetooth.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE < 1G	RE ≥ 1G	APCM	
-	√	√	√	-

Where **RE < 1G**: Radiated Emission below 1GHz **RE ≥ 1G**: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

NOTE:

The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	39	FHSS	GFSK	DH5

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

Antenna Port Conducted Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE<1G	22deg. C, 64%RH	120Vac, 60Hz	Evan Huang
RE≥1G	23deg. C, 73%RH	120Vac, 60Hz	Nelson Teng
APCM	25deg. C, 60%RH	120Vac, 60Hz	Rex Huang



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
558074 D01 DTS Meas Guidance v01
ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

3.5 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
2	TEST TOOL	Hon Hai	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

3.6 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST PROCEDURES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 29, 2011	Aug. 28, 2012
Pre-Selector Agilent	N9039A	MY46520310	Aug. 29, 2011	Aug. 28, 2012
Signal Generator Agilent	N5181A	MY49060347	July 25, 2012	July 24, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 15, 2011	Nov. 14, 2012
Pre-Amplifier Agilent	8449B	3008A02465	Feb. 27, 2012	Feb. 26, 2013
SPACEK LABS	SLKKa-48-6	9K16	Nov. 15, 2011	Nov. 14, 2012
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Apr. 06, 2012	Apr. 05, 2013
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 23, 2011	Nov. 22, 2012
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 07, 2011	Oct. 06, 2012
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 27, 2011	Dec. 26, 2012
RF Cable	NA	CHHCAB_001	Oct. 08, 2011	Oct. 07, 2012
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: July 31 to Aug. 01, 2012

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Connect the EUT with the support unit 1 (NOTEBOOK COMPUTER) which is placed on a testing table.
2. The communication partner run test program “DutApiSDSD8787.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

BT_GFSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	157.54	38.3 QP	43.5	-5.2	1.50 H	114	23.91	14.39
2	165.95	40.5 QP	43.5	-3.0	1.50 H	254	26.51	13.96
3	270.52	42.8 QP	46.0	-3.2	1.00 H	115	28.67	14.13
4	284.37	42.1 QP	46.0	-3.9	1.00 H	111	27.46	14.68
5	478.11	39.0 QP	46.0	-7.0	1.50 H	0	19.49	19.52
6	604.82	37.8 QP	46.0	-8.2	1.00 H	106	15.53	22.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.20	31.6 QP	40.0	-8.4	1.50 V	360	18.54	13.03
2	280.58	39.1 QP	46.0	-6.9	1.50 V	225	24.61	14.53
3	306.52	40.9 QP	46.0	-5.1	1.50 V	209	25.41	15.45
4	318.83	42.6 QP	46.0	-3.4	2.00 V	152	26.86	15.74
5	476.22	36.1 QP	46.0	-9.9	1.00 V	247	16.59	19.47
6	640.00	29.9 QP	46.0	-16.1	2.00 V	91	7.18	22.74

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	1.21 H	274	24.82	32.38
2	2390.00	27.1 AV	54.0	-26.9	1.21 H	274	-5.28	32.38
3	*2402.00	98.5 PK			1.21 H	274	66.08	32.42
4	*2402.00	68.4 AV			1.21 H	274	35.98	32.42
5	4804.00	57.3 PK	74.0	-16.7	1.31 H	272	15.39	41.91
6	4804.00	27.2 AV	54.0	-26.8	1.31 H	272	-14.71	41.91

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	1.00 V	112	24.32	32.38
2	2390.00	26.6 AV	54.0	-27.4	1.00 V	112	-5.78	32.38
3	*2402.00	94.2 PK			1.00 V	112	61.78	32.42
4	*2402.00	64.1 AV			1.00 V	112	31.68	32.42
5	4804.00	54.6 PK	74.0	-19.4	1.71 V	125	12.69	41.91
6	4804.00	24.5 AV	54.0	-29.5	1.71 V	125	-17.41	41.91

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	97.8 PK			1.15 H	266	65.28	32.52
2	*2441.00	67.7 AV			1.15 H	266	35.18	32.52
3	4882.00	57.1 PK	74.0	-16.9	1.28 H	275	15.10	42.00
4	4882.00	27.0 AV	54.0	-27.0	1.28 H	275	-15.00	42.00
5	7323.00	52.0 PK	74.0	-22.0	1.33 H	150	5.44	46.56
6	7323.00	21.9 AV	54.0	-32.1	1.33 H	150	-24.66	46.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.3 PK			1.00 V	115	60.78	32.52
2	*2441.00	63.2 AV			1.00 V	115	30.68	32.52
3	4882.00	54.7 PK	74.0	-19.3	1.96 V	112	12.70	42.00
4	4882.00	24.6 AV	54.0	-29.4	1.96 V	112	-17.40	42.00
5	7323.00	52.2 PK	74.0	-21.8	1.69 V	83	5.64	46.56
6	7323.00	22.1 AV	54.0	-31.9	1.69 V	83	-24.46	46.56

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	96.8 PK			1.15 H	268	64.18	32.62
2	*2480.00	66.7 AV			1.15 H	268	34.08	32.62
3	2483.50	57.5 PK	74.0	-16.5	1.15 H	268	24.87	32.63
4	2483.50	27.4 AV	54.0	-26.6	1.15 H	268	-5.23	32.63
5	4960.00	58.3 PK	74.0	-15.7	1.24 H	268	16.31	41.99
6	4960.00	28.2 AV	54.0	-25.8	1.24 H	268	-13.79	41.99
7	7440.00	54.1 PK	74.0	-19.9	1.34 H	157	7.29	46.81
8	7440.00	24.0 AV	54.0	-30.0	1.34 H	157	-22.81	46.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.5 PK			1.23 V	137	59.88	32.62
2	*2480.00	62.4 AV			1.23 V	137	29.78	32.62
3	2483.50	56.8 PK	74.0	-17.2	1.23 V	137	24.17	32.63
4	2483.50	26.7 AV	54.0	-27.3	1.23 V	137	-5.93	32.63
5	4960.00	55.2 PK	74.0	-18.8	2.00 V	104	13.21	41.99
6	4960.00	25.1 AV	54.0	-28.9	2.00 V	104	-16.89	41.99
7	7440.00	52.4 PK	74.0	-21.6	1.71 V	89	5.59	46.81
8	7440.00	22.3 AV	54.0	-31.7	1.71 V	89	-24.51	46.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.09 H	270	24.52	32.38
2	2390.00	26.8 AV	54.0	-27.2	1.09 H	270	-5.58	32.38
3	*2402.00	98.2 PK			1.17 H	275	65.78	32.42
4	*2402.00	68.1 AV			1.17 H	275	35.68	32.42
5	4804.00	57.0 PK	74.0	-17.0	1.35 H	244	15.09	41.91
6	4804.00	26.9 AV	54.0	-27.1	1.35 H	244	-15.01	41.91

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.3 PK	74.0	-17.7	1.00 V	114	23.92	32.38
2	2390.00	26.2 AV	54.0	-27.8	1.00 V	114	-6.18	32.38
3	*2402.00	93.9 PK			1.00 V	114	61.48	32.42
4	*2402.00	63.8 AV			1.00 V	114	31.38	32.42
5	4804.00	54.7 PK	74.0	-19.3	1.77 V	128	12.79	41.91
6	4804.00	24.6 AV	54.0	-29.4	1.77 V	128	-17.31	41.91

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	97.5 PK			1.11 H	281	64.98	32.52
2	*2441.00	67.4 AV			1.11 H	281	34.88	32.52
3	4882.00	56.8 PK	74.0	-17.2	1.26 H	265	14.80	42.00
4	4882.00	26.7 AV	54.0	-27.3	1.26 H	265	-15.30	42.00
5	7323.00	52.1 PK	74.0	-21.9	1.34 H	133	5.54	46.56
6	7323.00	22.0 AV	54.0	-32.0	1.34 H	133	-24.56	46.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.2 PK			1.00 V	122	60.68	32.52
2	*2441.00	63.1 AV			1.00 V	122	30.58	32.52
3	4882.00	54.7 PK	74.0	-19.3	1.93 V	102	12.70	42.00
4	4882.00	24.6 AV	54.0	-29.4	1.93 V	102	-17.40	42.00
5	7323.00	52.1 PK	74.0	-21.9	1.70 V	69	5.54	46.56
6	7323.00	22.0 AV	54.0	-32.0	1.70 V	69	-24.56	46.56

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	96.3 PK			1.11 H	261	63.68	32.62
2	*2480.00	66.2 AV			1.11 H	261	33.58	32.62
3	2483.50	57.5 PK	74.0	-16.5	1.11 H	261	24.87	32.63
4	2483.50	27.4 AV	54.0	-26.6	1.11 H	261	-5.23	32.63
5	4960.00	58.0 PK	74.0	-16.0	1.26 H	237	16.01	41.99
6	4960.00	27.9 AV	54.0	-26.1	1.26 H	237	-14.09	41.99
7	7440.00	53.6 PK	74.0	-20.4	1.35 H	163	6.79	46.81
8	7440.00	23.5 AV	54.0	-30.5	1.35 H	163	-23.31	46.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.8 PK			1.16 V	122	60.18	32.62
2	*2480.00	62.7 AV			1.16 V	122	30.08	32.62
3	2483.50	56.0 PK	74.0	-18.0	1.16 V	122	23.37	32.63
4	2483.50	25.9 AV	54.0	-28.1	1.16 V	122	-6.73	32.63
5	4960.00	54.7 PK	74.0	-19.3	1.96 V	113	12.71	41.99
6	4960.00	24.6 AV	54.0	-29.4	1.96 V	113	-17.39	41.99
7	7440.00	51.0 PK	74.0	-23.0	1.69 V	82	4.19	46.81
8	7440.00	20.9 AV	54.0	-33.1	1.69 V	82	-25.91	46.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

4.2 MAXIMUM PEAK OUTPUT POWER

4.2.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Limit is 125mW.

4.2.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date: July 31, 2012


4.2.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T

4.2.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)		OUTPUT POWER (dBm)		POWER LIMIT (mW)	PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	1.259	0.984	1.00	-0.07	125	PASS
39	2441	1.343	1.197	1.28	0.78	125	PASS
78	2480	1.268	0.984	1.03	-0.07	125	PASS





5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---