



FCC TEST REPORT

REPORT NO.: RF120802E01

MODEL NO.: J20H064

FCC ID: MCLJ20H064

RECEIVED: Aug. 06, 2012

TESTED: Aug. 07 to Sep. 04, 2012

ISSUED: Sep. 21, 2012

APPLICANT: Hon Hai PRECISION IND.CO.,LTD

ADDRESS: 5F-1, Hsin-An Road, Hsinchu, Science Industrial Park, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION.....	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4 DESCRIPTION OF SUPPORT UNITS	15
3.5 CONFIGURATION OF SYSTEM UNDER TEST	15
4. TEST TYPES AND RESULTS	16
4.1 CONDUCTED EMISSION MEASUREMENT	16
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	16
4.1.2 TEST INSTRUMENTS	16
4.1.3 TEST PROCEDURES	17
4.1.4 DEVIATION FROM TEST STANDARD	17
4.1.5 TEST SETUP	18
4.1.6 EUT OPERATING CONDITIONS	18
4.1.7 TEST RESULTS	19
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	21
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	21
4.2.2 TEST INSTRUMENTS	22
4.2.3 TEST PROCEDURES	23
4.2.4 DEVIATION FROM TEST STANDARD	23
4.2.5 TEST SETUP	24
4.2.6 EUT OPERATING CONDITIONS	24
4.2.7 TEST RESULTS	25
4.2.7.1 TEST RESULTS (LE MODE).....	35
4.3 6dB BANDWIDTH MEASUREMENT	39
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	39
4.3.2 TEST INSTRUMENTS	39
4.3.3 TEST PROCEDURE	39
4.3.4 DEVIATION FROM TEST STANDARD	39
4.3.5 TEST SETUP	39
4.3.6 EUT OPERATING CONDITIONS	39
4.3.7 TEST RESULTS	40
4.4 CONDUCTED OUTPUT POWER MEASUREMENT	41
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	41
4.4.2 INSTRUMENTS.....	41



A D T

4.4.3	TEST PROCEDURES	41
4.4.4	DEVIATION FROM TEST STANDARD	41
4.4.5	TEST SETUP	41
4.4.6	EUT OPERATING CONDITIONS	41
4.4.7	TEST RESULTS	42
4.5	POWER SPECTRAL DENSITY MEASUREMENT	43
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	43
4.5.2	TEST INSTRUMENTS	43
4.5.3	TEST PROCEDURE	43
4.5.4	DEVIATION FROM TEST STANDARD	43
4.5.5	TEST SETUP	43
4.5.6	EUT OPERATING CONDITION	43
4.5.7	TEST RESULTS	44
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	45
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	45
4.6.2	TEST INSTRUMENTS	45
4.6.3	TEST PROCEDURE	45
4.6.4	DEVIATION FROM TEST STANDARD	46
4.6.5	TEST SETUP	46
4.6.6	EUT OPERATING CONDITION	46
4.6.7	TEST RESULTS	46
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	51
6.	INFORMATION ON THE TESTING LABORATORIES	52
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	53



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120802E01	Original release	Sep. 21, 2012

1. CERTIFICATION

PRODUCT: WiFi+ BT Module
BRAND NAME: FOXCONN
MODEL NO.: J20H064
TEST SAMPLE: MASS-PRODUCTION
APPLICANT: Hon Hai PRECISION IND.CO.,LTD
TESTED: Aug. 07 to Sep. 04, 2012
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (Model: J20H064) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Sep. 21, 2012
(Claire Kuan, Specialist)

APPROVED BY :  , **DATE:** Sep. 21, 2012
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 2.4GHz(WLAN), 2412~2462MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.50dB at 0.16562MHz
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.5dB at 2483.50MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

For 2.4GHz(Bluetooth(LE mode)), 2402~2480MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.9dB at 68.00MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 dB
Radiated emissions (30MHz-1GHz)	5.59 dB
Radiated emissions (1GHz -6GHz)	3.56 dB
Radiated emissions (6GHz -18GHz)	4.10 dB
Radiated emissions (18GHz -40GHz)	4.24 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WiFi+ BT Module
MODEL NO.	J20H064
POWER SUPPLY	DC 5V \pm 5% from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE (GFSK) for DTS
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
TRANSFER RATE	802.11b: Up to 11Mbps 802.11g: Up to 54Mbps 802.11n (HT20): Up to 72.2Mbps BT-LE (GFSK): 1Mbps
OPERATING FREQUENCY	802.11b/g/n (HT20): 2.412 ~ 2.462GHz BT-LE (GFSK): 2.402 ~ 2.480GHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (HT20) 40 (37 hopping + 3 advertising channel) for BT-LE (GFSK)
MAXIMUM OUTPUT POWER	802.11b: 77.090mW 802.11g: 228.560mW 802.11n (HT20): 202.302mW BT-LE (GFSK): 1.268 mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

- There are Bluetooth technology and WLAN technology used for the EUT. And the report number corresponds with EUT functions are listed as below:

Function	Report No.
WLAN+ BT-LE (GFSK)	RF120802E01
Bluetooth	RF120802E01-1

- Spurious emission of the simultaneous operation (WLAN & Bluetooth) has been evaluated and no non-compliance was found.

3. The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Type	Connector	Gain (dBi)	Diversity Function	Frequency range From MHz to MHz
Chain (0) Ant. 1	PCB printed	NA	1.68	Yes	2400~2483.5
Chain (1) Ant. 2	PCB printed	NA	1.70	Yes	2400~2483.5

From above antennas, antenna 2 was chosen for final test

4. The EUT incorporates a SISO function without beam forming.

MODULATION MODE	Tx/Rx FUNCTION
802.11b	1Tx/1Rx
802.11g	1Tx/1Rx
802.11n (HT20)	1Tx/1Rx

5. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.

6. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's manual.



A D T

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Forty channels are provided for Bluetooth LE mode:

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

NOTE: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-Y plane**

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1	DSSS	DBPSK	1
Bluetooth LE	0 to 39	19	DTS	GFSK (LE mode)	1



A D T

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
Bluetooth LE	0 to 39	0, 19, 39	DTS	GFSK (LE mode)	1

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
Bluetooth LE	0 to 39	0, 19, 39	DTS	GFSK (LE mode)	1

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
Bluetooth LE	0 to 39	0, 19, 39	DTS	GFSK (LE mode)	1



A D T

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	26deg. C, 60%RH	120Vac, 60Hz (SYSTEM)	JyunChun Lin
RE<1G	28deg. C, 67%RH	120Vac, 60Hz (SYSTEM)	Robert Cheng
RE≥1G	28deg. C, 72%RH	120Vac, 60Hz (SYSTEM)	Robert Cheng
APCM	25deg. C, 60%RH	DC 5V	Rex Huang
OB	25deg. C, 60%RH	DC 5V	Rex Huang

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
558074 D01 DTS Meas Guidance v01
ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB cable (0.07m)

NOTE: The power cords of the above support units were unshielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST





A D T

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 12, 2012	Mar. 11, 2013
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 07, 2011	Sep. 06, 2012
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100072	June 08, 2012	June 07, 2013
RF Cable (JYEBAO)	5DFB	COCCAB-001	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	EMC-3	Sep. 26, 2011	Sep. 25, 2012
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Aug. 23, 2012

4.1.3 TEST PROCEDURES


- a. The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Turned on the power of all equipment.
2. Support unit 1 (Notebook computer) ran test program “DutApiBRIDGEETH8766(V1.1.7.46).exe” to enable EUT under transmission/receiving condition continuously via one USB cable.


4.1.7 TEST RESULTS

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
	1	0.16562	0.09	44.62	30.68	44.71	30.77	65.18	55.18	-20.47
2	0.22422	0.10	39.94	28.42	40.04	28.52	62.66	52.66	-22.62	-24.14
3	0.27109	0.11	38.56	30.64	38.67	30.75	61.08	51.08	-22.41	-20.33
4	1.26953	0.19	27.78	20.84	27.97	21.03	56.00	46.00	-28.03	-24.97
5	1.69922	0.21	29.28	22.74	29.49	22.95	56.00	46.00	-26.51	-23.05
6	3.56250	0.29	32.26	18.94	32.55	19.23	56.00	46.00	-23.45	-26.77

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
--------------	-------------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
	1	0.16562	0.08	46.96	40.60	47.04	40.68	65.18	55.18	-18.14
2	0.22031	0.10	43.58	37.16	43.68	37.26	62.81	52.81	-19.13	-15.55
3	0.32969	0.12	39.84	32.56	39.96	32.68	59.46	49.46	-19.50	-16.78
4	0.93906	0.16	32.46	23.94	32.62	24.10	56.00	46.00	-23.38	-21.90
5	1.71484	0.19	34.20	27.70	34.39	27.89	56.00	46.00	-21.61	-18.11
6	3.37500	0.22	34.28	21.34	34.50	21.56	56.00	46.00	-21.50	-24.44

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	July 09, 2012	July 08, 2013
Pre-Selector Agilent	N9039A	MY46520311	July 09, 2012	July 08, 2013
Signal Generator Agilent	N5181A	MY49060517	July 09, 2012	July 08, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 15, 2011	Nov. 14, 2012
Pre-Amplifier Agilent	8449B	3008A02578	June 26, 2012	June 25, 2013
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 15, 2011	Nov. 14, 2012
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Apr. 09, 2012	Apr. 08, 2013
Horn_Antenna AISI	AIH.8018	0000320091110	Nov. 14, 2011	Nov. 13, 2012
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 07, 2011	Oct. 06, 2012
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 26, 2011	Dec. 25, 2012
RF Cable	NA	CHGCAB_001	Oct. 07, 2011	Oct. 06, 2012
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Tested Date: Aug. 07 to Sep. 03, 2012

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	187.50	38.4 QP	43.5	-5.2	1.50 H	97	26.07	12.28
2	216.04	40.2 QP	46.0	-5.8	1.50 H	82	28.31	11.86
3	240.01	42.1 QP	46.0	-3.9	1.00 H	338	29.19	12.91
4	433.11	39.6 QP	46.0	-6.4	1.00 H	0	20.92	18.71
5	480.01	38.7 QP	46.0	-7.3	1.50 H	128	18.83	19.89
6	799.98	40.8 QP	46.0	-5.2	1.00 H	195	14.89	25.92
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.91	34.6 QP	40.0	-5.4	1.00 V	109	21.60	12.98
2	66.95	36.2 QP	40.0	-3.8	1.00 V	199	23.29	12.94
3	239.96	33.8 QP	46.0	-12.2	2.00 V	360	20.86	12.91
4	480.01	33.3 QP	46.0	-12.7	1.00 V	43	13.41	19.89
5	666.52	34.8 QP	46.0	-11.2	1.50 V	163	11.29	23.51
6	833.14	31.4 QP	46.0	-14.6	2.00 V	199	4.89	26.47

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.9 PK	74.0	-18.1	1.77 H	117	23.92	31.98
2	2390.00	43.8 AV	54.0	-10.2	1.77 H	117	11.82	31.98
3	*2412.00	97.7 PK			1.77 H	117	65.65	32.05
4	*2412.00	95.4 AV			1.77 H	117	63.35	32.05
5	4824.00	47.4 PK	74.0	-26.6	1.13 H	212	7.82	39.58
6	4824.00	34.9 AV	54.0	-19.1	1.13 H	212	-4.68	39.58

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.2 PK	74.0	-17.8	1.32 V	215	24.22	31.98
2	2390.00	44.3 AV	54.0	-9.7	1.32 V	215	12.32	31.98
3	*2412.00	93.8 PK			1.32 V	215	61.75	32.05
4	*2412.00	91.0 AV			1.32 V	215	58.95	32.05
5	4824.00	45.9 PK	74.0	-28.1	1.13 V	111	6.32	39.58
6	4824.00	34.6 AV	54.0	-19.4	1.13 V	111	-4.98	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.5 PK			1.78 H	112	65.38	32.12
2	*2437.00	95.2 AV			1.78 H	112	63.08	32.12
3	4874.00	47.0 PK	74.0	-27.0	1.10 H	206	7.30	39.70
4	4874.00	34.5 AV	54.0	-19.5	1.10 H	206	-5.20	39.70
5	7311.00	54.2 PK	74.0	-19.8	1.00 H	134	6.61	47.59
6	7311.00	41.8 AV	54.0	-12.2	1.00 H	134	-5.79	47.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	93.7 PK			1.40 V	187	61.58	32.12
2	*2437.00	91.1 AV			1.40 V	187	58.98	32.12
3	4874.00	45.8 PK	74.0	-28.2	1.17 V	113	6.10	39.70
4	4874.00	34.3 AV	54.0	-19.7	1.17 V	113	-5.40	39.70
5	7311.00	53.8 PK	74.0	-20.2	1.00 V	205	6.21	47.59
6	7311.00	41.4 AV	54.0	-12.6	1.00 V	205	-6.19	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.6 PK			1.71 H	113	66.42	32.18
2	*2462.00	96.4 AV			1.71 H	113	64.22	32.18
3	2483.50	56.2 PK	74.0	-17.8	1.71 H	113	23.96	32.24
4	2483.50	43.8 AV	54.0	-10.2	1.71 H	113	11.56	32.24
5	4924.00	47.3 PK	74.0	-26.7	1.08 H	201	7.46	39.84
6	4924.00	34.6 AV	54.0	-19.4	1.08 H	201	-5.24	39.84
7	7386.00	53.9 PK	74.0	-20.1	1.00 H	125	6.38	47.52
8	7386.00	41.5 AV	54.0	-12.5	1.00 H	125	-6.02	47.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.8 PK			1.39 V	185	62.62	32.18
2	*2462.00	92.2 AV			1.39 V	185	60.02	32.18
3	2483.50	56.1 PK	74.0	-17.9	1.39 V	185	23.86	32.24
4	2483.50	44.2 AV	54.0	-9.8	1.39 V	185	11.96	32.24
5	4924.00	46.1 PK	74.0	-27.9	1.21 V	110	6.26	39.84
6	4924.00	34.1 AV	54.0	-19.9	1.21 V	110	-5.74	39.84
7	7386.00	53.9 PK	74.0	-20.1	1.00 V	215	6.38	47.52
8	7386.00	41.5 AV	54.0	-12.5	1.00 V	215	-6.02	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



A D T

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.6 PK	74.0	-14.4	1.74 H	117	27.62	31.98
2	2390.00	48.7 AV	54.0	-5.3	1.74 H	117	16.72	31.98
3	*2412.00	100.1 PK			1.74 H	117	68.05	32.05
4	*2412.00	91.3 AV			1.74 H	117	59.25	32.05
5	4824.00	47.5 PK	74.0	-26.5	1.13 H	199	7.92	39.58
6	4824.00	35.3 AV	54.0	-18.7	1.13 H	199	-4.28	39.58

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.31 V	216	25.82	31.98
2	2390.00	45.4 AV	54.0	-8.6	1.31 V	216	13.42	31.98
3	*2412.00	94.0 PK			1.52 V	186	61.95	32.05
4	*2412.00	85.3 AV			1.52 V	186	53.25	32.05
5	4824.00	46.0 PK	74.0	-28.0	1.17 V	99	6.42	39.58
6	4824.00	34.9 AV	54.0	-19.1	1.17 V	99	-4.68	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.3 PK			1.72 H	112	68.18	32.12
2	*2437.00	91.6 AV			1.72 H	112	59.48	32.12
3	4874.00	47.4 PK	74.0	-26.6	1.08 H	192	7.70	39.70
4	4874.00	34.9 AV	54.0	-19.1	1.08 H	192	-4.80	39.70
5	7311.00	53.7 PK	74.0	-20.3	1.00 H	115	6.11	47.59
6	7311.00	41.6 AV	54.0	-12.4	1.00 H	115	-5.99	47.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	95.2 PK			1.40 V	186	63.08	32.12
2	*2437.00	86.1 AV			1.40 V	186	53.98	32.12
3	4874.00	45.6 PK	74.0	-28.4	1.20 V	128	5.90	39.70
4	4874.00	33.4 AV	54.0	-20.6	1.20 V	128	-6.30	39.70
5	7311.00	53.4 PK	74.0	-20.6	1.00 V	201	5.81	47.59
6	7311.00	41.0 AV	54.0	-13.0	1.00 V	201	-6.59	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.4 PK			1.73 H	112	70.22	32.18
2	*2462.00	90.7 AV			1.73 H	112	58.52	32.18
3	2483.50	65.8 PK	74.0	-8.2	1.73 H	112	33.56	32.24
4	2483.50	50.4 AV	54.0	-3.6	1.73 H	112	18.16	32.24
5	4924.00	47.5 PK	74.0	-26.5	1.04 H	194	7.66	39.84
6	4924.00	35.0 AV	54.0	-19.0	1.04 H	194	-4.84	39.84
7	7386.00	53.4 PK	74.0	-20.6	1.00 H	113	5.88	47.52
8	7386.00	41.2 AV	54.0	-12.8	1.00 H	113	-6.32	47.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	95.2 PK			1.31 V	188	63.02	32.18
2	*2462.00	86.6 AV			1.31 V	188	54.42	32.18
3	2483.50	58.4 PK	74.0	-15.6	1.31 V	188	26.16	32.24
4	2483.50	45.7 AV	54.0	-8.3	1.31 V	188	13.46	32.24
5	4924.00	45.8 PK	74.0	-28.2	1.20 V	101	5.96	39.84
6	4924.00	33.8 AV	54.0	-20.2	1.20 V	101	-6.04	39.84
7	7386.00	54.0 PK	74.0	-20.0	1.00 V	228	6.48	47.52
8	7386.00	41.8 AV	54.0	-12.2	1.00 V	228	-5.72	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



A D T

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.2 PK	74.0	-8.8	1.74 H	118	33.22	31.98
2	2390.00	49.7 AV	54.0	-4.3	1.74 H	118	17.72	31.98
3	*2412.00	100.4 PK			1.74 H	118	68.35	32.05
4	*2412.00	90.7 AV			1.74 H	118	58.65	32.05
5	4824.00	47.3 PK	74.0	-26.7	1.10 H	206	7.72	39.58
6	4824.00	34.9 AV	54.0	-19.1	1.10 H	206	-4.68	39.58

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.8 PK	74.0	-15.2	1.34 V	183	26.82	31.98
2	2390.00	45.9 AV	54.0	-8.1	1.34 V	183	13.92	31.98
3	*2412.00	92.5 PK			1.35 V	205	60.45	32.05
4	*2412.00	83.8 AV			1.35 V	205	51.75	32.05
5	4824.00	45.9 PK	74.0	-28.1	1.23 V	107	6.32	39.58
6	4824.00	34.9 AV	54.0	-19.1	1.23 V	107	-4.68	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.2 PK			1.73 H	107	68.08	32.12
2	*2437.00	90.7 AV			1.73 H	107	58.58	32.12
3	4874.00	47.3 PK	74.0	-26.7	1.08 H	179	7.60	39.70
4	4874.00	34.8 AV	54.0	-19.2	1.08 H	179	-4.90	39.70
5	7311.00	53.6 PK	74.0	-20.4	1.03 H	115	6.01	47.59
6	7311.00	41.7 AV	54.0	-12.3	1.03 H	115	-5.89	47.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	93.4 PK			1.48 V	185	61.28	32.12
2	*2437.00	85.6 AV			1.48 V	185	53.48	32.12
3	4874.00	45.6 PK	74.0	-28.4	1.16 V	134	5.90	39.70
4	4874.00	33.6 AV	54.0	-20.4	1.16 V	134	-6.10	39.70
5	7311.00	53.0 PK	74.0	-21.0	1.00 V	186	5.41	47.59
6	7311.00	40.9 AV	54.0	-13.1	1.00 V	186	-6.69	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.6 PK			1.69 H	110	68.42	32.18
2	*2462.00	91.0 AV			1.69 H	110	58.82	32.18
3	2483.50	66.7 PK	74.0	-7.3	1.69 H	110	34.46	32.24
4	2483.50	50.5 AV	54.0	-3.5	1.69 H	110	18.26	32.24
5	4924.00	47.3 PK	74.0	-26.7	1.08 H	186	7.46	39.84
6	4924.00	35.0 AV	54.0	-19.0	1.08 H	186	-4.84	39.84
7	7386.00	53.2 PK	74.0	-20.8	1.00 H	122	5.68	47.52
8	7386.00	41.1 AV	54.0	-12.9	1.00 H	122	-6.42	47.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	95.0 PK			1.36 V	186	62.82	32.18
2	*2462.00	86.3 AV			1.36 V	186	54.12	32.18
3	2483.50	58.4 PK	74.0	-15.6	1.36 V	186	26.16	32.24
4	2483.50	46.3 AV	54.0	-7.7	1.36 V	186	14.06	32.24
5	4924.00	45.3 PK	74.0	-28.7	1.15 V	121	5.46	39.84
6	4924.00	33.2 AV	54.0	-20.8	1.15 V	121	-6.64	39.84
7	7386.00	53.2 PK	74.0	-20.8	1.00 V	178	5.68	47.52
8	7386.00	40.8 AV	54.0	-13.2	1.00 V	178	-6.72	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

4.2.7.1 TEST RESULTS (LE MODE)

BELOW 1GHz WORST-CASE DATA

BT_LE-GFSK

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	191.00	38.2 QP	43.5	-5.3	1.50 H	97	26.25	11.97
2	216.20	40.1 QP	46.0	-5.9	1.50 H	82	28.19	11.87
3	240.08	42.0 QP	46.0	-4.0	1.00 H	338	29.09	12.92
4	433.18	39.5 QP	46.0	-6.5	1.00 H	0	20.81	18.71
5	480.08	38.6 QP	46.0	-7.4	1.50 H	128	18.72	19.89
6	803.00	40.7 QP	46.0	-5.3	1.00 H	195	14.73	25.97

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.95	34.5 QP	40.0	-5.5	1.00 V	109	21.50	12.98
2	68.00	36.1 QP	40.0	-3.9	1.00 V	199	23.31	12.83
3	241.00	33.7 QP	46.0	-12.3	2.00 V	360	20.70	12.96
4	480.06	33.2 QP	46.0	-12.8	1.00 V	43	13.30	19.89
5	666.57	34.7 QP	46.0	-11.3	1.50 V	163	11.15	23.52
6	833.20	31.3 QP	46.0	-14.7	2.00 V	199	4.80	26.47

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

ABOVE 1GHz DATA

BT_LE-GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.1 PK	74.0	-17.9	1.00 H	323	24.12	31.98
2	2390.00	43.1 AV	54.0	-10.9	1.00 H	323	11.12	31.98
3	*2402.00	93.2 PK			1.00 H	323	61.17	32.03
4	*2402.00	77.1 AV			1.00 H	323	45.07	32.03
5	4804.00	50.1 PK	74.0	-23.9	1.02 H	189	10.57	39.53
6	4804.00	38.6 AV	54.0	-15.4	1.02 H	189	-0.93	39.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.4 PK	74.0	-17.6	1.00 V	86	24.42	31.98
2	2390.00	42.2 AV	54.0	-11.8	1.00 V	86	10.22	31.98
3	*2402.00	88.8 PK			1.00 V	86	56.77	32.03
4	*2402.00	74.5 AV			1.00 V	86	42.47	32.03
5	4804.00	47.1 PK	74.0	-26.9	1.00 V	195	7.57	39.53
6	4804.00	35.4 AV	54.0	-18.6	1.00 V	195	-4.13	39.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	95.6 PK			1.00 H	322	63.48	32.12
2	*2440.00	78.8 AV			1.00 H	322	46.68	32.12
3	4880.00	50.4 PK	74.0	-23.6	1.04 H	176	10.69	39.71
4	4880.00	39.0 AV	54.0	-15.0	1.04 H	176	-0.71	39.71
5	7320.00	55.8 PK	74.0	-18.2	1.06 H	147	8.22	47.58
6	7320.00	44.3 AV	54.0	-9.7	1.06 H	147	-3.28	47.58

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	91.2 PK			1.00 V	85	59.08	32.12
2	*2440.00	74.4 AV			1.00 V	85	42.28	32.12
3	4880.00	46.4 PK	74.0	-27.6	1.00 V	186	6.69	39.71
4	4880.00	35.0 AV	54.0	-19.0	1.00 V	186	-4.71	39.71
5	7320.00	57.3 PK	74.0	-16.7	1.21 V	156	9.72	47.58
6	7320.00	45.4 AV	54.0	-8.6	1.21 V	156	-2.18	47.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	95.7 PK			1.00 H	319	63.47	32.23
2	*2480.00	78.9 AV			1.00 H	319	46.67	32.23
3	2483.50	57.7 PK	74.0	-16.3	1.00 H	319	25.46	32.24
4	2483.50	43.4 AV	54.0	-10.6	1.00 H	319	11.16	32.24
5	4960.00	50.6 PK	74.0	-23.4	1.09 H	186	10.65	39.95
6	4960.00	39.3 AV	54.0	-14.7	1.09 H	186	-0.65	39.95
7	7440.00	56.3 PK	74.0	-17.7	1.00 H	151	8.90	47.40
8	7440.00	44.6 AV	54.0	-9.4	1.00 H	151	-2.80	47.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.3 PK			1.00 V	85	59.07	32.23
2	*2480.00	74.5 AV			1.00 V	85	42.27	32.23
3	2483.50	56.5 PK	74.0	-17.5	1.00 V	85	24.26	32.24
4	2483.50	42.3 AV	54.0	-11.7	1.00 V	85	10.06	32.24
5	4960.00	46.4 PK	74.0	-27.6	1.00 V	194	6.45	39.95
6	4960.00	35.2 AV	54.0	-18.8	1.00 V	194	-4.75	39.95
7	7440.00	57.7 PK	74.0	-16.3	1.16 V	148	10.30	47.40
8	7440.00	45.5 AV	54.0	-8.5	1.16 V	148	-1.90	47.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 04, 2012


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	10.26	0.5	PASS
6	2437	10.27	0.5	PASS
11	2462	10.27	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.58	0.5	PASS
6	2437	16.56	0.5	PASS
11	2462	16.54	0.5	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.84	0.5	PASS
6	2437	17.83	0.5	PASS
11	2462	17.85	0.5	PASS

BT_LE-GFSK

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.76	0.5	PASS
19	2440	0.76	0.5	PASS
39	2480	0.76	0.5	PASS

4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 10, 2012	May 09, 2013
Peak Power Sensor	MA2411B	0738172	May 10, 2012	May 09, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 04, 2012


4.4.3 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



A D T

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	77.090	18.87	30	PASS
6	2437	55.847	17.47	30	PASS
11	2462	56.494	17.52	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	219.786	23.42	30	PASS
6	2437	228.560	23.59	30	PASS
11	2462	207.970	23.18	30	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	189.671	22.78	30	PASS
6	2437	202.302	23.06	30	PASS
11	2462	179.061	22.53	30	PASS

BT_LE-GFSK

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
0	2402	1.242	0.94	30	PASS
19	2440	1.268	1.03	30	PASS
39	2480	1.233	0.91	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 04, 2012


4.5.3 TEST PROCEDURE

1. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100\text{kHz})$

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



A D T

4.5.7 TEST RESULTS

802.11b

Channel	FREQUENCY (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	3.51	-11.72	8	PASS
6	2437	3.03	-12.20	8	PASS
11	2462	3.18	-12.05	8	PASS

802.11g

Channel	FREQUENCY (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	0.19	-15.04	8	PASS
6	2437	1.52	-13.71	8	PASS
11	2462	-1.07	-16.30	8	PASS

802.11n (HT20)

Channel	FREQUENCY (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	1.20	-14.03	8	PASS
6	2437	0.51	-14.72	8	PASS
11	2462	-0.13	-15.36	8	PASS

BT_LE-GFSK

Channel	FREQUENCY (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-0.03	-15.26	8	PASS
19	2440	0.08	-15.15	8	PASS
39	2480	-0.03	-15.26	8	PASS

4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 04, 2012

4.6.3 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

802.11b



CH 1



CH 6



CH 11









A D T

802.11g



CH 1



CH 6



CH 11









A D T

802.11n (HT20)



CH 1



CH 6



CH 11









A D T

BT_LE-GFSK



CH 0



CH 19



CH 39



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---