RF EXPOSURE REPORT

REPORT NO.:	SA120706E03
MODEL NO.:	J20H066
FCC ID:	MCLJ20H066
RECEIVED:	July 06, 2012
TESTED:	July 10, 2012
ISSUED:	Aug. 06, 2012
APPLICANT:	Hon Hai PRECISION IND.CO.,LTD
ADDRESS:	5F-1, Hsin-An Road, Hsinchu, Science Industrial Park, Taiwan, R.O.C.
ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
LAB ADDRESS:	No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

TABLE OF CONTENTS

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120706E03	Original release	Aug. 06, 2012

1. CERTIFICATION

PRODUCT:	Bluetooth Module
BRAND NAME:	FOXCONN
MODEL NO.:	J20H066
TEST SAMPLE:	ENGINEERING SAMPLE
APPLICANT:	Hon Hai PRECISION IND.CO.,LTD
TESTED DATE:	July 10, 2012
STANDARDS:	FCC Part 2 (Section 2.1091)
	FCC OET Bulletin 65, Supplement C (01-01)
	IEEE C95.1

The above equipment (Model: J20H066) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ , **DATE :** *Aug. 06, 2012*
(Claire Kuan, Specialist)

APPROVED BY : _____ , **DATE :** *Aug. 06, 2012*
(May Chen, Deputy Manager)

2. EVALUATION RESULT

No SAR Evaluation Required if power is below the following threshold:

Tunable Range		
F(GHz) Low	F(GHz) High	60/f SAR Limitation (mW)
2.402	2.480	24.19

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
1.66	1.466	1.07	1.875

Threshold for no SAR evaluation is 24.19 mW
Maximum TX Power is 1.466 mW Conducted and 1.875 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold

--- END ---