

## Operational Description

This device is a 802.11ac/abgn/BT wireless module, which operates in both of the 5GHz and 2.4GHz bands and can't transmitting simultaneously, the maximum data rate could be up to 433.3Mbps which OFDM technique. If the signal to noise ratio is too poor which could not support 433.3Mbps, the 11Mbps data rate with DSSS technique will be applied.

The transmitter of the EUT is powered DC 5V±5%.

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Gain (dBi) (Include cable loss)	Antenna Type	Connector Type	Frequency range (MHz to MHz)
Chain (0)	-0.4	PCB	NA	2400~2483.5
	1.12			5150~5850
Chain (1)	0.28	PCB	NA	2400~2483.5
	0.9			5150~5850

The other instruction, please have a look at the users manual.

FCC 15.407(c) states: The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met"

Data transmission is always initiated by software, which is then pass down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets (ACKs, CTS, PSpoll, etc...) are initiated by the MAC. There are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets are being transmitted.