





Notes:

- 1."  " "  " logo' dimension not less than 5mm
- 2."  " logo' dimension not less than 3mm
- 3."N10158,Z189" dimension not less than 1 mm
- 4."IC:2878D-J27H007"dimension not less than 1.5mm

VER.	MARK	DCR/ECN NO.	DATE	UPDATE DESCRIPTION	SIGNATURE
00			07.08.16	First Release	Yan-li



scale 3:1



scale 1:1

Notes:

- 1.貼於PCB板
- 2.文字顏色:黑色

MATERIAL MAKER	25# 白色特多龍商標紙 (冠郝)
MODEL NO.	HTKW 25J
SURFACE MATERIAL THICKNESS (mm)	0.025±0.004
ADHSTIVE NO.	arcylic #1
ADHSTIVE THICKNESS (mm)	0.026±0.002
TOTAL THICKNESS (mm)	0.051±0.005
PEEL ADHESION (kg/25mm)	0.8
RELEASE FORCE (g/25mm)	10±5
HOLDING POWER (hr/kg/20mm ²)	8
SERVICE TEMPERATURE (°C)	5~100

MATERIAL (SPEC.)										SCALE	FOXCONN HON HAI PRECISION IND. CO., LTD			
Mylar#25(white)+Light(pp)										1/1				
FINISH										SHEET	PART NAME			
										1 OF 1				
Select Dim.	tol.	A	B	C	EPS	EPE	BAG	CTN	Label	USR	UNIT	PART NO.		
										mm	DESIGNED			
										SIZE				APPROVED
										A4	Jun j cai			
										CUSTOMER MODEL				CUSTOMER PART NO.
0~6	0.05	0.05	0.10						0.20			500.xxxxx.xxx		
6~30	0.10	0.15	0.20	0.50	0.50	3.00			0.20		Yan-li			
30~120	0.15	0.20	0.30	0.50	0.50	5.00	2.00	0.25						Jun j cai
120~300	0.20	0.30	0.40	1.00	1.00	10.00	3.00	0.30			Jun j cai			
300~450	0.25	0.40	0.50	2.00	2.00	15.00	5.00	0.50						Jun j cai
450~600	0.30	0.50	0.60	3.00	3.00	20.00	5.00	0.80			Jun j cai			
DRAFT TOLERANCE ±0.2'										CRITICAL DIM. MARK *				

Label Location

