



RF EXPOSURE REPORT

REPORT NO.: RF921118R02A

MODEL NO.: T60H786

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: AMBIT Microsystems Corporation

ADDRESS: 5F-1, 5 Hsin-An Road Hsinchu, Science-
Based Industrial Park Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan,
R.O.C.



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	6
1500-100,000	1.0	30

F = Frequency in MHz



3. Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

This modular is specified to be installed in the notebook which is connected with host through wire. So it is easy to be re-located in the place where at least 20cm far away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**



6. Test Results

6.1 Antenna Gain

PIFA Antenna (Type H):

The maximum Gain measured in Fully Anechoic Chamber is 0.48dBi or 1.12 (numeric).

Lambda/4 PIFI Antenna (Type F'):

The maximum Gain measured in Fully Anechoic Chamber is 0.60dBi or 1.15 (numeric).

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

FOR CCK TECHNIQUE

ANTENNA TYPE: PIFA Antenna (Type H)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	90.573	0.0201	1.0
6	2437	87.096	0.1935	1.0
11	2462	85.704	0.0190	1.0

ANTENNA TYPE: Lambda/4 PIFI Antenna (Type F')

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	91.411	0.0209	1.0
6	2437	88.716	0.0206	1.0
11	2462	86.696	0.0198	1.0



FOR OFDM TECHNIQUE

ANTENNA TYPE: PIFA Antenna (Type H)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	140.929	0.0313	1.0
6	2437	189.671	0.0421	1.0
11	2462	134.586	0.0299	1.0

ANTENNA TYPE: Lambda/4 PIFI Antenna (Type F')

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	142.233	0.0325	1.0
6	2437	194.536	0.0444	1.0
11	2462	140.281	0.0320	1.0