




REV.	MARK	ECR/ECN NO.	DATE	UPDATE DESCRIPTION	SIGNATURE
0	N/A	N/A	08.12.22	First Release	Yanli-Yu



Scale:1:1

Note:
The minimum height of IC: 2878D-T77H054 is 1.5mm

"" The minimum height of 5mm for the logo

MATERIAL (SPEC.) Mylar 25 #										SCALE 1:1	 HON HAI PRECISION IND. CO., LTD CNSBG																																																																															
FINISH										SHEET 1/1																																																																																
<table border="1"> <thead> <tr> <th>Select Dim.</th> <th>Tol.</th> <th>A</th> <th>B</th> <th>C</th> <th>EPS</th> <th>EPE</th> <th>BAG</th> <th>CTN</th> <th>Label</th> <th>USR</th> </tr> </thead> <tbody> <tr> <td>0~6</td> <td></td> <td>0.05</td> <td>0.05</td> <td>0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0.20</td> </tr> <tr> <td>6~30</td> <td></td> <td>0.10</td> <td>0.15</td> <td>0.20</td> <td>0.50</td> <td>0.50</td> <td>3.00</td> <td></td> <td></td> <td>0.20</td> </tr> <tr> <td>30~120</td> <td></td> <td>0.15</td> <td>0.20</td> <td>0.30</td> <td>0.50</td> <td>0.50</td> <td>5.00</td> <td>2.00</td> <td></td> <td>0.25</td> </tr> <tr> <td>120~300</td> <td></td> <td>0.20</td> <td>0.30</td> <td>0.40</td> <td>1.00</td> <td>1.00</td> <td>10.00</td> <td>3.00</td> <td></td> <td>0.30</td> </tr> <tr> <td>300~450</td> <td></td> <td>0.25</td> <td>0.40</td> <td>0.50</td> <td>2.00</td> <td>2.00</td> <td>15.00</td> <td>5.00</td> <td></td> <td>0.50</td> </tr> <tr> <td>450~600</td> <td></td> <td>0.30</td> <td>0.50</td> <td>0.60</td> <td>3.00</td> <td>3.00</td> <td>20.00</td> <td>5.00</td> <td></td> <td>0.80</td> </tr> </tbody> </table>										Select Dim.	Tol.	A	B	C	EPS	EPE	BAG	CTN	Label	USR	0~6		0.05	0.05	0.10						0.20	6~30		0.10	0.15	0.20	0.50	0.50	3.00			0.20	30~120		0.15	0.20	0.30	0.50	0.50	5.00	2.00		0.25	120~300		0.20	0.30	0.40	1.00	1.00	10.00	3.00		0.30	300~450		0.25	0.40	0.50	2.00	2.00	15.00	5.00		0.50	450~600		0.30	0.50	0.60	3.00	3.00	20.00	5.00		0.80	UNIT MM	PART NAME PTT label		
Select Dim.	Tol.	A	B	C	EPS	EPE	BAG	CTN	Label	USR																																																																																
0~6		0.05	0.05	0.10						0.20																																																																																
6~30		0.10	0.15	0.20	0.50	0.50	3.00			0.20																																																																																
30~120		0.15	0.20	0.30	0.50	0.50	5.00	2.00		0.25																																																																																
120~300		0.20	0.30	0.40	1.00	1.00	10.00	3.00		0.30																																																																																
300~450		0.25	0.40	0.50	2.00	2.00	15.00	5.00		0.50																																																																																
450~600		0.30	0.50	0.60	3.00	3.00	20.00	5.00		0.80																																																																																
DRAFT TOLERANCE										SIZE	MODEL T77H054.00	PART NO.	DESIGNED Yanli-Yu																																																																													
±0.2°											CUSTOMER MODEL	CUSTOMER PART NO.	APPROVED Sunny																																																																													
CRITICAL DIM. MARK *																																																																																										