



# FCC TEST REPORT

**REPORT NO.:** RF980731H01

**MODEL NO.:** T77H114

**RECEIVED:** July 15, 2009

**TESTED:** Aug. 03 to 18, 2009

**ISSUED:** Sep. 14, 2009

**APPLICANT:** Hon Hai PRECISION IND. CO., LTD

**ADDRESS:** 5F-1, 5 Hsin-An Road Hsinchu, Science-Based  
Industrial Park Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung  
Tsuen, Chung Lin Hsiang, Hsin Chu Hsien 307,  
Taiwan

This test report consists of 97 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.



# TABLE OF CONTENTS

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS.....	5
2.1	measurement uncertainty .....	6
3	GENERAL INFORMATION .....	7
3.1	GENERAL DESCRIPTION OF EUT.....	7
3.2	DESCRIPTION OF TEST MODES.....	9
3.3	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL: .....	10
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
3.5	DESCRIPTION OF SUPPORT UNITS .....	13
3.6	CONFIGURATION OF SYSTEM UNDER TEST.....	13
4	TEST PROCEDURES AND RESULTS .....	14
4.1	CONDUCTED EMISSION MEASUREMENT .....	14
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	14
4.1.2	TEST INSTRUMENTS.....	14
4.1.3	TEST PROCEDURES .....	15
4.1.4	TEST SETUP .....	15
4.1.5	EUT OPERATING CONDITIONS.....	16
4.1.6	Test Results.....	17
4.2	number of hopping frequency used.....	19
4.2.1	LIMIT OF HOPPING FREQUENCY USED.....	19
4.2.2	TEST INSTRUMENTS.....	19
4.2.3	TEST PROCEDURES .....	19
4.2.4	DEVIATION FROM TEST STANDARD .....	19
4.2.5	TEST SETUP .....	20
4.2.6	TEST RESULTS .....	20
4.3	DWELL TIME ON EACH CHANNEL .....	24
4.3.1	LIMIT OF DWELL TIME USED .....	24
4.3.2	TEST INSTRUMENTS.....	24
4.3.3	TEST PROCEDURES .....	24
4.3.4	DEVIATION FROM TEST STANDARD .....	25
4.3.5	TEST SETUP .....	25
4.3.6	TEST RESULTS.....	25
4.4	CHANNEL BANDWIDTH .....	29
4.4.1	LIMITS OF CHANNEL BANDWIDTH .....	29
4.4.2	TEST INSTRUMENTS.....	29
4.4.3	TEST PROCEDURE.....	29
4.4.4	DEVIATION FROM TEST STANDARD .....	29
4.4.5	TEST SETUP .....	30
4.4.6	EUT OPERATING CONDITION .....	30
4.4.7	TEST RESULTS .....	31
4.5	HOPPING CHANNEL SEPARATION .....	37
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION.....	37
4.5.2	TEST INSTRUMENTS.....	37
4.5.3	TEST PROCEDURES .....	37
4.5.4	DEVIATION FROM TEST STANDARD .....	38



A D T

4.5.5	TEST SETUP .....	38
4.5.6	TEST RESULTS .....	39
4.6	MAXIMUM PEAK OUTPUT POWER .....	45
4.6.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	45
4.6.2	INSTRUMENTS .....	45
4.6.3	TEST PROCEDURES .....	45
4.6.4	DEVIATION FROM TEST STANDARD .....	45
4.6.5	TEST SETUP .....	46
4.6.6	EUT OPERATING CONDITION .....	46
4.6.7	TEST RESULTS – Dipole antenna.....	47
4.6.8	TEST RESULTS – Turned Monopole antenna.....	53
4.6.9	TEST RESULTS – PIFA antenna .....	59
4.7	RADIATED EMISSION MEASUREMENT .....	65
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	65
4.7.2	TEST INSTRUMENTS.....	66
4.7.3	TEST PROCEDURES .....	67
4.7.4	DEVIATION FROM TEST STANDARD .....	67
4.7.5	TEST SETUP .....	68
4.7.6	TEST RESULTS .....	69
4.8	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	90
4.8.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	90
4.8.2	TEST INSTRUMENTS.....	90
4.8.3	TEST PROCEDURE.....	90
4.8.4	DEVIATION FROM TEST STANDARD .....	90
4.8.5	EUT OPERATING CONDITION .....	90
4.8.6	TEST RESULTS .....	91
4.9	ANTENNA REQUIREMENT.....	95
4.9.1	STANDARD APPLICABLE.....	95
4.9.2	ANTENNA CONNECTED CONSTRUCTION .....	95
5	INFORMATION ON THE TESTING LABORATORIES.....	96
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	97



## 1 CERTIFICATION

**PRODUCT :** Bluetooth Module  
**BRAND NAME :** Foxconn  
**MODEL NO. :** T77H114  
**APPLICANT :** Hon Hai PRECISION IND. CO., LTD  
**TESTED DATE :** Aug. 03 to 18, 2009  
**TEST SAMPLE :** ENGINEERING SAMPLE  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2003

The above equipment (Model: T77H114) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Sunny Wen , **DATE:** Sep. 14, 2009  
( Sunny Wen, Specialist )

**TECHNICAL ACCEPTANCE :** Hank Chung , **DATE:** Sep. 14, 2009  
Responsible for RF ( Hank Chung, Deputy Manager )

**APPROVED BY :** May Chen , **DATE:** Sep. 14, 2009  
( May Chen, Deputy Manager )



A D T

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -19.35dB at 0.154MHz
15.247(a)(1)(I)-(ii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit
15.247(a)(1)(ii)	Dwell Time on Each Channel Spec.: Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit
15.247(a)(1)(I)-(ii)	Hopping Channel Separation Spec. : Min. 25 kHz or two-thirds of 20 dB bandwidth, which ever is greater	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Report reference
15.247(b)	Maximum Peak Output Power Spec.: max. 125mW	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -7.80dB at 7206.00MHz
15.247(c)	Conducted Out-Band Emissions Measurement	PASS	Meet the requirement of limit

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Measurement	Value
Conducted emissions	2.44 dB
Radiated emissions (30MHz-1GHz)	3.94 dB
Radiated emissions (1GHz ~18GHz)	2.49 dB
Radiated emissions (18GHz ~20GHz)	2.70 dB

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Bluetooth Module
<b>MODEL NO.</b>	T77H114
<b>FCC ID</b>	MCLT77H114
<b>POWER SUPPLY</b>	DC 3.3V±0.5% from host equipment
<b>MODULATION TYPE</b>	GFSK, 8DPSK, $\pi/4$ -DQPSK
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>FREQUENCY RANGE</b>	2402MHz ~ 2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>OUTPUT POWER</b>	1.164mW
<b>ANTENNA TYPE</b>	See note 1 below
<b>DATA CABLE</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. There are nine antennas provided to this EUT, please refer to the following table:

Brand	Model No.	Antenna Connector	Antenna Type	Antenna Gain with cable loss (dBi)	Cable Length (cm)
Wha Yu Group	C034-510481-A	I-PEX	Dipole	2.15	20±0.3
Typo Electronic	NA	I-PEX	Turned Monopole	3	8.8
Wha Yu Group	NE-8048	I-PEX	PIFA	3.07	5.7
Acon	APP6P-700320	I-PEX	PIFA	2.93	18±0.3
Acon	APP6P-700307	I-PEX	PIFA	-2.54	32.7±0.3
Foxconn	WDAN-SPM93007-1F	I-PEX	PIFA	1.32	27.5±0.3
Foxconn	WDAN-SPM87003-1F	I-PEX	PIFA	2.15	32.7±0.3
Whayu	C680-520196-A	I-PEX	PIFA	0.95	6.4±0.3
Acon	APP6P-700339	I-PEX	Monopole	1.66	27.9±0.3

From the above antennas, the **Dipole, Turned Monopole & PIFA antenna (model no.: NE-8048)** were selected as representative model for the test and its data was recorded in this report.

2. The EUT was pre-tested under the following modes:

Test Mode	Description	Antenna Type
Mode A	X-Y plane	<b>Turned Monopole</b>
Mode B	X-Z plane	
<b>Mode C</b>	<b>Y-Z plane</b>	
<b>Mode D</b>	<b>X-Y plane</b>	<b>PIFA</b>
Mode E	X-Z plane	
Mode F	Y-Z plane	

From the above modes, the worst emission levels were found in **Mode C & D**. Therefore only the test data of the modes were recorded in this report individually.

3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.





### 3.2 DESCRIPTION OF TEST MODES

Seventy-nine channels are provided to this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

### 3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	√	√	Dipole antenna
B		√	√	√	Turned Monopole antenna
C		√	√	√	PIFA antenna

Where PLC: Power Line Conducted Emission RE<1G RE: Radiated Emission below 1GHz  
 RE≥1G: Radiated Emission above 1GHz APCM: Antenna Port Conducted Measurement

#### **Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	8DPSK	DH5

#### **Radiated Emission Test (Below 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0	FHSS	GFSK	DH5

#### **Radiated Emission Test (Above 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**Conducted Out-Band Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 78	FHSS	GFSK	DH5
0 to 78	0, 78	FHSS	8DPSK	DH5

**Antenna Port Conducted Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ -DQPSK	DH5



### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a Bluetooth Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4 : 2003**

All test items have been performed and recorded as per the above standards.

### 3.5 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP17L	CN-ONF743-48643-7AV-0124	DoC
2	TEST TOOL	Foxconn	NA	NA	NA

No.	Signal cable description
1	NA
2	NA

Note: 1. All power cords of the above support units are unshielded (1.8m).

### 3.6 CONFIGURATION OF SYSTEM UNDER TEST





A D T

## 4 TEST PROCEDURES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 23, 2009	Mar. 22, 2010
Line-Impedance Stabilization Network (for Peripheral)	ENV-216	100071	Nov. 26, 2008	Nov. 25, 2009
Line-Impedance Stabilization Network (for EUT)	ESH3-Z5	848773/004	Nov. 05, 2008	Nov. 04, 2009
RF Cable (JYEBAO)	5DFB	COBCAB-001	Aug. 15, 2009	Aug. 14, 2010
50 ohms Terminator	50	3	Nov. 05, 2008	Nov. 04, 2009
Software	BV ADT_Cond_V7.3.7	NA	NA	NA


**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. B.
3. The VCCI Con B Registration No. is C-2193.

#### 4.1.3 TEST PROCEDURES

- a. The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT/HOST were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.5 EUT OPERATING CONDITIONS

- a. Connect the EUT with the support unit 1 (Notebook computer) which placed on a testing table.
- b. The support unit 1 (Notebook computer) ran a test program “Broadcom BlueTool v1.1.5.8” to enable EUT under transmission condition continuously.






A D T

#### 4.1.6 TEST RESULTS

<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>6DB BANDWIDTH</b>	9 kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 965 hPa	<b>PHASE</b>	Line (L)
<b>TESTED BY</b>	Frank Liu		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.20	43.23	-	43.43	-	64.82	54.82	-21.39	-
2	0.338	0.39	30.16	-	30.55	-	59.26	49.26	-28.71	-
3	3.863	0.57	26.29	-	26.86	-	56.00	46.00	-29.14	-
4	10.574	0.75	22.92	-	23.67	-	60.00	50.00	-36.33	-
5	23.496	1.64	17.01	-	18.65	-	60.00	50.00	-41.35	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>6dB BANDWIDTH</b>	9 kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 965 hPa	<b>PHASE</b>	Neutral (N)
<b>TESTED BY</b>	Frank Liu		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.12	46.30	-	46.42	-	65.77	55.77	-19.35	-
2	0.193	0.15	43.48	-	43.63	-	63.91	53.91	-20.28	-
3	0.243	0.20	38.44	-	38.64	-	61.99	51.99	-23.35	-
4	0.341	0.33	31.06	-	31.39	-	59.17	49.17	-27.78	-
5	4.011	0.51	23.60	-	24.11	-	56.00	46.00	-31.89	-
6	10.582	0.61	20.50	-	21.11	-	60.00	50.00	-38.89	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



## 4.2 NUMBER OF HOPPING FREQUENCY USED

### 4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.2.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP





#### 4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



A D T



For GFSK :





A D T



For 8DPSK :





A D T

For  $\pi/4$ -DQPSK :



### 4.3 DWELL TIME ON EACH CHANNEL

#### 4.3.1 LIMIT OF DWELL TIME USED

For FHSS, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 31.6 second period. For hybrid systems, the average time of occupancy on any frequency should not exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4.

#### 4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.



#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 TEST RESULTS



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	45 (times / 5 sec) *6.32=284.4 times	0.486	138.2	400
DH3	16 (times / 5 sec) *6.32=101.12 times	1.728	174.7	400
DH5	8 (times / 5 sec) *6.32=50.56 times	2.99	151.2	400

Test plots of the transmitting time slot are shown on next three pages.



A D T



# DH1





A D T



# DH3





A D T

# DH5



## 4.4 CHANNEL BANDWIDTH

### 4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the two-thirds 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

- 1.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.4.3 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




A D T

### 4.4.7 TEST RESULTS

<b>MODULATION TYPE</b>	GFSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	961.2
39	2441	958.3
78	2480	965.2


### Channel 0






A D T

### Channel 39



### Channel 78








A D T

<b>MODULATION TYPE</b>	8DPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	1344
39	2441	1349
78	2480	1347


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	$\pi/4$ -DQPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	1360
39	2441	1359
78	2480	1362


### Channel 0






A D T

### Channel 39



### Channel 78



## 4.5 HOPPING CHANNEL SEPARATION

### 4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25 kHz or two-thirds of 20dB hopping channel bandwidth (whichever is greater).

### 4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURES


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.



#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP





A D T


### 4.5.6 TEST RESULTS

<b>MODULATION TYPE</b>	GFSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

Channel	Frequency (MHz)	Adjacent Channel Separation (kHz)	Minimum Limit (kHz)	Pass / Fail
0	2402	1001	641	PASS
39	2441	1006	639	PASS
78	2480	1006	643	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next two pages.

### Channel 0




A D T




A D T

### Channel 39



### Channel 78








A D T

<b>MODULATION TYPE</b>	8DPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

Channel	Frequency (MHz)	Adjacent Channel Separation (kHz)	Minimum Limit (kHz)	Pass / Fail
0	2402	1006	896	PASS
39	2441	1008	899	PASS
78	2480	1008	898	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next two pages.

### Channel 0




A D T




A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	$\pi/4$ -DQPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

Channel	Frequency (MHz)	Adjacent Channel Separation (kHz)	Minimum Limit (kHz)	Pass / Fail
0	2402	1000	907	PASS
39	2441	1007	906	PASS
78	2480	1004	908	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next two pages.


### Channel 0






A D T

### Channel 39



### Channel 78



## 4.6 MAXIMUM PEAK OUTPUT POWER

### 4.6.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 125mW.

### 4.6.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.
4. Measure the captured power within the band and recording the plot.
5. Repeat above procedures until all frequencies measured were complete.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.6.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.6.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




A D T

### 4.6.7 TEST RESULTS – Dipole antenna

<b>MODULATION TYPE</b>	GFSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.457	-3.4	125	PASS
39	2441	0.557	-2.54	125	PASS
78	2480	0.589	-2.3	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78








A D T

<b>MODULATION TYPE</b>	8DPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.897	-0.47	125	PASS
39	2441	1.094	0.39	125	PASS
78	2480	1.164	0.66	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	$\pi/4$ -DQPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.826	-0.83	125	PASS
39	2441	1.012	0.05	125	PASS
78	2480	1.072	0.3	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

#### 4.6.8 TEST RESULTS – Turned Monopole antenna

<b>MODULATION TYPE</b>	GFSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.457	-3.4	125	PASS
39	2441	0.557	-2.54	125	PASS
78	2480	0.589	-2.3	125	PASS


#### Channel 0






A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	8DPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.897	-0.47	125	PASS
39	2441	1.094	0.39	125	PASS
78	2480	1.164	0.66	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78








A D T

<b>MODULATION TYPE</b>	$\pi/4$ -DQPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.826	-0.83	125	PASS
39	2441	1.012	0.05	125	PASS
78	2480	1.072	0.3	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

### 4.6.9 TEST RESULTS – PIFA antenna

<b>MODULATION TYPE</b>	GFSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.457	-3.4	125	PASS
39	2441	0.557	-2.54	125	PASS
78	2480	0.589	-2.3	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	8DPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.897	-0.47	125	PASS
39	2441	1.094	0.39	125	PASS
78	2480	1.164	0.66	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78






A D T

<b>MODULATION TYPE</b>	$\pi/4$ -DQPSK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 60%RH, 965 hPa	<b>TESTED BY</b>	Rex Huang

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	0.826	-0.83	125	PASS
39	2441	1.012	0.05	125	PASS
78	2480	1.072	0.3	125	PASS


### Channel 0






A D T

### Channel 39



### Channel 78





## 4.7 RADIATED EMISSION MEASUREMENT

### 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

#### 4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100036	Dec. 09, 2008	Dec. 08, 2009
Agilent PSA Spectrum Analyzer	E4446A	MY46180622	Apr. 24 , 2009	Apr. 23 , 2010
HP Pre_Amplifier	8449B	3008A01923	Nov. 10, 2008	Nov. 09, 2009
ROHDE & SCHWARZ Test Receiver	ESCS30	847124/029	Sep. 09, 2008	Sep. 08, 2009
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	April 29, 2009	April 28, 2010
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 09, 2008	Dec. 08, 2009
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 22, 2009	Jan. 21, 2010
RF Switches	EMH-011	08009	Oct. 07, 2008	Oct. 06, 2009
RF CABLE (Chaintek)	Sucoflex 106	28077	Aug. 15, 2009	Aug. 14, 2010
RF Cable	8DFB	STCCAB-30M-1GHz	Oct. 07, 2008	Oct. 06, 2009
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: FSP40) are used only for the measurement of emission frequency above 1GHz if tested.

3. The test was performed in Open Site No. C.

4. The FCC Site Registration No. is 656396.

5. The VCCI Site Registration No. is R-1626.

6. The CANADA Site Registration No. is IC 7450G-3.

#### 4.7.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz.

#### 4.7.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.7.6 TEST RESULTS

##### BELOW 1GHz WORST-CASE DATA : GFSK MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Rex Huang
TEST MODE	Dipole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	19.15 QP	43.50	-24.35	1.45 H	10	6.60	12.55
2	200.00	19.30 QP	43.50	-24.20	1.67 H	168	6.91	12.39
3	240.00	19.70 QP	46.00	-26.30	1.09 H	323	5.82	13.88
4	400.00	21.82 QP	46.00	-24.18	1.34 H	350	2.32	19.50
5	480.00	22.55 QP	46.00	-23.45	1.00 H	270	0.66	21.89
6	600.00	29.39 QP	46.00	-16.61	1.25 H	292	4.35	25.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	21.44 QP	43.50	-22.06	1.00 V	358	8.89	12.55
2	200.00	19.73 QP	43.50	-23.77	1.00 V	287	7.34	12.39
3	240.00	21.27 QP	46.00	-24.73	1.00 V	26	7.39	13.88
4	400.00	23.58 QP	46.00	-22.42	1.00 V	347	4.08	19.50
5	480.00	22.53 QP	46.00	-23.47	1.00 V	19	0.64	21.89
6	600.00	29.53 QP	46.00	-16.47	1.00 V	341	4.49	25.04

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Rex Huang
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	18.70 QP	43.50	-24.80	1.42 H	17	6.15	12.55
2	200.00	20.03 QP	43.50	-23.47	1.58 H	174	7.64	12.39
3	240.00	21.50 QP	46.00	-24.50	1.18 H	285	7.62	13.88
4	400.00	21.58 QP	46.00	-24.42	1.32 H	337	2.08	19.50
5	480.00	22.81 QP	46.00	-23.19	1.00 H	295	0.92	21.89
6	600.00	29.78 QP	46.00	-16.22	1.23 H	287	4.74	25.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	21.68 QP	43.50	-21.82	1.00 V	249	9.13	12.55
2	200.00	19.63 QP	43.50	-23.87	1.00 V	315	7.24	12.39
3	240.00	19.62 QP	46.00	-26.38	1.00 V	162	5.74	13.88
4	400.00	22.26 QP	46.00	-23.74	1.00 V	311	2.76	19.50
5	480.00	23.67 QP	46.00	-22.33	1.00 V	5	1.78	21.89
6	600.00	29.67 QP	46.00	-16.33	1.00 V	343	4.63	25.04

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Rex Huang
TEST MODE	PIFA antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	18.25 QP	43.50	-25.25	1.37 H	8	5.70	12.55
2	200.00	20.42 QP	43.50	-23.08	1.61 H	152	8.03	12.39
3	240.00	23.36 QP	46.00	-22.64	1.21 H	12	9.48	13.88
4	400.00	20.92 QP	46.00	-25.08	1.21 H	344	1.42	19.50
5	480.00	23.25 QP	46.00	-22.75	1.00 H	263	1.36	21.89
6	600.00	29.55 QP	46.00	-16.45	1.27 H	287	4.51	25.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	21.91 QP	43.50	-21.59	1.00 V	198	9.36	12.55
2	200.00	20.01 QP	43.50	-23.49	1.00 V	37	7.62	12.39
3	240.00	20.23 QP	46.00	-25.77	1.00 V	284	6.35	13.88
4	400.00	23.82 QP	46.00	-22.18	1.00 V	328	4.32	19.50
5	480.00	23.48 QP	46.00	-22.52	1.00 V	16	1.59	21.89
6	600.00	30.04 QP	46.00	-15.96	1.00 V	350	5.00	25.04

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



A D T

**ABOVE 1GHz WORST-CASE DATA : GFSK MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.02 PK	74.00	-20.98	1.00 H	327	22.74	30.28
2	2390.00	23.02 AV	54.00	-30.98	1.00 H	327	-7.26	30.28
3	*2402.00	84.30 PK			1.00 H	52	53.97	30.33
4	*2402.00	54.30 AV			1.00 H	52	23.97	30.33
5	4804.00	44.92 PK	74.00	-29.08	1.00 H	312	8.19	36.73
6	4804.00	14.92 AV	54.00	-39.08	1.00 H	312	-21.81	36.73

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.14 PK	74.00	-20.86	1.00 V	255	22.86	30.28
2	2390.00	23.14 AV	54.00	-30.86	1.00 V	255	-7.14	30.28
3	*2402.00	95.44 PK			1.00 V	94	65.11	30.33
4	*2402.00	65.44 AV			1.00 V	94	35.11	30.33
5	4804.00	52.97 PK	74.00	-21.03	1.21 V	198	16.24	36.73
6	4804.00	22.97 AV	54.00	-31.03	1.21 V	198	-13.76	36.73

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - “ \* “: Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	87.52 PK			1.02 H	327	57.05	30.47
2	*2441.00	57.52 AV			1.02 H	327	27.05	30.47
3	4882.00	44.38 PK	74.00	-29.62	1.00 H	307	7.44	36.94
4	4882.00	14.38 AV	54.00	-39.62	1.00 H	307	-22.56	36.94
5	7323.00	49.70 PK	74.00	-24.30	1.00 H	20	6.57	43.13
6	7323.00	19.70 AV	54.00	-34.30	1.00 H	20	-23.43	43.13

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	95.45 PK			1.00 V	94	64.98	30.47
2	*2441.00	65.45 AV			1.00 V	94	34.98	30.47
3	4882.00	51.72 PK	74.00	-22.28	1.07 V	19	14.78	36.94
4	4882.00	21.72 AV	54.00	-32.28	1.07 V	19	-15.22	36.94
5	7323.00	48.98 PK	74.00	-25.02	1.00 V	20	5.85	43.13
6	7323.00	18.98 AV	54.00	-35.02	1.00 V	20	-24.15	43.13

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - \* \*: Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	85.45 PK			1.00 H	327	54.83	30.62
2	*2480.00	55.45 AV			1.00 H	327	24.83	30.62
3	2483.50	52.59 PK	74.00	-21.41	1.00 H	326	21.96	30.63
4	2483.50	22.59 AV	54.00	-31.41	1.00 H	326	-8.04	30.63
5	4960.00	44.22 PK	74.00	-29.78	1.31 H	100	7.07	37.15
6	4960.00	14.22 AV	54.00	-39.78	1.31 H	100	-22.93	37.15
7	7440.00	48.99 PK	74.00	-25.01	1.00 H	20	5.87	43.12
8	7440.00	18.99 AV	54.00	-35.01	1.00 H	20	-24.13	43.12
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	96.42 PK			1.00 V	95	65.80	30.62
2	*2480.00	66.42 AV			1.00 V	95	35.81	30.62
3	2493.03	54.73 PK	74.00	-19.27	1.00 V	95	24.07	30.66
4	2493.03	24.73 AV	54.00	-29.27	1.00 V	95	-5.93	30.66
5	4960.00	50.49 PK	74.00	-23.51	1.31 V	150	13.34	37.15
6	4960.00	20.49 AV	54.00	-33.51	1.31 V	150	-16.66	37.15
7	7440.00	48.91 PK	74.00	-25.09	1.00 V	20	5.79	43.12
8	7440.00	18.91 AV	54.00	-35.09	1.00 V	20	-24.21	43.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2378.93	54.07 PK	74.00	-19.93	1.51 H	37	23.83	30.24
2	2378.93	24.07 AV	54.00	-29.93	1.51 H	37	-6.17	30.24
3	*2402.00	79.26 PK			1.34 H	128	48.93	30.33
4	*2402.00	49.26 AV			1.34 H	128	18.93	30.33
5	4804.00	47.31 PK	74.00	-26.69	1.31 H	178	10.58	36.73
6	4804.00	17.31 AV	54.00	-36.69	1.31 H	178	-19.42	36.73
7	#7206.00	51.46 PK	59.26	-7.80	1.21 H	296	8.32	43.14
8	#7206.00	21.46 AV	29.26	-7.80	1.21 H	296	-21.68	43.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2384.73	53.28 PK	74.00	-20.72	1.21 V	68	23.02	30.26
2	2384.73	23.28 AV	54.00	-30.72	1.21 V	68	-6.98	30.26
3	*2402.00	84.34 PK			1.00 V	34	54.01	30.33
4	*2402.00	54.34 AV			1.00 V	34	24.01	30.33
5	4804.00	48.11 PK	74.00	-25.89	1.12 V	271	11.38	36.73
6	4804.00	18.11 AV	54.00	-35.89	1.12 V	271	-18.62	36.73
7	#7206.00	51.38 PK	64.34	-12.96	1.08 V	45	8.24	43.14
8	#7206.00	21.38 AV	34.34	-12.96	1.08 V	45	-21.76	43.14

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
  8. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	80.96 PK			1.11 H	296	50.49	30.47
2	*2441.00	50.96 AV			1.11 H	296	20.49	30.47
3	4882.00	47.34 PK	74.00	-26.66	1.34 H	139	10.40	36.94
4	4882.00	17.34 AV	54.00	-36.66	1.34 H	139	-19.60	36.94
5	7323.00	51.29 PK	74.00	-22.71	1.28 H	46	8.16	43.13
6	7323.00	21.29 AV	54.00	-32.71	1.28 H	46	-21.84	43.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	83.37 PK			1.00 V	271	52.90	30.47
2	*2441.00	53.37 AV			1.00 V	271	22.90	30.47
3	4882.00	47.96 PK	74.00	-26.04	1.57 V	48	11.02	36.94
4	4882.00	17.96 AV	54.00	-36.04	1.57 V	48	-18.98	36.94
5	7323.00	51.57 PK	74.00	-22.43	1.61 V	37	8.44	43.13
6	7323.00	21.57 AV	54.00	-32.43	1.61 V	37	-21.56	43.13

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	81.35 PK			1.34 H	211	50.73	30.62
2	*2480.00	51.35 AV			1.34 H	211	20.73	30.62
3	2484.12	54.61 PK	74.00	-19.39	1.23 H	89	23.98	30.63
4	2484.12	24.61 AV	54.00	-29.39	1.23 H	89	-6.02	30.63
5	4960.00	47.46 PK	74.00	-26.54	1.27 H	98	10.31	37.15
6	4960.00	17.46 AV	54.00	-36.54	1.27 H	98	-19.69	37.15
7	7440.00	50.50 PK	74.00	-23.50	1.14 H	38	7.38	43.12
8	7440.00	20.50 AV	54.00	-33.50	1.14 H	38	-22.62	43.12

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	82.37 PK			1.37 V	260	51.75	30.62
2	*2480.00	52.37 AV			1.37 V	260	21.75	30.62
3	2484.86	53.20 PK	74.00	-20.80	1.34 V	171	22.57	30.63
4	2484.86	23.20 AV	54.00	-30.80	1.34 V	171	-7.43	30.63
5	4960.00	48.22 PK	74.00	-25.78	1.52 V	133	11.07	37.15
6	4960.00	18.22 AV	54.00	-35.78	1.52 V	133	-18.93	37.15
7	7440.00	51.04 PK	74.00	-22.96	1.27 V	138	7.92	43.12
8	7440.00	21.04 AV	54.00	-32.96	1.27 V	138	-22.08	43.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2384.77	55.06 PK	74.00	-18.94	1.23 H	37	24.80	30.26
2	2384.77	25.06 AV	54.00	-28.94	1.23 H	37	-5.20	30.26
3	*2402.00	92.35 PK			1.34 H	3	62.02	30.33
4	*2402.00	62.35 AV			1.34 H	3	32.02	30.33
5	4804.00	45.53 PK	74.00	-28.47	1.10 H	4	8.80	36.73
6	4804.00	15.53 AV	54.00	-38.47	1.10 H	4	-21.20	36.73
7	#7206.00	50.64 PK	72.35	-21.71	1.11 H	37	7.50	43.14
8	#7206.00	20.64 AV	42.35	-21.71	1.11 H	37	-22.50	43.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.14	53.89 PK	74.00	-20.11	1.02 V	24	23.63	30.26
2	2383.14	23.89 AV	54.00	-30.11	1.02 V	24	-6.37	30.26
3	*2402.00	93.90 PK			1.00 V	82	63.57	30.33
4	*2402.00	63.90 AV			1.00 V	82	33.57	30.33
5	4804.00	44.98 PK	74.00	-29.02	1.10 V	258	8.25	36.73
6	4804.00	14.98 AV	54.00	-39.02	1.10 V	258	-21.75	36.73
7	#7206.00	51.31 PK	73.90	-22.59	1.07 V	138	8.17	43.14
8	#7206.00	21.31 AV	43.90	-22.59	1.07 V	138	-21.83	43.14

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - " \* ": Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .
  - "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.31 PK			1.58 H	37	59.84	30.47
2	*2441.00	60.31 AV			1.58 H	37	29.84	30.47
3	4882.00	45.81 PK	74.00	-28.19	1.43 H	171	8.87	36.94
4	4882.00	15.81 AV	54.00	-38.19	1.43 H	171	-21.13	36.94
5	7323.00	49.95 PK	74.00	-24.05	1.31 H	93	6.82	43.13
6	7323.00	19.95 AV	54.00	-34.05	1.31 H	93	-23.18	43.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.37 PK			1.21 V	105	61.90	30.47
2	*2441.00	62.37 AV			1.21 V	105	31.90	30.47
3	4882.00	45.31 PK	74.00	-28.69	1.21 V	37	8.37	36.94
4	4882.00	15.31 AV	54.00	-38.69	1.21 V	37	-21.63	36.94
5	7323.00	50.68 PK	74.00	-23.32	1.43 V	87	7.55	43.13
6	7323.00	20.68 AV	54.00	-33.32	1.43 V	87	-22.45	43.13

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.24 PK			1.47 H	111	60.62	30.62
2	*2480.00	61.24 AV			1.47 H	111	30.62	30.62
3	2484.97	53.34 PK	74.00	-20.66	1.53 H	148	22.71	30.63
4	2484.97	23.34 AV	54.00	-30.66	1.53 H	148	-7.29	30.63
5	4960.00	46.63 PK	74.00	-27.37	1.28 H	178	9.48	37.15
6	4960.00	16.63 AV	54.00	-37.37	1.28 H	178	-20.52	37.15
7	7440.00	51.20 PK	74.00	-22.80	1.31 H	191	8.08	43.12
8	7440.00	21.20 AV	54.00	-32.80	1.31 H	191	-21.92	43.12

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.31 PK			1.37 V	29	61.69	30.62
2	*2480.00	62.31 AV			1.37 V	29	31.69	30.62
3	2492.23	54.85 PK	74.00	-19.15	1.41 V	37	24.19	30.66
4	2492.23	24.85 AV	54.00	-29.15	1.41 V	37	-5.81	30.66
5	4960.00	45.64 PK	74.00	-28.36	1.11 V	0	8.49	37.15
6	4960.00	15.64 AV	54.00	-38.36	1.11 V	0	-21.51	37.15
7	7440.00	51.47 PK	74.00	-22.53	1.32 V	147	8.35	43.12
8	7440.00	21.47 AV	54.00	-32.53	1.32 V	147	-21.65	43.12

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - \* \*: Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .



**ABOVE 1GHZ WORST-CASE DATA : 8DPSK MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.61 PK	74.00	-20.39	1.00 H	51	23.33	30.28
2	2390.00	23.61 AV	54.00	-30.39	1.00 H	51	-6.67	30.28
3	*2402.00	85.03 PK			1.00 H	51	54.70	30.33
4	*2402.00	55.03 AV			1.00 H	51	24.70	30.33
5	4804.00	46.30 PK	74.00	-27.70	1.62 H	90	9.57	36.73
6	4804.00	16.30 AV	54.00	-37.70	1.62 H	90	-20.43	36.73
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2388.89	54.89 PK	74.00	-19.11	1.00 V	95	24.61	30.28
2	2388.89	24.89 AV	54.00	-29.11	1.00 V	95	-5.39	30.28
3	*2402.00	96.47 PK			1.00 V	95	66.14	30.33
4	*2402.00	66.47 AV			1.00 V	95	36.14	30.33
5	4804.00	54.00 PK	74.00	-20.00	1.12 V	353	17.27	36.73
6	4804.00	24.00 AV	54.00	-30.00	1.12 V	353	-12.73	36.73

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	89.30 PK			1.02 H	328	58.83	30.47
2	*2441.00	59.30 AV			1.02 H	328	28.83	30.47
3	4882.00	45.09 PK	74.00	-28.91	1.52 H	92	8.15	36.94
4	4882.00	15.09 AV	54.00	-38.91	1.52 H	92	-21.85	36.94
5	7323.00	50.43 PK	74.00	-23.57	1.00 H	20	7.30	43.13
6	7323.00	20.43 AV	54.00	-33.57	1.00 H	20	-22.70	43.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	96.68 PK			1.00 V	95	66.21	30.47
2	*2441.00	66.68 AV			1.00 V	95	36.21	30.47
3	4882.00	52.61 PK	74.00	-21.39	1.07 V	17	15.67	36.94
4	4882.00	22.61 AV	54.00	-31.39	1.07 V	17	-14.33	36.94
5	7323.00	50.10 PK	74.00	-23.90	1.00 V	20	6.97	43.13
6	7323.00	20.10 AV	54.00	-33.90	1.00 V	20	-23.03	43.13

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - \* \*: Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 55%RH 965 hPa	TESTED BY	Duke Tseng
TEST MODE	Dipole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.70 PK			1.00 H	328	56.08	30.62
2	*2480.00	56.70 AV			1.00 H	328	26.08	30.62
3	2483.50	54.47 PK	74.00	-19.53	1.00 H	328	23.84	30.63
4	2483.50	24.47 AV	54.00	-29.53	1.00 H	328	-6.16	30.63
5	4960.00	44.65 PK	74.00	-29.35	1.33 H	88	7.50	37.15
6	4960.00	14.65 AV	54.00	-39.35	1.33 H	88	-22.50	37.15
7	7440.00	49.56 PK	74.00	-24.44	1.00 H	20	6.44	43.12
8	7440.00	19.56 AV	54.00	-34.44	1.00 H	20	-23.56	43.12
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	98.20 PK			1.00 V	95	67.58	30.62
2	*2480.00	68.20 AV			1.00 V	95	37.58	30.62
3	2493.14	55.16 PK	74.00	-18.84	1.00 V	95	24.50	30.66
4	2493.14	25.16 AV	54.00	-28.84	1.00 V	95	-5.50	30.66
5	4960.00	51.37 PK	74.00	-22.63	1.19 V	18	14.22	37.15
6	4960.00	21.37 AV	54.00	-32.63	1.19 V	18	-15.78	37.15
7	7440.00	49.73 PK	74.00	-24.27	1.00 V	20	6.61	43.12
8	7440.00	19.73 AV	54.00	-34.27	1.00 V	20	-23.39	43.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2380.44	54.26 PK	74.00	-19.74	1.33 H	99	24.01	30.25
2	2380.44	24.26 AV	54.00	-29.74	1.33 H	99	-5.99	30.25
3	*2402.00	81.24 PK			1.21 H	24	50.91	30.33
4	*2402.00	51.24 AV			1.21 H	24	20.91	30.33
5	4804.00	47.54 PK	74.00	-26.46	1.07 H	37	10.81	36.73
6	4804.00	17.54 AV	54.00	-36.46	1.07 H	37	-19.19	36.73
7	#7206.00	50.29 PK	61.24	-10.95	1.28 H	96	7.15	43.14
8	#7206.00	20.29 AV	31.24	-10.95	1.28 H	96	-22.85	43.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2387.08	53.28 PK	74.00	-20.72	1.00 V	128	23.01	30.27
2	2387.08	23.28 AV	54.00	-30.72	1.00 V	128	-6.99	30.27
3	*2402.00	84.78 PK			1.61 V	74	54.45	30.33
4	*2402.00	54.78 AV			1.61 V	74	24.45	30.33
5	4804.00	48.25 PK	74.00	-25.75	1.47 V	123	11.52	36.73
6	4804.00	18.25 AV	54.00	-35.75	1.47 V	123	-18.48	36.73
7	#7206.00	51.31 PK	64.78	-13.47	1.08 V	250	8.17	43.14
8	#7206.00	21.31 AV	34.78	-13.47	1.08 V	250	-21.83	43.14

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
  8. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	82.31 PK			1.07 H	285	51.84	30.47
2	*2441.00	52.31 AV			1.07 H	285	21.84	30.47
3	4882.00	47.34 PK	74.00	-26.66	1.14 H	233	10.40	36.94
4	4882.00	17.34 AV	54.00	-36.66	1.14 H	233	-19.60	36.94
5	7323.00	51.32 PK	74.00	-22.68	1.08 H	266	8.19	43.13
6	7323.00	21.32 AV	54.00	-32.68	1.08 H	266	-21.81	43.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	84.63 PK			1.21 V	14	54.16	30.47
2	*2441.00	54.63 AV			1.21 V	14	24.16	30.47
3	4882.00	46.39 PK	74.00	-27.61	1.00 V	238	9.45	36.94
4	4882.00	16.39 AV	54.00	-37.61	1.00 V	238	-20.55	36.94
5	7323.00	50.20 PK	74.00	-23.80	1.11 V	37	7.07	43.13
6	7323.00	20.20 AV	54.00	-33.80	1.11 V	37	-22.93	43.13

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 65%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	Turned Monopole antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	81.98 PK			1.92 H	68	51.36	30.62
2	*2480.00	51.98 AV			1.92 H	68	21.36	30.62
3	2488.12	54.83 PK	74.00	-19.17	1.91 H	37	24.18	30.65
4	2488.12	24.83 AV	54.00	-29.17	1.91 H	37	-5.82	30.65
5	4960.00	48.31 PK	74.00	-25.69	1.81 H	44	11.16	37.15
6	4960.00	18.31 AV	54.00	-35.69	1.81 H	44	-18.84	37.15
7	7440.00	50.58 PK	74.00	-23.42	1.73 H	37	7.46	43.12
8	7440.00	20.58 AV	54.00	-33.42	1.73 H	37	-22.54	43.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	84.34 PK			1.05 V	68	53.72	30.62
2	*2480.00	54.34 AV			1.05 V	68	23.72	30.62
3	2487.68	55.64 PK	74.00	-18.36	1.37 V	27	25.00	30.64
4	2487.68	25.64 AV	54.00	-28.36	1.37 V	27	-5.00	30.64
5	4960.00	48.27 PK	74.00	-25.73	1.34 V	21	11.12	37.15
6	4960.00	18.27 AV	54.00	-35.73	1.34 V	21	-18.88	37.15
7	7440.00	51.47 PK	74.00	-22.53	1.39 V	244	8.35	43.12
8	7440.00	21.47 AV	54.00	-32.53	1.39 V	244	-21.65	43.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2387.39	54.26 PK	74.00	-19.74	1.01 H	133	23.99	30.27
2	2387.39	24.26 AV	54.00	-29.74	1.01 H	133	-6.01	30.27
3	*2402.00	94.23 PK			1.00 H	134	63.90	30.33
4	*2402.00	64.23 AV			1.00 H	134	33.90	30.33
5	4804.00	46.60 PK	74.00	-27.40	1.00 H	27	9.87	36.73
6	4804.00	16.60 AV	54.00	-37.40	1.00 H	27	-20.13	36.73
7	#7206.00	51.55 PK	74.23	-22.68	1.16 H	38	8.41	43.14
8	#7206.00	21.55 AV	44.23	-22.68	1.16 H	38	-21.59	43.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2382.07	53.73 PK	74.00	-20.27	1.74 V	301	23.48	30.25
2	2382.07	23.73 AV	54.00	-30.27	1.74 V	301	-6.52	30.25
3	*2402.00	91.31 PK			1.85 V	319	60.98	30.33
4	*2402.00	61.31 AV			1.85 V	319	30.98	30.33
5	4804.00	46.31 PK	74.00	-27.69	1.24 V	88	9.58	36.73
6	4804.00	16.31 AV	54.00	-37.69	1.24 V	88	-20.42	36.73
7	#7206.00	51.01 PK	71.31	-20.30	1.39 V	65	7.87	43.14
8	#7206.00	21.01 AV	41.31	-20.30	1.39 V	65	-22.13	43.14

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
  8. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.13 PK			1.07 H	28	61.66	30.47
2	*2441.00	62.13 AV			1.07 H	28	31.66	30.47
3	4882.00	47.16 PK	74.00	-26.84	1.31 H	108	10.22	36.94
4	4882.00	17.16 AV	54.00	-36.84	1.31 H	108	-19.78	36.94
5	7323.00	51.83 PK	74.00	-22.17	1.33 H	69	8.70	43.13
6	7323.00	21.83 AV	54.00	-32.17	1.33 H	69	-21.30	43.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.33 PK			1.66 V	128	62.86	30.47
2	*2441.00	63.33 AV			1.66 V	128	32.86	30.47
3	4882.00	46.38 PK	74.00	-27.62	1.24 V	39	9.44	36.94
4	4882.00	16.38 AV	54.00	-37.62	1.24 V	39	-20.56	36.94
5	7323.00	51.24 PK	74.00	-22.76	1.00 V	137	8.11	43.13
6	7323.00	21.24 AV	54.00	-32.76	1.00 V	137	-21.89	43.13

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	28deg. C, 72%RH 965 hPa	TESTED BY	Eric Lee
TEST MODE	PIFA antenna		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.25 PK			1.35 H	26	61.63	30.62
2	*2480.00	62.25 AV			1.35 H	26	31.63	30.62
3	2488.89	54.45 PK	74.00	-19.55	1.83 H	215	23.80	30.65
4	2488.89	24.45 AV	54.00	-29.55	1.83 H	215	-6.20	30.65
5	4960.00	46.51 PK	74.00	-27.49	1.38 H	291	9.36	37.15
6	4960.00	16.51 AV	54.00	-37.49	1.38 H	291	-20.64	37.15
7	7440.00	50.46 PK	74.00	-23.54	1.06 H	354	7.34	43.12
8	7440.00	20.46 AV	54.00	-33.54	1.06 H	354	-22.66	43.12

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.13 PK			1.21 V	38	62.51	30.62
2	*2480.00	63.13 AV			1.21 V	38	32.51	30.62
3	2486.65	55.12 PK	74.00	-18.88	1.44 V	268	24.48	30.64
4	2486.65	25.12 AV	54.00	-28.88	1.44 V	268	-5.52	30.64
5	4960.00	46.24 PK	74.00	-27.76	1.58 V	296	9.09	37.15
6	4960.00	16.24 AV	54.00	-37.76	1.58 V	296	-20.91	37.15
7	7440.00	51.57 PK	74.00	-22.43	1.37 V	157	8.45	43.12
8	7440.00	21.57 AV	54.00	-32.43	1.37 V	157	-21.55	43.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .

## 4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT

### 4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz RBW).

### 4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 09, 2009	Aug. 08, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW a of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.8.5 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

### 4.8.6 TEST RESULTS


Emissions radiated outside of the specified frequency bands, please refer pages form 62 to 65 for met the requirement of the general radiated emission limits in § 15.209.

#### For GFSK MODULATION TYPE:

CH0




CH78






A D T

### CH0



### CH78







A D T

### FOR 8DPSK MODULATION TYPE:

CH0




CH78





A D T

### CH0



### CH78



## 4.9 ANTENNA REQUIREMENT

### 4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 4.9.2 ANTENNA CONNECTED CONSTRUCTION

There are nine antennas provided to this EUT, please refer to the following table:

Brand	Model No.	Antenna Connector	Antenna Type	Antenna Gain with cable loss (dBi)	Cable Length (cm)
Wha Yu Group	C034-510481-A	I-PEX	Dipole	2.15	20±0.3
Typo Electronic	NA	I-PEX	Turned Monopole	3	8.8
Wha Yu Group	NE-8048	I-PEX	PIFA	3.07	5.7
Acon	APP6P-700320	I-PEX	PIFA	2.93	18±0.3
Acon	APP6P-700307	I-PEX	PIFA	-2.54	32.7±0.3
Foxconn	WDAN-SPM93007-1F	I-PEX	PIFA	1.32	27.5±0.3
Foxconn	WDAN-SPM87003-1F	I-PEX	PIFA	2.15	32.7±0.3
Whayu	C680-520196-A	I-PEX	PIFA	0.95	6.4±0.3
Acon	APP6P-700339	I-PEX	Monopole	1.66	27.9±0.3



## 5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA, CSA
<b>R.O.C.</b>	TAF, BSMI, NCC
<b>Netherlands</b>	Telefication
<b>Singapore</b>	GOST-ASIA (MOU)
<b>Russia</b>	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Email:** [service@adt.com.tw](mailto:service@adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



## **6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

--- END ---