



RF Exposure Report

Report No.: SA130710E11H

FCC ID: MCLT77H462

Test Model: T77H462

Received Date: Oct. 14, 2015

Test Date: Nov. 24, 2015

Issued Date: Dec. 14, 2015

Applicant: Hon Hai PRECISION IND.CO.,LTD

Address: 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan,
R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	6
4 Calculation Result Of Maximum Conducted Power	8



A D T

Release Control Record

Issue No.	Description	Date Issued
SA130710E11H	Original release.	Dec. 14, 2015

1 Certificate of Conformity

Product: 802.11abgn+BT4.0 module

Brand: FOXCONN

Test Model: T77H462

Sample Status: ENGINEERING SAMPLE

Applicant: Hon Hai PRECISION IND.CO.,LTD

Test Date: Nov. 24, 2015

Standards: FCC Part 2 (Section 2.1093)
447498 D01 General RF Exposure Guidance v06
IEEE Std C95.1-2005

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Midoli Peng , **Date:** Dec. 14, 2015
Midoli Peng / Specialist

Approved by : May Chen , **Date:** Dec. 14, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna Set 1							
Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain (dBi)	Frequency range (MHz to MHz)	Connector Type	
Chain (0)	Foxconn	T77H462	PIFA	-0.6	2400~2500	MHF4	
				-2.3	5150~5850		
Chain (1)	Foxconn	T77H462	PIFA	-0.6	2400~2500	MHF4	
				-2.3	5150~5850		
Antenna Set 2							
Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain (dBi) <Including cable loss>	Frequency range (MHz to MHz)	Cable Length (mm)	Connector Type
Chain (0) & Chain (1)	Wistron Neweb Corporation	DC33001GL00	PIFA	1.32	2400~2500	55	MHF4 (i-pec)
				1.62	5150-5350		
				-1.84	5470-5725		
				-2.12	5725-5850		
Antenna Set 3							
Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain (dBi) <Including cable loss>	Frequency range (MHz to MHz)	Cable Length (mm)	Connector Type
Chain (0) & Chain (1)	Wistron Neweb Corporation	DC33001GL10	PIFA	0.48	2400~2500	239	MHF4 (i-pec)
				-2.19	5150-5350		
				-2.70	5470-5725		
				-1.77	5725-5850		
Antenna Set 4							
Transmitter Circuit	Antenna P/N	Manufacturer	Antenna Type	Cable Assembly P/N and Information	Frequency range (MHz to MHz)	Antenna Gain (dBi) <Including cable loss>	Antenna Gain (dBi) <Excluding cable loss>
Chain (0)	Main Antenna (P/N: LA22RF754-1H)	LUXSHARE-ICT Co., Ltd.	PIFA	50 ohm coaxial cable Cable length:750 mm Diameter: Lowloss 1.13mm	2400-2500	0.43	2.68
					5150-5350	-8.70	-5.15
					5470-5725	-8.82	-5.15
					5725-5850	-8.98	-5.25
Chain (1)	Auxiliary Antenna (P/N: LA22RF755-1H)	LUXSHARE-ICT Co., Ltd.	PIFA	50 ohm coaxial cable Cable length: 750 mm Diameter: Lowloss1.13 mm	2400-2500	0.43	2.68
					5150-5350	-8.70	-5.15
					5470-5725	-8.82	-5.15
					5725-5850	-8.98	-5.25

Antenna Set 5									
Transmitter Circuit	Antenna P/N	Manufacturer	Antenna Type	Cable Assembly P/N and Information	Frequency range (MHz to MHz)	Antenna Gain (dBi) <Including cable loss>	Antenna Gain (dBi) <Excluding cable loss>	Cable loss max.(dB)	VSWR
Chain (0)	Main Antenna (P/N: LA22RF764-1H)	LUXSHARE -ICT Co., Ltd.	PIFA	50 ohm coaxial cable Cable length:220 mm Diameter:1.13mm	2400-2500	2.34	3.0	0.66	2.5 max
					5150-5350	0.67	1.71	1.04	2.5 max
					5470-5725	0.15	1.22	1.07	2.5 max
					5725-5850	-0.54	0.55	1.09	2.5 max
Chain (1)	Auxiliary Antenna (P/N: LA22RF765-1H)	LUXSHARE -ICT Co., Ltd.	PIFA	50 ohm coaxial cable Cable length: 250 mm Diameter:1.13 mm	2400-2500	0.83	1.58	0.75	2.5 max
					5150-5350	2.05	3.23	1.18	2.5 max
					5470-5725	0.61	1.84	1.23	2.5 max
					5725-5850	0.61	1.85	1.24	2.5 max

Antenna Set 6						
Transmitter Circuit	Antenna P/N	Manufacturer	Antenna Type	Cable Assembly P/N and Information	Frequency range (MHz to MHz)	Antenna Gain (dBi) <Including cable loss>
Chain (0)	Main Antenna (P/N: 1415-04LN000)	WNC	PIFA	Black 1.13(dia) x 50mm	2400-2500	0.72
					5150-5350	1.75
					5470-5725	1.55
					5725-5850	0.41
Chain (1)	Auxiliary Antenna (P/N: 1415-04LP000)	WNC	PIFA	White 1.13(dia) x 190mm	2400-2500	-0.47
					5150-5350	-1.00
					5470-5725	0.77
					5725-5850	0.04

Antenna Set 7						
Transmitter Circuit	Antenna P/N	Manufacturer	Antenna Type	Cable Assembly P/N and Information	Frequency range (MHz to MHz)	Antenna Gain (dBi) <Including cable loss>
Chain (0)	Main Antenna (P/N: 1415-04LR000)	WNC	PIFA	Black 1.13(dia) x 120mm	2400-2500	0.67
					5150-5350	0.6
					5470-5725	-0.75
					5725-5850	1.25
Chain (1)	Auxiliary Antenna (P/N: 1415-04LQ000)	WNC	PIFA	White 1.13(dia) x 143mm	2400-2500	-1.59
					5150-5350	1.12
					5470-5725	0.82
					5725-5850	0.33

Note : 1. For U-NII-1, UNII-2A: Antenna 5 was chosen for final test
 Note : 2. For UNII-2C: Antenna 6 was chosen for final test
 Note : 3. For UNII-3: Antenna 7 was chosen for final test

4 Calculation Result Of Maximum Conducted Power

For 2.4GHz, BT-EDR & BT-LE data was copied from the original test report. (Report No.: SA130710E11E)

For WLAN

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	319.012	2.34	20	0.10878	1
5180-5240	94.695	2.05	20	0.03020	1
5260-5320	97.486	2.05	20	0.03109	1
5500--5700	83.079	1.55	20	0.02362	1
5745-5825	137.568	1.25	20	0.03650	1

For BT-EDR

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	9.099	2.34	20	0.00310	1

For BT-LE

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402 - 2480	6.237	2.34	20	0.00213	1

--- END ---