

RF Exposure Report

Report No.: SA160629E05D

FCC ID: MCLT77H747

Test Model: T77H747

Received Date: June 29, 2016

Test Date: Aug. 12, 2016

Issued Date: Oct. 19, 2017

Applicant: HON HAI PRECISION IND. CO., LTD.

Address: 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan,
R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	6



Release Control Record

Issue No.	Description	Date Issued
SA160629E05D	Original release.	Oct. 19, 2017

1 Certificate of Conformity

Product: NFC module

Brand: FOXCONN

Test Model: T77H747

Sample Status: ENGINEERING SAMPLE

Applicant: HON HAI PRECISION IND. CO., LTD.

Test Date: Aug. 12, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu , **Date:** Oct. 19, 2017
Wendy Wu / Specialist

Approved by : May Chen , **Date:** Oct. 19, 2017
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna No.	Brand	Model	Antenna Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
1	SAA	LX8416-12-000-C	NA	13.56	PCB	ACH connector (with 1.2mm pitch)
2	Dexerials	ANT-M041A	NA	13.56	PCB	ACH connector (with 1.2mm pitch)
3	Dexerials	ANT-M043A	NA	13.56	PCB	ACH connector (with 1.2mm pitch)
4	Dexerials	ANT-M047A	NA	13.56	PCB	ACH connector (with 1.2mm pitch)
5	SAA	LX7828-12-000-C	NA	13.56	PCB	ACH connector (with 1.2mm pitch)
6	Murata	FLANBPA-0715	NA	13.56	PCB	ACH connector (with 1.2mm pitch)

Note: 1: Antenna 3, the worse case one (for max field strength), was chosen for final test.

2.5 Calculation Result

All test data was copied from the original test report (Report No.: SA160629E05)

Freq. (MHz)	Electric field (dBuV/m)@3m	Pout EIRP (dBm)	Pout EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Pass /Fail
13.56	60.6	-34.63	0.0003443	0.000000068	0.97893335	PASS

NOTE:

Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

--- END ---