

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

| FCC Rule Part: | FCC Part 2 (Section 2.1091) |
|--------------------|--|
| Report No.: | MFBHQC-WTW-P22070414B |
| FCC ID: | MCLT77H747 |
| Product: | NFC module |
| Brand: | FOXCONN |
| Model No.: | Т77Н747 |
| Received Date: | 2023/10/16 |
| Test Date: | 2023/10/27 |
| Issued Date: | 2023/11/20 |
| Applicant: | HON HAI PRECISION IND. CO., LTD. |
| Address: | 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan, R.O.C. |
| Issued By: | Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory |
| Lab Address: | E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan |
| Test Location: | E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan |
| FCC Registration / | 723255 / TW2022 |
| esignation Number: | |

Desig

Approved by:

Wen Yu / Assistant Manager

This test report consists of 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



2023/11/20

Date:

Prepared by : Claire Kuan / Specialist



Table of Contents

| Relea | se Control Record | 3 |
|-------|---|---|
| 1 | Certificate | 4 |
| 2 | Applicable RF Exposure Limit | 5 |
| 3 | Test Results | 7 |
| 4 | Conclusion | 8 |
| 5 | Information of the Testing Laboratories | 9 |



Release Control Record

| Issue No. | Description | Date Issued |
|-----------------------|-------------------|-------------|
| MFBHQC-WTW-P22070414B | Original release. | 2023/11/20 |



1 Certificate

| Product: | NFC module |
|----------------|---|
| Brand: | FOXCONN |
| Test Model: | T77H747 |
| Sample Status: | Engineering sample |
| Applicant: | HON HAI PRECISION IND. CO., LTD. |
| Test Date: | 2023/10/27 |
| FCC Rule Part: | FCC Part 2 (Section 2.1091) |
| Standard: | KDB 447498 D04 Interim General RF Exposure Guidance v01 |

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



2 Applicable RF Exposure Limit

§ 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) | |
|---|----------------------------------|----------------------------------|--|---------------------------|--|
| Limits For General Population / Uncontrolled Exposure | | | | | |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 | |
| 1.34-30 | 824/f | 2.19/f | (180/f²)* | 30 | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | |
| 300-1500 | | | f/1500 | 30 | |
| 1500-100,000 | | | 1.0 | 30 | |

f = frequency in MHz. * = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|----------------------------------|----------------------------------|--|---------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | ⊴6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | <6 |
| 30-300 | 61.4 | 0.163 | 1.0 | <6 |
| 300-1,500 | | | f/300 | <6 |
| 1,500-100,000 | | | 5 | <6 |

f = frequency in MHz. * = Plane-wave equivalent power density.



1 mW Blanket Exemption - §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).



3 Test Results

| Environmental Conditions: | 25°C, 60% R | H Test | ed By: | S | ampson Chen |
|------------------------------|-------------------------|---------------------|---------------|---|-------------|
| 1 mW Blanket Exemption | | | | | |
| Operation Mode | Frequency Band (MHz) | Maximum ERP (mW) | Limit (mW) | | Test Result |
| NFC | 13.56 | 0.00006745 | 1 | | Pass |

Note: Calculate the ERP of NFC from the radiated field strength: ERP (dBm) = Radiated field strength (dBuV/m) + 20 x Log(d) - 104.77 - 2.15

d is the measurement distance, in 3 m.

 $ERP = 55.67 + 20 \times Log(3) - 104.77 - 2.15 = -41.71 dBm (0.00006745 mW)$



4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.



5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab Tel: 886-3-3183232

Fax: 886-3-3270892

Email: <u>service.adt@bureauveritas.com</u> Web Site: <u>http://ee.bureauveritas.com.tw</u>

The address and road map of all our labs can be found in our web site also.

---- END ----